

**EMC EVALUATION OF THE  
BELKIN CORPORATION  
TUNECAST 3 - MODEL F8M010**

**Date:** NOVEMBER 29, 2006  
**Test Report Number:** TRR0361.06 REVISION 2

**IN ACCORDANCE WITH  
FCC PART 15 SUBPART A 15.33  
FCC PART 15 SUBPART C 15.209  
FCC PART 15 SUBPART C 15.239  
AS/NZS 4268:2003**


**Prepared For:** BELKIN CORPORATION  
1057 EAST HENRIETTA ROAD  
ROCHESTER, NEW YORK 14623  
ATTENTION: JEFF MEYERS

**Prepared By:** DWIGHT SIMPSON / MATTHEW HANEL  
CHOMERICS TEST SERVICES  
ROCHESTER FACILITY  
100 INDIGO CREEK DRIVE ROCHESTER, NEW YORK 14626  
WOBURN FACILITY  
77 DRAGON COURT WOBURN, MASSACHUSETTS 01801


**Test Technician or Engineer:**



**Rochester Manager:**



**CTS Approved Signatory:**



This report shall not be reproduced except in full without the  
written approval of Chomerics Test Services.

## TABLE OF CONTENTS

### 1.0 General

#### 1.1 Introduction

- 1.1.1 Purpose
- 1.1.2 Requirements

#### 1.2 Test Summary

- 1.2.1 Summary of Recommendations

#### 1.3 Administrative Data

- 1.3.1 Test Facility
- 1.3.2 Equipment Calibration
- 1.3.3 Test Personnel

#### 1.4 Test Set-up

- 1.4.1 Test Site Matrix
- 1.4.2 Test Site Descriptions
- 1.4.3 Equipment Under Test
- 1.4.4 Block Diagram

### 2.0 Emissions Tests Performed

#### 2.1 -26 dB Fundamental Emission

- 2.1.1 Equipment Used
- 2.1.2 Test Conditions
- 2.1.3 Test Method
- 2.1.4 Results
- 2.1.5 Test data
- 2.1.6 Photographic Documentation

#### 2.2 FCC Part 15 Subpart C Field Strength (FCC 47 CFR 15.239)

- 2.2.1 Equipment Used
- 2.2.2 Test Conditions
- 2.2.3 Test Method
- 2.2.4 Results
- 2.2.5 Test Data
- 2.2.6 Photographic Documentation

#### 2.3 FCC Part 15 Subpart C Field Strength (FCC 47 CFR 15.209)

- 2.3.1 Equipment Used
- 2.3.2 Test Conditions
- 2.3.3 Test Method
- 2.3.4 Result
- 2.3.5 Test Data
- 2.3.6 Photographic Documentation

**TABLE OF CONTENTS**  
**(continued)**

|            |  |
|------------|--|
| <b>2.4</b> | <b>Effective Isotropic Radiated Power (EIRP)</b>           |
| 2.4.1      | Equipment Used   |
| 2.4.2      | Test Conditions  |
| 2.4.3      | Test Method  |
| 2.4.4      | Result   |
| 2.4.5      | Test Data  |
| 2.4.6      | Photographic Documentation                                 |
| <b>2.5</b> | <b>FCC Subpart A Radiated Emissions (FCC 47 CFR 15.33)</b> |
| 2.5.1      | Equipment Used   |
| 2.5.2      | Test Conditions  |
| 2.5.3      | Test Method  |
| 2.5.4      | Results  |
| 2.5.5      | Test Data  |
| 2.5.6      | Photographic Documentation                                 |

**Appendix A: Test Log**

**LIST OF DEFINITIONS/ABBREVIATIONS**

|        |                               |
|--------|-------------------------------|
| AC     | Alternating Current           |
| BB     | Broadband                     |
| BW     | Bandwidth                     |
| cm     | Centimeter                    |
| CPU    | Calibrate Prior to Use        |
| dB     | Decibel                       |
| DC     | Direct Current                |
| EMC    | Electromagnetic Compatibility |
| EMI    | Electromagnetic Interference  |
| ER     | Electric Radiation            |
| EUT    | Equipment Under Test          |
| GHz    | GigaHertz                     |
| Hz     | Hertz                         |
| I-face | Interface                     |
| kHz    | KiloHertz                     |
| m      | Meter                         |
| MHz    | MegaHertz                     |
| mm     | Millimeter                    |
| mS     | Millisecond                   |
| mV     | MilliVolt                     |
| MR     | Magnetic Radiation            |
| NB     | Narrowband                    |
| NCR    | No Calibration Required       |
| PLC    | Power Line Conduction         |
| PPS    | Pulses Per Second             |
| uF     | MicroFarad                    |
| uH     | MicroHenry                    |
| uS     | Microsecond                   |
| uV     | MicroVolt                     |
| UWC    | Use With Calibrated Equipment |

## 1.0 GENERAL

### 1.1 Introduction

#### 1.1.1 Purpose

The purpose of this report is to document the performance of the Belkin Corporation TuneCast 3 - Model F8M010 during an electromagnetic interference (EMI) test and record the test requirements and procedures used. At the request of Belkin Corporation, the tests were performed by Chomerics Test Services (CTS) of Woburn, Massachusetts at Chomerics' test facility located in Rochester, New York. The assessment will determine the compliance or non-compliance with the requirements set up by the FCC Part 15 Subpart C 15.239 and AS/NZS 4268:2003 Radio Equipment and Systems – Short Range Devices- Limits and Methods measurement.

Jeff Meyers from the Belkin Corporation was present during testing. Testing was performed during the period of October 26-30, 2006 under Chomerics' order number 953555.

#### 1.1.2 Requirements

The requirements for the sequence of tests performed on the TuneCast 3 - Model F8M010 are as follows:

#### **FCC Part 15 Subpart C 15.239 – Section 2.0**

FCC Part 15 Subpart C 15.239, Emission requirements:

Sec. 15.239: Operation in the band 88-108 MHz. - Emissions from the intentional radiator shall be confined within a band 200 kHz wide centered on the operating frequency. The 200 kHz band shall lie wholly within the frequency range of 88-108 MHz. The field strength of any emissions within the permitted 200 kHz band shall not exceed 250 microVolts/meter (47.95 dBuV) at 3 meters. The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions for limiting Peak emissions in 15.35 apply. The field strength of any emissions radiated on any frequency outside of the specified 200 kHz band shall not exceed the general radiated emission limits in Sec. 15.209.

#### **AS/NZS 4268:2003 – Section 2.4**

##### Table 1

Maximum EIRP = 10uW

Maximum Transmitter Spurious Emissions EIRP = 0.1uW

Maximum -26 dB Bandwidth 180 kHz

## FCC Part 15 Subpart C 15.33 – Section 2.5

FCC Part 15 Subpart C 15.33, Radio Frequency Devices:

For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in paragraph (1).

(1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental or to 40 GHz, whichever is lower.

## FCC Part 15 Subpart A 15.35

FCC Part 15 Subpart C 15.35, Measurement Detector Functions and Bandwidths:

(a) On any frequency or frequencies below or equal to 1000 MHz, the limits shown are based on measuring equipment employing a CISPR quasi-peak detector function and related measurement bandwidths, unless otherwise specified. The specifications for the measuring instrument used were in accordance with CISPR 16. Peak detector measured data may be substituted for the appropriate detector data to show compliance if the peak level obtained does not exceed the limit. The bandwidth used shall be greater than or equal to 100 Hz from 9 kHz to 150 kHz, 9 kHz from 150 kHz to 30 MHz and 100 kHz from 30 MHz to 1000 MHz.

Actual Bandwidths used;

1 – 30 MHz; 9 kHz

30 – 1000 MHz; 120 kHz

## 1.2 TEST SUMMARY

The terms "Passed" or "Failed" in this section are intended to guide the reader as to whether or not the EUT met the minimum requirements that can be interpreted from the FCC Part 15 Subpart C 15.239 Emissions Standard as defined in Section 1.5. The "Results" paragraph in each test section to follow and the test data sheets will outline specifically how the EUT performed during each test.

|  |        |
|--|--------|
| FCC Part 15.239 -26 dB Bandwidth           | Passed |
| FCC Part 15.239 Field Strength             | Passed |
| FCC Radiated Emissions (FCC 47 CFR 15.209) | Passed |
| AS/NZS 4268: 2003 EIRP of Fundamental      | Passed |
| AS/NZS 4268:2003 EIRP Spurious             | Passed |
| AS/NZS 4268:2003 -26 dB Bandwidth          | Passed |
| FCC Radiated Emissions (FCC 47 CFR 15.33)  | Passed |

## 1.2.1 Summary of Recommendations

The Belkin Corporation TuneCast 3 - Model F8M010 will require no modifications in order to ensure compliance with the Electromagnetic Interference Standard FCC Part 15 Subpart C 15.239, Subpart A 15.33, Subpart C 15.209 or AS/NZS 4268:2003.

Please note that if any modifications and or fixes were implemented to the EUT to achieve compliance, other approaches to solving the problem may exist. In addition, any EMI/EMC shielding products listed in this report may be substituted with an equivalent.

## 1.3 Administrative Data

### 1.3.1 Test Facility

Chomerics Test Services in Rochester, New York is an American Association for Laboratory Accreditation (A2LA) accredited facility as defined on Certification Number 1980-02. The Scope of Accreditation is limited to the following tests:

#### *Emissions*

|                                       |   |
|---------------------------------------|---|
| Radiated (up to 2 GHz)<br>+ Conducted | Code of Federal Regulation (CFR) 47, FCC Part 15 (Subpart B, ITE devices) using ANSI C63.4 (2001, 2003); CISPR 11; EN 55011; CISPR 14; EN 55014-1; CISPR 22; EN 55022; AS/NZS CISPR 14; AS/NZS CISPR 11; AS/NZS CISPR 22; VCCI; CNS 13738-1; CAN/CSA CISPR 22; KN 22; RRL Notice 2005-82 (September 29, 2005) |
| Current Harmonics                     | EN 61000-3-2  |
| Voltage Fluctuations + Flicker        | EN 61000-3-3  |
| Generic Standards                     | EN 61000-6-3; EN 61000-6-4  |

#### *Immunity*

|  |   |
|--|---|
| Electrostatic Discharge (ESD)                                  | EN 61000-4-2:1995+A1:1998+A2:2000; IEC 61000-4-2:1995+A1:1998+A2:2000; KN 61000-4-2   |
| Radiated Immunity  | EN 61000-4-3:1996+A1:2002; IEC 61000-4-3:1995+A1:2002; KN 61000-4-3   |
| Electrical Fast Transient/Burst                                | EN 61000-4-4:1995+A1:2000+A2:2001; EN 61000-4-4: 2004; IEC 61000-4-4:1995+A1:2000+A2:2001; IEC 61000-4-4:2004; KN 61000-4-4 |
| Surge Immunity   | EN 61000-4-5:1995+A1:2001 IEC 61000-4-5:1995+A1:2000; KN 61000-4-5  |
| Conducted Immunity   | EN 61000-4-6:1996+A1:2001; IEC 61000-4-6:1996+A1:2000; IEC 61000-4-6: 2003 + A1;2004; KN 61000-4-6                          |
| Power Frequency Magnetic Field Immunity                        | EN 61000-4-8:1993+A1:2001; IEC 61000-4-8:1993+A1:2001; KN 61000-4-8   |
| Voltage Dips, Short Interruptions, and Line Voltage Variations | EN 61000-4-11:1994+A1:2000; IEC 61000-4-11:1994+A1:2000; EN 61000-4-11:2004; IEC 61000-4-11: 2004; KN 61000-4-11            |

***Product Standards***

IEC/EN 60601-1-2, EN 300 386, EN 61326; CISPR 24; EN 55024; CISPR 14; EN 55014-2; RRL Notice No.2005-130 (December 27, 2005)

Any tests in this report that are not listed above are not covered by the A2LA Accreditation.

**ALL test(s)** included within this report are covered under Chomerics' A2LA Scope of Accreditation.

Chomerics' Semi-anechoic Test Chamber is listed by the Federal Communications Commission (FCC) for Radiated and Conducted Emissions testing under file number 102772.

Chomerics' Semi-anechoic Test Chamber is accredited for Radiated and Conducted Emissions tests through Industry Canada (IC) under file numbers IC4154.

Chomerics test facility operates under the current revision of Chomerics Quality Assurance (QA) Manual Document Number QA002.

The QA Manual has been constructed to reflect a quality program in accordance with the requirements of the National Institute of Standards and Technology (NIST), ISO 9002, ISO 17025, ISO Guide 25, NIST Handbook 150, EN 45001, MIL-I-45208A, MIL-STD-461D, 462D and Chomerics Quality Assurance Program (QAP).

The QA Manual outlines and describes the procedures for establishing and maintaining the quality of analysis, research, inspection, and testing within Chomerics Test Service (CTS).

This test report does not represent an endorsement by the U.S. Government.

The results and/or conclusions within this test report refer and/or apply only to the unit(s) tested as defined by this report.

Measurements performed for this test are traceable to the National Institute of Standards and Technology (NIST) based on the fact that all test equipment used for the measurements were previously calibrated using standards traceable to NIST.

Additions to, or exclusions from the test specification(s) were made. AS/NZS 4268:2003 tests were performed as well as the FCC Part 15 Subpart C 15.239 measurements.

Chomerics Test Services measurement uncertainty calculations are available for review upon request.

## Sample Calculation:

### Radiated Emissions

The tabular data listed in the report is the highest signal detected during the scan. At a minimum six of the highest signals will be selected and maximized. The tabular data sheet shall contain the measured value "QP-Value", field level, limit, margin to the limit, antenna height, antenna polarity and turn table azimuth.

The field level is the final value that will be compared to the limit in order to determine if the EUT is in compliance. The field level will be calculated by the following for each of the signals maximized:

Field Level dBuV = Measured Value dBuV + Antenna Factor dB + Cable Loss dB

$$37\text{dBuV} = 30\text{dBuV} + 5\text{dB} + 2\text{dB}$$

The margin to the limit shall be calculated by subtracting the field level to the limit. The margin to the limit shall be calculated by the following for each of the signal maximized.

$$\begin{aligned} \text{Margin to Limit dB} &= \text{Field Level dBuV} - \text{Limit dBuV} \\ -3\text{dB} &= 37\text{dBuV} - 40\text{dBuV} \end{aligned}$$

### Conducted Emissions

The tabular data listed in the report is the highest signal detected during the scan. At a minimum six of the highest signals will be selected and maximized. The tabular data sheet shall contain the measured value, final level, limit, margin to the limit, LISN factor

The final value will be compared to the limit in order to determine if the EUT is in compliance. The final value will be calculated by the following for each of the maximized signals.

$$\begin{aligned} \text{Final Value dBuV} &= \text{measured value dBuV} + \text{LISN Factor dB} \\ 50\text{dBuV} &= 49\text{dBuV} + 1\text{dB} \end{aligned}$$

The margin to the limit shall be calculated by subtracting the final value to the limit. The margin to the limit shall be calculated by the following for each signal maximized.

$$\begin{aligned} \text{Margin to Limit dB} &= \text{Field Level dBuV} - \text{Limit dBuV} \\ -3\text{dB} &= 37\text{dBuV} - 40\text{dBuV} \end{aligned}$$

## 1.3.2 Equipment Calibration

The calibration of Chomerics test facility equipment is controlled under the current edition of Chomerics Laboratory Test Equipment Calibration Manual Document Number QA001.

The test equipment used throughout this test sequence conforms to laboratory calibration standards, MIL-STD-45662, traceable to the National Institute of Standards and Technology (NIST). The date of the next due scheduled calibration is listed in each test section for the applicable equipment.

All test equipment is calibrated in one year intervals.

## 1.3.3 Test Personnel

The test personnel performing or supervising the tests are accredited by the National Association of Radio and Telecommunications Engineers, Inc. (NARTE) as Certified Electromagnetic Compatibility Engineers (N.C.E.) and Technicians (N.C.T.).

## 1.4 Test Set-up

### 1.4.1 Test Site Matrix

The specific test locations used for the emissions testing of the Belkin Corporation TuneCast 3 - Model F8M010 are as follows: (Refer to Section 1.4.2 for test site descriptions).

#### Emissions Test

FCC Part 15.239 -26 dB Bandwidth  
 FCC Part 15.239 Field Strength  
 FCC Radiated Emissions (FCC 47 CFR 15.209)  
 AS/NZS 4268:2003 EIRP of Fundamental  
 AS/NZS 4268:2003 EIRP Spurious  
 AS/NZS 4268:2003 -26 dB Bandwidth  
 FCC Radiated Emissions (FCC 47 CFR 15.33)

#### Test Site

Semi-Anechoic Chamber  
 Semi-Anechoic Chamber  
 Semi-Anechoic Chamber  
 Semi-Anechoic Chamber  
 Semi-Anechoic Chamber  
 Semi-Anechoic Chamber  
 Semi-Anechoic Chamber

## 1.4.2 Test Site Descriptions

The following is a list of test sites and descriptions of each. Refer to Section 1.4.1 for specific test sites used for testing.

**Semi-anechoic Chamber:** Chomerics' Semi-anechoic Test Chamber is located at 100 Indigo Creek Drive, Rochester, NY 14626 (see Figure 1). The shielded enclosures were manufactured and installed by EMC Test Systems of Texas. The normal exterior dimensions of the shielded indoor semi-anechoic chamber are approximately 28 feet long by 20 feet wide by 18 feet high and consist of rigid, steel-clad, wood core modular panels with steel framing.

The shielding performance is as follows:

| Field    | Attenuation   |
|----------|---|
| Magnetic | 20dB at 1kHz, increasing to 56dB at 10kHz and increasing to 100dB at 200kHz |
| Electric | 100dB from 200kHz to 18GHz  |

The anechoic absorber treatment is broadband hybrid EMC absorbers, FerroSorb model number FS-400. All interior surfaces of the chamber with the exception of the ground plane are covered with FS-400 absorber. The FS-400 absorber material is a combination of dielectric foam absorber and magnetic ferrite tile, which is 16 inches thick.

Two swing type shielded doors are provided for personal access into the control room and chamber. The doors are 4 feet wide by 7 feet high. The doors are a single unit containing a brass door leaf and frame and a single leaf of spring finger gaskets. The doors provide 100dB of attenuation from 30MHz to 18 GHz.

The quiet zone for the Chomerics semi-anechoic test chamber is a cylinder two meters in diameter.

Air conditioning is provided by honeycomb wave-guide to supply and return air in the main chamber. Four (4) incandescent light fixtures provide lighting of the chamber.

The turntable is an electrically driven EMCO metal top turntable with a 2-meter diameter. The turntable is grounded around its circumference with continuous metallic brush to the semi-anechoic chamber floor by a ground ring. The electrically driven turntable doesn't introduce conducted or radiated noise above the ambient levels existing within the chamber. An EMCO 2090 Controller controls the turntable with an IEEE-488 data/controller for automation. Interconnecting cables are routed along an access area through the center bearing.

The ground plane consists of raised standard steel floor panels. RF and fiber optic cables are routes under the raised steel floor of the chamber.

Power is supplied on separate circuits to the chamber and the control room. Separate filters are provided for signal distribution as well in the semi-anechoic chamber. All filters provided a minimum of 100dB attenuation from 10kHz to 10GHz per MIL-STD 220A.

See Figure 1 for the overall dimensional drawing of the semi-anechoic chamber.




Figure 1

### 1.4.3 Equipment Under Test

The Belkin Corporation TuneCast 3 - Model F8M010 is a device that wirelessly transmits audio signals to an FM receiver. It is designed to allow the user to set the transmission frequency in the band of 88.1 MHz – 107.9 MHz in 0.1 MHz intervals. The device was manually adjusted and it was verified that it is not possible for the user to adjust the device to frequencies outside of this range.

The support equipment needed to run the Belkin Corporation TuneCast 3 - Model F8M010 in the normal mode of operation consisted of the following:

|    | <u>Manufactory</u> | <u>Device</u> | <u>Serial #</u> | <u>Model #</u> |
|----|--------------------|---------------|-----------------|----------------|
| a. | Apple              | iPod Nano     | YM6367ZBV8W     | A1199          |

The TuneCast 3 - Model F8M010 is a DC powered device that operates on 3.0 VDC power. For the purpose of the radiated emission tests, power was supplied by two fully charged AAA batteries. The internal transmitter of the device runs off of 3.75VDC regardless of the input supply voltage.

There are no I/O connections.


The normal mode of operation was used for emissions tests. The TuneCast 3 - Model F8M010 was monitored during the tests by Jeff Meyers of the Belkin Corporation.

The equipment under test was setup as illustrated on CTS-Form-014.

#### 1.4.4 Block Diagram

**CUSTOMER:** BELKIN CORPORATION  
**EQUIPMENT:** TUNECast 3 - MODEL F8M010

**DATE:** OCTOBER 26, 2006  
**TESTED BY:** DWIGHT SIMPSON/MATTHEW HANEL



System Configuration Block Diagram – Provide a line drawing identifying the EUT, simulators, support equipment, I/O cables, and any other pertinent components to be used during testing. Use a dashed line to separate the equipment in the testing field versus equipment outside the testing field.

**FORM CTS-014**

## 2.0 EMISSIONS TESTS PERFORMED

### 2.1 -26 dB BANDWIDTH OF FUNDAMENTAL EMISSION

#### 2.1.1 Equipment Used

| Test Equipment |   | Asset # | Serial #    | Cal Date |
|----------------|---|---------|-------------|----------|
| X              | EMC Test Systems Semi-anechoic Chamber    | 667     | N/A         | 10/07    |
| X              | Rohde and Schwarz ESCS30 Test Receiver    | 638     | 826547/024  | 12/06    |
| X              | EMCO 3142B Biconilog Antenna              | 668     | 9903-1357   | 12/06    |
| X              | Hewlett Packard Vectra VL                 | N/A     | US71656121  | NCR      |
| X              | EMCO Multi Device Controller Model 2090   | 639     | 9808-1343   | NCR      |
| X              | EMCO Antenna Mast Model 3801/2NM          | 666     | N/A         | NCR      |
| X              | EMCO Video Camera Controller Model VCC-01 | 653     | N/A         | NCR      |
| X              | EMCO Video Camera Model 2075              | 680     | 00183858    | NCR      |
| X              | Quantum Change Tile Software              | N/A     | Version 3.2 | NCR      |

#### 2.1.2 Test Conditions

The -26 dB Bandwidth measurement testing was performed with the TuneCast 3 - Model F8M010 set up on a wooden table above the turntable at a distance of 3 meters from Biconilog antenna within the semi-anechoic chamber. The TuneCast 3 - Model F8M010 was configured to operate at the low, mid and then high transmit frequencies. The device was also configured to operate at its maximum audio input using a typical audio file from an iPod Nano MP3 player.

#### 2.1.3 Test Method

The bandwidth of the TuneCast 3 - Model F8M010 was measured through an air interface. The TuneCast 3 - Model F8M010 was placed on top of a wooden turntable 3 meters from a receiving antenna. The bandwidths of the TuneCast 3 - Model F8M010 were measured at the low, mid, and high transmit frequencies. During this test, the antenna, turntable and the EUT were manipulated to maximize the emission level. In accordance with ANSI C63.4, the device was positioned to maximize radiation in all three orthogonal planes during preliminary testing.

#### 2.1.4 Results

The Belkin Corporation TuneCast 3 - Model F8M010 meets the maximum 200 kHz bandwidth requirements of FCC Part 15.239 and 180 kHz requirement of AS/NZS 4268:2033 at the frequencies tested. As shown on the plots, the radiated fundamental signal lies wholly within the authorized frequency band at the -26 dB bandwidth measurement as required by 15.239 (a) within the frequency range of 88.1 MHz to 107.9 MHz.

Belkin Corporation TuneCast 3 - Model F8M010  
Document #: TRR0361.06 Rev. 2  
Date: November 29, 2006

## 2.1.5 Test Data

### -26 dB BANDWIDTH MEASUREMENTS

CUSTOMER: BELKIN CORPORATION

DATE: OCTOBER 30, 2006

EQUIPMENT: TUNECast 3 - MODEL F8M010

TEST NUMBER: 4


TESTED BY: MATTHEW HANEL

OPERATING MODE: CONTINUOUS TRANSMISSION LOW FREQ.

20, Oct 06 13:21

### -26 dB Bandwidth 88.1 MHz Fundamental Emission (110 kHz Actual Bandwidth)

Marker : 88.100 MHz 30.3 dB



50 kHz / div  
Span 500 kHz  
RBW 10 kHz  
Sweep 50 ms  
Attn 0 dB

Q4: MaxHold  
Q2: Blank

Ambient Temperature: 72°F

Humidity: 46%

Atmospheric Pressure: 30.3"

Belkin Corporation TuneCast 3 - Model F8M010

Document #: TRR0361.06 Rev. 2

Date: November 29, 2006

CUSTOMER: BELKIN CORPORATION  
EQUIPMENT: TUNECast 3 - MODEL  
F8M010  
TESTED BY: MATTHEW HANEL


DATE: OCTOBER 30, 2006  
TEST NUMBER: 4

OPERATING MODE: CONTINUOUS TRANSMISSION MID FREQ.

20, Oct 06 13:21

# **-26 dB Bandwidth** **98.1 MHz Fundamental Emission** **(150 kHz Actual Bandwidth)**

Marker : 98.100 MHz -26.1 dB



50 kHz / div  
Span 500 kHz  
RBW 10 kHz  
Sweep 50 ms  
Attn 0 dB

C1: MaxHold  
C2: Blank

Ambient Temperature: 72°F

Humidity: 46%

Atmospheric Pressure: 30.3"

CUSTOMER: BELKIN CORPORATION  
EQUIPMENT: TUNECast 3 - MODEL  
F8M010  
TESTED BY: DWIGHT SIMPSON


DATE: OCTOBER 30, 2006  
TEST NUMBER: 4

OPERATING MODE: CONTINUOUS TRANSMISSION HIGH FREQ.

20, Oct 06 13:31

# **-26 dB Bandwidth** **107.9 MHz Fundamental Emission** **(155 kHz Actual Bandwidth)**

Marker : 107.901 MHz 30.6 dB



Ambient Temperature: 72°F

Humidity: 46%

Atmospheric Pressure: 30.3"

### 2.1.6 Photographic Documentation

CUSTOMER: BELKIN CORPORATION

EQUIPMENT: TUNECAST 3 - MODEL F8M010

TESTED BY: MATTHEW HANEL

DATE: OCTOBER 30, 2006

TEST NUMBER: 4

OPERATING MODE: CONTINUOUS TRANSMISSION



**Photograph Description:** Test set-up

FORM CTS-PHOTO

**Photographic Documentation**

CUSTOMER: BELKIN CORPORATION  
EQUIPMENT: TUNECAST 3 - MODEL F8M010  
TESTED BY: MATTHEW HANEL

DATE: OCTOBER 30, 2006  
TEST NUMBER: 4  
OPERATING MODE: CONTINUOUS TRANSMISSION



**Photograph Description:** Test set-up

FORM CTS-PHOTO

## 2.2 FCC Part 15 Subpart C Field Strength (FCC 47 CFR 15.239)

### 2.2.1 Equipment Used

| Test Equipment |   | Asset # | Serial #    | Cal Date |
|----------------|---|---------|-------------|----------|
| X              | EMC Test Systems Semi-anechoic Chamber    | 667     | N/A         | 10/07    |
| X              | Rohde and Schwarz ESCS30 Test Receiver    | 638     | 826547/024  | 12/06    |
| X              | EMCO 3142B Biconilog Antenna              | 668     | 9903-1357   | 12/06    |
| X              | IBM Personal Computer Model 300XL         | N/A     | 23TMP08     | NCR      |
|                | Electro Metrics ALR-25M Loop Antenna      | 17      | 4706        | 1/07     |
|                | EMCO 3115 Microwave Horn Antenna          | 376     | 2796        | 1/07     |
|                | Luthi EM101 Absorbing Clamp               | 654     | 35543       | 11/06    |
| X              | EMCO Multi Device Controller Model 2090   | 639     | 9808-1343   | NCR      |
| X              | EMCO Antenna Mast Model 3801/2NM          | 666     | N/A         | NCR      |
| X              | EMCO Video Camera Controller Model VCC-01 | 653     | N/A         | NCR      |
| X              | EMCO Video Camera Model 2075              | 680     | 00183858    | NCR      |
| X              | Quantum Change Tile Software              | N/A     | Version 3.2 | NCR      |

### 2.2.2 Test Conditions

Output Power tests were performed on the Belkin Corporation TuneCast 3 - Model F8M010 while it was set up on a wooden table above the turntable at a distance of 3 meters from Biconilog antenna within the semi-anechoic chamber. The TuneCast 3 - Model F8M010 was configured to operate in the normal mode of operation at the lowest possible, the midpoint and then high possible transmit frequencies allowed by the device. In accordance with ANSI C63.4, the device was positioned to maximize radiation in all three orthogonal planes during preliminary testing.

### 2.2.3 Test Method

The field strength of the Belkin Corporation TuneCast 3 - Model F8M010 was measured with the Rohde and Schwarz ESCS30 Test Receiver.

### 2.2.4 Results

The Belkin Corporation TuneCast 3 - Model F8M010 meets the field strength requirement of FCC Part 15 Subpart C 15.239, for the frequencies tested.

## 2.2.5 Test Data

### OUTPUT POWER MEASUREMENTS

CUSTOMER: BELKIN CORPORATION  
EQUIPMENT: TUNECast 3 - MODEL F8M010  
TESTED BY: DWIGHT SIMPSON

DATE: OCTOBER 26, 2006  
TEST NUMBER: 1  
OPERATING MODE: CONTINUOUS TRANSMISSION

#### TuneCast 3

##### Field Strength of Fundamental Emission - High Frequency 88.1 MHz

###### Peak

| Frequency<br>MHz | Measured PK<br>dBuV | Antenna<br>Factor | Cable<br>Factor | Corrected QP<br>dBuV | FCC 15.239<br>Limit | Pass / Fail<br>Margin | Angle<br>Deg. | Height<br>cm | Polarity<br>H / V |
|------------------|---------------------|-------------------|-----------------|----------------------|---------------------|-----------------------|---------------|--------------|-------------------|
| 88.13            | 35.10               | 8.06              | 0.92            | 44.08                | 67.95               | -23.87                | 261           | 209          | H                 |

###### Avg

| Frequency<br>MHz | Measured Avg<br>dBuV | Antenna<br>Factor | Cable<br>Factor | Corrected QP<br>dBuV | FCC 15.239<br>Limit | Pass / Fail<br>Margin | Angle<br>Deg. | Height<br>cm | Polarity<br>H / V |
|------------------|----------------------|-------------------|-----------------|----------------------|---------------------|-----------------------|---------------|--------------|-------------------|
| 88.13            | 34.48                | 8.06              | 0.92            | 43.46                | 47.95               | -4.49                 | 261           | 209          | H                 |

##### Field Strength of Fundamental Emission - High Frequency 98.1 MHz

###### Peak

| Frequency<br>MHz | Measured PK<br>dBuV | Antenna<br>Factor | Cable<br>Factor | Corrected QP<br>dBuV | FCC 15.239<br>Limit | Pass / Fail<br>Margin | Angle<br>Deg. | Height<br>cm | Polarity<br>H / V |
|------------------|---------------------|-------------------|-----------------|----------------------|---------------------|-----------------------|---------------|--------------|-------------------|
| 98.09            | 32.70               | 9.38              | 1.00            | 43.07                | 67.95               | -24.88                | 261           | 245          | H                 |

###### Avg

| Frequency<br>MHz | Measured Avg<br>dBuV | Antenna<br>Factor | Cable<br>Factor | Corrected QP<br>dBuV | FCC 15.239<br>Limit | Pass / Fail<br>Margin | Angle<br>Deg. | Height<br>cm | Polarity<br>H / V |
|------------------|----------------------|-------------------|-----------------|----------------------|---------------------|-----------------------|---------------|--------------|-------------------|
| 98.09            | 31.68                | 9.38              | 1.00            | 42.05                | 47.95               | -5.90                 | 261           | 245          | H                 |

##### Field Strength of Fundamental Emission - High Frequency 107.9 MHz

###### Peak

| Frequency<br>MHz | Measured Pk<br>dBuV | Antenna<br>Factor | Cable<br>Factor | Corrected QP<br>dBuV | FCC 15.239<br>Limit | Pass / Fail<br>Margin | Angle<br>Deg. | Height<br>cm | Polarity<br>H / V |
|------------------|---------------------|-------------------|-----------------|----------------------|---------------------|-----------------------|---------------|--------------|-------------------|
| 107.89           | 35.18               | 9.10              | 1.04            | 45.32                | 67.95               | -22.63                | 248           | 277          | H                 |

###### Avg

| Frequency<br>MHz | Measured Avg<br>dBuV | Antenna<br>Factor | Cable<br>Factor | Corrected QP<br>dBuV | FCC 15.239<br>Limit | Pass / Fail<br>Margin | Angle<br>Deg. | Height<br>cm | Polarity<br>H / V |
|------------------|----------------------|-------------------|-----------------|----------------------|---------------------|-----------------------|---------------|--------------|-------------------|
| 107.89           | 34.14                | 9.10              | 1.04            | 44.28                | 47.95               | -3.67                 | 248           | 277          | H                 |

Ambient Temperature: 72°F

Humidity: 46%

Atmospheric Pressure: 30.3"

Belkin Corporation TuneCast 3 - Model F8M010  
Document #: TRR0361.06 Rev. 2  
Date: November 29, 2006

## 2.2.6 Photographic Documentation

CUSTOMER: BELKIN CORPORATION  
EQUIPMENT: TUNECast 3 - MODEL F8M010  
TESTED BY: DWIGHT SIMPSON  
OPERATING MODE: NORMAL

DATE: OCTOBER 26, 2006  
TEST NUMBER: 1  
COUPLING DEVICE: EMCO BICONILOG



Photograph Description: Test set-up

FORM CTS-PHOTO

**Photographic Documentation**

CUSTOMER: BELKIN CORPORATION  
EQUIPMENT: TUNECast 3 - MODEL F8M010  
TESTED BY: DWIGHT SIMPSON  
OPERATING MODE: NORMAL

DATE: OCTOBER 26, 2006  
TEST NUMBER: 1  
COUPLING DEVICE: EMCO BICONILOG



**Photograph Description:** Test set-up

FORM CTS-PHOTO

## 2.3 FCC Part 15 Subpart C Radiated Emissions (FCC 47 CFR 15.209)

### 2.3.1 Equipment Used

| Test Equipment |   | Asset # | Serial #    | Cal Date |
|----------------|---|---------|-------------|----------|
| X              | EMC Test Systems Semi-anechoic Chamber    | 667     | N/A         | 10/07    |
| X              | Rohde and Schwarz ESCS30 Test Receiver    | 638     | 826547/024  | 12/06    |
| X              | EMCO 3142B Biconilog Antenna              | 668     | 9903-1357   | 12/06    |
| X              | IBM Personal Computer Model 300XL         | N/A     | 23TMP08     | NCR      |
| X              | EMCO Multi Device Controller Model 2090   | 639     | 9808-1343   | NCR      |
| X              | EMCO Antenna Mast Model 3801/2NM          | 666     | N/A         | NCR      |
| X              | EMCO Video Camera Controller Model VCC-01 | 653     | N/A         | NCR      |
| X              | EMCO Video Camera Model 2075              | 680     | 00183858    | NCR      |
| X              | Quantum Change Tile Software              | N/A     | Version 3.2 | NCR      |

### 2.3.2 Test Conditions

Radiated emissions testing was performed with the EUT set up on a wooden table above the turntable at a distance of 3 meters from the Biconilog antenna within the Semi-anechoic Chamber.

The Belkin Corporation TuneCast 3 - Model F8M010 was configured to operate in the normal mode of operation to maximize the emissions. The TuneCast 3 - Model F8M010 was set up and powered by 3.0 VDC for radiated emission tests. The worst case signals detected were recorded.

### 2.3.3 Test Method

The test method of FCC Part 15.209 Radiated Emissions was followed for Intentional Radiators. For the radiated emission measurements, a manual scan was performed from 30 MHz – 1080 MHz. In accordance with ANSI C63.4, the antenna, turntable and the EUT's cable positions were manipulated to maximize the emission levels in a given frequency band displayed on the receiver.


Subsequently, an automated scan was performed in first the peak and then the quasi-peak detection modes using the Quantum Change Tile Software.

### 2.3.4 Results


The Belkin Corporation TuneCast 3 - Model F8M010 meets the requirements for radiated emissions as required by FCC Part 15.209.

### 2.3.5 Test Data

#### Low Frequency 88.1 MHz Graph Horizontal



#### Graph Vertical



Ambient Temperature: 72°F

Humidity: 46%

Atmospheric Pressure: 30.3"

Belkin Corporation TuneCast 3 - Model F8M010

Document #: TRR0361.06 Rev. 2

Date: November 29, 2006

## Tabular Data – 88.1 MHz

Chomerics Test Services  
Radiated Emissions 30 MHz - 1080 MHz

Operator: Dwight Simpson  
C:\tile\Customer Files\Belkin\TuneCast 3 88.1 10.26.06.TIL  
04:46:10 PM, Thursday, October 26, 2006  
Equipment ID: TuneCast 3 88.1  
Contact: Jeff Meyers  
Company: Belkin

### Final Quasi-Peak Values


| Frequency<br>MHz | Measured QP<br>dBuV | Antenna<br>Factor | Cable<br>Factor | Corrected QP<br>dBuV | FCC 15.209<br>Limit | Pass / Fail<br>Margin | Angle<br>Deg. | Height<br>cm | Polarity<br>H / V |
|------------------|---------------------|-------------------|-----------------|----------------------|---------------------|-----------------------|---------------|--------------|-------------------|
| 30.340           | 2.75                | 16.26             | 0.55            | 19.56                | 40.00               | -20.44                | 236           | 199          | V                 |
| 30.652           | 3.23                | 16.08             | 0.56            | 19.87                | 40.00               | -20.13                | 96            | 180          | H                 |
| 140.946          | 3.40                | 8.32              | 1.24            | 13.02                | 43.52               | -30.50                | 326           | 108          | H                 |
| 176.150          | 11.21               | 10.30             | 1.38            | 22.86                | 43.52               | -20.66                | 202           | 202          | V                 |
| 176.190          | 22.12               | 10.30             | 1.38            | 33.80                | 43.52               | -9.72                 | 76            | 174          | H                 |
| 192.110          | 3.30                | 10.30             | 1.44            | 15.04                | 43.52               | -28.48                | 63            | 248          | V                 |
| 742.700          | 2.22                | 20.90             | 2.91            | 26.03                | 46.02               | -19.99                | 285           | 352          | V                 |

**Ambient Temperature: 72°F**


**Humidity: 46%**

**Atmospheric Pressure: 30.3"**

# Mid Frequency 98.1 MHz Graph Horizontal



# Graph Vertical



Ambient Temperature: 72°F

Humidity: 46%

Atmospheric Pressure: 30.3"

Belkin Corporation TuneCast 3 - Model F8M010  
Document #: TRR0361.06 Rev. 2  
Date: November 29, 2006

## Tabular Data – 98.1 MHz

Chomerics Test Services  
Radiated Emissions 30 MHz - 1080 MHz

Operator: Dwight Simpson  
C:\tile\Customer Files\Belkin\TuneCast 3 98.1 10.29.06.TIL  
03:00:08 PM, Sunday, October 29, 2006  
Equipment ID: TuneCast 3 98.1MHz  
Contact: Jeff Meyers  
Company: Belkin

### Final Quasi-Peak Values

| Frequency<br>MHz | Measured QP<br>dBuV | Antenna<br>Factor | Cable<br>Factor | Corrected QP<br>dBuV | FCC 15.209<br>Limit | Pass / Fail<br>Margin | Angle<br>Deg. | Height<br>cm | Polarity<br>H / V |
|------------------|---------------------|-------------------|-----------------|----------------------|---------------------|-----------------------|---------------|--------------|-------------------|
| 30.522           | 2.92                | 16.16             | 0.56            | 19.63                | 40.00               | -20.37                | 81            | 198          | H                 |
| 31.020           | 3.00                | 15.88             | 0.57            | 19.45                | 40.00               | -20.56                | 357           | 363          | V                 |
| 95.660           | 3.61                | 9.39              | 0.98            | 13.97                | 43.52               | -29.55                | 193           | 321          | V                 |
| 100.020          | 3.52                | 9.20              | 1.01            | 13.73                | 43.52               | -29.79                | 117           | 288          | H                 |
| 196.160          | 3.13                | 10.20             | 1.50            | 14.83                | 43.52               | -28.69                | 70            | 380          | H                 |
| 683.780          | 2.28                | 20.46             | 2.82            | 25.55                | 46.02               | -20.47                | 3             | 286          | V                 |


**Ambient Temperature: 72°F**

**Humidity: 46%**


**Atmospheric Pressure: 30.3"**

Belkin Corporation TuneCast 3 - Model F8M010  
Document #: TRR0361.06 Rev. 2  
Date: November 29, 2006

## High Frequency 107.9 MHz Graph Horizontal



## Graph Vertical



Ambient Temperature: 72°F

Humidity: 46%

Atmospheric Pressure: 30.3"

Belkin Corporation TuneCast 3 - Model F8M010

Document #: TRR0361.06 Rev. 2

Date: November 29, 2006

## Tabular Data – 107.9 MHz

Chomerics Test Services  
Radiated Emissions 30 MHz - 1080 MHz

Operator: Dwight Simpson  
C:\tile\Customer Files\Belkin\TuneCast 3 107.9 10.29.06.TIL  
06:03:05 PM, Sunday, October 29, 2006  
Equipment ID: TuneCast 3 107.9MHz  
Contact: Jeff Meyers  
Company: Belkin

### Final Quasi-Peak Values

| Frequency<br>MHz | Measured QP<br>dBuV | Antenna<br>Factor | Cable<br>Factor | Corrected QP<br>dBuV | FCC 15.209<br>Limit | Pass / Fail<br>Margin | Angle<br>Deg. | Height<br>cm | Polarity<br>H / V |
|------------------|---------------------|-------------------|-----------------|----------------------|---------------------|-----------------------|---------------|--------------|-------------------|
| 31.190           | 3.22                | 15.78             | 0.57            | 19.57                | 40.00               | -20.43                | 338           | 367          | H                 |
| 37.039           | 3.57                | 12.40             | 0.68            | 16.65                | 40.00               | -23.36                | 315           | 286          | V                 |
| 37.309           | 3.42                | 12.27             | 0.68            | 16.39                | 40.00               | -23.57                | 272           | 294          | V                 |
| 39.709           | 3.37                | 11.09             | 0.68            | 15.14                | 40.00               | -24.86                | 326           | 128          | V                 |
| 40.369           | 3.40                | 10.70             | 0.68            | 14.78                | 40.00               | -25.22                | 258           | 205          | V                 |
| 44.629           | 3.58                | 9.36              | 0.70            | 13.63                | 40.00               | -26.37                | 248           | 313          | V                 |
| 47.509           | 3.52                | 8.60              | 0.74            | 12.85                | 40.00               | -27.15                | 116           | 177          | V                 |
| 48.219           | 3.44                | 8.41              | 0.75            | 12.60                | 40.00               | -27.40                | 275           | 344          | V                 |
| 48.469           | 3.44                | 8.40              | 0.75            | 12.59                | 40.00               | -27.41                | 270           | 159          | V                 |
| 949.694          | 1.62                | 22.66             | 3.33            | 27.61                | 46.02               | -18.41                | 125           | 287          | V                 |

**Ambient Temperature: 72°F**

**Humidity: 46%**

**Atmospheric Pressure: 30.3"**

Belkin Corporation TuneCast 3 - Model F8M010  
Document #: TRR0361.06 Rev. 2  
Date: November 29, 2006

### 2.3.6 Photographic Documentation

CUSTOMER: BELKIN CORPORATION  
EQUIPMENT: TUNECast 3 - MODEL F8M010  
TESTED BY: DWIGHT SIMPSON  
OPERATING MODE: NORMAL

DATE: OCTOBER 29, 2006  
TEST NUMBER: 2  
COUPLING DEVICE: EMCO BICONILOG



Photograph Description: Test set-up

FORM CTS-PHOTO

## Photographic Documentation

CUSTOMER: BELKIN CORPORATION  
EQUIPMENT: TUNECast 3 - MODEL F8M010  
TESTED BY: DWIGHT SIMPSON  
OPERATING MODE: NORMAL

DATE: OCTOBER 29, 2006  
TEST NUMBER: 2  
COUPLING DEVICE: EMCO BICONILOG



Photograph Description: Test set-up

FORM CTS-PHOTO

## 2.4 Effective Isotropic Radiated Power Fundamental and Spurious Emissions

### 2.4.1 Equipment Used

| Equipment Used |   | Asset # | Serial #   | Cal Date |
|----------------|---|---------|------------|----------|
| X              | EMC Test Systems Semi-anechoic Chamber    | 667     | N/A        | 10/07    |
| X              | Rohde and Schwarz ESCS30 Test Receiver    | 638     | 826547/024 | 12/06    |
| X              | EMCO 3142B Biconilog Antenna              | 668     | 9903-1357  | 12/06    |
| X              | EMCO Biconical Antenna                    | 679     | 9106-2444  | 11/06    |
| X              | Rohde and Schwarz SML01 Signal Generator  | 689     | 33216      | 10/06    |
| X              | EMCO Multi Device Controller Model 2090   | 639     | 9808-1343  | NCR      |
| X              | EMCO Antenna Mast Model 3801/2NM          | 666     | N/A        | NCR      |
| X              | EMCO Video Camera Controller Model VCC-01 | 653     | N/A        | NCR      |
|                | EMCO Video Camera Model 2075              | 680     | 00183858   | NCR      |

### 2.4.2 Test Conditions

EIRP measurements were performed with the TuneCast 3 - Model F8M010 set up on a wooden table above the turntable at a distance of 3 meters from Biconilog antenna within the semi-anechoic chamber.

The TuneCast 3 - Model F8M010 was configured to operate in the continuous mode of operation to maximize the emissions. The TuneCast 3 - Model F8M010 was tested at the low mid and high frequencies. The TuneCast 3 - Model F8M010 was set up and powered by 3.0 VDC for this test.

### 2.4.3 Test Method

The test method of ESTI EN 300 220-1 Clause 8.3 was followed for the EIRP measurement. A manual signal substitution test was performed. During this test, the antenna, turntable and the EUT were manipulated to maximize the emission level. In accordance with ANI C63.4, the device was positioned to maximize radiation in all three orthogonal planes during preliminary testing.

### 2.4.4 Results

The Belkin Corporation TuneCast 3 - Model F8M010 is fully compliant with the EIRP requirement for the Fundamental and Spurious Emissions of AS/NZS 4268:2003.

No Spurious emissions were detected. The maximum EIRP measured was 20.9 nW at 107.9 MHz.

## 2.4.5 Test Data

### EIRP OF THE FUNDAMENTAL

CUSTOMER: BELKIN CORPORATION  
 EQUIPMENT: TUNECast 3 - MODEL F8M010  
 TESTED BY: MATTHEW HANEL  
 OPERATING MODE: NORMAL

DATE: OCTOBER 30, 2006  
 TEST NUMBER: 5  
 PROCEDURE: ESTI EN 300 220-1 CLAUSE 8.3

| FREQUENCY<br>MHz | Signal<br>Generator<br>-dBm | ANTENNA<br>HEIGHT<br>(METERS) | TURNTABLE<br>AZIMUTH<br>(DEGREES) | ANTENNA<br>H / V | CABLE<br>LOSS<br>dB | NUMERIC<br>GAIN<br>dBi | EIRP<br>-dBm | EIRP<br>nW |
|------------------|-----------------------------|-------------------------------|-----------------------------------|------------------|---------------------|------------------------|--------------|------------|
| 88.1             | -52.3                       | 2.14                          | 336                               | H                | 1.2                 | 1.3                    | -49.8        | 10.5       |
| 98.1             | -54.9                       | 2.23                          | 313                               | H                | 1.2                 | 1.4                    | -52.3        | 5.9        |
| 107.9            | -49.4                       | 2.89                          | 330                               | V                | 1.2                 | 1.4                    | -46.8        | 20.9       |
|                  |                             |                               |                                   |                  |                     |                        |              |            |

Ambient Temperature: 72°F

Humidity: 43%


Atmospheric Pressure: 30.1"

FORM CTS-DS-001R

## 2.4.6 Photographic Documentation

CUSTOMER: BELKIN CORPORATION  
EQUIPMENT: TUNECast 3 - MODEL F8M010  
TESTED BY: MATTHEW HANEL  
OPERATING MODE: NORMAL

DATE: OCTOBER 30, 2006  
TEST NUMBER: 5  
PROCEDURE: ESTI EN 300 220-1 CLAUSE 8.3




Photograph Description: Test set-up

FORM CTS-PHOTO

## Photographic Documentation

CUSTOMER: BELKIN CORPORATION  
EQUIPMENT: TUNECast 3 - MODEL F8M010  
TESTED BY: MATTHEW HANEL  
OPERATING MODE: NORMAL

DATE: OCTOBER 30, 2006  
TEST NUMBER: 5  
PROCEDURE: ESTI EN 300 220-1 CLAUSE 8.3



Photograph Description: Test set-up

FORM CTS-PHOTO

## 2.5 FCC Part 15 Subpart A Radiated Emissions (FCC 47 CFR 15.33)

### 2.5.1 Equipment Used

| Test Equipment |   | Asset # | Serial #    | Cal Date |
|----------------|---|---------|-------------|----------|
| X              | EMC Test Systems Semi-anechoic Chamber    | 667     | N/A         | 10/07    |
| X              | Rohde and Schwarz ESCS30 Test Receiver    | 638     | 826547/024  | 12/06    |
| X              | EMC Test Systems 6512 Loop Antenna        | 787     | 00051667    | 11/06    |
| X              | IBM Personal Computer Model 300XL         | N/A     | 23TMP08     | NCR      |
| X              | EMCO Multi Device Controller Model 2090   | 639     | 9808-1343   | NCR      |
| X              | EMCO Antenna Mast Model 3801/2NM          | 666     | N/A         | NCR      |
| X              | EMCO Video Camera Controller Model VCC-01 | 653     | N/A         | NCR      |
| X              | EMCO Video Camera Model 2075              | 680     | 00183858    | NCR      |
| X              | Quantum Change Tile Software              | N/A     | Version 3.2 | NCR      |

### 2.5.2 Test Conditions

Radiated emissions testing was performed with the EUT set up on a wooden table above the turntable at a distance of 1 meter from the Loop antenna within the Semi-anechoic Chamber.

The Belkin Corporation TuneCast 3 - Model F8M010 was configured to operate in the normal mode of operation to maximize the emissions. The TuneCast 3 - Model F8M010 was set up and powered by 3.0 VDC for radiated emission tests. The worst case signals detected were recorded.

### 2.5.3 Test Method

The test method of FCC Part 15.33 Radio Frequency Devices was followed. The lowest frequency generated or used on this device was identified to be 1.0 MHz; therefore, a manual scan was performed from 1 MHz – 30 MHz. In accordance with ANSI C63.4, the antenna, turntable and the EUT's position was manipulated to maximize the emission levels in a given frequency band displayed on the receiver. The device was positioned to maximize radiation in all three orthogonal planes during preliminary testing.

Subsequently, an automated scan was performed in 3 antenna polarizations to maximize the emissions from the EUT using the Quantum Change Tile Software.


### 2.5.4 Results

Peak measurements recorded across the frequency range of 1 – 30 MHz revealed no signals that were within 6dB of the limit. The Belkin Corporation TuneCast 3 - Model F8M010 meets the requirements for radiated emissions as required by FCC Part 15.33.


Belkin Corporation TuneCast 3 - Model F8M010  
Document #: TRR0361.06 Rev. 2  
Date: November 29, 2006

## 2.5.5 Test Data

### Low Frequency 88.1 MHz – X Polarization



### Low Frequency 88.1 MHz – Y Polarization



Ambient Temperature: 72°F

Humidity: 46%


Atmospheric Pressure: 30.3"

Belkin Corporation TuneCast 3 - Model F8M010

Document #: TRR0361.06 Rev. 2

Date: November 29, 2006

# Low Frequency 88.1 MHz – Z Polarization




Ambient Temperature: 72°F


Humidity: 46%

Atmospheric Pressure: 30.3"

### Middle Frequency 98.1 MHz – X Polarization



### Middle Frequency 98.1 MHz – Y Polarization



Ambient Temperature: 72°F

Humidity: 46%


Atmospheric Pressure: 30.3"

Belkin Corporation TuneCast 3 - Model F8M010

Document #: TRR0361.06 Rev. 2

Date: November 29, 2006

# Middle Frequency 98.1 MHz – Z Polarization




Ambient Temperature: 72°F


Humidity: 46%

Atmospheric Pressure: 30.3"

## High Frequency 98.1 MHz – X Polarization



## High Frequency 98.1 MHz – Y Polarization




Ambient Temperature: 72°F

Humidity: 46%

Atmospheric Pressure: 30.3"

## High Frequency 98.1 MHz – Z Polarization



Ambient Temperature: 72°F

Humidity: 46%

Atmospheric Pressure: 30.3"

### 2.5.6 Photographic Documentation

CUSTOMER: BELKIN CORPORATION  
EQUIPMENT: TUNECast 3 - MODEL F8M010  
TESTED BY: MATTHEW HANEL  
OPERATING MODE: NORMAL

DATE: OCTOBER 30, 2006  
TEST NUMBER: 3  
FCC SUBPART C 15.33



Photograph Description: Test set-up

FORM CTS-PHOTO

## Photographic Documentation

CUSTOMER: BELKIN CORPORATION  
EQUIPMENT: TUNECast 3 - MODEL F8M010  
TESTED BY: MATTHEW HANEL  
OPERATING MODE: NORMAL

DATE: OCTOBER 30, 2006  
TEST NUMBER: 3  
FCC SUBPART C 15.33



Photograph Description: Test set-up

FORM CTS-PHOTO

## **APPENDIX A**

### **TEST LOG**


## TEST LOG

CUSTOMER: BELKIN CORPORATION

PROGRAM: EMISSIONS

EQUIPMENT: TUNECast 3 - MODEL F8M010

TESTED BY: DWIGHT SIMPSON

|                                  |                        |   |                               |  |   |                                    |               |
|----------------------------------|------------------------|---|-------------------------------|--|---|------------------------------------|---------------|
| <b>Pre-Test Checklist</b>        | Date                   | Comments  |                               |  |   |                                    |               |
|                                  | October 26, 2006       | Test Plan/Procedure: ANSI C63.4 & ESTI EN 300 220-1 Clause 8.3<br>Test Specification: FCC Part 15 Subpart C 15.209 and 15.239<br>Chomerics Procedure: CHO TPECROC T1, T2<br>EUT Power Requirement Verified:<br>Voltage 3.0 VDC    Frequency N/A    Phase N/A<br>EUT Functional Operational Check: [ X ] Pass    [ ] Fail<br>Environmental: Bonding/Grounding: N/A    Safety Issues: N/A |                               |  |   |                                    |               |
| <b>In-Process Test Checklist</b> | Date                   | Test #  | Test Type                     | Test Equipment Calibrated  | Test Performed Properly – Data Accepted | EUT Set-up Check/Operational Check | EUT Pass/Fail |
|                                  | 10.26.06               | 1   | FCC 15.239 Radiated Emissions | Yes  | Yes                                     | Yes                                | Pass          |
|                                  | 10.26.06-10.29.06      | 2   | FCC 15.209 Radiated Emissions | Yes  | Yes                                     | Yes                                | Pass          |
|                                  | 10.30.06               | 4   | -26 dB Width Measurements     | Yes  | Yes                                     | Yes                                | Pass          |
|                                  |                        |   |                               |  |   |                                    |               |
|                                  |                        |   |                               |  |   |                                    |               |
|                                  |                        |   |                               |  |   |                                    |               |
|                                  |                        |   |                               |  |   |                                    |               |
|                                  |                        |   |                               |  |   |                                    |               |
|                                  |                        |   |                               |  |   |                                    |               |
|                                  |                        |   |                               |  |   |                                    |               |
| <b>Post Test Checklist</b>       | Date: October 30, 2006 | EUT Functional Operation Check:<br>[ X ] Pass    [ ] Fail   |                               | <br>Test Engineer/Tech    Approved Signatory |   |                                    |               |

FORM CTS-010

Belkin Corporation TuneCast 3 - Model F8M010



Document #: TRR0361.06 Rev. 2

Date: November 29, 2006

## TEST LOG

CUSTOMER: BELKIN CORPORATION  
EQUIPMENT: TUNECast 3 - MODEL F8M010

PROGRAM: EMISSIONS  
TESTED BY: MATTHEW HANEL

|                                  |                        |   |                                       |   |   |                                    |               |
|----------------------------------|------------------------|---|---------------------------------------|---|---|------------------------------------|---------------|
| <b>Pre-Test Checklist</b>        | Date                   | Comments  |                                       |   |   |                                    |               |
|                                  | October 30, 2006       | Test Plan/Procedure: ANSI C63.4 & ESTI EN 300 220-1 Clause 8.3<br>Test Specification: FCC Part 15 Subpart C 15.33 & AS/NZS 4268:2003<br>Chomerics Procedure: CHO TPECROC T1, T2<br>EUT Power Requirement Verified:<br>Voltage 3.0 VDC Frequency Single Phase Single<br>EUT Functional Operational Check: <input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail<br>Environmental: Bonding/Grounding: NA Safety Issues: NA |                                       |   |   |                                    |               |
| <b>In-Process Test Checklist</b> | Date                   | Test #  | Test Type                             | Test Equipment Calibrated   | Test Performed Properly – Data Accepted | EUT Set-up Check/Operational Check | EUT Pass/Fail |
|                                  | 10.30.06               | 3   | FCC 15.33 Radiated Emissions          | Yes   | Yes                                     | Yes                                | Pass          |
|                                  | 10.30.06               | 4   | -26 dB Width Measurements (Continued) | Yes   | Yes                                     | Yes                                | Pass          |
|                                  | 10.30.06               | 5   | EIRP                                  | Yes   | Yes                                     | Yes                                | Pass          |
|                                  |                        |   |                                       |   |   |                                    |               |
|                                  |                        |   |                                       |   |   |                                    |               |
|                                  |                        |   |                                       |   |   |                                    |               |
|                                  |                        |   |                                       |   |   |                                    |               |
|                                  |                        |   |                                       |   |   |                                    |               |
|                                  |                        |   |                                       |   |   |                                    |               |
| <b>Post Test Checklist</b>       | Date: October 30, 2006 | EUT Functional Operation Check:<br><input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail   |                                       | <br>Test Engineer/Tech  |   |                                    |               |
|                                  |                        |   |                                       | <br>Approved Signatory |   |                                    |               |

FORM CTS-010

Belkin Corporation TuneCast 3 - Model F8M010  
Document #: TRR0361.06 Rev. 2  
Date: November 29, 2006