Go to www.vtechphones.com to register your product for enhanced warranty support and the latest VTech

VM928-2HD Full Color Pan and Tilt HD Video Monitor

VM928HD



vtech Quick start quide



The mean security and sound the was dreated by zarabadeu, and is used under the creative commons noeries. The Bodggound Noise sound file was created by Caroline Ford, and is used rose freather commons from The Bodggound Noise sound file was created by Caroline Ford, and is used under the Ceraline Commons license. The Crises A Might sound file was received by Miles Rectard, and is used under the Creative Commons license. The Beard Review of Miles and Service of the Miles Rectard and a seed under the Creative Commons license.

Power requirements	Parent unit: 3.7V 5000mAb, 18.7Wh Lithium-ion battery Baby unit power adapter: Output: 5V DC @ 1A Parent unit power adapter: Output: 5V DC @ 2A
Nominal effective range	Maximum power, allowed by FCC and IC. Actual operating range may vary according to environmental conditions at the time of use.
rcp	(IbZ TSB0x\JS0 bixels)
Channels	35
Transmit frequency	sHə2f4.5-204.5 :tinu yde8

Fredneucy control Crystal controlled FLL synthesizer TECHNICAL SPECIFICATIONS

Press @ to zoom in or out

IMPORTANT SAFFTY INSTRUCTIONS

- rry, including the following: Follow all warnings and instructions marked on the product. equired.
- This product is intended as an aid. It is not a substitute for responsible and proper adult supervision and should not be used as such.
- swimming pool, or in a wet basement or shower.

 CAUTION: Use only the battery provided. There may be a rist of explosion if a wrong type of battery is used for the parent unit. The battery cannot be subjected to high or low extreme temperature and low air pressure at high affitted during use.
- temperature and low air pressure at high affluide during use stronge or francopartation. Disposal of battery into fire or a hot oven, or mechanically cruziling or cutting or the battery can exult in an explosion. Leaving the battery in an extremely high temperature survivouring environment of part attery high temperature survivouring environment of part attery subjected to extremely low air pressure may receib in an explosion or the leakage of flammable liquid or gas. Dispose of used battery according to the information in The RBRC seal.

Power adapter inform VTech Telecommunications Ltd. Model: VT05EUS05100 Unit Output: 5V DC 2A VTech Telecommunication
Model: VT07EUS0S200

Rechargeable battery information Zhuhai Great Power Energy Co., Ltd. Model: GSP806090-SAh-3.7V-1S1P

For pluggable equipment, the socket-outlet (power adapter shall be installed near the equipment and shall be easily

accessible. Unplug this product from the wall outlet before cleaning. Do not use liquid or aerosol cleaners. Use a damp cloth for cleaning. Do not cut off the power adapters to replace them with other plugs, as this causes a hazardous situation.

Do not allow anything to rest on the power cords. Do not install this product where the cords may be walked on or

all power company.

e equipment is to be supplied from an identified USB port mplying with the requirements of Limited Power Source.

not overload wall outlets or use an extension cord.

not place this product on an unstable table, shell, stand or

 This product should not be placed in any area where proper ventilation is not provided. Slots and openings in the back or radiator or heat register.

Press MENU to enter the menu, choose a

menu item, or save a setting. You can use

operations, such as to play or stop the baby

unit lullaby, or to adjust the baby unit sound

Press ∧, ∨, <or> to scroll among the

Press TALK to return to the live video.

Press SELECT to select an item, or to save

ice the risk of electric shock, do not disassem

n carnage. here is a very low risk of privacy loss when using certain elec

itc. To protect your privacy, make sure the product has n seen used before purchase, reset the balov monitor per

Use and store the product at a temperature between 32°F and 104°F. Burn hazard, fire hazard, explosion hazard associated with mishandling of the battery

Do not expose the product to extreme cold, heat or direct sunlight. Do not put the product close to a heating source. Do not expose the production of the production o

Children have \$TRANGEED in cords. Keep this cord out of the need of children (more than 3 it (0.9m) away). Do not remove this 1st, (0.9m) away). Do not remove this 1st, or hower place the camera unitify) inside the baby's crib or playpan. Newer cover the camera unitify) balance crib or playpan. Newer cover the camera unitify) balance (but the control of the control of the cover the camera unity) balance unit. Typ (stalling your camera unit as far away from these electronic flowices as possible; wireless routiers, radio

utions for users of implanted cardiac pacemaker cardiac pacemakers. Supported by the U.S. Food and Drug Ariministration. WTR recommends to physicians that

tients on wireless devices at least six inches from the


Flectromagnetic fields (FMF)

This VTech product complies with all standards regarding electromagnetic fields (EMF). If handled properly and acc

0

((<

WHAT'S IN THE BOX



CONNECT THE BABY MONITOR

⊞NOTES

The rechargeable battery in the parent unit is built-in Use only the power adapters supplied with this product


Make sure the parent unit and the baby unit are not connected to the switch controlled electric outlets. Connect the power adapters in a vertical or floor me

Make sure the parent unit, the baby unit and the power adapter cords are out of reach of children.

mpliance with the ECC's RF exposure quidelines place the baby unit at least 20cm from nearby person

Raise the parent unit antenna for better reception






screen appears

CONNECT THE BABY MONITOR (CONT'D)

Charge the parent unit battery before use









To avoid interference from other electronic devices, place your baby monitor at least 3 feet (1 meter) away from devices such as wireless routers, microwaves, cell phones and computers



The default volume of your parent unit is level 3, and the maximum volume is level 5. If you experience high-pitched screeching noise from your baby monitor while positioning:

Make sure your baby unit and parent unit are more than 3 feet (1 meter) apart, OR Lower the volume of your parent unit.

4 STATUS CHECK

baby unit and parent unit, your parent unit displays image from the baby unit, and the LINK LED

The green LED light of the baby unit turns on.



BASIC OPERATION - PARENT UNIT

Adjust speaker volume

Press - VOL/ VOL+ to adjust your parent unit speaker volume. It determines the volume of sound transmitted from your baby unit.



Talk to your baby via the baby unit 1. Press and hold the TALK key.

- 2. When the licon displays on screen, speak to your parent unit. Your voice is transmitted to the baby unit.
- When finish talking, release the TALK key and hear your baby again.



Turn on/off the parent unit screen

- You can turn on or off the parent unit screen without powering off the parent unit. You can still hear sound from the baby unit.
 - Press POWER on the parent unit to turn off the screen.
 - Press any keys on the parent unit to
 - turn on the screen again



Press to go to the Help & info page.

× Q

آ@

Use the menu


sensitivity.

While in the menu:

menu options

a setting.

OVERVIEW - PARENT UNIT




- **■** LED light
- Θ. When in the main menu press to go to the Help & Info page.
- TALK Press and hold to talk to the haby unit
- MENU/SELECT

 Press to enter 11 Speaker
 - 12 POWER key
- VOL/ VOL+

- 13 Power iack 14 RESET
- 15 Stand





- Camera lens
- Light sensor
- LED indicator
- Infrared LEDs
- 6 U ON/OFF switch 7 Antenna
- Position the sensor horizontally for its optimal usage
 - 10 Power jack
 - 11 Threaded socket for wall mounting

0


W,

1

- 12 Pair button

NEED HELP?

For operations and guides to help you using your video monito and for latest information and supports, go and check the online help topics and online FAQs



Scan the QR code on the right. Launch the camera app or QR code scanner app or your smartphone or tablet. Hold the device's camera up to the QR code and fame It. Tap the notification to rigger the redirection of the online help.

- If the QR code is not clearly displayed, adjust your camera's focus by moving your device closer of further away until it is clear.

ou can also call our Customer Support at 1 (800) 595-9511 [in US] or (800) 267-7377 [in Canada] for help.









PARENT UNIT ICONS

Main menu icons

(•

Monitoring mode (For VM928-2HD only



Baby unit 1 in Single mode

· Select play all melodies or play one of the five melodies and four soothing sounds





Alerts - Sound, motion and temperature

- Select sound Sensitivity level
- Turn on/off Auto Wake Up function. (See Sound Detection and Auto Wake Up section)

Turn on/off Motion Alert.

 Select motion Sensitivity level. (See Motion Detection section)

Main menu

Baby unit 2 in Single mod

12 Split mode

Melodies and soothing sounds

Melodies and Soothing Sounds

You can also set the timer to stop playing after 15, 30 or 60 minutes, or playing non



- Turn on/off Sound Detection Alert.

Temperature Turn on/off Temperature Alert. Set the parent unit to beep whenever the room temperature detected by the baby

unit falls outside of the set temperature Select Minimum temperature for alert

Select Maximum temperature for alert

range. Select temperature Format. Set temperature display in Fahrenheit (°F)

Parent unit settings

 Adjust parent unit screen Brightness Turn on/off Dim Mode.

or Celsius (°C)

Baby unit settings



Turn on/off baby unit's Status LED.

 Select Field of View Choose Wide angle 🖾 or Standard 🔠 Adjust baby unit's speaker Volume.



 Turn on/off Low Battery Alert Tone Set the parent unit to beep when the battery is low.

 Turn on/off No Link Alert Tone Set the parent unit to beep when the link between the parent unit and the baby unit

Status icons

. The haby unit number that is being viewed

 Single CAM mode. Patrol mode (* For VM928-2HD only).

- Split mode (* For VM928-2HD only)

Split mode (* For VM928-2HD only) \Box


(* For VM928-2HD only) Night vision feature is activated automatically.

Motion alert is turned on.

Sound detection alert is turned on.


Melodies or soothing sound are turned on Parent unit speaker is muted.

Displays when parent unit's battery is low and needs charging.



Temperature alert is turned on





Baby unit detects temperature is lower than the set minimum.



Sound Detection and Auto Wake UP

Adjust sound detection sensitivity

You can turn on Sound Detection Alert and adjust the Sound Sensitivity to detect sounds and turn on the parent unit while its screen is switched off or dimmed

When the baby unit detects sounds that exceed certain levels, the parent unit screen will turn on and the baby unit starts transmitting the sounds to the parent unit, and you can

If you have turned on **Sound Detection Alert**, the parent unit beeps when the baby unit

Level 3 (Highest)	Level 2 (Medium)	Level 1 (Lowest)
9	9	2.
The parent unit screen and speaker turn on for very small sounds, including background noises from your baby's room.	The parent unit screen and speaker turns on for loud babbling and louder sounds from your baby. The parent unit remains quiet when your baby makes soft sounds.	The parent unit screen and speaker turn on for loud crying or screeching sounds from your baby. The parent unit remains quiet when your baby makes soft sounds.

Sound activated screen and audio - Auto Wake Up


When Auto Wake Up is turned on the parent unit screen stays off to save power when the baby unit detects no sound

detects no sound.

Once the baby unit detects sounds that are louder than the chosen sound sensitivity level, the parent unit screen and speaker turn on automatically. The parent unit will then turn of flaggin after 50 seconds of no sound detection.

■Notes If you have muted the parent unit speaker, only the parent unit screen will turn on when a sound is detected.

If you have turned on Auto Wake
Up but turned off Sound Detection
Alert, the parent unit will wake up
when the baby unit detects sounds that are louder than the chosen sound





Adjust motion detection sensitivity

You can turn on Motion Alert and adjust the Motion Sensitivity to detect motions and turn on the parent unit while its screen is switched off or dimmed.

When the baby unit's camera detects motions that exceed certain levels, the parent unit screen will turn on and the baby unit starts transmitting the sounds to the parent unit, and you can see and hear your baby

If you have turned on Motion Alert, the parent unit beeps when the baby unit detects

	Level 3 (Highest)	Level 2 (Medium)	Level 1 (Lowest)
	* ***	*	*
Description	The parent unit screen and speaker turn on for small motions, such as yawning or stretching.	The parent unit screen and speaker turns on for normal daily motions, such as people walking around the house.	The parent unit screen ar speaker turn on for large motions, such as children are chasing or jumping around.

NIGHT VISION



The baby unit has infrared LEDs that allow The bary unit has intrafed LEUS that allow you to see your baby clearly at night or in a dark room. When the baby unit being viewed detects low light levels, the infrared LEDs are switched on automatically. The images from the baby unit are in black and white, and a papears on the screen.

Notes

- It is normal if you see a short white glare on your parent unit screen as the baby unit is adapting to the dark environment. When the infrared LEDs are on, the images are in black and white. This is normal.
- 8% Tip
- Depending on the surroundings and other Depending on the surrouncings and other interfering factors, like lightings, objects, colors and backgrounds, the video quality may vary. Adjust the baby unit's angle or place the baby unit at a higher level to prevent glare and blurry display.

FOR VM928-2HD ONLY

Monitoring mode







Ŋ,





Select Split mode as your monitoring mode to view the images from both baby units at once. ■ Note

While in Split mode, you can press < or > to highlight the view of the baby unit 1 1 rill or

MOUNT THE BABY UNIT ON DRY WALL (OPTIONAL)

MOTES

- ita. Af the coult. Year many moned to more have the second and anothers consented at many at once habit contra
- a pencil to mark the top and the bottom holes as shown. Remove the wall mount bracket and drill two holes in the wall (7/32 inch drill bit).



- 2. If you drill the holes into a stud, go to step 3.
- If you drill the holes into an object other than a stud, insert the wall
 anchors into the holes. Tap gently on the ends with a hammer until the wall anchors are flush with the wall.

3. Align the wall mount bracket and screws with the holes in the wall as shown. Tighten the screw in the middle hole first, so that the wall mount bracket position is fixed. You can tighten the other screw in the top hole.

4. Place the baby unit on the wall mount bracket.

bottom to secure the baby unit

Tighten the screw into the threaded socket at the



3. Insert the screws into the holes and tighten the screws until only 1/4 inch



4. Place the baby unit on the wall mount bracket. Tighten the screw into the threaded socket at the bottom to secure the baby unit. Align the holes on the wall mount bracket with the screws on the wall, and slide the wall mount bracket down until it locks into place.



5. You can maximize your baby unit's viewing angles by tilting the wall mount bracker Hold the baby unit, and then rotate the knob in anticlockwise direction. This will loosen the joint of the wall mount bracket. Tilt your baby unit up or down to adjust to your preferred angle. Then, rotate the knob in clockwise direction to fighten the joint and





■ DIM MODE

The parent unit display will dim to conserve energy after 5 minutes of inactivity, in which there is neither key pressed nor alert received from the baby unit









CABLE MANAGEMENT







monitor produce a high-pitched noise?

^Q_A Frequently asked questions Below are the questions most frequently asked about the baby monitor.

Try the following (in the order listed) for com-

Why does the baby monitor not respond normally? Disconnect the power to the baby units and the parent unit.

Wait a few seconds before connecting power back to the baby units and the parent unit.
 Turn on the baby units and the parent unit.

Wait for the parent unit to synchronize with the baby units. Allow up to one minute for this to take place.

Why don't the lights of Perhaps the parent unit's battery is depleted. Insert the appliance plug into the parent unit and put the adapter in a wall socket. The parent unit will establish connection with the baby unit.

baby unit and put the adapter in a wall socket. Then, slide the Θ **ON/OFF** to switch on the baby unit and to establish connection with the parent unit.

Make sure the power is not controlled by a wall switch

ected to AC nower?

Why is my screen in black
The screen is in black and white during night-time or in a dark room when the night vision feature is activated. This is normal.

During night-time or in a dark room, the surroundings and other interfering factors, like lightings, objects, colors and backgrounds may affect the image quality on your parent unit screen. Adjust the baby unit's angle or place the baby unit at a higher level to Why do I get glare or screen when viewing my baby at night? prevent glare and blurry display. Why does the baby

The parent unit and baby units may be too close to each other Move the parent unit away from the baby units until the noise stops; OR Turn down the volume of your parent unit.

Why does the parent unit The baby units may be out of range. Move the parent unit closer to the baby units (but been?

The parent unit may not have enough charge for the parent unit to perform norr Charge the battery in the parent unit until the battery icon becomes solid The temperature of your baby's room may be too high or too low.

Why don't I hear a count/ The perent unit meaker volume may be too low Press VOI a to increase the vol Why can't I hear my baby use the parent unit menu to change sound sensitivity level to the highest level.

The baby units may be out of range. Move the parent unit closer to the baby units (but not less than 3 feet).

you have powered on via menu.

If you power on only one baby unit, your parent unit may display Make sure baby unit X is on or move closer to baby unit X, and the LINK LED light flashes. Switch to the baby unit

THE RBRC SEAL



*** Insurance waste, which may be integal in your area.

**Yeich's participation makes it easy for you to drop of the spent battery at local retailers participating in the program of at authorized VTech product service centers. Please call 1,800 g BATTERY for information on Li-inb battery recycling a disposal banary/estrictions in your area. VTech involvement in this procrams is sard of its commitment to not restriction.

The RBRC Seal and 1 (800) 8 BATTERY® are registered trademarks of California Inc.

FCC AND IC REGULATIONS

This equipment has been tested and found to comply with the requirements for a Class B digital device under Part IS of the Federal Communications Communication (Communications Communications Communications Communications Communications Communications and Part IS of the Federal Communications and Part I Part I

- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected. Consult the dealer or an experienced radio/TV technician for help.

WARNING: Changes or modifications to this equipment not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This Class B digital apparatus complies with Canadian requirement: CAN ICES-3 (B)/NMB-3(B)

Industry Canada

.. rm "IC." before the certification/registration number only signifies that the Industry Canada technical specifications wer

oduct meets the applicable Innovation, Science and Economic Development Canada technical specifications RF radiation exposure statement

CALIFORNIA ENERGY COMMISSION BATTERY CHARGING TESTING MODE

This baby monitor moets the California Energy Commission (ECC) regulations for energy consumption. Your baby monitor is set up to comply with the energy conserving standard ingly out of the box. Follow in the instructions to install and charge the battery. The CEC battery charging testing mode is activated while charging. Even if the parent unit is paired to baby units, the CEC battery charging reting mode is activated while it is powered of and chargen.

FOR CETL COMPLIANCE ONLY

Mesures de sécurité importantes La plaque signalétique appliquée est située au bas du socie de l'unité La plaque signalétique appliquée est shuée au des ou souve du beble du beble de la commentation de la commen

Observez toutes les instructions et mises en garde inscrites sur

- 'installation par un adulte est requise. MISE EN GARDE: N'installez pas l'unité du bébé à une hauteur
- super nouve a £ mittres.

 Ce produit a dé conçu pour être un dispositif d'appoint seulement.

 Il n'est pas le remplacement d'une supervision responsable et adéquate per un aduté et he devrait pas être utilisé comme telle.

 Ce groduit n'est pas conçu pour être utilisé en tant que moniteur.
- medical.

 Nutilise pas ce a appareil prist de l'assu ni de toute autre source
 Nutilise pas ce a appareil prist de l'assu ni de toute autre source
 Nutilise pas ce annut, puis chi une polipholise, cur à à locoix
 nutilise pas ce annut puis ce d'une polipholise, cur à à locoix
 nutilise pas ce annut puis ce autre de l'assuré de la commandate pas de l'assuré de l'assuré

Adaptateur de l'unité du bébé; Sortié : 5 V CC 1A. Adaptation for time du pouce, some : 3 v CC 2A.
VTech Telecommunications Ltd.
Modéle : VTDSELSOS.100
Adaptateur de l'unité du parent: Sortie : 5 V CC 2A.
VTech Telecommunications Ltd.
Modéle : VTDTELSOS.200

Modèlie: YTD7EU Suszuu

| The properties of the piles rechargeables: 3,74 SOQMAR, 18, SWh Lithium-ion Battery
Zhuhai Great Power Brangy Co., Ltd.
Modèle: GSP80009-SAR-374SIP
| orsau'ils sont branchis dans une prise de courant, les adaj
| orsau'ils sont branchis dans une prise de courant, les adaj

- Pour les appareils raccordés, la prise de courant (de l'adaptateur secteur) doit être installée prês de l'équipement et doit être
- Ne laissez aucun objet reposer ni appuyer sur le cordon d'alimentation. N'installez pas cet appareil dans un endroit où
- Pon risque d'écraser le coroon or aramémanion ou une permission. Ne faites fonctionner cet appareil qu'avec le type d'alimentation indiqué sur l'étiquette. Si vous ne connaissez pas le type d'alimentation que vous possèdes à votre domicle, consultez votre distinction que vous possèdes à votre domicle, consultez votre des l'étiques de l'étiqu
- Ne placez pas cet appareil sur un chariot, meuble, trépied, support de montage ni table chancelants.

- Transport. I d'ilimination faits pais clans de les ou directs in fold c'haud our l'entirement ou l'actionation provincipau de la pile pauvert our l'entirement ou l'actionation provincipau de la pile pauvert température extérimenter dévivel pour entraîner une explosion température extérimenter dévivel pour entraîner une explosion à une preston d'en entirementer la bespe puit provoquer une explosion ou une faite de la qualde ou de pas influentemable. Effernier Multillez que les explosites une faite pour product d'un fait des la comment de la comment de la commente de la commente d'un adaptiture d'un production de la fonction possir nacionation format de la commente de la commente de la commente socialment port.

- Lorsqu'ils sont branchés dans une prise de courant, les adaptateurs secleur ont été concus pour être orientés correctement, soit à la verticale ou au plancher. Les broches ront pas été concues pour supporter le poids du bloc d'alimentation et le maintenir en plac si celuid est branché dans une prise au plationd, sous une table ou sous de la prise au plationd, sous une table ou
- Débranchez ce produit de la prise de courant avant de procéder au nettoyage. Nutilisez pas de nettoyants en aérosols. Utilisez un réliffon humidos.
- chimon numide pour le nemoyer. 12. Ne coupez pas les cordons d'alimentation pour remplacer les fiches, car céci peut présenter un danger potentiel.
- Indiqué sur l'étiqueme, as voes de déficience, consumé son d'alimentation que lous posséde à votre domicile, consumé son d'alimentation que lous posséde à votre d'électricité.
 L'équipement doit être fournit à partir d'un acquisecement gauche identifié d'USB aux conditions de la source d'énergie limitée.

 Le voites de courant murales ni les rationges

- source de chaleur ou d'un calorifère. De plus, ne placez pas l'appareil dans un endroit avant de vous assurer qu'il y ait une bonne circulation d'air.
- bórine circulation d'air.

 N'enfoncesjamais d'objets à travers les ouvertures d car ils pourraient entrer en contact avec des poir dangeteux ou causer des courts-circults qui pouve en incendies ou en risques d'électrocution. Ne rer de liquide dans ce produit. ou sujuide dans ce produit.

 Afin de réduire les risques d'électrocution, ne démontez pas cet appareil, mais apportez-le dans un centre de service autorisé.

 L'ouverture du bolitier ou le retrait de toutes pièces que contient cet appareil, à l'exception de l'accès autorisé à confient
- ou apparen, e rexcepsion de racces autorisé à certaines portes ou ouvertures, risque de vous exposer à des points de tension dangereux ou d'autres dangers. Un remontage incorrect peut par la suite présenter des risqués d'électrocution ia suns presented des risques d'electrocumon.

 Vous devriez tester la réception chaque fois que vous mettez l'appareil en fonction.

 Examinez les composantes afin de vérifier si celles-ci ne sont pas conferences de la composante de la conference de la conferenc
- endommagees.

 Il existe un très faible risque de perte de confidentialité avec certains appareils électroniques (autres écoute-béhés Ménhones
- Jouent pas avec rappareil.

 Les petites pièces de ce moniteur peuvent être avalées par les bébés ou les petits enfants. Veuillez tenir ces pièces hors de portide des enfants. Le produit rivest pas conçu pour être utilisé par des personnes (incluant des enfants) aux capacités physiques, sensorielles ou mentales réduites ou qui manquent d'appérience et de ou mentales réduites ou qui manquent d'appérience et de supervision ou frantactions relativement à l'utilisation de l'appareil par une personne responsable de leur decurrent.

CONSERVEZ CES INSTRUCTIONS Vises en garde

- Utilisez et entreposez le produit à une température entre 0° C (32°F) et 40°C (104°F). Risque de brûlure, risque d'incendie, risque d'explosion associé à une mauvaise manipulation de la batterie. N'exposez pas cet appareil à des froids ou des chaleurs extrêmes, ainsi qu'à la lumière directe du soleil. Ne l'installez pas près d'une sourcé de chauffage.
- when the programmer is a contract to the formal part point of the contract of
- Product whose warranty/quality stickers, product serial number plates or electronic serial numbers have been removed, altered or rendered illegible; or removed, altered or rendered flegible; or
 8- Product purchased, used, serviced, or shipped for repair
 from outside the United States of America or Canada, or
 used for connected for inhalthod purposes pickeding
 or
 set of the Connected for the Connected for
 product returned without a wild proof of purchase (pee
 file 20 below). The Connected for
 10- Product returned without a wild proof of purchase
 10- file and
 10- file of the Connected for
 10- file of the Connected for
 10- file of
 10 du simulateur cardiaque. Ils ne doivent PAS placer le téléphone sans fil directement sur le stimulateur cardiaque, tel que dans une poche de chemise, lor-sque colui-ci est en marche.
- sque celui-ci est en marcne. L'étude effectuée par l'organisme WRS n'a pas identifié de risque pour les détenteurs de simulateurs cardiaques causés par les gens qui utilisent dispositifs sans fil à proximité de ceux-d.

LIMITED WARRANTY

How long is the limited warranty period? dow long is the limited warranty period:

(he limited warranty period for the product extends for ONE (1) YEAR from date of purchase (90 days on products purchased as Refurbished'). This limited warranty also replacement Products for a period of either (a)

applies to replacement Products for a period of eith 90 days from the date the replacement Product is sh to you or (b) the time remaining on the original one-limited warranty (90-day limited warranty on produare purchased as Refurbished'). Whichever is longe

What is not covered by this limited warranty? what is not covered by this limited warranty?

This limited warranty does not cover:

1. Product that has been subjected to misuse, accident, shipping or other physical damage, improper installat abnormal operation or handling, neglect, inundation, fire, water or other liquid intrusion; or

*Refurbished products purchased from our online store carry a 90-day replacement warranty.

Product to the extent that the problem experienced is caused by signal conditions, network reliability, or cable or

To obtain warranty service in the United States of America, please visit our website at www.vtechphones.com or call 1 (800) 955-9511 for instructions regarding where to return the Product In Canada, go to phones.vtechcanada.com or dial 1 (800) 267-7377. The manufacturer of this VTech product, VTech Communications, inc. ("VTech"), warrants to the holder of a valid proof of purchase ("Consumer" or "you") that the Product and all accessories provided by VTech in sales package ("Product") are free from material defect

What will VTech do if the Product is not free from defects

- service?

 1. Return the entire original package and contents includ the Product to the VTech service location along with a description of the malfunction or difficulty, and 2. Include a "valid proof of purchase" (sales receipt) identifying the Product purchased (Product model) and the date of purchase (product model) and the date of purchase or eceipt; and

Provide your name, complete and correct mailing address, and telephone number. Other limitations

Other imitiations. This warranty is the complete and exclusive agreeme between you and VTech. It supersedes all other written or oral communications related to this product. VTecl provides no other warranties for this product. The we exclusively describes all of VTech's responsibilities regarding the product.

There are no other expressed warranties. No one is authorized to make modifications to this warranty and yo should not rely on any such modification. State Law Rights: This warranty gives you specific legal rights, and you also have other rights which vary from stat to state.

Limitations: Implied warranties, including those of fitness for climatation. Implication was families, including indoor on fillies to on fillies to a particular purpose and merchantantability (an unwritten warranty that the product is fill for ordinary use) are limited to one year from date of purchase. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation was not apply to you.

above limitation may not apply to you. In no event shall ViRich be liable for any indirect, special, incidental, consequential, or, similar dramages (including, but not limited to lost profils or revenue, inability to use the product, or other associated equipment, the cost of substitute equipment, and claims by third parinel yrestillor from the use of this product. Some states of on all low the exclusion or imitation of incidental or consequential damages, to the above limitation or exclusion may not apply to you.

Please retain your original sales receipt as proof of purchase.