



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V04

Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No. : CQASZ20210701128E-02
Applicant: XIAMEN COMFORT SCIENCE & TECHNOLOGY GROUP CO., LTD.
Address of Applicant: (5/F) NO.168, QIANPU ROAD, SIMING DISTRICT, XIAMEN, CHINA.
Equipment Under Test (EUT):
Product: Massage Chair
Model No.: EI-8602A, OS-Hiro LT
Test Model No. OS-Hiro LT
Brand Name: N/A
FCC ID: YMX-EI8602A-02
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2021-07-20
Date of Test: 2021-07-20 to 2021-08-11
Date of Issue: 2021-09-03
Test Result : PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

Lewis Zhou

(Lewis Zhou)

Reviewed By:

Rock Huang

(Rock Huang)

Approved By:

Jack ai

(Jack ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20210701128E-02	Rev.01	Initial report	2021-09-03

2 Contents

	Page
1 VERSION.....	2
2 CONTENTS.....	3
.....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
4 RF EXPOSURE EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 Limits.....	5
4.1.2 Test Procedure.....	5
4.1.3 EUT RF Exposure Evaluation standalone operations.....	6

3 General Information

3.1 Client Information

Applicant:	XIAMEN COMFORT SCIENCE & TECHNOLOGY GROUP CO., LTD.
Address of Applicant:	(5/F) NO.168, QIANPU ROAD, SIMING DISTRICT, XIAMEN, CHINA.
Manufacturer:	XIAMEN HEALTHCARE ELECTRONIC CO., LTD.
Address of Manufacturer:	65-66#, 62-63#Building, Siming Zone, Tongan Industrial District, Xiamen City, Fujian Province, P.R. China
Factory:	XIAMEN HEALTHCARE ELECTRONIC CO., LTD.
Address of Factory:	65-66#, 62-63#Building, Siming Zone, Tongan Industrial District, Xiamen City, Fujian Province, P.R. China

3.2 General Description of EUT

Product Name:	Massage Chair
All Model No.:	EI-8602A, OS-Hiro LT
Test Model No.:	OS-Hiro LT
Trade Mark:	N/A
EUT Supports Radios application	2402-2480MHz
Hardware Version:	WLT3266_V1.1
Software Version:	M27_V28.13.0
Power Supply:	Rating: 110-120V~ 60Hz Rated current: 1.4A
Product Type:	☐ Mobile ☐ Portable ☒ Fix Location
Test Software of EUT:	FCCAssist 1.0.0.2
Antenna Type:	PCB antenna
Antenna Gain:	3dBi

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure Evaluation standalone operations

1) For BT Classic (for CSR chip)

Antenna Gain: 3dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.995 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-0.550	-1.5±1	-0.5	0.891
Middle(2441MHz)	0.540	0±1	1.0	1.259
Highest(2480MHz)	2.020	1.5±1	2.5	1.778
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	0.100	-0.5±1	0.5	1.122
Middle(2441MHz)	1.120	0.5±1	1.5	1.413
Highest(2480MHz)	2.540	2.0±1	3.0	1.995
8DPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	0.980	0±1	1.0	1.259
Middle(2441MHz)	1.120	0.5±1	1.5	1.412
Highest(2480MHz)	1.380	0.5±1	1.5	1.412

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm²)	Limit	Result
1.995	3	0.0008	1.0	PASS

Note: 1) Refer to report No. CQASZ20210701128-01E for EUT test Max Conducted Peak Output Power value.

2) $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2) = (1.995 \cdot 1.995) / (4 \cdot 3.1416 \cdot 20^2) = 0.0008$