

FCC ID.: JFZLP3XBT Report No.: T210622N01-MF



Page: 1 / 7 Rev.: 00

KDB 447498 D03 47 C.F.R. Part 1, Subpart I, Section 1.1310 47 C.F.R. Part 2, Subpart J, Section 2.1091

RF EXPOSURE REPORT

For

Automatic Wireless Turntable

Model: AT-LP3XBT

Trade Name: audio-technica

Issued to

Audio-Technica Corporation 2-46-1 Nishi-naruse, Machida, Tokyo 194-8666, JAPAN

Issued By

Compliance Certification Services Inc. No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)

Issued Date: August 13, 2021





 Report No.:
 T210622N01-MF
 Page: 2 / 7

 Rev.:
 00

REVISION HISTORY

Rev.	Issue Date	Revisions		Revised By
00	August 13, 2021	Initial Issue	ALL	Angel Cheng



Report No.: T210622N01-MF

Page: 3 / 7 Rev.: 00

TABLE OF CONTENTS

1.	LIMIT	. 4
	EUT SPECIFICATION	
3.	TEST RESULTS	. 6
4.	MAXIMUM PERMISSIBLE EXPOSURE	. 7



 Report No.:
 T210622N01-MF
 Page: 4 / 7

 Rev.:
 00

1. TEST RESULT CERTIFICATION

We hereby certify that:

The equipment has been tested by Compliance Certification Services Inc., and found compliance with the requirement of the applicable standards. The test record, data evaluation and Equipment under Test (EUT) configurations represented herein are true and accurate accounts of the measurement of the sample's RF characteristics under the conditions specified in this report.

APPLICABLE STANDARDS						
STANDARD	TEST RESULT					
KDB 447498 D03						
47 C.F.R. Part 1, Subpart I, Section 1.1310	No non-compliance noted					
47 C.F.R. Part 2, Subpart J, Section 2.1091	-					

Statements of Conformity
Determining compliance shall be based on the results of the compliance measurement,
not taking into account measurement instrumentation uncertainty.

Approved by:

Kevin Tsai

Deputy Manager

Compliance Certification Services Inc.





 Report No.:
 T210622N01-MF
 Page: 5 / 7

 Rev.:
 00

2. LIMIT

According to §15.247(i), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See § 1.1307(b)(1) of this chapter.

3. EUT SPECIFICATION

EUT	Automatic Wireless Turntable				
Model	AT-LP3XBT				
Brand	audio-technica				
RF Module	GT-TRONICS Model: BC870				
Frequency band (Operating)	 ■ 802.11b/g/n HT20: 2412MHz ~ 2462MHz 802.11n HT40: 2422MHz ~ 2452MHz ☑ Others 2402MHz ~ 2480MHz (BT3.0 BT 4.0) ☑ Portable (<20cm separation) ☑ Mobile (>20cm separation) ☑ Others ☐ Occupational/Controlled exposure (S = 5mW/cm²) ☑ General Population/Uncontrolled exposure (S=1mW/cm²) 				
Device category					
Exposure classification					
Antenna Specification	ANTENNA WIFI FOR FI	PC / Gain:	0.50 dBi (N	lumeric gain:	1.12)
Maximum Average output power	GFSK: 8-DPSK GFSK(4.0)	-23.90 dB -19.00 dB -22.70 dB	m	(0.004 mW) (0.013 mW) (0.005 mW)	
Maximum Tune up Power	GFSK: 8-DPSK: GFSK(4.0)	-23.50 dB -18.50 dB -22.00 dB	m	(0.004 mW) (0.014 mW) (0.006 mW)	
Evaluation applied	✓ MPE Evaluation*✓ SAR Evaluation✓ N/A				
Received Date	June 22, 2021				
Reported Date	July 23, 2021				

Remark:

- 1. RF power data reference report (T210622N01-RP1-1 \ T210622N01-RP1-2)
- 2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.



Page: 6 / 7 **Report No.:** T210622N01-MF Rev.: 00

4. TEST RESULTS

No non-compliance noted.

Calculation

Given
$$E = \frac{\sqrt{30 \times P \times G}}{d}$$
 & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377d^2}$$

Changing to units of mW and cm, using:

$$P(mW) = P(W) / 1000$$
 and

$$d(cm) = d(m) / 100$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2}$$
 Equation 1

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

 $S = Power density in mW / cm^2$



 Page:
 7 / 7

 Report No.:
 T210622N01-MF

 Rev.:
 00

5. MAXIMUM PERMISSIBLE EXPOSURE

Substituting the MPE safe distance using d = 20 cm into Equation 1:

 $S = 0.000199 \times P \times G$

Where P = Power in mW

G = Numeric antenna gain

 $S = Power density in mW / cm^2$

GFSK:

	Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
Ī	Low	2402	0.004	1.12	20	0.000001	1	Pass

8-DPSK:

(Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
L	Low	2402	0.014	1.12	20	0.00003	1	Pass

GFSK(4.0):

Ch.	Frq.(MHz)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm2)	Result
High	2480	0.006	1.12	20	0.000001	1	Pass