



Engineering and Testing for EMC and Safety Compliance

TYPE CERTIFICATION REPORT

Topaz3, L.L.C.
10828 NW Air World Drive
Kansas City, MO 64153

MODEL: MURS-22

FCC ID: O7KMURS22

April 18, 2001

STANDARDS REFERENCED FOR THIS REPORT	
PART 2: 1999	FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS
PART 15: 1999	§15.109: RADIATED EMISSIONS LIMITS
PART 22: 1998	PUBLIC MOBILE SERVICES
PART 74: 1998	LOW POWER AUXILIARY STATION
PART 90: 1998	PRIVATE LAND MOBILE RADIO SERVICES
PART 95 (A): 1998	GENERAL MOBILE RADIO SERVICES
ANSI C63.4-1992	STANDARD FORMAT MEASUREMENT/TECHNICAL REPORT PERSONAL COMPUTER AND PERIPHERALS
ANSI/TIA/EIA603- 1992	LAND MOBILE FM OR PM COMMUNICATIONS EQUIPMENT MEASUREMENT AND PERFORMANCE STANDARDS
ANSI/TIA/EIA 603-1-1998	ADDENDUM TO ANSI/TIA/EIA 603-1992
RSS-119, Issue 5: 1996	LAND MOBILE AND FIXED RADIO TRANSMITTERS AND RECEIVERS.27.41 TO 960.0 MHZ

FCC Rules Parts	Frequency Range	Output Power (W)	Freq. Tolerance	Emission Designator
90.210	151.820	2.14	5 ppm	11K0F3E
90, 22, 74, 95	154.570	2.16	5 ppm	11K0F3E
Canadian	Frequency Range	Output Power (W)	Freq. Tolerance	
RSS-119	151.820	2.14	5 ppm	11K0F3E
RSS-119	154.570	2.16	5 ppm	11K0F3E

REPORT PREPARED BY:

EMC Engineer: Daniel Baltzell
Technical Writer: Melissa Fleming

Document Number: 2001083

No part of this report may be reproduced without the full written approval of Rhein Tech Laboratories, Inc.

360 Herndon Parkway, Suite 1400
Herndon, VA 20170
Phone: 703-689-0368; Fax: 703-689-2056; Metro: 703-471-6441



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	4
1.1	TEST FACILITY.....	4
1.2	RELATED SUBMITTAL(S)/GRANT(S).....	4
2	CONFORMANCE STATEMENT.....	5
3	TESTED SYSTEM DETAILS	6
3.1	CONFIGURATION OF TESTED SYSTEM.....	6
4	FIELD STRENGTH CALCULATION.....	7
5	CONDUCTED MEASUREMENT	8
5.1	PART 15.207(D) CONDUCTED EMISSION TEST RESULTS.....	9
6	RADIATED MEASUREMENT	10
6.1	PART 15.109 RADIATED EMISSION TEST RESULTS.....	11
7	FCC RULES AND REGULATIONS PART 2 §2.1046 (A): RF POWER OUTPUT: CONDUCTED	12
7.1	TEST PROCEDURE	12
7.2	TEST DATA.....	12
7.3	TEST EQUIPMENT.....	12
8	PART 2.1046 (A) RF POWER OUTPUT: RADIATED - ERP.....	13
8.1	TEST PROCEDURE	13
8.2	TEST DATA.....	13
8.3	TEST EQUIPMENT.....	13
9	FCC RULES AND REGULATIONS PART 2 §2.1051: SPURIOUS EMISSIONS AT ANTENNA TERMINALS	14
9.1	TEST PROCEDURE	14
9.2	TEST DATA.....	14
9.2.1	CFR Part 90 Requirements.....	14
9.2.2	Test Equipment.....	15
10	FCC RULES AND REGULATIONS PART 2 §2.1053 (A): FIELD STRENGTH OF SPURIOUS RADIATION	16
10.1	TEST PROCEDURE	16
10.2	TEST DATA.....	16
10.3	TEST EQUIPMENT.....	17
11	FCC RULES AND REGULATIONS PART 2 §2.1049 (C) (1): OCCUPIED BANDWIDTH	18
11.1	TEST PROCEDURE	18
11.2	TEST DATA.....	18
11.2.1	Channel 1: 2 W for 11.25 kHz Channel Bandwidth: Mask B (Audio Modulation: 2,500 Hz).....	18
11.2.2	Channel 2: 2 W for 12.5 kHz Channel Bandwidth: Mask D (Audio Modulation: 2,500 Hz).....	18
11.3	TEST EQUIPMENT.....	19
12	FCC RULES AND REGULATION PART 2 §2.1055: FREQUENCY STABILITY.....	20
12.1	TEST PROCEDURE	20
12.2	TEST DATA.....	20
12.2.1	Frequency stability/Temperature variation	20
12.2.2	Frequency Stability/Voltage Variation	22
12.3	7.3 TEST EQUIPMENT	22
13	FCC RULES AND REGULATIONS PART 2 §2.1047 (A): MODULATION CHARACTERISTICS - AUDIO FREQUENCY RESPONSE.....	23
13.1	TEST PROCEDURE	23
13.2	TEST DATA.....	23
13.2.1	Channel 1 – 11.25 kHz Audio Frequency Response.....	23
13.2.2	Channel 2 – 12.5 kHz Audio Frequency Response.....	24
13.3	TEST EQUIPMENT.....	24
14	FCC RULES AND REGULATIONS PART 2 §2.1047 (A): MODULATION CHARACTERISTICS - AUDIO LOW PASS FILTER RESPONSE.....	25



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

14.1	TEST PROCEDURE	25
14.2	TEST DATA.....	25
14.2.1	Channel 1 – 11.25 kHz Audio Low Pass Filter Response.....	25
14.2.2	Channel 2 – 12.5 kHz Audio Low Pass Filter Response.....	26
14.3	TEST EQUIPMENT.....	26
15	FCC RULES AND REGULATIONS PART 2 §2.1047 (B): MODULATION CHARACTERISTICS - MODULATION LIMITING.....	27
15.1	TEST PROCEDURE	27
15.2	TEST DATA.....	27
15.2.1	Channel 1 (11.25 kHz channel spacing) Positive Peak	27
15.2.2	Channel 1 (11.25 kHz channel spacing) Negative Peak.....	28
15.2.3	Channel 2 (12.5 kHz channel spacing) Positive Peak	29
15.2.4	Channel 2 (12.5 kHz channel spacing) Negative Peak.....	30
15.3	TEST EQUIPMENT.....	30
16	FCC RULES AND REGULATIONS PART 90 §90.214 : TRANSIENT FREQUENCY BEHAVIOR.....	31
16.1	TEST PROCEDURE	31
16.2	TEST DATA.....	31
16.3	TEST EQUIPMENT.....	35
17	FCC RULES AND REGULATIONS PART 2.202: NECESSARY BANDWIDTH AND EMISSION BANDWIDTH	36
18	BLOCK DIAGRAM.....	37
19	LABEL INFORMATION.....	38
20	PRODUCT DESCRIPTION	39
21	SCHEMATICS	40
22	OPERATOR’S MANUAL.....	41
23	TEST CONFIGURATION PHOTOGRAPHS	42
24	INTERNAL PHOTOGRAPHS	44
25	EXTERNAL PHOTOGRAPHS	45



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

1 GENERAL INFORMATION

The following Report of a Type Certification is prepared on behalf of *Topaz3, L.L.C. Standard Co., LTD* in accordance with the Federal Communications Commissions and Industry Canada Rules and Regulations. The Equipment Under Test (EUT) was the *MURS-22*. The test results reported in this document relate only to the item that was tested.

All measurements contained in this application were conducted in accordance with FCC Rules and Regulations CFR 47, Industry Canada RSS-119, and ANSI C63.4 Methods of Measurement of Radio Noise Emissions, 1992. The instrumentation utilized for the measurements conforms to the ANSI C63.4 standard for EMI and Field Strength Instrumentation. Calibration checks are performed regularly on the instruments, and all accessories including high pass filter, coaxial attenuator, preamplifier and cables.

1.1 TEST FACILITY

The open area test site and conducted measurement facility used to collect the radiated data is located on the parking lot of Rhein Tech Laboratories, Inc. 360 Herndon Parkway, Suite 1400, Herndon, Virginia 20170. This site has been fully described in a report dated March 3, 1994, submitted to and approved by the Federal Communication Commission to perform AC line conducted and radiated emissions testing (ANSI C63.4 1992).

1.2 RELATED SUBMITTAL(S)/GRANT(S)

This is an original application report.



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

2 CONFORMANCE STATEMENT

STANDARDS REFERENCED FOR THIS REPORT	
PART 2: 1999	FREQUENCY ALLOCATIONS AND RADIO TREATY MATTERS; GENERAL RULES AND REGULATIONS
PART 15: 1999	§15.109: RADIATED EMISSIONS LIMITS
PART 22: 1998	PUBLIC MOBILE SERVICES
PART 74: 1998	LOW POWER AUXILIARY STATION
PART 90: 1998	PRIVATE LAND MOBILE RADIO SERVICES
PART 95 (A): 1998	GENERAL MOBILE RADIO SERVICES
ANSI C63.4-1992	STANDARD FORMAT MEASUREMENT/TECHNICAL REPORT PERSONAL COMPUTER AND PERIPHERALS
ANSI/TIA/EIA603- 1992	LAND MOBILE FM OR PM COMMUNICATIONS EQUIPMENT MEASUREMENT AND PERFORMANCE STANDARDS
ANSI/TIA/EIA 603-1-1998	ADDENDUM TO ANSI/TIA/EIA 603-1992
RSS-119, Issue 5: 1996	LAND MOBILE AND FIXED RADIO TRANSMITTERS AND RECEIVERS.27.41 TO 960.0 MHZ

FCC Rules Parts	Frequency Range	Output Power (W)	Freq. Tolerance	Emission Designator
90.210	151.820	2.14	5 ppm	11K0F3E
90, 22, 74, 95	154.570	2.16	5 ppm	11K0F3E
Canadian	Frequency Range	Output Power (W)	Freq. Tolerance	
RSS-119	151.820	2.14	5 ppm	11K0F3E
RSS-119	154.570	2.16	5 ppm	11K0F3E

I, the undersigned, hereby declare that the equipment tested and referenced in this report conforms to the identified standard(s) as described in this attached test record. No modifications were made to the equipment during testing in order to achieve compliance with these standards.


Furthermore, there was no deviation from, additions to or exclusions from the FCC Part 2, FCC Part 22, FCC Part 74, FCC Part 90, FCC Part 95 and Industry Canada RSS-119 Certification methodology.

Signature: 

Date: June 5, 2001

Typed/Printed Name: Desmond A. Fraser

Position: President
(NVLAP Signatory)



Accredited by the National Voluntary Accreditation Program for the specific scope of accreditation under Lab Code 200061-0.

Note: This report may not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.




COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

3 TESTED SYSTEM DETAILS

Listed below are the identifiers and descriptions of all equipment, cables, and internal devices used with the EUT for this test, as applicable.

PART	MANUFACTURER	MODEL	SERIAL NUMBER	FCC ID
RADIO	TOPAZ3, L.L.C.	MURS-22	N/A	07KMURS22
ANTENNA WHIP	TOPAZ3, L.L.C.	N/A	N/A	N/A
BATTERY	TOPAZ3, L.L.C.	N/A	N/A	N/A
BATTERY CHARGER	TOPAZ3, L.L.C.	N/A	N/A	N/A

3.1 CONFIGURATION OF TESTED SYSTEM





COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

4 FIELD STRENGTH CALCULATION

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FI(\text{dBuV/m}) = SAR(\text{dBuV}) + SCF(\text{dB/m})$$

FI = Field Intensity

SAR = Spectrum Analyzer Reading

SCF = Site Correction Factor

The Site Correction Factor (SCF) used in the above equation is determined empirically, and is expressed in the following equation:

$$SCF(\text{dB/m}) = -PG(\text{dB}) + AF(\text{dB/m}) + CL(\text{dB})$$

SCF = Site Correction Factor

PG = Pre-amplifier Gain

AF = Antenna Factor

CL = Cable Loss

The field intensity in microvolts per meter can then be determined according to the following equation:

$$FI(\text{uV/m}) = 10^{FI(\text{dBuV/m})/20}$$

For example, assume a signal at a frequency of 125 MHz has a received level measured as 49.3 dBuV. The total Site Correction Factor (antenna factor plus cable loss minus preamplifier gain) for 125 MHz is -11.5 dB/m. The actual radiated field strength is calculated as follows:

$$49.3 \text{ dBuV} - 11.5 \text{ dB/m} = 37.8 \text{ dBuV/m}$$

$$10^{37.8/20} = 10^{1.89} = 77.6 \text{ uV/m}$$



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

5 CONDUCTED MEASUREMENT

The power line conducted emission measurements were performed in a Series 81 type shielded enclosure manufactured by Rayproof. The EUT was assembled on a wooden table 80 centimeters high. Power was fed to the EUT through a 50 ohm / 50 microhenry Line Impedance Stabilization Network (EUT LISN). The EUT LISN was fed power through an A.C. filter box on the outside of the shielded enclosure. The filter box and EUT LISN housing are bonded to the ground plane of the shielded enclosure. A second LISN, the peripheral LISN, provides isolation for the EUT test peripherals. This peripheral LISN was also fed A.C. power. A metal power outlet box, which is bonded to the ground plane and electrically connected to the peripheral LISN, powers the EUT host peripherals.

The spectrum analyzer was connected to the A.C. line through an isolation transformer. The 50-ohm output of the EUT LISN was connected to the spectrum analyzer input through a Solar 400 kHz high-pass filter. The filter is used to prevent overload of the spectrum analyzer from noise below 400 kHz. Conducted emission levels were measured on each current-carrying line with the spectrum analyzer operating in the CISPR quasi-peak mode (or peak mode if applicable). The analyzer's 6 dB bandwidth was set to 9 kHz. No video filter less than 10 times the resolution bandwidth was used. Average measurements are performed in linear mode using a 10 kHz resolution bandwidth, a 1 Hz video bandwidth, and by increasing the sweep time in order to obtain a calibrated measurement. The emission spectrum was scanned from (150/450) kHz to 30 MHz. The highest emission amplitudes relative to the appropriate limit were measured and have been recorded in this report.



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

5.1 PART 15.207(D) CONDUCTED EMISSION TEST RESULTS


NEUTRAL SIDE (Line 1)

Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	Limit (dBuV)	Margin (dBuV)
1.100	Pk	17.9	1.0	18.9	48.0	-29.1
1.100	Pk	17.9	1.0	18.9	48.0	-29.1
11.890	Pk	15.7	3.0	18.7	48.0	-29.3
17.710	Pk	15.4	3.7	19.1	48.0	-28.9
23.110	Pk	15.8	4.1	19.9	48.0	-28.1
28.730	Pk	15.4	4.4	19.8	48.0	-28.2

HOT SIDE (Line 2)

Emission Frequency (MHz)	Test Detector	Analyzer Reading (dBuV)	Site Correction Factor (dB)	Emission Level (dBuV)	Limit (dBuV)	Margin (dBuV)
0.510	Pk	16.8	0.9	17.7	48.0	-30.3
1.130	Pk	15.5	1.0	16.5	48.0	-31.5
2.400	Pk	16.3	1.5	17.8	48.0	-30.2
8.780	Pk	17.1	2.4	19.5	48.0	-28.5
16.760	Pk	16.2	3.6	19.8	48.0	-28.2
27.780	Pk	15.9	4.4	20.3	48.0	-27.7

TEST PERSONNEL:

Signature: 

Date: April 18, 2001

Typed/Printed Name: Daniel Baltzell



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

6 RADIATED MEASUREMENT

Before final measurements of radiated emissions were made on the open-field three meter range, the EUT was scanned indoors at a three meter distance in order to determine its emissions spectrum signature. The physical arrangement of the test system and associated cabling was varied in order to determine the effect on the EUT's emissions in amplitude, direction and frequency. This process was repeated during final radiated emissions measurements on the open-field range, at each frequency, in order to insure that maximum emission amplitudes were attained.

Final radiated emissions measurements were made on the three-meter, open-field test site. The EUT was placed on a nonconductive turntable approximately 0.8 meters above the ground plane.

At each frequency, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters in order to determine the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarizations.

Note: Rhein Tech Laboratories, Inc. has implemented procedures to minimize errors that occur from test instruments, calibration, procedures, and test setups. Test instrument and calibration errors are documented from the manufacturer or calibration lab. Other errors have been defined and calculated within the Rhein Tech quality manual, section 6.1. Rhein Tech implements the following procedures to minimize errors that may occur: yearly as well as daily calibration methods, technician training, and emphasis to employees on avoiding error.




COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

6.1 PART 15.109 RADIATED EMISSION TEST RESULTS

Emission Frequency (MHz)	Test Detector	Antenna Polarity (H/V)	Turntable Azimuth (deg)	Antenna Height (m)	Analyzer Reading (dBuV/m)	Site Correction Factor (dB/m)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
130.120	Qp	V	30	1.0	19.2	-15.4	3.8	43.5	-39.7
260.240	Qp	V	23	1.0	18.7	-14.4	4.3	46.0	-41.7
390.361	Qp	V	25	1.0	18.6	-10.8	7.8	46.0	-38.2
520.481	Qp	V	17	1.0	18.2	-7.8	10.4	46.0	-35.6
650.601	Qp	V	12	1.0	18.1	-5.5	12.6	46.0	-33.4
780.722	Qp	V	27	1.0	18.2	-4.2	14.0	46.0	-32.0
910.842	Qp	V	33	1.0	18.4	-3.4	15.0	46.0	-31.0

TEST PERSONNEL:

Signature: 

Date: April 18, 2001

Typed/Printed Name: Daniel Baltzell



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

7 FCC RULES AND REGULATIONS PART 2 §2.1046 (A): RF POWER OUTPUT: CONDUCTED

7.1 TEST PROCEDURE

ANSI/TIA/EIA-603-1992, section 2.2.1

The EUT was connected to a coaxial attenuator having a 50 Ω load impedance.

7.2 TEST DATA

The following channel (in MHz) were tested 151.820, 154.570 MHz

The worst-case Output Power (highest) levels are shown.

CARRIER OUTPUT POWER (UNMODULATED)

Frequency	RF Power measured (Watt)*
151.820	2.138
154.570	2.158

*Measurement accuracy: +/- 3%

Rated Power:

Frequency	Rated Power (Watt)
151.820	2.0
154.570	2.0

7.3 TEST EQUIPMENT

Power Meter	HP437B	s/n 2949A02966
	HP 8901A	s/n 2545A04102 (power mode)
Power Sensor	HP8481B	s/n 2702A05059
Frequency Counter	HP8901A	s/n 2545A04102 (Frequency mode)



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

8 PART 2.1046 (A) RF POWER OUTPUT: RADIATED - ERP

8.1 TEST PROCEDURE

Substitution Method:

The EUT was setup at an antenna to EUT distance of 3 meters on an open area test site. The EUT was placed on a nonconductive turntable approximately 0.8 meters above the ground plane.

The physical arrangement of the EUT and associated cabling was varied in order to determine the effect on the EUT's emissions in amplitude, direction and frequency. At each frequency, the EUT was rotated 360 degrees, and the antenna was raised and lowered from one to four meters in order to determine the maximum emission levels. Measurements were taken using both horizontal and vertical antenna polarizations.

The worst-case, maximum radiated emission was recorded and used as reference for the ERP measurement.

The EUT was then replaced by an $\frac{1}{2}$ wave dipole antenna and polarized in accordance with the EUT's antenna polarization. The $\frac{1}{2}$ wave dipole antenna was connected to a RF signal generator with a coaxial cable.

The search antenna height, and search antenna polarity was set to levels that produced the maximum reading obtained in step 3. The signal generator was adjusted to a level that produced the radiated emission level obtained in step 3.

The signal generator level was recorded and corrected by the power loss in the cable between the generator and the antenna and further corrected for the gain of the substitution antenna used relative to an ideal $\frac{1}{2}$ wave dipole antenna. The signal generator corrected level is the ERP level

8.2 TEST DATA

Settings:

- Power: 2 Watt delivered to antenna*
- MURS-22 radiated power measurements (3 meter)

Frequency (MHz)	Signal Generator Level (dBm)*	Cable Loss (dB)	Corrected Antenna Gain (dBi)	Corrected level (dBm)	(Watt)
151.82	31.1	2.1	-0.3	28.7	0.7413
154.57	33.3	1.9	-0.2	31.3	1.349

*Antenna as specified by manufacturer

**Measurement accuracy is +/- 1.5 dB

8.3 TEST EQUIPMENT

Spectrum Analyzer HP8566B
Antenna Roberts $\frac{1}{2}$ wave dipoles



9 FCC RULES AND REGULATIONS PART 2 §2.1051: SPURIOUS EMISSIONS AT ANTENNA TERMINALS

9.1 TEST PROCEDURE

ANSI/TIA/EIA-603-1992, Section 2.2.13

The transmitter is terminated with a 50Ω load and interfaced with a spectrum analyzer.

The transmitter is modulated with a 2,500 Hz sine wave at an input level 16 dB greater than that required to produce 50% of the rated system deviation at 1000 Hz.

9.2 TEST DATA

9.2.1 CFR PART 90 REQUIREMENTS

Frequency range of measurement per Part 2.1057: 9kHz to $10 \times F_c$

Limits: Mask B (dBm): $P(\text{dBm}) - (43 + 10 \times \text{LOG } P(\text{W}))$

Mask D (dBm): $P(\text{dBm}) - (50 + 10 \times \text{LOG } P(\text{W}))$

Both 151.82 and 154.57 MHz were investigated, representing 25 kHz and 12.5 kHz channel spacing.

The worst case (unwanted emissions) channels are shown. The magnitude of emissions attenuated more than 20 dB below the FCC limit need not be recorded.

Channel 1 (151.820 MHz) – 2 Watt and 11.25 kHz Channel Bandwidth: Mask B

Frequency (MHz)	Level Measured (-dBc)	Limit (-dBc)	Margin (dB)
303.64	-60.7	-46.3	-14.4
455.46	-74.6	-46.3	-28.3
607.28	-75.9	-46.3	-29.6
759.10	-83.3	-46.3	-37.0
910.92	-90.4	-46.3	-44.1
1062.74	-95.7	-46.3	-49.4
1214.56	-95.9	-46.3	-49.6
1366.38	-103.4	-46.3	-57.1
1518.20	-106.0	-46.3	-59.7

Channel 2 (154.570 MHz) – 2 Watt and 12.5 kHz Channel Bandwidth: Mask D

Frequency (MHz)	Level Measured (-dBc)	Limit (-dBc)	Margin (dB)
309.14	-68.5	-53.3	-15.2
463.71	-72.9	-53.3	-19.5
618.28	-76.8	-53.3	-23.4
772.85	-80.7	-53.3	-27.4
927.42	-93.3	-53.3	-39.9
1081.99	-94.0	-53.3	-40.7
1236.56	-98.6	-53.3	-45.2
1391.13	-94.9	-53.3	-41.5
1545.70	-107.5	-53.3	-54.1



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

9.2.2 TEST EQUIPMENT

Audio Generator:

Synthesized Level Generator	HP3336B	s/n 2127A00559
Selective Level Meter	HP3585	s/n B032374

Spectrum Analyzer:

HP8564E	s/n 3943A01719
HP8546A	s/n 3525A00159



COMPANY NAME: VERTEX STANDARD CO., LTD.
 EUT: MURS-22 VHF
 WORK ORDER NUMBER: 2001083
 FCC ID: 07KMURS22

10 FCC RULES AND REGULATIONS PART 2 §2.1053 (A): FIELD STRENGTH OF SPURIOUS RADIATION

10.1 TEST PROCEDURE

ANSI/TIA/EIA-603-1992, section 2.2.12

The transmitter is terminated with a 50 Ω load and is modulated with a 2,500 Hz sine wave at an input level 16 dB greater than that required to produce 50% of the rated system deviation at 1000 Hz.

Refer to section “Radiated Measurement” in this report for further information.

10.2 TEST DATA

The worst-case emissions test data are shown. The magnitude of emissions attenuated more than 20 dB below the FCC limit need not be recorded.

2Watt at 11.25 kHz channel spacing						
Radiated Emissions (Channel 1 at 151.820 MHz)						
Substitution Method						
Frequency (MHz)	Signal Generator Emission Level (dBm)	Cable Loss (dB)	Antenna Gain (corrected to 1/2 wave) (dBi)	Corrected Emission Level (-dBc)	Limit (-dBc)	Margin (dB)
303.64	-30.4	2.7	-0.8	-67.2	-46.3	-20.9
455.46	-22.7	3.7	-0.6	-60.3	-46.3	-14.0
607.28	-26.2	3.8	-1.2	-64.5	-46.3	-18.2
759.10	-34.6	4.5	-1.2	-73.6	-46.3	-27.3
910.92	-39.7	5.1	-1.1	-79.2	-46.3	-32.9
1062.74	-51.6	5.0	0.5	-89.4	-46.3	-43.1
1214.56	-55.6	6.0	1.9	-93.0	-46.3	-46.7
1366.38	-61.1	5.4	3.4	-96.4	-46.3	-50.1
1518.20	-54.7	6.6	4.7	-89.9	-46.3	-43.6

*This insertion loss corresponds to the cable connecting the RF Signal Generator to the $\frac{1}{2}$ wave dipole antenna.

2Watt at 12.5 kHz channel spacing						
Radiated Emissions (Channel 2 at 154.57 MHz)						
Substitution Method						
Frequency (MHz)	Signal Generator Emission Level (dBm)	Cable Loss (dB)	Antenna Gain (corrected to 1/2 wave) (dBi)	Corrected Emission Level (-dBc)	Limit (-dBc)	Margin (dB)
309.14	-32.5	2.9	-0.6	-69.3	-53.3	-16.0
463.71	-21.4	3.7	-0.6	-59.0	-53.3	-5.7
618.28	-33.9	3.9	-1.2	-72.3	-53.3	-19.0
772.85	-32.7	4.6	-1.3	-71.9	-53.3	-18.6
927.42	-25.4	4.8	-1.2	-64.7	-53.3	-11.4
1081.99	-36.5	5.1	0.7	-74.3	-53.3	-21.0
1236.56	-39.0	5.9	2.1	-76.1	-53.3	-22.8
1391.13	-36.6	5.9	3.6	-72.2	-53.3	-18.9
1545.70	-33.1	6.5	4.7	-68.3	-53.3	-14.9

*This insertion loss corresponds to the cable connecting the RF Signal Generator to the $\frac{1}{2}$ wave dipole antenna.



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

10.3 TEST EQUIPMENT

Antenna:	CHASE CBL6112	s/n 2099
Amplifier:	HP8449B	s/n 3008A00505
Spectrum analyzer:	HP8564E	s/n 3943A01719
RF Signal Generator	HP8648C	s/n 3537A01741
Synthesized Sweeper	HP83752A	s/n 3610A00846



COMPANY NAME: VERTEX STANDARD Co., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

11 FCC RULES AND REGULATIONS PART 2 §2.1049 (C) (1): OCCUPIED BANDWIDTH

OCCUPIED BANDWIDTH - COMPLIANCE WITH THE EMISSION MASKS

11.1 TEST PROCEDURE


ANSI/TIA/EIA-603-1992, section 2.2.11

Device with audio modulation: Transmitter is modulated with a 2500 Hz sine wave at an input level of 16 dB greater than that required to produce 50% of rated system deviation at 1000 Hz.

Device with digital modulation: N/A

11.2 TEST DATA


11.2.1 CHANNEL 1: 2 W FOR 11.25 kHz CHANNEL BANDWIDTH: MASK B (AUDIO MODULATION: 2,500 Hz)



11.2.2 CHANNEL 2: 2 W FOR 12.5 kHz CHANNEL BANDWIDTH: MASK D (AUDIO MODULATION: 2,500 Hz)



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22



11.3 TEST EQUIPMENT

Spectrum Analyzer HP8564E s/n 3943A01719



12 FCC RULES AND REGULATION PART 2 §2.1055: FREQUENCY STABILITY

12.1 TEST PROCEDURE

ANSI/TIA/EIA-603-1992, section 2.2.2

The carrier frequency stability is the ability of the transmitter to maintain an assigned carrier frequency.

The EUT was evaluated over the temperature range -30°C to +50°C.

The temperature was initially set to -30°C and a 2-hour period was observed for stabilization of the EUT.

The frequency stability was measured within one minute after application of primary power to the transmitter. The temperature was raised at intervals of 10 degrees centigrade through the range. A ½ an hour period was observed to stabilize the EUT at each measurement step and the frequency stability was measured within one minute after application of primary power to the transmitter.

Additionally, the power supply voltage of the EUT was varied from 85% to 115% of the nominal voltage.


The worst-case test data are shown.

12.2 TEST DATA

12.2.1 FREQUENCY STABILITY/TEMPERATURE VARIATION

Limit is 5 ppm for MURS devices.

The MURS-22 2 Watt radio was tested with 11.25 kHz and 12.5 kHz channel bandwidth. The worst-case temperature deviation on the following plot is for channel 1 (11.25 kHz channel bandwidth).



Narrow Band Frequency Stability vs Temperature Channel 1 = 151.82 MHz



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

Temperature (C)	Frequency (MHz)	ppm
-30.00000	151.8200900	0.59
-20.00000	151.8205080	3.35
-10.00000	151.8206080	4.00
0.00000	151.8203000	1.98
10.00000	151.8202080	1.37
20.00000	151.8200670	0.44
30.00000	151.8197580	-1.59
40.00000	151.8195330	-3.08
50.00000	151.8193420	-4.33



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

12.2.2 FREQUENCY STABILITY/VOLTAGE VARIATION

Assigned Frequency 151.82 MHz

Battery end point = 3.3V

Voltage (7.2V +/- 85-115%)	Frequency (MHz)	ppm
6.12	151.819782	-1.44
7.2	151.819782	-1.44
8.28	151.819782	-1.44

12.3 7.3 TEST EQUIPMENT

Temperature Chamber Tenney TH65 s/n 11380

Frequency Counter HP8901A (Frequency Mode) s/n 2545A04102



13 FCC RULES AND REGULATIONS PART 2 §2.1047 (A): MODULATION CHARACTERISTICS - AUDIO FREQUENCY RESPONSE

13.1 TEST PROCEDURE

ANSI/TIA/EIA-603-1992, section 2.2.6

The audio frequency response is the degree of closeness to which the frequency deviation of the transmitter follows a prescribed characteristic.

The input audio level at 1000 Hz is set to produce 20% of the rated system deviation. This point is shown as the 0 dB reference level, noted DEVref.

The audio signal generator was varied from 300Hz to 6kHz with the input level held constant.


The deviation in kHz was recorded using a modulation analyzer as DEVfreq.

The response in dB relative to 1 kHz was calculated as follows:

$$\text{Audio Frequency Response} = 20 \text{ LOG } (\text{DEVfreq}/\text{DEVref})$$

13.2 TEST DATA

13.2.1 CHANNEL 1 – 11.25 kHz AUDIO FREQUENCY RESPONSE






COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

13.2.2 CHANNEL 2 – 12.5 kHz AUDIO FREQUENCY RESPONSE

RTL Audio Frequency Response (154.57 MHz, 12.5 kHz Channel Spacing)



13.3 TEST EQUIPMENT

Audio generator	HP3336B	s/n 2127A00559
Modulation analyzer	HP8901A	s/n 2545A04102



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

14 FCC RULES AND REGULATIONS PART 2 §2.1047 (A): MODULATION CHARACTERISTICS - AUDIO LOW PASS FILTER RESPONSE


14.1 TEST PROCEDURE

ANSI/TIA/EIA-603-1992, 2.2.15

The Audio Low Pass Filter Response is the frequency response of the post limiter low pass filter circuit above 3000 Hz.

14.2 TEST DATA

14.2.1 CHANNEL 1 – 11.25 kHz AUDIO LOW PASS FILTER RESPONSE






COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

14.2.2 CHANNEL 2 – 12.5 kHz AUDIO LOW PASS FILTER RESPONSE

RTL Audio Low Pass Filter Response (154.57 MHz, 12.5 kHz Channel Spacing)



14.3 TEST EQUIPMENT

Audio generator	HP3336B	s/n 2127A00559
Modulation analyzer	HP8901A	s/n 2545A04102
Selective level meter	HP3586B	s/n 1928A01892
Synthesizer/Level generator	HP3336B	s/n 2514A02585



15 FCC RULES AND REGULATIONS PART 2 §2.1047 (B): MODULATION CHARACTERISTICS - MODULATION LIMITING


15.1 TEST PROCEDURE

ANSI/TIA/EIA-603-1992, section 2.2.3

The transmitter is adjusted for full rated system deviation. The audio input level is adjusted for 60% of rated system deviation at 1000Hz. Using this level as a reference (0dB) the audio input level is varied from the reference to a level +20 dB above it and -20 dB under it, for modulation frequencies of 300Hz, 1,000Hz, and 2,500Hz. The system deviation obtained as a function of the input level is recorded. Both Positive and Negative Peak deviations were recorded.

15.2 TEST DATA

15.2.1 CHANNEL 1 (11.25 KHz CHANNEL SPACING) POSITIVE PEAK






COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

15.2.2 CHANNEL 1 (11.25 kHz CHANNEL SPACING) NEGATIVE PEAK

RTL Modulation Limiting Response (151.82 MHz : 11.25 kHz Channel Spacing) Negative Peak






COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

15.2.3 CHANNEL 2 (12.5 kHz CHANNEL SPACING) POSITIVE PEAK


RTL Modulation Limiting Response (154.57 MHz : 12.5 kHz Channel Spacing) Positive Peak





COMPANY NAME: VERTEX STANDARD Co., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

15.2.4 CHANNEL 2 (12.5 kHz CHANNEL SPACING) NEGATIVE PEAK



15.3 TEST EQUIPMENT

Audio generator	HP3336B	s/n 2127A00559
Modulation analyzer	HP8901A	s/n 2545A04102
Selective level meter	HP3586B	s/n 1928A01892
Synthesizer/Level generator	HP3336B	s/n 2514A02585



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

16 FCC RULES AND REGULATIONS PART 90 §90.214 : TRANSIENT FREQUENCY BEHAVIOR

16.1 TEST PROCEDURE


ANSI/TIA/EIA-603-1992, section 2.2.19

16.2 TEST DATA

Channel 1; 151.82 MHz; 11.25 kHz channel spacing; On

Tek Stop: 5.00kS/s

7 Acqs




17 May 2001
11:47:58



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

Channel 1; 151.82 MHz; 11.25 kHz channel spacing; Off

Tek Run: 5.00kS/s Sample Trig



Ch1 250mV

M10.0ms

Ch2

-7.6mV

17 May 2001

11:50:26




COMPANY NAME: VERTEX STANDARD Co., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

Channel 2; 154.57 MHz; 12.5 kHz channel spacing; On

Tek **Stop:** 5.00kS/s

2 Acqs




17 May 2001
11:53:50



COMPANY NAME: VERTEX STANDARD CO., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

Channel 2; 154.57 MHz; 12.5 kHz channel spacing; Off

Tek Run: 5.00kS/s Sample Trig?



17 May 2001
11:52:57



COMPANY NAME: VERTEX STANDARD Co., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

Limits:

Requirements for EUT with 25 kHz channel spacing:

Time Intervals (*)(**)	Maximum Frequency Difference(***)	150-174 MHz	421-512 MHz
t1(****)	± 25 kHz	5.0 mSec	10.0 mSec
t2	± 12.5 kHz	20.0 mSec	25.0 mSec
t3(****)	± 25 kHz	5.0 mSec	10.0 mSec

Requirements for EUT with 12.5 kHz channel spacing:

Time Intervals (*)(**)	Maximum Frequency Difference(***)	150-174 MHz	421-512 MHz
t1(****)	± 12.5 kHz	5.0 mSec	10.0 mSec
t2	± 6.25 kHz	20.0 mSec	25.0 mSec
t3(****)	± 12.5 kHz	5.0 mSec	10.0 mSec

(*) t on is the instant when a 1 kHz test signal is completely suppressed, including any capture time due to phasing.

t 1 is the time period immediately following ton.

t2 is the time period immediately following t1.

t3 is the time period from the instant when the transmitter is turned off until toff.

toff is the instant when the 1 kHz test signal starts to rise.

(**) During the time from the end of t2 to the beginning of t3, the frequency difference must not exceed the limits specified in § 90.213.

(***) Difference between the actual transmitter frequency and the assigned transmitter frequency.

(****) If the transmitter carrier output power rating is 6 watts or less, the frequency difference during this time period may exceed the maximum frequency difference for this time period.

Maximum frequency difference between time T2 and T3: Calculation for Channel 6:

The frequency stability is required to be 2.5ppm.

Calculation for Channel 6:

4 div. on scope represent 12.5kHz for narrow band channel.

Therefore, 487.975M times 2.5 ppm times +/- 4 Divisions divided by 12.5kHz equals about +/- 0.4 division. 0.4 Div. correspond to 1.219 kHz

16.3 TEST EQUIPMENT

Detector: HP8471D s/n 2952A
RF signal generator: HP8648C s/n 3537A01741
Modulation Analyzer: HP8901A s/n 2545A04102
Oscilloscope: Tektronix TDS540B s/n B020129
Receiver: HP 8546A s/n 3525A00159



COMPANY NAME: VERTEX STANDARD Co., LTD.
EUT: MURS-22 VHF
WORK ORDER NUMBER: 2001083
FCC ID: 07KMURS22

17 FCC RULES AND REGULATIONS PART 2.202: NECESSARY BANDWIDTH AND EMISSION BANDWIDTH

Type of Emission: F3E

Necessary Bandwidth and Emission Bandwidth:
11.25 kHz and 12.5kHz : $B_n = 11K0F3E$

Calculation:

Max modulation(M) in kHz : 3

Max deviation (D) in kHz: 2.5 (NB)

Constant factor (K) : 1

$B_n = 2xM + 2xDK$