

# Radio Frequency Exposure Evaluation Report

FOR:

Telular AMETEK

**Model Name:** 

**VUE2000** 

**Product Description:** 

Asset tracking.

FCC ID: MTFVUE2000 IC ID: 2175D-VUE2000

### Per:

CFR Part Part1 (1.1307 &1.1310), Part 2 (2.1091), FCC KDB 447498 D01 General RF Exposure Guidance v06 ISEDC RSS-102 Issue 5

Report number: EMC\_TELUL-094-20001\_FCC\_ISED\_MPE

**DATE:** 2021-09-30



### CETECOM Inc.

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: info@cetecom.com • <a href="http://www.cetecom.com">http://www.cetecom.com</a> CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

V5.0 2015-10-27 © Copyright by CETECOM

Test Report #:
Date of Report

EMC\_TELUL-094-20001\_FCC\_ISED\_MPE

2021-09-30

Page 2 of 8

FCC ID: MTFVUE2000 IC ID: 2175D-VUE2000



### 1 Assessment

This RF Exposure evaluation report provides evidence for compliance of the below identified device with the RF Exposure limits for mobile devices as defined in FCC CFR Part 1 (1.1307 &1.1310), Part 2 (2.1091) and IC standard RSS-102 issue 5 under worst case conditions (measured or rated RF output power, antenna gain, distance towards human body, multiple transmitter information as presented by the applicant). In addition, maximum antenna gain or minimum distance towards the human body is calculated respectively, where relevant.

The device meets the limits as stipulated by the above given FCC and IC rule parts based on available specifications for worst case conditions at 20cm distance to the body.

Company	Description	Model #
Telular AMETEK	Asset tracking.	VUE2000

Report reviewed by: TCB Evaluator

Kevin Wang

Date	Section	Name	Signature
2021-09-30	Compliance	(Lab Manager)	
		· J	

## Responsible for the Report:

Yuchan Lu

2021-09-30	Compliance	(Test Engineer)	
Date	Section	Name	Signature



### **Administrative Data** 2

### Identification of the Testing Laboratory Issuing the Test Report 2.1

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
Lab Manager:	Kevin Wang
Responsible Project Leader:	Cathy Palacios

#### **Identification of the Client / Manufacturer** 2.2

Client's Name: Telular AMETEK			
Street Address:	3225 Cumberland Blvd. Suite 300		
City/Zip Code Atlanta, GA 30339			
Country	USA		

### **Identification of the Applicant** 2.3

Applicant's Name: Telular Corporation				
Applicant's Address: 3225 Cumberland Blvd. Suite 300				
City/Zip Code	Atlanta, GA 30339			
Country	USA			

Test Report #: EMC\_TELUL-094-20001\_FCC\_ISED\_MPE

Date of Report 2021-09-30 Page 4 of 8



FCC ID: MTFVUE2000

IC ID: 2175D-VUE2000

# 3 Equipment under Assessment

Marketing name:	SkyVue			
HW Version :	В			
SW Version :	EM.00.01.1085,BM.00.01.0048			
Hardware Version Identification Number (HVIN):	VUE2000			
Product Marketing Name (PMN):	SkyVue			
Regulatory Band:	<ul> <li>Cellular Module:         <ul> <li>LTE BAND 2: 1850.7 ~ 1909.3 MHz</li> <li>LTE BAND 4: 1710.7 ~ 1754.3 MHz</li> <li>LTE BAND 5: 824.7 ~ 848.3 MHz</li> <li>LTE BAND 12: 699.7 ~ 715.3 MHz</li> <li>LTE BAND 13: 779.5 ~ 784.5 MHz</li> </ul> </li> <li>★ BLE:         <ul> <li>Nominal band: 2400 MHz – 2483.5 MHz;</li> <li>Center to center: 2402 MHz (ch 0) – 2480 MHz (ch 39), 40 channels</li> </ul> </li> </ul>			
Integrated Module Info:	<ul> <li>Manufacture: Telit</li> <li>Module name/number: ME910G1-W1</li> <li>FCC ID: RI7ME910G1W1</li> <li>IC ID: 5131A-ME910G1W1</li> <li>BLE</li> <li>Manufacture: Laird Connectivity</li> <li>Module name/number: BL654 451-00001</li> <li>FCC ID: SQGBL654</li> <li>IC ID: 3147A-BL654</li> <li>GNSS/GPS</li> <li>Manufacture: Quectel</li> <li>Module name/number: L86s-M3</li> </ul>			
Antenna Type:	<ul> <li>❖ Cellular:         <ul> <li>Antenna maximum gain:</li> <li>LTE Band 2: 4.4 dBi</li> <li>LTE Band 4: 4.4 dBi</li> <li>LTE Band 5: 2.6 dBi</li> </ul> </li> </ul>			

Test Report #:
Date of Report

EMC\_TELUL-094-20001\_FCC\_ISED\_MPE

2021-09-30 Page 5 of 8

FCC ID: MTFVUE2000 IC ID: 2175D-VUE2000



	○ LTE Band 12: 2.6 dBi		
	○ LTE Band 13: 2.6 dBi		
	❖ BLE:		
	<ul> <li>Antenna gain: 0 dBi</li> </ul>		
	❖ Cellular: From modular grant [Watts]:		
	■ LTE Band 2: 0.138		
	■ LTE Band 4: 0.131		
Maximum Conducted Output Power:	■ LTE Band 5: 0.154		
	■ LTE Band 12: 0.145		
	■ LTE Band 13: 0.138		
	❖ BLE: From measurement [Watts]: 0.006		
Power Supply/ Rated Operating Voltage Range:	Vmin: 10 VDC/ Vnom: 12 VDC / Vmax: 30 VDC		
Operating Temperature Range:	Low -40°C, Nominal 25°C, High 70°C		
Sample Revision:	□Prototype Unit; ■Production Unit; □Pre-Production		

2021-09-30 Page 6 of 8

FCC ID: MTFVUE2000 IC ID: 2175D-VUE2000



### 4 RF Exposure Limits and FCC and IC Basic Rules

For the specific described radio apparatus the following basic limits and rules apply for both, FCC and IC where not indicated differently.

### 4.1 Power Density Limits acc. to FCC 1.1310(e) / RSS-102 i5, cl. 4:

**FCC** 

Frequency Range (MHz)	Power density (mW/cm²)	Averaging time (minutes)		
300 – 1500	f (MHz) /1500	30		
1500 – 100000	1.0	30		

IC

300 – 6000	0.02619 x f (MHz) <sup>0.6834</sup>	6

# 4.2 Routine Environmental Evaluation Categorical Exclusion Limits acc. to FCC 2.1091(c) / RSS-102, cl. 2.5 (rounded to 1 decimal point):

**FCC** 

operating frequency < 1.5GHz: excluded if ERP < 1.5W / 31.8dBm (EIRP: 33.9 dBm); operating frequency > 1.5GHz: excluded if ERP < 3.0W / 34.8dBm (EIRP: 36.9 dBm);

IC

 $300MHz < = operating frequency < 6 GHz: excluded if EIRP < 0.0131 x f (MHz) <math>^{0.6834}W$ 

## 4.3 RF Exposure Estimation (MPE Estimation)

Having available the source based average output power and peak antenna gain or the ERP/EIRP of the specified device and for a known minimum distance of its radiating structures from the body of persons according to its use cases (at least 20cm) the power density at that distance can be estimated by the following formula for plane-wave equivalent conditions (far-field conditions), when ground reflection is neglected.

$$S = \frac{PG}{4\pi R^2}$$

where:  $S = power density (mW/cm^2 or W/m^2)$ 

P = power input to the antenna (mW or W)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (cm or m)

Test Report #: EMC\_TELUL-094-20001\_FCC\_ISED\_MPE

Date of Report 2021-09-30 Page 7 of 8

FCC ID: MTFVUE2000 IC ID: 2175D-VUE2000



### 5 Evaluations

### 5.1 Analysis of RF Exposure for simultaneous transmission

- Evaluations are based on worst case power density limits for Canada.
- Calculations are made for 20cm.
- Evaluations are based on ERP/EIRP measured or calculated from known gain and conducted output power.
- Cellular can transmit simultaneously with BLE.

Radio	freq [MHz]	Max Conducted power [W]	Max Conducted power+Tune up[W]	Gain [dBi]	Gain [lin]	EIRP [W]	IC Limit [W/m2]	FCC Llmit [W/m2]	Actual [W/m2] <sup>2</sup>	How much of limit is used up
LTE 2	1850	0.138	0.158	4.4	2.75	0.435	4.476	10.000	0.866	19.33%
LTE 4	1710	0.131	0.158	4.4	2.75	0.435	4.242	10.000	0.866	20.40%
LTE 5	824	0.154	0.158	2.6	1.82	0.288	2.576	5.493	0.572	22.17%
LTE 12	699	0.145	0.158	2.6	1.82	0.288	2.302	4.660	0.572	24.82%
LTE 13	777	0.138	0.158	2.6	1.82	0.288	2.474	5.180	0.572	23.08%
BTLE	2402	0.006	0.006	0	1.00	0.006	5.351	10.000	0.012	0.21%

Note1: The calculation is based on the distance of 20cm

### 5.2 Conclusion:

The worst-case simultaneous transmission is LTE Band 12 simultaneous with BLE, which is using 25.03 of a limit of 100%. The equipment is passing RF exposure requirements for 20cm distance.

Test Report #: EMC\_TELUL-094-20001\_FCC\_ISED\_MPE FCC ID: MTFVUE2000

Date of Report 2021-09-30 Page 8 of 8 IC ID: 2175D-VUE2000



# 6 Revision History

Date	Report Name	Changes to report	Prepared by
2021-09-30	EMC_TELUL-094-20001_FCC_ISED_MPE	Initial Release	Yuchan Lu

<<< The End >>>