

# 1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

---

## 1.1 General Information

### Client Information

Applicant: Soan Electronic Technology Co.,Ltd  
Address of applicant: 3/F, No.18 Industrial south road, Xinhe Community, fuyong,  
BaoAn,ShenZhen,China

Manufacturer: Soan Electronic Technology Co.,Ltd  
Address of manufacturer: 3/F, No.18 Industrial south road, Xinhe Community, fuyong,  
BaoAn,ShenZhen,China

### General Description of EUT:

Product Name: wifi water/Door alarm  
Trade Name: SOAN  
Model No.: SNT921W, SNT931W  
FCC ID: 2ATRQ-SNT921W  
Rated Voltage: Battery:DC3.7V  
Battery Capacity: 500mAh

### Technical Characteristics of EUT:

Support Standards: 802.11b, 802.11g, 802.11n  
Frequency Range: 2412-2462MHz for 802.11b/g/n-HT20  
RF Output Power: 10.93dBm (Conducted)  
Type of Modulation: DBPSK,BPSK,DQPSK,QPSK,16QAM,64QAM  
Data Rate: 1-11Mbps, 6-54Mbps, up to 72.2Mbps  
Quantity of Channels: 11 for 802.11b/g/n-HT20  
Channel Separation: 5MHz  
Type of Antenna: PCB Antenna  
Antenna Gain: 2.5dBi

## 1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: \* = Plane-wave equivalents power density

### 1.3 MPE Calculation Method

$$S = (30 * P * G) / (377 * R^2)$$

S = power density (in appropriate units, e.g., mw/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

### 1.4 MPE Calculation Result

Maximum Tune-Up output power: 10.93 (dBm)

Maximum peak output power at antenna input terminal: 12.39 (mW)

Prediction distance: >20(cm)

Prediction frequency: 2437 (MHz)

Antenna gain: 2.5 (dBi)

Directional gain (numeric gain): 1.78

The worst case is power density at prediction frequency at 20cm: 0.0044(mw/cm<sup>2</sup>)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm<sup>2</sup>)

Result: Pass