

(1) This device may not cause harmful interference.

(2) This device must accept any interference received, including

interference that may cause This device complies with Part 15 of the FCC Rules. Operation is subject to the following two

Safety warning: The cooler's normal operating temperature is $0^{\circ}C \sim 40^{\circ}C$. In order to ensure the normal cooler functions, do not use this cooler outside the temperature range. This device may be used in each EU member state.

技术要求:

1、材质:105g黑色特种纸;

WARNING: Cancer and Reproductive Harm -www.P65Warnings.ca.gov.

- 2、工艺:2专色印刷+过哑油
- 3、成型: 5折页,风琴折 12P 80*114mm
- 4、尺寸公差: ±1 mm。

PDF

Electrical characteristics

Common parameters of electronic price tag

parameter	Range	Remarks
working temperature (normal temp)	0-40°C	Display screen
Storage temperature	-25-60°C	Display screen
Ice screen working temperature	-20-40°C (2.13inch)	Display screen
Waterproof grade	IP54	
Endurance time	5 years	Refresh 4 times a day
display technique	E-ink	
material	ABS+PC	
density	0.226x0.227mm	
battery	CR2450	2pcs/group
Battery capacity	600mAhx2	
Encryption mode	AES-128	
LED	RED	
Transmission frequency	2.4GHz2.4835GHz	
language	Chinese/English	PNG format picture
update	OTA	

DC characteristics of display screen working voltage Vcc 2.2 3.3 3.7 V

nennig renage				0.0		
Working current	IOPR	Vcc=3V	2	2.4	2	mA
Standby current	IIDLE	Vcc=3V		0.63		uA
Wrieless frequency	F			2.4		GHz

Working characteristics

working characteri	SUCS
patameter	Typical value
ESL display	Report the tag heartbeat every 3-10 minutes and
	receive the base station instruction within 15 seconds
Refresh success rate	100% success rate within the base station
Working status of	Reply after receiving the refresh information, and
receiving information	reply after the refresh successfully
Identification	Radium carving MAC address
LBS	Beacon tag
LED	red

Main CPU parameter Dominant frequency 32bit RISC+dual 8051 mum power Idle current 0.9uA sensitivity -95dBm Working frequency 2.4GHz-2.4835GHz Sleep mode Support remote wake-up orking mode Star networking on Accuracy Im (location beacon density 10m)

Mechanical Dimensions

 parameter
 dimensions (L*W*T) mm
 pixel
 Display area (mm)
 Battery(mAh)

 4.2
 104.83x86.83x16.68
 400x300
 84.8x63.6
 2400

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance of 20 cm between the radiator and your body. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.

Warranty Provisions

Warranty period: The warranty period commences from the warranty period: The warranty period commences from the date of purchase. The product and other accessories carry a warranty period according to local regulations and policy. The date on the proof of purchase or any other valid voucher will be considered as the date of purchase. For more detailed warranty information, please consult your local dealer or visit Nubia official website: http://www.nubia.com/en/

Non-Warranty Provisions

The warranty doesn't cover products which have been handled in any of the following cases:

Products malfunctioned or damaged due to misuse, improper use, abuse, negligence, or any improper use not according to the

user manual. ♦ Product repaired,replaced or altered by any person other than

Nubia customer service center. Products malfunctioned or damaged due to natural calamity, force majeure, unpredictable accidents and any other factors

Applicable accention and any other back of a second second

Product whose serial nunber or warranty sticker is missing.

Products which expire the warranty period specified in warranty card.If those provisions conflict with local laws and regulations, it subject to the local regulation.



Warranty Card

Warranty Information

Name

Purchase Date

Charger S/N

Dealer

Dealer Tel.

Notes

If the product does not contain charger or battery , you don't have to fill in the serial number. This certificate will become effective only after stamped by a dealer authorized by Nubia Technology Co., Ltd.

Nubia Technology Co., Ltd.

Address: Room 1801, Building 2, Chongwen Park, Nanshan Zhiyuan, No.3370, Liuxian Rd, Nanshan District, Shenzhen City, Guangdong Province, P. R. China Official website: www.nubia.com/en/