

TEST REPORT								
FCC ID::	2BEQO-T11							
Test Report No::	TCT250226E041							
Date of issue::	Mar. 04, 2025							
Testing laboratory:	SHENZHEN TONGCE TE	STING LAB						
Testing location/ address:	Fuhai Subdistrict, Bao'an	101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Tuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 18103, People's Republic of China						
Applicant's name:	SHENZHEN HAOCHENG	HENZHEN HAOCHENG TECHNOLOGY CO., LTD						
Address::		501, Main Building, Qiaocheng No.1 Plaza, No.2 shenyun Road, Gaofa Community, Shahe Street, Nanshan District, Shenzhen city, 518000 China						
Manufacturer's name:	SHENZHEN HAOCHENG	TECHNOLOGY	CO., LTD					
Address::	501, Main Building, Qiaocheng No.1 Plaza, No.2 shenyun Road, Gaofa Community, Shahe Street, Nanshan District, Shenzhen city, 518000 China							
Standard(s):	KDB 447498 D01 Genera	l RF Exposure Gu	uidance v06					
Product Name:	Smart Band							
Trade Mark::	N/A	(C)	(C)					
Model/Type reference:	T11							
Rating(s)::	Rechargeable Li-ion Batte	ery DC 3.8V						
Date of receipt of test item :	Feb. 26, 2025							
Date (s) of performance of test:	Feb. 26, 2025 ~ Mar. 04,	2025						
Tested by (+signature):	Yannie ZHONG	Yannie	TOMOCETA					
Check by (+signature):	Beryl ZHAO	Boyl 24	TCT					
Approved by (+signature):	Tomsin	Toms	84					

#### General disclaimer:

This report shall not be reproduced except in full, without the written approval of SHENZHEN TONGCE TESTING LAB. This document may be altered or revised by SHENZHEN TONGCE TESTING LAB personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

Hotline: 400-6611-140 Tel: 86-755-27673339 Fax: 86-755-27673332 http://www.tct-lab.com





# **Table of Contents**

1.1 1.2 2. Ge 2.1 2.2 3. Fa 3.1 3.2	EUT desc. Model(s) neral Info Test envi Descripti cilities ar Facilities Location	listormation armation on of Sup	and mode. port Units ditations	ent Data .		3445



# 1. General Product Information

# 1.1. EUT description

Product Name:	Smart Band	(C)		
Model/Type reference:	T11			
Sample Number:	TCT250226E021-0101			
Operation Frequency:	2402MHz~2480MHz		(0)	
Modulation Type:	For BT: GFSK, π/4-DQPSK For BLE: GFSK			
Antenna Type:	Internal Antenna			
Antenna Gain:	-9.13dBi			
Rating(s):	Rechargeable Li-ion Battery DC	3.8V		

Note: The antenna gain listed in this report is provided by applicant, and the test laboratory is not responsible for this parameter.

1.2. N	arameter. <b>lodel(s) l</b> lone.	ist			



# 2. General Information

## 2.1. Test environment and mode

Item	Normal condition						
Temperature	+25°C						
Voltage	DC 3.8V						
Humidity	56%						
Atmospheric Pressure:	1008 mbar						
Test Mode:							
Engineering mode:	Keep the EUT in continuous transmitting by select channel						

## 2.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment Model No.		Serial No.	FCC ID	Trade Name	
1		1	1	1	

#### Note:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
- 3. For conducted measurements (Output Power, 20dB Occupied Bandwidth, Carrier Frequencies Separation, Hopping Channel Number, Dwell Time, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.



### 3. Facilities and Accreditations

#### 3.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

• FCC - Registration No.: 645098

SHENZHEN TONGCE TESTING LAB

**Designation Number: CN1205** 

The testing lab has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

IC - Registration No.: 10668A

SHENZHEN TONGCE TESTING LAB

CAB identifier: CN0031

The testing lab has been registered by Innovation, Science and Economic Development Canada for radio equipment testing.

#### 3.2. Location

SHENZHEN TONGCE TESTING LAB

Address: 2101 & 2201, Zhenchang Factory, Renshan Industrial Zone, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518103, People's Republic of China

TEL: +86-755-27673339





### 4. Test Results and Measurement Data

According to KDB 447498 D01 General RF Exposure Guidance v06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the commission's guidance.

The 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- When the minimum test separation distance is < 5 mm, a distance of 5 mm according is applied to determine SAR test exclusion.
- The result is rounded to one decimal place for comparison

#### BDR+EDR:

Channel	Frequency (GHz)	Max. Power (dBm)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
CH 39	2.441	3.23	2.5±1	3.5	2.24	5	0.70	3.0

BLE(1M):

	Channel	Frequency (GHz)	Max. Power (dBm)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
L	CH 19	2.440	3.27	2.5±1	3.5	2.24	5	0.70	3.0

BLE(2M):

Channel	Frequency (GHz)	Max. Power (dBm)	Tune up Power (dBm)	Max. Tune up Power (dBm)	Max. Tune up Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
CH 19	2.440	3.27	2.5±1	3.5	2.24	5	0.70	3.0

Result:

Base on the calculation value, No SAR measurement is required.

\*\*\*\*\*END OF REPORT\*\*\*\*