



KSIGN (Guangdong) Testing Co., Ltd.

West Side of 1/F., Building C, Zone A, Fuyuan New Factory, Jiujiu Industrial Park,
Minzhu, Shatou, Shajing, Bao'an District, Shenzhen, Guangdong, People's Republic of China
Tel.: + (86)755-29852678 Fax: + (86)755-29852397 E-mail: info@gdkesign.cn Website: www.gdkesign.com

RF Exposure Evaluation

FCC ID:2AO94-MK05

REQUIREMENT

KDB447498 D01 General RF Exposure Guidance v06, Clause 4.3.1(a)

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$

Where

-f(GHz) is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

TEST RESULT

☒ **Passed**

☐ **Not Applicable**

BLE:

Test mode	Channel Frequency (MHz)	Max. Measured Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Maximum Output Power (mW)	Calculating data	Limit	Results
GFSK_1M	2402	0.08	0.08±1	1.08	1.28	0.40	3.00	Pass
	2440	-0.32	-0.32±1	0.68	1.17	0.36		
	2480	-0.78	-0.78±1	0.22	1.05	0.33		
GFSK_2M	2402	-0.37	-0.37±1	0.63	1.28	0.36	3.00	Pass
	2440	-0.93	-0.93±1	0.07	1.17	0.32		
	2480	-1.24	-1.24±1	-0.24	1.05	0.30		

Note:

-The exposure safety distance is less than 5mm.

*****THE END*****