

Receiver: Antenna 1/4λ wire antenna		Frequency Chart Transmitter A				Transmitter B					NOT HAPPY? LET US HELP!	This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accep any interference received, including interference that may cause undesired operation.
		Channel(CH) Frequency(I				Channel(CH)	Frequency(MHz)	Channel(CH)	Frequency(MHz)	We love to hear from customers! Share your experience with others by reviewing	Have any questions or concerns? Our friendly and responsive customer service	Changes or modifications not expressly approved by the party responsible for compliance couvoid the user's authority to operate the equipment.
Audio output connector		diamiei(Cii)	556,710	25	566,550	1	576.390	25	586,230	your product on Amazon. Scan the QR code below or visit:	wants to make sure you have the best experience	NOTE: This equipment has been tested and found to comply with the limits for a Class B digital
Signal to noise ratio	80dB or more	1				2	576,800	26	586,640	or visit: amazon.com/review/review-your-purchases#:	possible!	increase the separation between the equipment and receiver.
Distortion	0.5% or less	2	557.120	26	566,960	3	577.210	27	587.050	-		
Headphone output level	el 30mW (16 Ω) -60 dBV	3	557.530	27	567.370	4	577,620	28	587,460		Call us at 1-800-354-1739 (US)	
Audio output level Power supply	Two AA size batteries	4	557.940	28	567.780		578,030	29	587,870	-	Now! Monday-Friday: 9 am - 4 pm (PST) roduct includes a 1 year limited warranty. register the product within 30 days of	
Dimensions	208(H) × 67(W) × 29(L)mm	5	558.350	29	568.190			30	588,280	Act Now!		
Weight	95g without batteries	6	558.760	30	568.600	6	578.440			If you register the product within 30 days of purchase, you'll receive an additional 1-year warranty extension for a total of two years of		
		7	559.170	31	569,010	7	578,850	31	588,690		Email us at support@movophoto.com	
		8	559,580	32	569,420	8	579.260	32	589.100	protection.	Live chat us at www.movophoto.com	 Connect the equipment into an outlet on a circuit different from that to which the receiver i connected.
Lavalier Microphone		9	559,990	33	569.830	9	579.670	33	589.510	To register your product and for full details on the warranty, visit www.movophoto.com/warranty or scan QR code:	Live chat us at www.movophoto.com	 Consult the dealer or an experienced radio/TV technician for help. Radiation Exposure Statement Radiation Exposure Statement
		10	560,400	34	570.240 570.650	10	580.080	34	589.920 590.330			
		11					580.490	35				
Transducer:	Back electret Condenser		560.810			12	580,900	36	590.740			The device has been evaluated to meet general RF exposure requirement. The device can be us in portable exposure condition without restriction.
Polar pattern:	Omni-directional	12	561,220	36	571.060	13	581.310	37	591.150			
Frequency Range:	35Hz ~ 18 KHz	13	561,630	37	571,470	14	581.720	38	591.560			
Signal / Noise:	74dB SPL	14	562.040	38	571.880	15	582,130	39	591,970			
Sensitivity:	-30dB +/-3dB / 0dB=1V/Pa, 1 kHz	15	562.450	39	572.290							
Connector:	3.5mm locking mini plug	16	562.860	40	572.700	16	582.540	40	592.380	f 🗹 🖸		
Length:	1.2m (4')	17	563.270	41	573.110	17	582,950	41	592,790			
		18	563,680	42	573,520	18	583.360	42	593.200	Facebook & Youtube: /movophotogroup Twitter & Instagram: @movophoto	 	
		19	564,090	43	573.930	19	583.770	43	593.610		·	
		20	564,500	44	574,340	20	584.180	44	594.020			
		21	564,910	45	574,750	21	584.590	45	594.430			
						22	585,000	46	594,840			
		22	565.320	46	575.160	23	585,410	47	595,250			
		23	565.730	47	575.570	24	585,820	48	595,660	Movo Photo Group		
		24	566,140	48	575,980					www.movophoto.com support@movophoto.com		

技术要求:

1、表面无色差

2、无正负公差

3、包装标注尺寸为内尺寸