

RF Exposure Report

Report No.: SA190524D09

FCC ID: P27BC950NA4

Test Model: BC950NA4

Series Model: BC950NA4yxxxxxxx, BC950NA4Cyxxxxxxx (y should be "blank" or "-"; x could be 0 to 9, A to Z,

a to z, "blank" or "-", for marketing purpose) (See section 2.4 for more details)

Received Date: May 24, 2019

Date of Evaluation: Jun. 17, 2019

Issued Date: Jun. 19, 2019

Applicant: Sercomm Corp.

Address: 8F, No. 3-1, YuanQu St., NanKang, Taipei 115, Taiwan, R.O.C. (NanKang

Software Park)

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan,

R.O.C.

Test Location: No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil, Kwei Shan Dist., Taoyuan City

33383, Taiwan (R.O.C)

FCC Registration /

788550 / TW0003

Designation Number:





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: SA190524D09 Page No. 1 / 6 Report Format Version: 6.1.1



Table of Contents

Relea	ase Control Record	3
1	Certificate of Conformity	4
2	RF Exposure	5
2.1	Limits for Maximum Permissible Exposure (MPE)	5
2.2	MPE Calculation Formula	5
	Classification	
2.4	Description of EUT	5
	Antenna Gain	
2.6	Calculation Result of Maximum Conducted Power	6



Release Control Record

Issue No.	Description	Date Issued
SA190524D09	Original Release	Jun. 19, 2019



1 Certificate of Conformity

Product: LTE Battery Camera

Brand: Sercomm

Test Model: BC950NA4

Series Model: BC950NA4yxxxxxxx, BC950NA4Cyxxxxxxx (y should be "blank" or "-"; x could be 0 to 9, A to Z, a to z,

"blank" or "-", for marketing purpose) (See section 3.2.1 for more details)

Sample Status: Engineering Sample

Applicant: Sercomm Corp.

Date of Evaluation: Jun. 17, 2019

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by: Jun. 19, 2019

Rona Chen / Specialist

Approved by: , **Date:** Jun. 19, 2019

Dylan Chiou / Project Engineer



2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Power Density Strength (A/m) (mW/cm²)		Average Time (minutes)		
Limits For General Population / Uncontrolled Exposure						
0.3-1.34	614	1.63	(100)*	30		
1.34-30	824/f	2.19/f	(180/f ²)*	30		
30-300	27.5	0.073	0.2	30		
300-1500			f/1500	30		
1500-100,000			1.0	30		

f = Frequency in MHz; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

pi = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Description of EUT

All models are listed as below.

Product	Brand	Model	Difference		
	Sercomm	BC950NA4yxxxxxxx	With GPS function		
LTE Battery Camera		BC950NA4Cyxxxxxxx	Without GPS function		
(y should be "blank" or "-"; x could be 0 to 9, A to Z, a to z, "blank" or "-", for marketing purpose)					

Report No.: SA190524D09 Page No. 5 / 6 Report Format Version: 6.1.1



2.5 Antenna Gain

	Gain (dBi)					
Antenna Type	WCDMA II /	LTE David 4	WCDMA V /	LTE D == 140	LTE Band 13	
	LTE Band 2	LTE Band 4	LTE Band 5	LTE Band 12		
PIFA	2.94	2.88	-0.98	-2.90	-0.14	

2.6 Calculation Result of Maximum Conducted Power

Band	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WCDMA II	1850-1910	23.52	2.94	20	0.088	1.00
WCDMA V	824-849	24.09	-0.98	20	0.041	0.55
LTE 2	1850-1910	22.75	2.94	20	0.074	1.00
LTE 4	1710-1755	22.75	2.88	20	0.073	1.00
LTE 5	824-849	23.11	-0.98	20	0.032	0.55
LTE 12	699-716	23.09	-2.90	20	0.021	0.47
LTE 13	777-787	22.94	-0.14	20	0.038	0.52

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

--- END ---