



# 1 MAXIMUM PERMISSIBLE EXPOSURE (MPE)

## 1.1 General Description of E.U.T

**Product Name** ..... : Kettle  
**Model No.** ..... : CS108-NK  
**FCC ID** ..... : 2ARBY-CS108-NK  
**Rated Voltage** ..... : AC 120V, 60Hz, 1200W

## 1.2 Standard Applicable

According to §1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

### (a) Limits for Occupational / Controlled Exposure

| Frequency range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|-----------------------------------------|------------------------------------------------------------------------|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                  | 6                                                                      |
| 3.0-30                | 1842/f                            | 4.89/f                            | (900/f)*                                | 6                                                                      |
| 30-300                | 61.4                              | 0.163                             | 1.0                                     | 6                                                                      |
| 300-1500              | /                                 | /                                 | F/300                                   | 6                                                                      |
| 1500-100000           | /                                 | /                                 | 5                                       | 6                                                                      |

### (b) Limits for General Population / Uncontrolled Exposure

| Frequency range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm <sup>2</sup> ) | Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|-----------------------------------------|------------------------------------------------------------------------|
| 0.3-1.34              | 614                               | 1.63                              | (100)*                                  | 30                                                                     |
| 1.34-30               | 824/f                             | 2.19/f                            | (180/f)*                                | 30                                                                     |
| 30-300                | 27.5                              | 0.073                             | 0.2                                     | 30                                                                     |
| 300-1500              | /                                 | /                                 | F/1500                                  | 30                                                                     |
| 1500-100000           | /                                 | /                                 | 1                                       | 30                                                                     |

Note: f = frequency in MHz; \* = Plane-wave equivalents power density



### 1.3 MPE Calculation Method

$$S = (30 \cdot P \cdot G) / (377 \cdot R^2)$$

S = power density (in appropriate units, e.g., mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

### 1.4 MPE Calculation Result

| Prediction distance (mm) | Prediction frequency (MHz) | Antenna Gain (dBi) | Numeric gain | Maximum Tune-up output power (dBm) | Maximum peak output power (mW) | PD (mW/cm <sup>2</sup> ) | Limit (mW/cm <sup>2</sup> ) |
|--------------------------|----------------------------|--------------------|--------------|------------------------------------|--------------------------------|--------------------------|-----------------------------|
| >200                     | 2480                       | 0                  | 1            | 0.386                              | 1.093                          | 0.00021744               | 1.0                         |

Result: Pass

=====End of Report=====

# WALTEK