



Test Report No.: FM2010WDG0259

RF EXPOSURE REPORT

Applicant	Belkin International, Inc.
Address	12045 East Waterfront Drive, Playa Vista, CA 90094 USA

Manufacturer or Supplier	Belkin International, Inc.
Address	12045 East Waterfront Drive, Playa Vista, CA 90094 USA
Product	SOUNDFORM™ CONNECT Audio Adapter with AirPlay 2
Brand Name	belkin
Model	AUZ002
Additional Model & Model Difference	N/A
Date of tests	Nov. 25, 2020 ~ Dec. 07, 2020

☒ FCC Part 2 (Section 2.1091)☒ KDB 447498 D01☒ IEEE C95.1**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**Tested by Lucas Chen
Project Engineer / EMC DepartmentApproved by Glyn He
Assistant Manager / EMC Department

Date: Jan. 28, 2021

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



Test Report No.: FM2010WDG0259

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM2010WDG0259	Original release	Jan. 28, 2021

1. CERTIFICATION

FCC ID:	K7SAUZ002
PRODUCT:	SOUNDFORM™ CONNECT Audio Adapter with AirPlay 2
BRAND NAME:	belkin
MODEL NO.:	AUZ002
ADDITIONAL NO.:	N/A
TEST SAMPLE:	Engineering Sample
APPLICANT:	Belkin International, Inc.
STANDARDS:	FCC Part 2 (Section 2.1091)
	KDB 447498 D01
	IEEE C95.1

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
Wi-Fi 2.4GHz	5.24	FPC Antenna
Wi-Fi 5GHz (5150-5250MHz)	1.81	FPC Antenna
Wi-Fi 5GHz (5260-5320MHz)	1.32	FPC Antenna
Wi-Fi 5GHz (5500-5700MHz)	3.53	FPC Antenna
Wi-Fi 5GHz (5725-5850MHz)	3.53	FPC Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
802.11b	2412-2462	12	+2	10	14
802.11g	2412-2462	9	+2	7	11
802.11n(HT20)	2412-2462	9	+2	7	11
Wi-Fi 5GHz(Band1)	5150-5250	12	+2	10	14
Wi-Fi 5GHz(Band2)	5260-5320	11	+2	9	13
Wi-Fi 5GHz(Band3)	5500-5700	11	+2	9	13
Wi-Fi 5GHz(Band4)	5725-5850	13	+2	11	15

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
802.11b	2437	12.54
802.11g	2437	9.46
802.11n(HT20)	2437	9.68
Wi-Fi 5GHz(Band1)	5180	13.31
Wi-Fi 5GHz(Band2)	5260	12.03
Wi-Fi 5GHz(Band3)	5610	12.45
Wi-Fi 5GHz(Band4)	5775	14.24

FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
Wi-Fi 2.4GHz	14	5.24	20	0.016700	1.0
Wi-Fi 5GHz(Band1)	14	1.81	20	0.007581	1.0
Wi-Fi 5GHz(Band2)	13	1.32	20	0.005379	1.0
Wi-Fi 5GHz(Band3)	13	3.53	20	0.008948	1.0
Wi-Fi 5GHz(Band4)	15	3.53	20	0.014182	1.0

The Wi-Fi 2.4GHz and 5GHz can not transmit simultaneously.

--- END ---