

Prüfbericht-Nr.: Test report no.:	CN22NYGA(FCC-MPE) 001	Auftrags-Nr.: Order no.:	238544116	Seite 1 von 9 Page 1 of 9
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2022-06-01	
Auftraggeber: Client:	CUBTEK INC. Rm. 7, 6F., No.38, Taiyuan St., Zhubei City, Hsinchu County, 30265 Taiwan			
Prüfgegenstand: Test item:	Advanced millimeter wave vehicle turn assist system			
Bezeichnung / Typ-Nr.: Identification / Type no.:	B122-036			
Auftrags-Inhalt: Order content:	FCC Certification			
Prüfgrundlage: Test specification:	IEEE Std C95.1 47 CFR §2.1091 47 CFR §1.1310			
Wareneingangsdatum: Date of sample receipt:	2022-06-03			
Prüfmuster-Nr.: Test sample no.:	A003274378-017			
Prüfzeitraum: Testing period:	2022-06-06 - 2022-06-07			
Ort der Prüfung: Place of testing:	EMC/RF Taipei Testing Site			
Prüflaboratorium: Testing laboratory:	Taipei Testing Laboratories			
Prüfergebnis*: Test result*:	Pass			
zusammengestellt von: compiled by:	genehmigt von: authorized by:			
Datum: Date: 2022-08-30				
Stellung / Position:	Senior Project Manager	Ausstellungsdatum: Issue date: 2022-08-30	Brenda Chen	
Sonstiges / Other:				
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged			
* Legende:	1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n)	2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	4 = ausreichend N/A = nicht anwendbar
* Legend:	1 = very good P(ass) = passed a.m. test specification(s)	2 = good F(ail) = failed a.m. test specification(s)	3 = satisfactory F(ail) = failed a.m. test specification(s)	4 = sufficient N/A = not applicable
5 = mangelhaft N/T = nicht getestet 5 = poor N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.				

Contents

HISTORY OF THIS TEST REPORT	3
1 GENERAL REMARKS	4
1.1 COMPLEMENTARY MATERIALS.....	4
1.2 DECISION RULE OF CONFORMITY	4
2 TEST SITES	5
2.1 TEST FACILITIES	5
2.2 TEST FACILITY.....	5
3 GENERAL PRODUCT INFORMATION.....	6
3.1 PRODUCT FUNCTION AND INTENDED USE	6
3.2 RATINGS AND SYSTEM DETAILS.....	6
4 MAXIMUM PERMISSIBLE EXPOSURE EVALUATION.....	7
4.1 INTRODUCTION	7
4.2 REFERENCE LEVELS	7
4.3 CLASSIFICATION OF THE ASSESSMENT METHODS.....	8
5 TEST RESULTS	9
5.1 MAXIMUM POWER DENSITY	9

APPENDIX EP - PHOTOGRAPHS OF EUT

Prüfbericht - Nr.: CN22NYGA(FCC-MPE) 001
Test Report No.

Seite 3 von 9
Page 3 of 9

HISTORY OF THIS TEST REPORT

Revision	Description	Date Issued
00	Original Release	2022-07-05
01	Modified the antenna gain in page 6	2022-08-30

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:
Appendix EP - Photographs of EUT

1.2 Decision Rule of Conformity

The decision rule of conformity of this test report is following the requirements of the requested standard in the quotation, and agreed among testing laboratory and manufacturer (applicant) to exclude the consideration of Measurement Uncertainty, unless it is required by the specific standard.

2 Test Sites

2.1 Test Facilities

Taipei Testing Laboratories

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

2.2 Test Facility

Taipei Testing Laboratories

No.458-18, Sec. 2, Fenliao Rd., Linkou Dist.,
New Taipei City 244
Taiwan (R.O.C.)

3 General Product Information

3.1 Product Function and Intended Use

The EUT is an Advanced millimeter wave vehicle turn assist system.
It contains a 76-77 GHz compatible mmwave module enabling the user to detect the object through this wireless interface.
For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Basic Information of EUT

Item	EUT Information
Kind of Equipment/Test Item	Advanced millimeter wave vehicle turn assist system
Type Identification	B122-036
FCC ID	2AN3BB122036

Technical Specification of EUT

Item	EUT Information
Operating Frequency	76 ~ 77GHz
Modulation	FMCW
Operation Voltage	24 Vdc
Antenna Type	Array Antenna
Antenna Gain	13.88 dBi

4 Maximum Permissible Exposure Evaluation

4.1 Introduction

This Standard specifies requirements for, and provides guidance on, assessing compliance with the exposure limits of radiofrequency (RF) safety standards such as IEEE Std C95.1. This includes methodologies for making an assessment (by measurement or computation) of human exposure to ambient RF fields and induced body currents in the frequency range of 0 kHz to 300 GHz.

This Standard may also be used as a guide for making low-level environmental exposure assessments in areas around RF sources listed above, as well as other sources such as Wi-Fi devices.

4.2 Reference Levels

Where appropriate, the reference levels are derived from the basic restrictions by mathematical modelling and by extrapolation from the results of laboratory investigations at specific frequencies. They are given for the condition of maximum coupling of the field to the exposed individual, thereby providing maximum protection.

According to FCC 1.1310, the criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

The FCC MPE limits from 47 CFR §1.1310 are shown in the table below

Frequency Range [MHz]	Electric Field Strength [V/m]	Magnetic Field Strength [A/m]	Power Density [mW/cm ²]	Average Time [minutes]
(A) Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f ²	6
30 – 300	61.4	0.163	1.0	6
300 – 1500			f/300	6
1500 – 100000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 – 1500			f/1500	30
1500 – 100000			1.0	30

NOTE –

- (1) f is the frequency in MHz.
- (2) Provided that basic restrictions are met and adverse indirect effects can be excluded, field strength values can be exceeded. For the specific case of occupational exposures at frequencies up to 100 kHz, the derived electric fields can be increased by a factor of 2 under conditions in which adverse indirect effects from contact with electrically charged conductors can be excluded.
- (3) For frequencies between 100 kHz and 10 GHz, the quantities Seq, E2 and H2 are averages over any 6 minutes.
- (4) For frequencies exceeding 10 GHz, Seq, the quantities E2 and H2 are averages over any $68/f$ 1.05 minutes (f in GHz).

4.3 Classification of the Assessment Methods

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user. Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. So, this product under normal use is located on electromagnetic far field between the human body.

MPE Calculation Method according to KDB 447487 D01 General RF Exposure Guidance v06

Power Density: $S_{(mW/cm^2)} = PG/4\pi R^2$ or $EIRP/4\pi R^2$

Where:

S = power density (mW/cm²)

P = power input to the antenna (mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (cm)

5 Test Results

5.1 Maximum Power Density

The maximum power density at a distance of 20 cm are shown as below:

Frequency (GHz)	Average Output Power (dBm)	Average Output Power (mW)	Antenna Gain (dBi)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)	Pass / Fail
76.45	-8.22	0.15	13.88	0.00073	1.0	Pass

Conclusion

The device complies with the FCC exposure requirements since the maximum transmitter power density is below the FCC limit.