

FCC RF Test Report

APPLICANT : TCT Mobile Limited
EQUIPMENT : HSUPA, HSDPA, UMTS triband, GSM
quadband mobile phone
BRAND NAME : ALCATEL ONETOUCH
MODEL NAME : TCL D55
FCC ID : RAD548
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Feb. 13, 2015 and testing was completed on Mar. 05, 2015. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Reviewed by: Joseph Lin / Supervisor



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification subjective to this standard	5
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Applicable Standards	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 Carrier Frequency Channel	7
2.2 Pre-Scanned RF Power	8
2.3 Test Mode	9
2.4 Connection Diagram of Test System	10
2.5 Support Unit used in test configuration and system	11
2.6 EUT Operation Test Setup	11
2.7 Measurement Results Explanation Example	11
3 TEST RESULT	12
3.1 6dB Bandwidth Measurement	12
3.2 Output Power Measurement	14
3.3 Power Spectral Density Measurement	16
3.4 Conducted Band Edges and Spurious Emission Measurement	18
3.5 Radiated Band Edges and Spurious Emission Measurement	31
3.6 AC Conducted Emission Measurement	35
3.7 Antenna Requirements	39
4 LIST OF MEASURING EQUIPMENT	40
5 UNCERTAINTY OF EVALUATION	41
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED SPURIOUS EMISSION	
APPENDIX C. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR521301C	Rev. 01	Initial issue of report	Mar. 18, 2015

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.37 dB at 30.970 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 15.39 dB at 1.740 MHz
0	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

TCT Mobile Limited

5F, C building, No. 232, Liang Jing Road, ZhangJiang High-Tech Park, Pudong Area, Shanghai, P.R. China 201203

1.2 Manufacturer

TCT Mobile Limited

5F, C building, No. 232, Liang Jing Road, ZhangJiang High-Tech Park, Pudong Area, Shanghai, P.R. China. 201203

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	HSUPA, HSDPA, UMTS triband, GSM quadband mobile phone
Brand Name	ALCATEL ONETOUCH
Model Name	TCL D55
FCC ID	RAD548
EUT supports Radios application	GSM/GPRS/EGPRS(Downlink Only)/WCDMA/HSPA/HSPA+(Downlink Only)/ WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth v3.0 + EDR/Bluetooth v4.0 LE
HW Version	PIO
SW Version	01001
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	802.11b/g/n : 2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to Antenna	802.11b : 19.55 dBm (0.0902 W)
	802.11g : 23.27 dBm (0.2123 W)
	802.11n HT20 : 23.14 dBm (0.2061 W)
	802.11n HT40 : 23.21 dBm (0.2094 W)
Antenna Type	802.11b/g/n : PIFA Antenna with gain -2.88 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK)
	802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
Test Site No.	Sporton Site No.	
	TH01-SZ	CO01-SZ

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.	
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958	
Test Site No.	Sporton Site No.	FCC Registration No.
	03CH01-KS	149928

Note: The test site complies with ANSI C63.4 2009 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. FCC permits the use of the 1.5 meter table as an alternative in C63.10-2013 through inquiry tracking number 961829.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

2.4GHz 802.11b RF Output Power (dBm)						
Power vs. Channel			Power vs. Data Rate			
Channel	Frequency (MHz)	Data Rate 1Mbps	Channel	2Mbps	5.5Mbps	11Mbps
CH 01	2412 MHz	19.24	CH 11	19.54	19.45	19.50
CH 06	2437 MHz	19.43				
CH 11	2462 MHz	19.55				

2.4GHz 802.11g RF Output Power (dBm)										
Power vs. Channel			Power vs. Data Rate							
Channel	Frequency (MHz)	Data Rate	Channel	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
		6Mbps								
CH 01	2412 MHz	22.94	CH 11	23.21	23.22	23.18	23.21	23.19	23.17	23.16
CH 06	2437 MHz	23.05								
CH 11	2462 MHz	23.27								

2.4GHz 802.11n HT20 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
		MCS0								
CH 01	2412 MHz	22.74	CH 11	23.11	23.07	23.08	23.06	23.04	23.02	23.03
CH 06	2437 MHz	22.98								
CH 11	2462 MHz	23.14								

2.4GHz 802.11n HT40 RF Output Power (dBm)										
Power vs. Channel			Power vs. MCS Index							
Channel	Frequency (MHz)	MCS Index	Channel	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
		MCS0								
CH 03	2422 MHz	22.98	CH 09	23.04	23.00	22.87	22.85	22.79	22.81	22.78
CH 06	2437 MHz	23.08								
CH 09	2452 MHz	23.21								

2.3 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.


<2.4GHz>

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0


Test Cases	
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter)
Remark: For Radiated TCs, The tests were performance with Adapter, Earphone and USB Cable.	

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	E540	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Hawk	B690	03-HKB690	N/A	N/A

2.6 EUT Operation Test Setup

For WLAN function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 5 + 10 = 15 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A of this test report.



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r02.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup





3.2.5 Test Result of Peak Output Power

Please refer to Appendix A of this test report.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A of this test report.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A of this test report.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	Issac Song


WLAN 802.11b Channel 01

100kHz PSD reference Level




Date: 3.MAR.2015 09:29:37

Low Channel Plot




Date: 3.MAR.2015 09:31:04

Spurious Emission 30MHz~3GHz



Date: 3.MAR.2015 09:32:02

Spurious Emission 2GHz~25GHz




Date: 3.MAR.2015 09:32:20



Test Mode :	802.11b	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song


WLAN 802.11b Channel 06

100kHz PSD reference Level




Date: 3.MAR.2015 09:38:54

Spurious Emission 30MHz~3GHz



Date: 3.MAR.2015 09:41:12


Spurious Emission 2GHz~25GHz




Date: 3.MAR.2015 09:41:31




Test Mode :	802.11b	Temperature :	24~25℃
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	Issac Song

WLAN 802.11b Channel 11**100kHz PSD reference Level**


Date: 3.MAR.2015 09:46:39

High Channel Plot

Date: 3.MAR.2015 09:47:40

Spurious Emission 30MHz~3GHz

Date: 3.MAR.2015 09:50:15

Spurious Emission 2GHz~25GHz


Date: 3.MAR.2015 09:50:33



Test Mode :	802.11g	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	Issac Song


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 3.MAR.2015 10:26:55

Low Channel Plot




Date: 3.MAR.2015 10:29:45

Spurious Emission 30MHz~3GHz



Date: 3.MAR.2015 10:31:13


Spurious Emission 2GHz~25GHz




Date: 3.MAR.2015 10:31:31




Test Mode :	802.11g	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song

WLAN 802.11g Channel 06**100kHz PSD reference Level**

Date: 3.MAR.2015 10:43:15

Spurious Emission 30MHz~3GHz


Date: 3.MAR.2015 10:43:53

Spurious Emission 2GHz~25GHz


Date: 3.MAR.2015 10:44:10




Test Mode :	802.11g	Temperature :	24~25℃
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	Issac Song

WLAN 802.11g Channel 11**100kHz PSD reference Level**


Date: 3.MAR.2015 09:59:51

High Channel Plot

Date: 3.MAR.2015 10:00:51

Spurious Emission 30MHz~3GHz


Date: 3.MAR.2015 10:01:23

Spurious Emission 2GHz~25GHz


Date: 3.MAR.2015 10:01:41




Test Mode :	802.11n HT20	Temperature :	24~25℃
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	01	Test Engineer :	Issac Song

WLAN 802.11n HT20 Channel 01**100kHz PSD reference Level**


Date: 3.MAR.2015 10:51:22

Low Channel Plot

Date: 3.MAR.2015 10:56:01

Spurious Emission 30MHz~3GHz

Date: 3.MAR.2015 10:56:37

Spurious Emission 2GHz~25GHz


Date: 3.MAR.2015 10:56:55



Test Mode :	802.11n HT20	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song


WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level




Date: 3.MAR.2015 11:02:35

Spurious Emission 30MHz~3GHz



Date: 3.MAR.2015 11:04:13


Spurious Emission 2GHz~25GHz




Date: 3.MAR.2015 11:04:30




Test Mode :	802.11n HT20	Temperature :	24~25℃
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	11	Test Engineer :	Issac Song

WLAN 802.11n HT20 Channel 11**100kHz PSD reference Level**


Date: 3.MAR.2015 11:18:31

High Channel Plot

Date: 3.MAR.2015 11:19:51

Spurious Emission 30MHz~3GHz


Date: 3.MAR.2015 11:20:25

Spurious Emission 2GHz~25GHz


Date: 3.MAR.2015 11:20:42




Test Mode :	802.11n HT40	Temperature :	24~25°C
Test Band :	2.4GHz Low	Relative Humidity :	49~51%
Test Channel :	03	Test Engineer :	Issac Song

WLAN 802.11n HT40 Channel 03**100kHz PSD reference Level**


Date: 3.MAR.2015 11:26:17

Low Channel Plot

Date: 3.MAR.2015 11:26:45

Spurious Emission 30MHz~3GHz


Date: 3.MAR.2015 11:27:28

Spurious Emission 2GHz~25GHz


Date: 3.MAR.2015 11:27:46




Test Mode :	802.11n HT40	Temperature :	24~25°C
Test Band :	2.4GHz Mid	Relative Humidity :	49~51%
Test Channel :	06	Test Engineer :	Issac Song

WLAN 802.11n HT40 Channel 06**100kHz PSD reference Level**

Date: 3.MAR.2015 11:32:27

Spurious Emission 30MHz~3GHz

Date: 3.MAR.2015 11:36:27

Spurious Emission 2GHz~25GHz


Date: 3.MAR.2015 11:35:07



Test Mode :	802.11n HT40	Temperature :	24~25°C
Test Band :	2.4GHz High	Relative Humidity :	49~51%
Test Channel :	09	Test Engineer :	Issac Song


WLAN 802.11n HT40 Channel 09

100kHz PSD reference Level




Date: 3.MAR.2015 11:40:52

High Channel Plot




Date: 3.MAR.2015 11:41:13

Spurious Emission 30MHz~3GHz



Date: 3.MAR.2015 11:42:54

Spurious Emission 2GHz~25GHz



Date: 3.MAR.2015 11:41:53

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r02.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.


For average measurement:

 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11b	98.25	-	-	10Hz
802.11g	88.71	1.40	0.72	1kHz
2.4GHz 802.11n HT20	87.77	1.31	0.77	1kHz
2.4GHz 802.11n HT40	78.68	0.64	1.56	3kHz

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	24~26℃
Test Engineer :	Tiny You	Relative Humidity :	50~53%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter)		




Site : C001-SZ
Condition: FCC 15C_QP LISN_L_20140304 LINE

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.67	23.24	-22.76	46.00	12.90	0.19	10.15	Average
2	0.67	36.14	-19.86	56.00	25.80	0.19	10.15	QP
3	0.90	24.99	-21.01	46.00	14.60	0.24	10.15	Average
4	0.90	35.39	-20.61	56.00	25.00	0.24	10.15	QP
5	1.74	27.51	-18.49	46.00	17.10	0.23	10.18	Average
6 *	1.74	40.61	-15.39	56.00	30.20	0.23	10.18	QP
7	1.89	27.31	-18.69	46.00	16.90	0.22	10.19	Average
8	1.89	39.71	-16.29	56.00	29.30	0.22	10.19	QP
9	3.88	23.29	-22.71	46.00	12.69	0.37	10.23	Average
10	3.88	35.89	-20.11	56.00	25.29	0.37	10.23	QP
11	11.93	26.20	-23.80	50.00	14.80	0.99	10.41	Average
12	11.93	39.00	-21.00	60.00	27.60	0.99	10.41	QP



Test Mode :	Mode 1	Temperature :	24~26°C
Test Engineer :	Tiny You	Relative Humidity :	50~53%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + USB Cable (Charging from Adapter)		



Site : C001-SZ
Condition: FCC 15C_QP LISN_N_20140304 NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	1.61	26.63	-19.37	46.00	16.09	0.36	10.18	Average
2	1.61	39.33	-16.67	56.00	28.79	0.36	10.18	QP
3	1.79	28.35	-17.65	46.00	17.81	0.36	10.18	Average
4 *	1.79	40.15	-15.85	56.00	29.61	0.36	10.18	QP
5	1.91	26.45	-19.55	46.00	15.89	0.37	10.19	Average
6	1.91	38.15	-17.85	56.00	27.59	0.37	10.19	QP
7	2.57	25.11	-20.89	46.00	14.51	0.40	10.20	Average
8	2.57	38.01	-17.99	56.00	27.41	0.40	10.20	QP
9	3.92	23.18	-22.82	46.00	12.49	0.46	10.23	Average
10	3.92	36.28	-19.72	56.00	25.59	0.46	10.23	QP
11	12.45	26.84	-23.16	50.00	15.20	1.21	10.43	Average
12	12.45	37.34	-22.66	60.00	25.70	1.21	10.43	QP



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Jan. 28, 2015	Mar. 03, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	10Hz~40GHz	Jan. 28, 2015	Mar. 03, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
Power Sensor	Anritsu	MA2411B	1207253	0.3GHz~40GHz	Jan. 28, 2015	Mar. 03, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Oct. 25, 2014	Mar. 05, 2015	Oct. 24, 2015	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP30	101399	9kHz~30GHz	May 04, 2014	Mar. 05, 2015	May 03, 2015	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 13, 2014	Mar. 05, 2015	Nov. 12, 2015	Radiation (03CH01-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	25Mhz-2Ghz	Jan. 17, 2015	Mar. 05, 2015	Jan. 16, 2016	Radiation (03CH01-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 17, 2015	Mar. 05, 2015	Jan. 16, 2016	Radiation (03CH01-KS)
Active Horn Antenna	com-power	AHA-118	701030	1GHz~18GHz	Nov. 08, 2014	Mar. 05, 2015	Nov. 07, 2015	Radiation (03CH01-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Mar. 10, 2014	Mar. 05, 2015	Mar. 09, 2015	Radiation (03CH01-KS)
Amplifier	com-power	PA-103A	161069	1MHz~1GHz /32dB	May 04, 2014	Mar. 05, 2015	May 03, 2015	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02371	1GHz~26.5GHz	Oct. 28, 2014	Mar. 05, 2015	Oct. 27, 2015	Radiation (03CH01-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Mar. 05, 2015	NCR	Radiation (03CH01-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Mar. 05, 2015	NCR	Radiation (03CH01-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Mar. 05, 2015	NCR	Radiation (03CH01-KS)
EMI TEST Receiver	R&S	ESCI7	100768	9kHz~3GHz	May 04, 2014	Feb. 27, 2015	May 03, 2015	Conduction (CO01-SZ)
AC LISN	EMCO	3816/2SH	00103912	9kHz~30MHz	Feb. 02, 2015	Feb. 27, 2015	Feb. 01, 2016	Conduction (CO01-SZ)
AC LISN (for auxiliary equipment)	EMCO	3816/2SH	00103892	9kHz~30MHz	Feb. 02, 2015	Feb. 27, 2015	Feb. 01, 2016	Conduction (CO01-SZ)
AC Power Source	Chroma	61602	616020000891	100Vac~250Vac	Sep. 29, 2014	Feb. 27, 2015	Sep. 28, 2015	Conduction (CO01-SZ)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.5dB
---	-------

Test Engineer:	Tiny You	Temperature:	21~25	°C
Test Date:	2015/3/3	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412	12.55	9.56	0.50	Pass
11b	1Mbps	1	6	2437	12.55	9.56	0.50	Pass
11b	1Mbps	1	11	2462	12.55	9.56	0.50	Pass
11g	6Mbps	1	1	2412	17.45	15.64	0.50	Pass
11g	6Mbps	1	6	2437	17.45	15.44	0.50	Pass
11g	6Mbps	1	11	2462	17.35	15.48	0.50	Pass
HT20	MCS0	1	1	2412	18.25	15.48	0.50	Pass
HT20	MCS0	1	6	2437	18.15	15.16	0.50	Pass
HT20	MCS0	1	11	2462	18.20	15.72	0.50	Pass
HT40	MCS0	1	3	2422	36.30	35.20	0.50	Pass
HT40	MCS0	1	6	2437	36.20	35.20	0.50	Pass
HT40	MCS0	1	9	2452	36.30	35.16	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	19.24	30.00	-2.88	16.36	36.00	Pass
11b	1Mbps	1	6	2437	19.43	30.00	-2.88	16.55	36.00	Pass
11b	1Mbps	1	11	2462	19.55	30.00	-2.88	16.67	36.00	Pass
11g	6Mbps	1	1	2412	22.94	30.00	-2.88	20.06	36.00	Pass
11g	6Mbps	1	6	2437	23.05	30.00	-2.88	20.17	36.00	Pass
11g	6Mbps	1	11	2462	23.27	30.00	-2.88	20.39	36.00	Pass
HT20	MCS0	1	1	2412	22.74	30.00	-2.88	19.86	36.00	Pass
HT20	MCS0	1	6	2437	22.98	30.00	-2.88	20.10	36.00	Pass
HT20	MCS0	1	11	2462	23.14	30.00	-2.88	20.26	36.00	Pass
HT40	MCS0	1	3	2422	22.98	30.00	-2.88	20.10	36.00	Pass
HT40	MCS0	1	6	2437	23.08	30.00	-2.88	20.20	36.00	Pass
HT40	MCS0	1	9	2452	23.21	30.00	-2.88	20.33	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.08	16.45
11b	1Mbps	1	6	2437	0.08	16.59
11b	1Mbps	1	11	2462	0.08	16.75
11g	6Mbps	1	1	2412	0.52	14.47
11g	6Mbps	1	6	2437	0.52	14.64
11g	6Mbps	1	11	2462	0.52	14.89
HT20	MCS0	1	1	2412	0.57	13.50
HT20	MCS0	1	6	2437	0.57	13.84
HT20	MCS0	1	11	2462	0.57	13.99
HT40	MCS0	1	3	2422	1.04	13.22
HT40	MCS0	1	6	2437	1.04	13.29
HT40	MCS0	1	9	2452	1.04	13.49

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-6.92	-2.88	8.00	Pass
11b	1Mbps	1	6	2437	-7.24	-2.88	8.00	Pass
11b	1Mbps	1	11	2462	-6.83	-2.88	8.00	Pass
11g	6Mbps	1	1	2412	-9.93	-2.88	8.00	Pass
11g	6Mbps	1	6	2437	-10.88	-2.88	8.00	Pass
11g	6Mbps	1	11	2462	-9.46	-2.88	8.00	Pass
HT20	MCS0	1	1	2412	-11.78	-2.88	8.00	Pass
HT20	MCS0	1	6	2437	-11.50	-2.88	8.00	Pass
HT20	MCS0	1	11	2462	-11.84	-2.88	8.00	Pass
HT40	MCS0	1	3	2422	-15.43	-2.88	8.00	Pass
HT40	MCS0	1	6	2437	-15.40	-2.88	8.00	Pass
HT40	MCS0	1	9	2452	-14.81	-2.88	8.00	Pass



Appendix B. Radiated Spurious Emission

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2374.71	50.17	-23.83	74	48.88	31.28	6.17	36.16	160	335	P	H
		2373.54	35.1	-18.9	54	33.81	31.28	6.17	36.16	160	335	A	H
	*	2410.521	95.76	-	-	94.25	31.31	6.22	36.02	160	335	P	H
	*	2410.271	89.71	-	-	88.2	31.31	6.22	36.02	160	335	A	H
		2332.14	49.35	-24.65	74	48.43	31.23	6.12	36.43	154	109	P	V
		2390	34.84	-19.16	54	33.45	31.3	6.17	36.08	154	109	A	V
	*	2410.521	94.87	-	-	93.36	31.31	6.22	36.02	154	109	P	V
	*	2410.187	88.87	-	-	87.36	31.31	6.22	36.02	154	109	A	V
802.11b CH 06 2437MHz	*	2435.655	93.98	-	-	92.39	31.33	6.22	35.96	155	334	P	H
	*	2438.66	88.04	-	-	86.33	31.34	6.28	35.91	155	334	A	H
	*	2435.571	93.32	-	-	91.73	31.33	6.22	35.96	167	112	P	V
	*	2435.154	87.28	-	-	85.69	31.33	6.22	35.96	167	112	A	V
802.11b CH 11 2462MHz	*	2463.376	94.16	-	-	92.37	31.36	6.28	35.85	153	323	P	H
	*	2463.627	88.22	-	-	86.43	31.36	6.28	35.85	153	323	A	H
		2486.56	49.32	-24.68	74	47.41	31.37	6.33	35.79	153	323	P	H
		2483.52	34.73	-19.27	54	32.82	31.37	6.33	35.79	153	323	A	H
	*	2460.621	95.15	-	-	93.36	31.36	6.28	35.85	176	106	P	V
	*	2460.204	89.05	-	-	87.26	31.36	6.28	35.85	176	106	A	V
		2485.52	49.26	-24.74	74	47.35	31.37	6.33	35.79	176	106	P	V
		2483.52	34.41	-19.59	54	32.5	31.37	6.33	35.79	176	106	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11b (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		4824	48.13	-25.87	74	41.16	34.89	8.73	36.65	159	224	P	H
		4824	47.09	-26.91	74	40.12	34.89	8.73	36.65	174	236	P	V
802.11b CH 06 2437MHz		4875	47.96	-26.04	74	41.12	34.92	8.76	36.84	175	301	P	H
		7311	48.16	-25.84	74	40.62	35.56	10.84	38.86	206	336	P	H
		4875	46.54	-27.46	74	39.7	34.92	8.76	36.84	196	251	P	V
		7311	49.15	-24.85	74	41.61	35.56	10.84	38.86	223	261	P	V
802.11b CH 11 2462MHz		4923	47.43	-26.57	74	40.72	34.95	8.79	37.03	159	86	P	H
		7386	48.93	-25.07	74	41.65	35.58	10.89	39.19	164	229	P	H
		4923	46.46	-27.54	74	39.75	34.95	8.79	37.03	183	261	P	V
		7386	48.26	-25.74	74	40.98	35.58	10.89	39.19	148	53	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		2389.29	59.45	-14.55	74	58.06	31.3	6.17	36.08	150	263	P	H
		2390	38.95	-15.05	54	37.56	31.3	6.17	36.08	150	263	A	H
	*	2413.611	93.44	-	-	91.93	31.31	6.22	36.02	150	263	P	H
	*	2413.36	82.63	-	-	81.12	31.31	6.22	36.02	150	263	A	H
		2389.83	60.64	-13.36	74	59.25	31.3	6.17	36.08	175	37	P	V
		2390	41.04	-12.96	54	39.65	31.3	6.17	36.08	175	37	A	V
	*	2410.855	95.92	-	-	94.41	31.31	6.22	36.02	175	37	P	V
	*	2412.274	84.65	-	-	83.14	31.31	6.22	36.02	175	37	A	V
802.11g CH 06 2437MHz	*	2434.068	92.96	-	-	91.37	31.33	6.22	35.96	154	165	P	H
	*	2435.237	81.71	-	-	80.12	31.33	6.22	35.96	154	165	A	H
	*	2433.901	92.65	-	-	91.06	31.33	6.22	35.96	154	163	P	V
	*	2434.987	80.9	-	-	79.31	31.33	6.22	35.96	154	163	A	V
802.11g CH 11 2462MHz	*	2463.627	93.42	-	-	91.63	31.36	6.28	35.85	154	155	P	H
	*	2462.542	82.18	-	-	80.39	31.36	6.28	35.85	154	155	A	H
		2483.96	61.75	-12.25	74	59.84	31.37	6.33	35.79	154	155	P	H
		2483.52	41.19	-12.81	54	39.28	31.37	6.33	35.79	154	155	A	H
	*	2460.788	95.59	-	-	93.8	31.36	6.28	35.85	369	345	P	V
	*	2462.041	84.47	-	-	82.68	31.36	6.28	35.85	369	345	A	V
		2484.04	64.95	-9.05	74	63.04	31.37	6.33	35.79	369	345	P	V
		2483.52	43.71	-10.29	54	41.8	31.37	6.33	35.79	369	345	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11g (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g		4824	46.4	-27.6	74	39.43	34.89	8.73	36.65	189	210	P	H
CH 01		4824	47.38	-26.62	74	40.41	34.89	8.73	36.65	178	123	P	V
2412MHz													
802.11g		4875	47.17	-26.83	74	40.33	34.92	8.76	36.84	195	260	P	H
CH 06		7311	46.18	-27.82	74	38.64	35.56	10.84	38.86	200	0	P	H
2437MHz		4875	47.67	-26.33	74	40.83	34.92	8.76	36.84	166	302	P	V
		7311	46.52	-27.48	74	38.98	35.56	10.84	38.86	195	351	P	V
802.11g		4923	45.53	-28.47	74	38.82	34.95	8.79	37.03	156	230	P	H
CH 11		7386	45.94	-28.06	74	38.66	35.58	10.89	39.19	210	15	P	H
2462MHz		4923	46.11	-27.89	74	39.4	34.95	8.79	37.03	178	221	P	V
		7386	45.43	-28.57	74	38.15	35.58	10.89	39.19	233	135	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		2389.83	65.23	-8.77	74	63.84	31.3	6.17	36.08	214	51	P	H
		2389.92	40.74	-13.26	54	39.35	31.3	6.17	36.08	214	51	A	H
	*	2414.362	94.68	-	-	93.17	31.31	6.22	36.02	214	51	P	H
	*	2413.193	83.3	-	-	81.79	31.31	6.22	36.02	214	51	A	H
		2389.74	61.48	-12.52	74	60.09	31.3	6.17	36.08	175	141	P	V
		2390	38.48	-15.52	54	37.09	31.3	6.17	36.08	175	141	A	V
	*	2411.439	93.58	-	-	92.07	31.31	6.22	36.02	175	141	P	V
	*	2410.104	82.33	-	-	80.82	31.31	6.22	36.02	175	141	A	V
802.11n HT20 CH 06 2437MHz	*	2439.412	93.03	-	-	91.32	31.34	6.28	35.91	151	72	P	H
	*	2437.742	81.54	-	-	79.89	31.34	6.22	35.91	151	72	A	H
	*	2435.905	93.66	-	-	92.07	31.33	6.22	35.96	173	146	P	V
	*	2434.987	82.35	-	-	80.76	31.33	6.22	35.96	173	146	A	V
802.11n HT20 CH 11 2462MHz	*	2460.621	93.51	-	-	91.72	31.36	6.28	35.85	230	334	P	H
	*	2460.12	81.89	-	-	80.1	31.36	6.28	35.85	230	334	A	H
		2484.36	58.68	-15.32	74	56.77	31.37	6.33	35.79	230	334	P	H
		2483.68	38.06	-15.94	54	36.15	31.37	6.33	35.79	230	334	A	H
	*	2464.629	94.17	-	-	92.38	31.36	6.28	35.85	150	108	P	V
	*	2462.792	82.91	-	-	81.12	31.36	6.28	35.85	150	108	A	V
		2483.96	59.7	-14.3	74	57.79	31.37	6.33	35.79	150	108	P	V
		2483.56	38.41	-15.59	54	36.5	31.37	6.33	35.79	150	108	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n		4824	47.77	-26.23	74	40.8	34.89	8.73	36.65	213	210	P	H
HT20													
CH 01		4824	46.89	-27.11	74	39.92	34.89	8.73	36.65	167	302	P	V
2412MHz													
802.11n		4875	48.06	-25.94	74	41.22	34.92	8.76	36.84	160	309	P	H
HT20		7311	46.55	-27.45	74	39.01	35.56	10.84	38.86	254	216	P	H
CH 06		4875	46.74	-27.26	74	39.9	34.92	8.76	36.84	188	265	P	V
2437MHz		7311	47.5	-26.5	74	39.96	35.56	10.84	38.86	199	205	P	V
802.11n		4923	46.47	-27.53	74	39.76	34.95	8.79	37.03	164	203	P	H
HT20		7386	47.55	-26.45	74	40.27	35.58	10.89	39.19	188	260	P	H
CH 11		4923	47.73	-26.27	74	41.02	34.95	8.79	37.03	200	0	P	V
2462MHz		7386	46.62	-27.38	74	39.34	35.58	10.89	39.19	188	290	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 03 2422MHz		2388.66	67.85	-6.15	74	66.46	31.3	6.17	36.08	159	190	P	H
		2385.06	43.55	-10.45	54	42.26	31.28	6.17	36.16	159	190	A	H
	*	2416.7	91.86	-	-	90.35	31.31	6.22	36.02	159	190	P	H
	*	2415.865	80.69	-	-	79.18	31.31	6.22	36.02	159	190	A	H
		2492.2	49.57	-24.43	74	47.59	31.39	6.33	35.74	159	190	P	H
		2485.8	35.71	-18.29	54	33.8	31.37	6.33	35.79	159	190	A	H
	!	2388.66	68.51	-5.49	74	67.12	31.3	6.17	36.08	151	173	P	V
		2381.01	44.02	-9.98	54	42.73	31.28	6.17	36.16	151	173	A	V
	*	2412.358	93.23	-	-	91.72	31.31	6.22	36.02	151	173	P	V
	*	2415.781	82.07	-	-	80.56	31.31	6.22	36.02	151	173	A	V
		2483.76	50.42	-23.58	74	48.51	31.37	6.33	35.79	151	173	P	V
		2483.72	36.13	-17.87	54	34.22	31.37	6.33	35.79	151	173	A	V
802.11n HT40 CH 06 2437MHz		2371.02	61.41	-12.59	74	60.12	31.28	6.17	36.16	157	178	P	H
		2387.85	42.02	-11.98	54	40.63	31.3	6.17	36.08	157	178	A	H
	*	2430.478	89.35	-	-	87.76	31.33	6.22	35.96	157	178	P	H
	*	2430.979	78.65	-	-	77.06	31.33	6.22	35.96	157	178	A	H
		2484.8	52.49	-21.51	74	50.58	31.37	6.33	35.79	157	178	P	H
		2484.28	37	-17	54	35.09	31.37	6.33	35.79	157	178	A	H
		2370.93	61.46	-12.54	74	60.17	31.28	6.17	36.16	178	25	P	V
		2389.56	41.57	-12.43	54	40.18	31.3	6.17	36.08	178	25	A	V
	*	2430.478	90.45	-	-	88.86	31.33	6.22	35.96	178	25	P	V
	*	2427.555	79.34	-	-	77.75	31.33	6.22	35.96	178	25	A	V
		2483.64	51.83	-22.17	74	49.92	31.37	6.33	35.79	178	25	P	V
		2483.6	36.36	-17.64	54	34.45	31.37	6.33	35.79	178	25	A	V



802.11n HT40 CH 09 2452MHz		2385.33	61.03	-12.97	74	59.74	31.28	6.17	36.16	150	176	P	H
		2388.93	41.15	-12.85	54	39.76	31.3	6.17	36.08	150	176	A	H
	*	2446.009	90.7	-	-	88.99	31.34	6.28	35.91	150	176	P	H
	*	2446.259	79.96	-	-	78.25	31.34	6.28	35.91	150	176	A	H
		2483.6	63.54	-10.46	74	61.63	31.37	6.33	35.79	150	176	P	H
		2483.56	41.43	-12.57	54	39.52	31.37	6.33	35.79	150	176	A	H
		2384.34	60.58	-13.42	74	59.29	31.28	6.17	36.16	150	163	P	V
		2380.83	40.5	-13.5	54	39.21	31.28	6.17	36.16	150	163	A	V
	*	2443.67	92.52	-	-	90.81	31.34	6.28	35.91	150	163	P	V
	*	2445.842	81.25	-	-	79.54	31.34	6.28	35.91	150	163	A	V
		2483.8	63.64	-10.36	74	61.73	31.37	6.33	35.79	150	163	P	V
		2484.24	41.52	-12.48	54	39.61	31.37	6.33	35.79	150	163	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n		4845	47.29	-26.71	74	40.38	34.9	8.73	36.72	186	231	P	H
HT40		7266	47.72	-26.28	74	40.08	35.56	10.81	38.73	156	228	P	H
CH 03		4845	47.19	-26.81	74	40.28	34.9	8.73	36.72	150	201	P	V
2422MHz		7266	48.94	-25.06	74	41.3	35.56	10.81	38.73	196	54	P	V
802.11n		4875	46.98	-27.02	74	40.14	34.92	8.76	36.84	164	261	P	H
HT40		7311	48.53	-25.47	74	40.99	35.56	10.84	38.86	186	98	P	H
CH 06		4875	46.93	-27.07	74	40.09	34.92	8.76	36.84	175	48	P	V
2437MHz		7311	47.7	-26.3	74	40.16	35.56	10.84	38.86	168	49	P	V
802.11n		4905	47.7	-26.3	74	40.93	34.94	8.79	36.96	206	337	P	H
HT40		7356	47.96	-26.04	74	40.59	35.57	10.86	39.06	167	224	P	H
CH 09		4905	47.52	-26.48	74	40.75	34.94	8.79	36.96	159	246	P	V
2452MHz		7356	48.21	-25.79	74	40.84	35.57	10.86	39.06	186	351	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C Emission below 1GHz

2.4GHz WIFI 802.11b (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11b LF		30	24.17	-15.83	40	36.84	19.2	0.79	32.66	195	0	P	H
		55.22	19.12	-20.88	40	43.53	7.4	0.79	32.6	-	-	P	H
		78.5	19.52	-20.48	40	42.19	8.94	1.04	32.65	-	-	P	H
		92.08	23.82	-19.68	43.5	44.97	10.42	1.04	32.61	-	-	P	H
		172.59	22.07	-21.43	43.5	42.29	10.84	1.44	32.5	-	-	P	H
		214.3	21.75	-21.75	43.5	42.17	10.46	1.61	32.49	-	-	P	H
	!	30.97	35.63	-4.37	40	48.79	18.71	0.79	32.66	174	351	P	V
		36.79	31.95	-8.05	40	48	15.77	0.79	32.61	-	-	P	V
		54.25	26.55	-13.45	40	50.7	7.66	0.79	32.6	-	-	P	V
		80.44	25	-15.00	40	47.51	9.1	1.04	32.65	-	-	P	V
		115.36	16.62	-26.88	43.5	36.61	11.42	1.23	32.64	-	-	P	V
		225.94	22.67	-23.33	46	42.56	10.99	1.61	32.49	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



15C Emission below 1GHz

2.4GHz WIFI 802.11g (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11g LF		30	21.37	-18.63	40	34.04	19.2	0.79	32.66	-	-	P	H
		48.43	17.72	-22.28	40	39.84	9.72	0.79	32.63	-	-	P	H
		77.53	20.48	-19.52	40	43.24	8.85	1.04	32.65	-	-	P	H
		93.05	27.84	-15.66	43.5	48.87	10.53	1.04	32.6	152	325	P	H
		119.24	18.04	-25.46	43.5	38	11.45	1.23	32.64	-	-	P	H
		218.18	17.25	-28.75	46	37.49	10.64	1.61	32.49	-	-	P	H
		30	31.56	-8.44	40	44.23	19.2	0.79	32.66	243	216	P	V
		36.79	25.5	-14.50	40	41.55	15.77	0.79	32.61	-	-	P	V
		53.28	23.31	-16.69	40	47.21	7.92	0.79	32.61	-	-	P	V
		80.44	22.32	-17.68	40	44.83	9.1	1.04	32.65	-	-	P	V
		117.3	18.69	-24.81	43.5	38.66	11.44	1.23	32.64	-	-	P	V
		225.94	18.91	-27.09	46	38.8	10.99	1.61	32.49	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**15C Emission below 1GHz****2.4GHz WIFI 802.11n HT20 (LF)**

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT20 LF		30.97	27.23	-12.77	40	40.39	18.71	0.79	32.66	188	305	P	H
		36.79	24.58	-15.42	40	40.63	15.77	0.79	32.61	-	-	P	H
		53.28	21.43	-18.57	40	45.33	7.92	0.79	32.61	-	-	P	H
		79.47	21.28	-18.72	40	43.87	9.02	1.04	32.65	-	-	P	H
		93.05	26.9	-16.60	43.5	47.93	10.53	1.04	32.6	-	-	P	H
		142.52	18.3	-25.20	43.5	37.99	11.64	1.23	32.56	-	-	P	H
		30	30.42	-9.58	40	43.09	19.2	0.79	32.66	251	230	P	V
		36.79	27.14	-12.86	40	43.19	15.77	0.79	32.61	-	-	P	V
		53.28	25.19	-14.81	40	49.09	7.92	0.79	32.61	-	-	P	V
		80.44	22.05	-17.95	40	44.56	9.1	1.04	32.65	-	-	P	V
		94.99	20.44	-23.06	43.5	41.25	10.75	1.04	32.6	-	-	P	V
		118.27	18.14	-25.36	43.5	38.1	11.45	1.23	32.64	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



15C Emission below 1GHz

2.4GHz WIFI 802.11n HT40 (LF)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT40 LF		30	24.62	-15.38	40	37.29	19.2	0.79	32.66	169	258	P	H
		36.79	22.36	-17.64	40	38.41	15.77	0.79	32.61	-	-	P	H
		50.37	18.14	-21.86	40	41.27	8.7	0.79	32.62	-	-	P	H
		79.47	19.22	-20.78	40	41.81	9.02	1.04	32.65	-	-	P	H
		92.08	26.5	-17.00	43.5	47.65	10.42	1.04	32.61	-	-	P	H
		241.46	17.3	-28.70	46	36.33	11.7	1.75	32.48	-	-	P	H
		30	29.37	-10.63	40	42.04	19.2	0.79	32.66	211	241	P	V
		36.79	25.56	-14.44	40	41.61	15.77	0.79	32.61	-	-	P	V
		53.28	22.2	-17.80	40	46.1	7.92	0.79	32.61	-	-	P	V
		66.86	18.61	-21.39	40	42.87	7.57	0.79	32.62	-	-	P	V
		79.47	21.88	-18.12	40	44.47	9.02	1.04	32.65	-	-	P	V
		116.33	15.97	-27.53	43.5	35.95	11.43	1.23	32.64	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.