



RF EXPOSURE EVALUATION

Applicant: D-ROBOTICS HOLDING LIMITED

Address: SUITE 603,6/F LAWS COMM PLAZA 788 CHEUNG SHA WAN RD KLN HONG KONG

FCC ID: 2BGUG-RDKX5K

Product Name: RDK X5

Standard(s): 47 CFR §1.1307, 47 CFR §2.1091 447498 D04 Interim General RF Exposure Guidance v01

The above device has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: 2403Z107562E-RF-00F

Reviewed By: Calvin Chen

Calvin Chen Swn Zhong

Title: RF Engineer

Approved By:	Sun Zhong		
Title:	Manager		

Test Laboratory: China Certification ICT Co., Ltd (Dongguan) No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China

> Tel: +86-769-83085888 www.ccttt.com.cn

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol "▲". Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk " \star ".

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision	
1.0	2403Z107562E-RF-00F	Original Report	2024/12/28	

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	RDK X5	
EUT Model:	RDK X5 8G	
Multiple Model:	RDK X5 4G	
Rated Input Voltage:	DC 5V from Type-C Port	
EUT Received Date:	2024/11/29	
EUT Received Status:	Good	
Note: The multiple models are electrically	v identical with the test model. Please refer to the declaration letter for	
more detail, which was provided by manufacturer.		

2. RF EXPOSURE EVALUATION

2.1 Applicable Standard

According to §1.1307(b)(3)(i)

(C) Or using Table 1 and the minimum separation distance (R in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, R must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 \text{ R}^2.$
1.34-30	$3,450 \text{ R}^2/\text{f}^2.$
30-300	3.83 R^2 .
300-1,500	$0.0128 \text{ R}^2 \text{f.}$
1,500-100,000	19.2R ² .

2.2 Measurement Result

Radio	Frequency (MHz)	λ/2Π (mm)	Distance (mm)	Exemption ERP (mW)	Maximum Conducted Power including	Antenna Gain (dBi)	ERP	
				(Tolerance (dBm)	(uDi)	dBm	mW
BDR/EDR	2402-2480	19.88	200	768	5	0.43	3.28	2.13
BLE	2402-2480	19.88	200	768	5	0.43	3.28	2.13
2.4G Wi-Fi	2412-2462	19.80	200	768	23	0.43	21.28	134.28
5.2G Wi-Fi	5180-5240	9.22	200	768	20	2.86	20.71	117.76
5.8G Wi-Fi	5745-5825	8.31	200	768	18	3.00	18.85	76.74

Note:

1. The Maximum Conducted Power including Tune-up Tolerance was declared by manufacturer.

2. The Bluetooth and Wi-Fi cannot transmit simultaneously.

Result: The device compliant the MPE-Based Exemption at 20cm distances.

China Certification ICT Co., Ltd (Dongguan)

Report No.: 2403Z107562E-RF-00F

3. EUT PHOTOGRAPHS

Please refer to the attachment 2403Z107562E-RF-EXP EUT EXTERNAL PHOTOGRAPHS and 2403Z107562E-RF-INP EUT INTERNAL PHOTOGRAPHS

==== END OF REPORT =====