

User Manual

Product name: MP24-Xenon2-L

Use: Treadmill flat screen

Content:

BLUETOOTH VERSION: 5.3 MINIMUM

WIFI-6: a/b/g/n/ac/ax, MT7921 2.4 & 5 GHZ,

2X2 MIMO MT7921LSN (SDIO) 2.4 & 5 GHZ. 3rd BT ANTENNA, FDD MODE.

GPS: NO

FRONT CAMERA: YES,

REAR CAMERA: NO

MICROPHONES: YES TWO (2) DIGITAL MEM

SPEAKER: NO

WIFI: MEET 5GHZ RADAR NON INTERFERENCE DIRECTIVE (IEEE 802.11h-2003)

USB 2.0 PORT (HOST) 5 PIN HEADER JST (PN: S05B-XASK-1)

DC IN: 12VDC ON 4 PIN HEADER JST (PN: SO4B-XASK-1) MAX POWER 5A Vin UVP, 8V DIP OK

USB-C 3.1 PORT WITH RETENTION MECHANISM, PD 3.0, MAX POWER 60W,

SYSTEM 12V APPLIED TO JST PROTECTION. OPTIONAL: USB3.1 DP ATL MODE (USB HDMI)

User Manual

FCC regulatory compliance statement

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Caution: Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

To satisfy RF exposure requirements, a separation distance of 20 cm or more should be maintained between the antenna of this device and persons during device operation.

To ensure compliance, operations at closer than this distance is not recommended.

User Manual

ISED Regulatory Compliance

This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS(s). Operation is subject to the following two conditions:

- (1) This device may not cause interference.
- (2) This device must accept any interference, including interference that may cause undesired operation of the device.

L'émetteur/récepteur exempt de licence contenu dans le présent appareil est conforme aux CNR d'Innovation, Sciences et Développement économique Canada applicables aux appareils radio exempts de licence.

L'exploitation est autorisée aux deux conditions suivantes :

- 1) L'appareil ne doit pas produire de brouillage;*
- 2) L'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.*

The device for operation in the band 5150–5250 MHz is only for indoor use to reduce the potential for harmful interference to co-channel mobile satellite systems;

le dispositif utilisé dans la bande 5150-5250 MHz est réservé à une utilisation en intérieur afin de réduire le risque de brouillage préjudiciable aux systèmes mobiles par satellite dans le même canal;

This equipment complies with IC RSS-102 radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance 20cm between the radiator and your body.

Cet équipement est conforme aux limites d'exposition aux radiations IC CNR-102 établies pour un environnement non contrôlé. Cet équipement doit être installé et utilisé avec une distance minimale de 20cm entre le radiateur et votre corps.