

ASAP Technology (jiangxi) Co., Ltd

# TEST REPORT

**SCOPE OF WORK**

FCC TESTING—080-08-3787

**REPORT NUMBER**

240430021SZN-001

**ISSUE DATE**

05 June 2024

**[REVISED DATE]**

[-----]

**PAGES**

20

**DOCUMENT CONTROL NUMBER**

FCC ID 209\_b

© 2017 INTERTEK



Intertek Report No.: 240430021SZN-001

**ASAP Technology (jiangxi) Co., Ltd**Application  
For  
Certification**FCC ID: 2APXNLACC136****Wireless charger****Model: 080-08-3787****Transmitter**

Report No.: 240430021SZN-001

We hereby certify that the sample of the above item is considered to comply with the  
requirements of FCC Part 15, Subpart C for Intentional Radiator,  
mention 47 CFR [10-1-23]

**Prepared and Checked by:****Approved by:****Tenet Cao**  
**Assistant Engineer**

---

**Ryan Chen**  
**Sr. Project Engineer**  
**Date: 05 June 2024**

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

**Intertek Testing Services Shenzhen Ltd. Longhua Branch**

101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen.

Tel: (86 755) 8601 6288 Fax: (86 755) 8601 6751

## MEASUREMENT/TECHNICAL REPORT

This report concerns (check one)      Original Grant ☒ Class II Change ☐

Equipment Type: DCD - Part 15 Low Power Transmitter Below 1705 kHz

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)?      Yes ☐ No ☒

If yes, defer until : \_\_\_\_\_  
date

Company Name agrees to notify the Commission by: \_\_\_\_\_  
date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37?      Yes ☐ No ☒

If no, assumed Part 15, Subpart C for intentional radiator - the new 47 CFR [10-01-23] Edition] provision.

Report prepared by:

**Tenet Cao**  
**Intertek Testing Services Shenzhen Ltd. Longhua Branch**  
101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing  
Community, GuanHu Subdistrict, LongHua District,  
ShenZhen.  
Tel: (86 755) 8614 0743 Fax: (86 755) 8601 6751

## Table of Contents

<b>1.0</b>	<b>Summary of Test Results</b>	<b>4</b>
<b>2.0</b>	<b>General Description</b>	<b>5</b>
2.1	Product Description	5
2.2	Related Submittal(s) Grants	5
2.3	Test Methodology	5
2.4	Test Facility	5
<b>3.0</b>	<b>System Test Configuration</b>	<b>6</b>
3.1	Justification	6
3.2	EUT Exercising Software	6
3.3	Special Accessories	6
3.4	Equipment Modification	6
3.5	Measurement Uncertainty	7
3.6	Support Equipment List and Description	7
<b>4.0</b>	<b>Measurement Results</b>	<b>8</b>
4.1	Field Strength Calculation	8
4.2	Radiated Emission Configuration Photograph	9
4.3	Radiated Spurious Emission	9
4.4	Conducted Emission Configuration Photograph	13
4.5	Conducted Emission	13
<b>5.0</b>	<b>Equipment Photographs</b>	<b>16</b>
<b>6.0</b>	<b>Product Labelling</b>	<b>16</b>
<b>7.0</b>	<b>Technical Specifications</b>	<b>16</b>
<b>8.0</b>	<b>Instruction Manual</b>	<b>16</b>
<b>9.0</b>	<b>Miscellaneous Information</b>	<b>17</b>
9.1	20dB Bandwidth	17
9.2	Emissions Test Procedures	18
9.2	Emissions Test Procedures (cont'd)	19
<b>10.0</b>	<b>Test Equipment List</b>	<b>20</b>

## 1.0 Summary of Test Results

Applicant: ASAP Technology (jiangxi) Co., Ltd

Applicant Address: Ji'an Industrial Park, Ji'an, Jiangxi 343100 China

Manufacturer: ASAP Technology (jiangxi) Co., Ltd

Manufacturer Address: Ji'an Industrial Park, Ji'an, Jiangxi 343100 China

**Model: 080-08-3787**

**FCC ID: 2APXNLACC136**

TEST ITEM	REFERENCE	RESULTS
Power Line Conducted Emissions	15.207	Pass
Transmitter Radiated Emissions	15.209	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses an Integral Antenna which in accordance to Section 15.203 is considered sufficient to comply with the provisions of this section.

## 2.0 General Description

### 2.1 Product Description

The Equipment Under Test (EUT) is a Wireless charger operating at 115-360 kHz. The EUT is powered by DC 5.0V 3A ,DC 9V 2.22A, the output of the wireless charger is 15W. The EUT has only one coil antenna, and the EUT will discharge according to the placement of the charged product. For more detailed features description, please refer to the user's manual.

Antenna Type: Integral Antenna(embedded coil antenna)

For electronic filing, the brief circuit description is saved with filename: descri.pdf.

### 2.2 Related Submittal(s) Grants

This is an application for certification of the Wireless charger portion.

### 2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.10 (2013). Radiated emission measurement was performed in Semi-anechoic chamber and conducted emission measurement was performed in shield room. For radiated emission measurement, preliminary scans were performed in the semi-anechoic chamber only to determine the worst-case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application. All other measurements were made in accordance with the procedures in part 2 of CFR 47.

### 2.4 Test Facility

The Semi-Anechoic chamber and shield room used to collect the radiated data and conducted data are Intertek **Testing Services Shenzhen Ltd. Longhua Branch** and located at 101, 201, Building B, No. 308 Wuhe Avenue, Zhangkengjing Community, GuanHu Subdistrict, LongHua District, ShenZhen. This test facility and site measurement data have been fully placed on file with File Number: CN1188.

### 3.0 System Test Configuration

#### 3.1 Justification

The system was configured for testing in a typical fashion (as a customer would normally use it), and in the confines as outlined in ANSI C63.10 (2013).

The EUT was powered by an adapter with 120V/60Hz input during the test. The test system was pre-scanning tested based on the consideration of following EUT operation mode. All designing schemes were tested, Only the worst-case data was shown in this report.

Pertest mode	Description
Mode 1	Standby mode
Mode 2	Mobile phone is charging at 1% battery power
Mode 3	Mobile phone is charging at 50% battery power
Mode 4	Mobile phone is charging at 99% battery power

For maximizing emissions below 30 MHz, the EUT was rotated through 360°, the bottom of the loop antenna was placed 1 meter above the ground, and the antenna polarization was changed. For maximizing emission at and above 30 MHz, the EUT was rotated through 360°, the antenna height was varied from 1 meter to 4 meters above the ground plane, and the antenna polarization was changed. This step by step procedure for maximizing emissions led to the data report in Section 4.0.

The rear of unit shall be flushed with the rear of the table.

The equipment under test (EUT) was configured for testing in a typical fashion (as a customer would normally use it). The EUT was mounted to a plastic stand if necessary and placed on the styrene turntable, which enabled the engineer to maximize emissions through its placement in the three orthogonal axes.

#### 3.2 EUT Exercising Software

N/A

#### 3.3 Special Accessories

There is no special accessories necessary for compliance of this product.

#### 3.4 Equipment Modification

Any modifications installed previous to testing by ASAP Technology (jiangxi) Co., Ltd will be incorporated in each production model sold / leased in the United States.

No modifications were installed by Intertek Testing Services Shenzhen Ltd. Longhua Branch.

### 3.5 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

Measurement Uncertainty	Uncertainty
Channel Bandwidth	$\pm 3.46\%$
Radiated emission (Up to 1GHz)	$\pm 4.8\text{dB}$
AC Conducted emission	$\pm 3.2\text{ dB}$
Temperature	$\pm 1^{\circ}\text{C}$
Humidity	$\pm 5\%$

### 3.6 Support Equipment List and Description

This product was tested in the following configuration:

Description	Manufacturer	Detail
Mobile phone	Samsung (Provided by Intertek)	Model: Samsung (SM-G9300)
Adapter	dealworthy™ (Provided by Client)	Model: 080-08-3787 Input: 100-240Vac 50/60Hz 0.5A Output: 5Vdc 3A, 9Vdc 2.22A



## 4.0 Measurement Results

### 4.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in dB $\mu$ V/m

RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB/m

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

#### Example

Assume a receiver reading of 62.0dB $\mu$ V is obtained. The antenna factor of 7.4dB/m and cable factor of 1.6dB is added. The amplifier gain of 29dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0dB, and the resultant average factor was -10dB. The net field strength for comparison to the appropriate emission limit is 32dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

$$RA = 62.0\text{dB}\mu\text{V}$$

$$AF = 7.4\text{ dB/m}$$

$$CF = 1.6\text{dB}$$

$$AG = 29.0\text{dB}$$

$$PD = 0\text{dB}$$

$$AV = -10\text{dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32\text{dB}\mu\text{V/m}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(32\text{dB}\mu\text{V/m})/20] = 39.8\mu\text{V/m}$$

#### 4.2 Radiated Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

#### 4.3 Radiated Spurious Emission

Worst Case Radiated Spurious Emission  
at  
80.763333MHz

Judgement: Passed by 8.9 dB margin

For the electronic filing, the worst case radiated emission configuration photographs are saved with filename: radiated photos.pdf.

*Sign on file*

Tenet Cao, Assistant Engineer  
*Typed/Printed Name*

May 22, 2024  
*Date*

Applicant: ASAP Technology (jiangxi) Co., Ltd

Date of Test: May 22, 2024


Model: 080-08-3787

Worst Case Operating Mode: Mode 2

## Radiated Emissions (30MHz – 1000MHz)

ANT Polarity: Horizontal

FCC Part 15



Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
186.960000	24.7	1000.0	120.000	H	16.8	18.8	43.5
242.520000	25.8	1000.0	120.000	H	18.8	20.2	46.0
713.280000	31.3	1000.0	120.000	H	30.9	14.7	46.0

### Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line (dBμV/m) – Level (dBμV/m)

Applicant: ASAP Technology (jiangxi) Co., Ltd


Date of Test: May 22, 2024

Model: 080-08-3787

Worst Case Operating Mode: Mode 2

ANT Polarity: Vertical

## FCC Part 15



Frequency (MHz)	QuasiPeak (dBμV/m)	Meas. Time (ms)	Bandwidth (kHz)	Polarization	Corr. (dB/m)	Margin - QPK (dB)	Limit - QPK (dBμV/m)
33.360000	27.0	1000.0	120.000	V	20.9	13.0	40.0
80.763333	31.1	1000.0	120.000	V	13.6	8.9	40.0
187.301667	27.0	1000.0	120.000	V	16.8	16.5	43.5

### Remark:

1. Corr. (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB)
2. QuasiPeak (dBμV/m) = Corr. (dB/m) + Read Level (dBμV)
3. Margin (dB) = Limit Line(dBμV/m) – Level (dBμV/m)

Applicant: ASAP Technology (jiangxi) Co., Ltd

Date of Test: May 22, 2024

Model: 080-08-3787

Worst Case Operating Mode: Mode 2

### Fundamental & Spurious Emission Below 30MHz

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Distance Factor (-dB)	Calculated at 300m (dBμV/m)	Limit at 300m (dBμV/m)	Margin (dB)
Horizontal	0.1450	57.7	0.0	15.1	72.8	80	-7.2	24.4	-31.6
Horizontal	0.2883	40.5	0.0	15.1	55.6	80	-24.4	18.4	-42.8

- Notes:
1. The specified limits of frequency band 9~90 KHz, 110~490 KHz are in average and measurements are made with peak detectors. Quasi-Peak detector is used for other frequency band.
  2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Loop antenna is used for the emission under 30MHz.
  5. Horizontal and Vertical polarization were tested and Only the worst Case data is shown.

#### 4.4 Conducted Emission Configuration Photograph

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: conducted photos.pdf.

#### 4.5 Conducted Emission

Worst Case Conducted Configuration  
at  
0.454000MHz

Judgement: Passed by 3.1dB margin

*Sign on file*

Tenet Cao, Assistant Engineer

*Typed/Printed Name*

May 22, 2024

*Date*

Applicant: ASAP Technology (jiangxi) Co., Ltd

Date of Test: May 22, 2024

Worst Case Operating Mode

Test Voltage: 120V/60Hz


Model: 080-08-3787

Mode 2

Phase: Live

## Graphic / Data Table

### Conducted Emissions Pursuant to FCC 15.207: Emissions Requirement



#### Limit and Margin QP

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.454000	50.3	9.000	L1	9.6	6.5	56.8
0.486000	48.2	9.000	L1	9.6	8.0	56.2
0.726000	42.2	9.000	L1	9.6	13.8	56.0
1.018000	41.4	9.000	L1	9.6	14.6	56.0
1.306000	42.6	9.000	L1	9.6	13.4	56.0
1.886000	41.7	9.000	L1	9.7	14.3	56.0

#### Limit and Margin AV

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.454000	43.7	9.000	L1	9.6	3.1	46.8
0.486000	41.7	9.000	L1	9.6	4.5	46.2
0.726000	36.8	9.000	L1	9.6	9.2	46.0
1.018000	34.9	9.000	L1	9.6	11.1	46.0
1.306000	36.9	9.000	L1	9.6	9.1	46.0
1.886000	36.8	9.000	L1	9.7	9.2	46.0

Applicant: ASAP Technology (jiangxi) Co., Ltd

Date of Test: May 22, 2024

Worst Case Operating Mode

Test Voltage: 120V/60Hz


Model: 080-08-3787

Mode 2

Phase: Neutral

## Graphic / Data Table

### Conducted Emissions Pursuant to FCC 15.207: Emissions Requirement Conducted Emission Test FCC Part 15



### Limit and Margin QP

Frequency (MHz)	QuasiPeak (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.450000	47.4	9.000	N	9.6	9.5	56.9
0.486000	44.6	9.000	N	9.6	11.6	56.2
0.726000	36.3	9.000	N	9.6	19.7	56.0
1.014000	36.4	9.000	N	9.6	19.6	56.0
1.306000	36.2	9.000	N	9.6	19.8	56.0
1.886000	36.2	9.000	N	9.7	19.8	56.0

### Limit and Margin AV

Frequency (MHz)	Average (dBuV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBuV)
0.450000	41.3	9.000	N	9.6	5.6	46.9
0.486000	38.5	9.000	N	9.6	7.7	46.2
0.726000	32.6	9.000	N	9.6	13.4	46.0
1.014000	32.9	9.000	N	9.6	13.1	46.0
1.306000	32.9	9.000	N	9.6	13.1	46.0
1.886000	32.4	9.000	N	9.7	13.6	46.0



## 5.0 Equipment Photographs

For electronic filing, the photographs are saved with filename: external photos.pdf & internal photos.pdf.

## 6.0 Product Labeling

For electronic filing, the FCC ID label artwork and location is saved with filename: label.pdf.

## 7.0 Technical Specifications

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

## 8.0 Instruction Manual

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.


This manual will be provided to the end-user with each unit sold/leased in the United States.

## 9.0 Miscellaneous Information

This miscellaneous information includes 20dB bandwidth and emission measuring procedure.

### 9.1 20dB bandwidth

Pursuant to FCC part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over excepted variations in temperature and supply voltage were considered. The test plots are reported as below.



## 9.2 Emissions Test Procedures

The following is a description of the test procedure used by Intertek Testing Services in the measurements of transmitters operating under Part 15, Subpart C rules.

The test set-up and procedures described below are designed to meet the requirements of ANSI C63.10 - 2013.

The transmitting equipment under test (EUT) is placed on a styrene turntable which is four feet in diameter and approximately 0.8 meter in height above the ground plane. During the radiated emissions test, the turntable is rotated and any cables leaving the EUT are manipulated to find the configuration resulting in maximum emissions. The EUT is adjusted through all three orthogonal axes to obtain maximum emission levels. The antenna height and polarization are varied during the testing to search for maximum signal levels.

Average detector is used for 9–90 KHz, 110–490 KHz and Quasi-Peak detector is used for other frequency band. The IF bandwidth used for measurement of radiated signal strength was 10 KHz for emission below 30 MHz and 120 KHz for emission from 30 MHz to 1000 MHz.

The frequency range scanned is from the lowest radio frequency signal generated in the device which is greater than 9 kHz up to the 1GHz. For line-conducted emissions, the range scanned is 150kHz to 30MHz.

## 9.2 Emissions Test Procedures (cont'd)

The EUT is warmed up for 15 minutes prior to the test.

AC power to the unit is varied from 85% to 115% nominal and variation in the fundamental emission field strength is recorded. If battery powered, a new, fully charged battery is used.

Conducted measurements are made as described in ANSI C63.10 - 2013.

The IF bandwidth used for measurement of radiated signal strength was 10 kHz for emission below 30 MHz and 120 kHz for emission from 30 MHz to 1000 MHz. Where pulsed transmissions of short enough pulse duration warrant, a greater bandwidth is selected according to the recommendations of Hewlett Packard Application Note 150-2. A discussion of whether pulse desensitivity is applicable to this unit is included in this report.

Transmitter measurements are normally conducted at a measurement distance of three meters. However, to assure low enough noise floor in the restricted bands, signals are acquired at a distance of one meter or less. All measurements are extrapolated to three meters using inverse scaling, but those measurements taken at a closer distance are so marked.

## 10.0 Test Equipment List

Equipment No.	Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Due Date
SZ061-12	BiConiLog Antenna	ETS	3142E	00166158	2021-08-04	2024-08-04
SZ185-04	EMI Receiver	R&S	ESCI	100547	2023-11-10	2024-11-10
SZ061-06	Active Loop Antenna	Electro-Metrics	EM-6876	217	2021-05-18 2024-05-05	2024-05-18 2027-05-05
SZ056-03	Spectrum Analyzer	R&S	FSP 30	101148	2024-04-22	2025-04-22
SZ056-06	Signal Analyzer	R&S	FSV 40	101101	2023-12-13	2024-12-13
SZ188-01	Anechoic Chamber	ETS	RFD-F/A-100	4102	2021-12-12	2024-12-12
SZ062-02	RF Cable	RADIAL	RG 213U	--	2023-11-15	2024-11-10
SZ062-05	RF Cable	RADIAL	0.04-26.5GHz	--	2023-11-15	2024-11-10
SZ062-12	RF Cable	RADIAL	0.04-26.5GHz	--	2023-11-15	2024-11-10
SZ185-02	EMI Test Receiver	R&S	ESCI	100692	2023-07-11	2024-07-11
SZ187-02	Two-Line V-Network	R&S	ENV216	100073	2024-04-23	2025-04-23
SZ188-03	Shielding Room	ETS	RFD-100	4100	2022-12-20	2025-12-20
SZ062-16	RF Cable	HUBER+SUHNER	CBL2-BN-1m	110127-2231000	2023-07-11	2024-07-11

\*\*\*\*\*End of Report\*\*\*\*\*