Certification of Compliance

CFR 47 Part 15 Subpart B

Test Report File No.	:	05-IST-0375	Date	of Issue :	Dece	ember 02, 2005
FCC ID	:	R7DLC-32IU21				
Model(s) Kind of Product	:	LC-32IU11 LCD TV MONITOR	Ba	asic		Alternate
Applicant Address	:	IND TEK Co., Ltd. Bloc 11-1, Lot 35,	Koogka 4 da:	nji, Kumi-C	itv,	Kvoungbuk,
		Korea		,	/	,
Manufacturer Address	:	IND TEK Co., Ltd. Bloc 11-1, Lot 35,	Koogka 4 da:	nji, Kumi-C	ity,	Kyoungbuk,
		Korea				

Test Result

Positive

□ Negative

Approved By

Reviewed By

Pe

from 14. Cae

J.H.Lee / Chief

Comment(s)

- Investigations requested : Measurement to the relevant clauses of FCC rules and regulations Part 15 Subpart B - Unintentional Radiators, Class B.

S.J.Cho / EMC Group Manager

The test report with appendix consists of 23 pages.The test result only responds to the tested sample.

It is not allowed to copy this report even partly without the allowance of IST EMC Laboratory.This equipment as for has been shown to be capable

of continued compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4 2003.



1 of 23

TABLE OF CONTENTS

Table of contents	2
Information of test laboratory, Environmental conditions, Power supply system used, Product information	3
Descriptions of test	
Conducted Emission	4
Radiated Emission	5
Measurement Uncertainty Calculations	6
Equipment Under Test	7
Test Set-Up (Figure)	8
Summary	9

Test Conditions and Data - Emissions

♦ Conducted Emissions	0.15MHz- 30MHz	Applicable
Test Conditions / Data and Plots		10-12
♦ Radiated Emissions	30MHz - 1GHz	Applicable
Test Conditions / Data and Plots		13-19

Appendix	A.	The	Photos	of	Test Setup	20-21
	в.	The	Photos	of	Equipment Under Test	22-23

Note:

INFORMATIONS OF TEST LABORATORY

EMC LABORATORY of IST Co., Ltd. *(FCC Filing Lab.)* San 21-8, Goan-Ri, Baekam-Myun, Yongin-City Kyonggi-Do, 449-860, Korea TEL : +82 31 333 4093 FAX : +82 31 333 4094

ENVIRONMENTAL CONDITIONS

Temperature	18.5	C
Humidity	36 %	
Atmospheric pressure	1014	mbar

POWER SUPPLY SYSTEM USED

Power	vlqquz	svstem	
LOWCT	Suppig	bybcciii	

AC120V, 60Hz (Refer to the product information)

PRODUCT INFORMATION

Type:	32Inch Flat Panel LCD
Resolution(Max):	1600 x 1200060Hz
Power:	AC100~240, 50/60Hz, 160W

- EMC suppression device is not used during the test.
- Please refer to user's manual.

DESCRIPTIONS OF TEST

Conducted Emissions:

The measurement were performed over the frequency range of 0.15MHz to 30MHz using a $50 \Omega/50$ uH LISN as the input transducer to a Spectrum Analyzer or a Field Intensity Meter. The measurements were made with the detector set for "Peak" amplitude within a bandwidth of 10KHz or for "quasi-peak" & "Average" within a bandwidth of 9KHz.

-Procedure of Test

The line-conducted facility is located inside a shielded room No.1. A lm X 1.5m wooden table 80cm height is placed 40cm away from the vertical wall and 1.5m away from the other wall of the shielded room. The R/S 3725/2 and Hyup-Rip KNW-407 LISN are bonded to bottom of the shielded room. The EUT is located on the wooden table with distance more than 80cm from the LISN and powered from the LISN. The peripheral equipment is powered from the other LISN. Power to the LISNs are filtered by a noise cut power line filters. All electrical cables are shielded by braided tinned steel tubing with inner ϕ 1.2cm. If the EUT is a DC-powered device, power will be derived from the SOURCE power supply it normally will be powered from and this supply lines will be connected to the EMCO LISN. All interconnecting cables more than 1m were shortened by non-inductive bundling to a 1m length. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating conditions. The RF output of the LISN was connected to the R/S receiver to determine the frequency producing the maximum emission from the EUT. The frequency producing the maximum level was reexamined using Quasi-Peak mode by manual measurement, after scanned by automatic Peak mode for frequency range from 0.15 to 30MHz. The bandwidth of the receiver was set to 10kHz. The EUT, peripheral equipment, and interconnecting cables were arranged and manipulated to maximize each EME emission.



DESCRIPTION OF TEST

Radiated Emissions:

The measurement was performed over the frequency range of 30MHz to 1GHz using antenna as the input transducer to a Spectrum analyzer or a Field Intensity Meter. The measurement was made with the detector set for "quasi-peak" within a bandwidth of 120KHz.

-Procedure of Test

Preliminary measurements were made at 3 meter using bi-conical and log-periodic antennas, and spectrum analyzer to determine the frequency producing the max. emission in anechoic chamber. Appropriate precaution was taken to ensure that all emission from the EUT were maximized and investigated. The system configuration, mode of operation, turn-table azimuth and height with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30MHz to 1000MHz using S/B LogBicon antenna VL9160. Under 30MHz, magnetic loop antenna were used. Final measurements were made at open site with 3-meters test distance using the same antenna. The OATS have been verified in regular for its normalized site attenuation. The test equipment was placed on a wooden table. Sufficient time for the EUT, peripheral equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined by manual. The detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 120kHz or 1MHz depending on the frequency of type of signal. The EUT, peripheral equipment and interconnecting cables were re-configured to the set-up producing the max. emission for the frequency and were placed on top of a 0.8-meter high nonmetallic 1 x 1.5 meter table. The EUT, peripheral equipment, and interconnecting cables were re-arranged and manipulated to maximize each emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation to the EUT and/or peripheral equipment and changing the polarity of the antenna, whichever determined the worst-case emission.





Measurement Uncertainty Calculations

The measurement uncertainties stated were calculated in accordance with the requirements of NIST Technical Note 1297 and NIS 81 (1994).

Contribution	Probability	Uncertainty (±dB)
(Conducted Emissions)	Distribution	0.15-30MHz
Receiver Specification	Rectangular	1.5
LISN Coupling Specification	Rectangular	1.5
Cable and Input Attenuator Calibration	Normal (k=2)	0.5
Mismatch to Reciver	U-Shaped	-0.8 / +0.7
System Repeatability	Normal (k=1)	0.2
Combined Standard Uncertainty	Normal (k=2)	-1.85 / +1.71
Expanded Uncertainty U	Normal (k=2)	-3.7 / +3.42

 $U_{c,minus} = -1.85$, $U_{c,plus} = 1.71$

U = -3.70 / +3.42 (k=2, 95.45% confidence level)

Contribution	Probability	Uncertainties(±dB)
(Radiated Emissions)	Distribution	3 m
Antenna		
Factor	Normal (k=2)	0.9968
Frequency Interpolation	Rectangular	0.1039
Height Variation	Rectangular	-2.6 / +1.5
Directivity Difference	Rectangular	-1.0 / +0
Phase Center Location	Rectangular	1.0
Cable Loss	Normal (k=2)	0.5
Receiver		
Voltage Accuracy	Normal (k=2)	2.0
Pulse Response	Rectangular	1.5
Absolute Repetition Rate	Rectangular	1.5
Mismatch to Receiver		
$ \Gamma_{antenna} = 0.33$	U-Shaped	-1.0 / +0.9
$ \Gamma_{\text{receiver}} = 0.33$		
Sustom Popostibility	Std	0 5
System vehearthitth	Deviation	0.5
Combined Standard Uncertainty	Normal	-2.6048 / 2.2775
Expanded Uncertainty U	Normal (k=2)	-5.21 / +4.55

 $U_{c,minus} = -2.6048$, $U_{c,plus} = 2.2775$

U = -5.21 / +4.55 (k=2, 95.45% confidence level)

Equipment Under Test

EUT Type :

■ Table-Top. □ Floor-Standing.

□ Table-Top and Floor-Standing(Combination).

Operation - mode of the E.U.T. :

The equipment under test was operated during the measurement under following conditions :

- □ Standby Mode
- Operational Condition : Display scrollong 'H' pattern on the windows

Configuration of the equipment under test :

Following peripheral devices and interface cables were connected during the measurement :

Equipment	Туре	Brand	Serial No.	FCC Compliance Info.
PC	Pavilion t328k	HP	KRJ33800KY	DOC
Keyboard(PS/2)	5219	HP	BN32402948	E5XKB5209
Mouse(PS/2)	MO42KO	HP	030330777	DOC
Mouse(Serial)	M-M28	Logitech	N/A	DZL210365
Printer	A0302380	Northern Telecom	2516S60951	BS46XU225C-L

Connecting Interface Cables :

- -Unshielded AC power cable : 1.8 m
- -Shielded monitor signal (D-sub) cable (with two ferrite core) : 1.6 m
- -Shielded monitor signal(DVI) cable (with two ferrite core) : 1.6 m
- -Unshielded keyboard(PS/2) signal cable (without ferrite core) : 1.8 m
- -Unshielded mouse(PS/2) signal cable (without ferrite core) : 1.8 m
- -Unshielded mouse(Serial) signal cable (without ferrite core) : 1.6 m
- -Unshielded printer(Parallel) signal cable (without ferrite core) : 1.8 m

SUMMARY

Emissions Conducted Emission Test Rule Part 15.107(c) ○ Not MET The requirements are • MET Minimum limit margin 10.0dB at 0.312MHz Maximum limit exceeding Remarks : Limits are kept with more 3dB margin. Find the test data in following pages 11 to 12. Radiated Emission Test Rule Part 15.109(a) (e) The requirements are • MET 🔾 Not MET Minimum limit margin 3.2dB at 682.7MHz Maximum limit exceeding Remarks : Limits are kept with more 3dB margin. Find the test data in following page 14 to 19. test Date Begin of testing : Nov. 23, 2005 End of testing : Nov. 29, 2005 Prepared By Note : - means the test is applicable, - 🗌 is not applicable. J.H.Park / EMC Engineer 9 of 23

TEST CONDITIONS AND DATA

Conducted Emissions

[Applicable]

♦ Test Equipment Used

Model Name	Description	Manufacture	Calibration Date	Serial Number
ESH 3	Test Receiver	Rohde & Schwarz	Jul. 12, 2005	892108/018
3725/2	LISN	Rohde & Schwarz	Jul. 12, 2005	9101-2068
KNW-407	LISN	Hyup-Rip	Jul. 12, 2005	9101-2068
ESH 3-Z2	Pulse limiter	Rohde & Schwarz	Jul. 12, 2005	357.8810.52

♦ Test Accessories Used

Туре	Manufacturer
Aneroid Barometer	Sato
Hygrometer	Sato

- \blacklozenge Test Program See the operation in page 7.
- ♦ Test Date Nov. 23, 2005

♦ Test Area Shielded Room (for Conducted Emission test)

Note : The equipment used is calibrated in regular for every year.

Conducted Emissions

MODEL NAME : LC-32IU11 120Vac 60Hz PHASE : L1

Freq. [MHz]	Measurement [dB ∦]		Limit [dB		Insertion Loss	Cable Loss	Result [dB ∉∛]		Margin [dB]	
	Q-peak	Average	Q-peak	Average	[dB]	[dв ∦]	Q-peak	Average	Q-peak	Average
0.177	49.1	29.5	64.6	54.6	0.3	0.2	49.6	30.0	15.0	24.6
0.305	48.0	20.0	60.1	50.1	0.3	0.4	48.7	20.7	11.4	29.4
0.357	43.5	24.6	58.8	48.8	0.2	0.4	44.1	25.2	14.7	23.6
15.263	27.1	19.8	60.0	50.0	0.6	0.9	28.6	21.3	31.4	28.7

Note :

Conducted Emissions

Freq. [MHz]	Measurement [dB ∉∛]		Limit [dB		Insertion Loss	Cable Loss	Result [dB ⊭V]		Margin [dB]	
	Q-peak	Average	Q-peak	Average	[dB]	[dв #∛]	Q-peak	Average	Q-peak	Average
0.187	47.0	32.1	64.2	54.2	0.3	0.2	47.5	32.6	16.7	21.6
0.312	49.2	36.5	59.9	49.9	0.3	0.4	49.9	37.2	10.0	12.7
0.362	43.0	23.9	58.7	48.7	0.2	0.4	43.6	24.5	15.1	24.2
15.559	27.4	20.4	60.0	50.0	0.6	0.9	28.9	21.9	31.1	28.1

Note :

TEST CONDITIONS AND DATA

Radiated Emission

[Applicable]

♦ Test Equipment Used

Name	Туре	Manufacturer	Calibration Date	Serial Number	
ESVS10	Test Receiver	Rohde & Schwarz	Aug. 16, 2005	839049/004	
VULB 9160	LogBicon Ant.	Schwarzbeck	Aug. 23, 2005	3048	

♦ Test Accessories Used

Туре	Manufacturer
Aneroid Barometer	Sato
Hygrometer	Sato

- \blacklozenge Test Program See the operation in page 7.
- ♦ Test Date Nov. 29, 2005
- ♦ Test Area Open Area Test Site No.2

Note : The equipment used is calibrated in regular for every year.

Freq. [MHz]	Reading [dBuV]	Antenna Factor [dB/m]	Cable Loss [dB]	Polar. [H/V]	Limit [dBuV/m]	Result [dBuV/m]	Margin [dB]
77.2	12.3	11.4	1.7	V	40.0	25.4	14.7
111.2	18.7	12.0	2.4	Н	43.5	33.1	10.4
133.1	14.4	12.5	2.8	Н	43.5	29.7	13.8
188.6	16.8	10.1	3.4	Н	43.5	30.3	13.2
225.8	15.5	10.1	3.9	V	46.0	29.5	16.5
270.0	14.9	11.7	4.5	V	46.0	31.1	14.9
345.5	16.6	13.6	4.9	Н	46.0	35.1	10.9
473.3	18.9	16.7	6.0	V	46.0	41.6	4.4
562.6	15.8	18.4	6.5	V	46.0	40.7	5.3
724.0	13.3	21.0	7.8	Н	46.0	42.1	3.9
829.8	11.9	22.4	8.4	Н	46.0	42.7	3.3
889.9	10.4	22.9	8.9	Н	46.0	42.2	3.8

Radiated Emissions

Note : 800 x 600, 85Hz mode

Freq. [MHz]	Reading [dBuV]	Antenna Factor [dB/m]	Cable Loss [dB]	Polar. [H/V]	Limit [dBuV/m]	Result [dBuV/m]	Margin [dB]
77.4	13.8	11.4	1.7	V	40.0	26.9	13.1
108.0	21.8	12.0	2.3	Н	43.5	36.1	7.4
121.7	3.0	12.0	2.5	V	43.5	17.5	26.0
151.0	9.6	13.1	3.0	Н	43.5	25.7	17.8
188.2	19.2	10.1	3.4	V	43.5	32.7	10.8
269.9	14.7	11.7	4.5	Н	46.0	30.9	15.1
481.2	15.0	16.8	6.1	Н	46.0	37.9	8.1
522.4	19.0	17.5	6.1	V	46.0	42.6	3.4
682.7	16.1	20.1	7.6	V	46.0	43.8	3.2
724.0	13.6	21.0	7.8	Н	46.0	42.4	3.6
823.6	11.9	22.3	8.4	V	46.0	42.6	3.4
833.4	9.4	22.4	8.5	V	46.0	40.3	5.7

Radiated Emissions

Note : 1280 x 1024, 85Hz mode

Freq. [MHz]	Reading [dBuV]	Antenna Factor [dB/m]	Cable Loss [dB]	Polar. [H/V]	Limit [dBuV/m]	Result [dBuV/m]	Margin [dB]
77.5	14.9	11.4	1.7	V	40.0	28.0	12.0
131.6	18.9	12.0	2.7	V	43.5	33.6	9.9
141.8	17.7	12.8	2.9	V	43.5	33.4	10.1
151.0	10.5	13.1	3.0	Н	43.5	26.6	16.9
188.2	18.7	10.1	3.4	V	43.5	32.2	11.3
269.9	15.1	11.7	4.5	Н	46.0	31.3	14.7
454.8	18.8	16.5	6.0	Н	46.0	41.3	4.7
508.7	17.4	17.2	6.1	V	46.0	40.7	5.3
695.1	14.7	20.3	7.7	V	46.0	42.7	3.3
758.2	12.2	21.7	8.0	Н	46.0	41.9	4.1
809.0	12.0	22.1	8.3	Н	46.0	42.4	3.6
846.0	11.1	22.6	8.6	Н	46.0	42.3	3.7

Radiated Emissions

Note : 1600 x 1200, 60Hz mode

End of Data

Appendix A. The Photos of Test Setup

Conducted Emissions-Front View

Conducted Emissions-Rear View

20 of 23

Appendix A. The Photos of Test Setup

Radiated Emissions (30MHz-1GHz) - Front View

Radiated Emissions(30MHz-1GHz)-Rear View

Appendix B. The Photos of EUT

Rear View

Appendix B. The Photos of EUT

Remote control