



Antenna Specification

SPECIFICATIONS	
Frequency (MHz)	2400-2500
Peak Gain (dBi)	3
Average Gain (dBi)	>-4
VSWR	<3.2
Impedance (Ω)	$50\ \Omega$
Antenna Type	PCB Antenna
Antenna model	SY008
Manufacturer	Shenzhen ArtFast Tech Co., Ltd

Testing environment: darkroom testing system




Antenna physical and physical dimensions



Antenna passive S parameter:


Standing wave ratio (VSWR)、Return loss (Return Loss) and smith chart




Antenna efficiency and gain

Frequency (MHz)	Peak Gain (dBi)	Efficiency (%)	AverageGain (dBi)	Efficiency (dB)
2400	1.433	59.329%	-2.717	-2.267
2410	0.927	51.861%	-3.416	-2.852
2420	0.829	52.112%	-3.166	-2.831
2430	0.881	49.299%	-3.258	-3.072
2440	1.192	50.672%	-3.144	-2.952
2450	1.688	53.067%	-2.735	-2.752
2460	2.194	59.423%	-2.276	-2.260
2470	2.518	56.680%	-2.438	-2.466
2480	3.000	61.727%	-2.112	-2.095
Average	1.629	54.908%	-2.806	-2.616
Peak	3.000	61.727%	-2.112	-2.095


Antenna 2440MHz 2D-Theta Pattern




Antenna 2440MHz 2D-Phi Pattern



Antenna 2440MHz 3D-Horizontal Pattern



Antenna 2440MHz 3D-Vertical Pattern



2440MHz 3D-Total Pattern

