

RF Exposure Evaluation

FCC ID: 2AZWI-3326LEQI

1. Client Information

Applicant	:	Shenzhen Leqi Network Technology Co., LTD
Address	:	Room 101, Building 9 & Room 401, Building 12, Yazhou Industrial Park, Bantian, Longgang, Shenzhen, Guangdong, China.
Manufacturer	:	Shenzhen Leqi Network Technology Co., LTD
Address	:	Room 101, Building 9 & Room 401, Building 12, Yazhou Industrial Park, Bantian, Longgang, Shenzhen, Guangdong, China.

2. General Description of EUT

EUT Name	:	Wireless Shooting Grip	
Model(s)	:	SR-RG1, 3759	
Model Difference	:	All these models are identical in the same PCB, layout and electrical circuit, The only difference is model name.	
Product Description	:	Operation Frequency:	Bluetooth 5.0(BLE): 2402MHz~2480MHz
		Number of Channel:	Bluetooth 5.0(BLE): 40 channels
		RF Output Power:	-7.275dBm (Max)
		Antenna Gain:	-3.26 dBi PCB Antenna
		Modulation Type:	GFSK
		Bit Rate of Transmitter:	1Mbps
Power Rating	:	Input: DC 5V2A DC 3.7V by 200mAh Rechargeable Li-ion battery	
Software Version	:	20210804153157	
Hardware Version	:	V2.1	
Connecting I/O Port(S)	:	Please refer to the User's Manual	

Remark: The antenna gain provided by the applicant, the adapter and verified for the RF conduction test and adapter provided by TOBY test lab.

Note: More test information about the EUT please refer the RF Test Report.

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

- [(max. power of channel, including tune-up tolerance, mW)/(min. test separation, mm)]*[$\sqrt{f_{\text{(GHz)}}}$] ≤ 3.0 for 1-g SAR

- [(max. power of channel, including tune-up tolerance, mW)/(min. test separation, mm)]*[$\sqrt{f_{\text{(GHz)}}}$] $\leq 7.5.0$ for 10-g SAR

2. Calculation:

Test separation: 5mm						
BLE Mode (1Mbps)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	-7.275	-7 ± 1	-6	0.251	0.078	3.0
2.442	-12.167	-12 ± 1	-11	0.079	0.025	3.0
2.480	-14.514	-14 ± 1	-13	0.050	0.016	3.0

Conclusion:

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

-----END OF REPORT-----