



From 30MHz to 1000MHz: Conclusion: PASS

Vertical:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	30.0000	58.94	-23.40	35.54	40.00	-4.46	QP	200	320	P	
2 !	45.0951	57.45	-22.22	35.23	40.00	-4.77	QP	100	313	P	
3	56.8644	49.97	-22.45	27.52	40.00	-12.48	QP	200	89	P	
4	87.9136	49.88	-25.76	24.12	40.00	-15.88	QP	200	23	P	
5	210.1294	50.67	-25.11	25.56	43.50	-17.94	QP	100	234	P	
6	294.4260	50.59	-22.37	28.22	46.00	-17.78	QP	100	7	P	

Horizontal:



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	31.0728	46.91	-23.30	23.61	40.00	-16.39	QP	200	11	P	
2 *	39.7370	46.08	-22.11	23.97	40.00	-16.03	QP	100	74	P	
3	45.7333	46.01	-22.20	23.81	40.00	-16.19	QP	100	348	P	
4	88.5335	49.40	-25.76	23.64	43.50	-19.86	QP	200	165	P	
5	201.4538	48.95	-24.74	24.21	43.50	-19.29	QP	200	259	P	
6	216.1196	44.42	-25.17	19.25	46.00	-26.75	QP	200	287	P	

Remark: All modes have been tested, and only worst data of GFSK mode, Channel 2402MHz was listed in this report.


From 1G-25GHz

All modes had been tested, only show the worst mode GFSK

Test Mode: GFSK TX Low									
Freq (MHz)	Read Level (dBuV/m)	Polar (H/V)	Antenna Factor (dB/m)	Cable loss(dB)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
4804	55.63	V	33.93	10.18	34.26	65.48	74	-8.52	55.63
4804	36.39	V	33.93	10.18	34.26	46.24	54	-7.76	36.39
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
4804	55.61	H	33.93	10.18	34.26	65.46	74	-8.54	PK
4804	36.95	H	33.93	10.18	34.26	46.80	54	-7.20	AV
7206	/	/	/	/	/	/	/	/	/
9608	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX Mid									
4882	55.64	V	33.95	10.2	34.97	64.82	74	-9.18	PK
4882	37.25	V	33.95	10.2	34.97	46.43	54	-7.57	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
4882	54.61	H	33.95	10.2	34.97	63.79	74	-10.21	PK
4882	38.94	H	33.95	10.2	34.97	48.12	54	-5.88	AV
7323	/	/	/	/	/	/	/	/	/
9764	/	/	/	/	/	/	/	/	/
Test Mode: GFSK TX High									
4960	54.61	V	33.98	10.22	34.25	64.56	74	-9.44	PK
4960	36.94	V	33.98	10.22	34.25	46.89	54	-7.11	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
4960	54.32	H	33.98	10.22	34.25	64.27	74	-9.73	PK
4960	36.69	H	33.98	10.22	34.25	46.64	54	-7.36	AV
7440	/	/	/	/	/	/	/	/	/
9920	/	/	/	/	/	/	/	/	/
Note:									
1, Result = Read level + Antenna factor + cable loss-Amp factor									
2, All the other emissions not reported were too low to read and deemed to comply with FCC limit.									

9. BAND EDGE COMPLIANCE

9.1. Block Diagram of Test Setup



9.2. Limit

All the lower and upper band-edges emissions appearing within restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

9.3. Test Procedure

All restriction band and non- restriction band have been tested , only worse case is reported.

9.4. Test Result

PASS. (See below detailed test data)

Test Results					PASS			
Frequency Range					2310MHz~2410MHz			
Test Mode					GFSK TX 2402MHz			
N o.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	74.36	-21.47	52.89	74.00	-21.11	Peak
2	2390	H	--	-21.47	--	54.00	--	Avg
3	2400	H	74.32	-26.12	48.2	74.00	-25.80	Peak
4	2400	H	--	-26.12	--	54.00	--	Avg
1	2390	V	74.93	-21.47	53.46	74.00	-20.54	Peak
2	2390	V	--	-21.47	--	54.00	--	Avg
3	2400	V	74.62	-26.12	48.5	74.00	-25.50	Peak
4	2400	V	--	-26.12	--	54.00	--	Avg
Test Results					PASS			
Frequency Range					2450MHz~2550MHz			
Test Mode					GFSK TX 2480MHz			
1	2483.5	H	76.69	-25.29	51.40	74.00	-22.60	Peak
2	2483.5	H	--	-25.29	--	54.00	--	Avg
1	2483.5	V	76.28	-25.29	50.99	74.00	-23.01	Peak
2	2483.5	V	--	-25.29	--	54.00	--	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								

Test Results					PASS			
Frequency Range					2310MHz~2410MHz			
Test Mode					$\pi/4$ DQPSK TX 2402MHz			
N o.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	74.91	-21.47	53.44	74.00	-20.56	Peak
2	2390	H	--	-21.47	--	54.00	--	Avg
3	2400	H	75.68	-26.12	49.56	74.00	-24.44	Peak
4	2400	H	--	-26.12	--	54.00	--	Avg
1	2390	V	74.57	-21.47	53.1	74.00	-20.90	Peak
2	2390	V	--	-21.47	--	54.00	--	Avg
3	2400	V	76.26	-26.12	50.14	74.00	-23.86	Peak
4	2400	V	--	-26.12	--	54.00	--	Avg
Test Results					PASS			
Frequency Range					2450MHz~2550MHz			
Test Mode					$\pi/4$ DQPSK TX 2480MHz			
1	2483.5	H	78.21	-25.29	52.92	74.00	-21.08	Peak
2	2483.5	H	--	-25.29	--	54.00	--	Avg
1	2483.5	V	77.29	-25.29	52.00	74.00	-22.00	Peak
2	2483.5	V	--	-25.29	--	54.00	--	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								

Test Results					PASS			
Frequency Range					2310MHz~2410MHz			
Test Mode					8DPSK TX 2402MHz			
N o.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	74.28	-21.47	52.81	74.00	-21.19	Peak
2	2390	H	--	-21.47	--	54.00	--	Avg
3	2400	H	75.99	-26.12	49.87	74.00	-24.13	Peak
4	2400	H	--	-26.12	--	54.00	--	Avg
1	2390	V	74.05	-21.47	52.58	74.00	-21.42	Peak
2	2390	V	--	-21.47	--	54.00	--	Avg
3	2400	V	75.62	-26.12	49.5	74.00	-24.50	Peak
4	2400	V	--	-26.12	--	54.00	--	Avg
Test Results					PASS			
Frequency Range					2450MHz~2550MHz			
Test Mode					8DPSK TX 2480MHz			
1	2483.5	H	78.21	-25.29	52.92	74.00	-21.08	Peak
2	2483.5	H	--	-25.29	--	54.00	--	Avg
1	2483.5	V	77.28	-25.29	51.99	74.00	-22.01	Peak
2	2483.5	V	--	-25.29	--	54.00	--	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								

Test Results					PASS			
Frequency Range					2310MHz~2410MHz			
Test Mode					GFSK Hopping			
N o.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	73.01	-21.47	51.54	74.00	-22.46	Peak
2	2390	H	--	-21.47	--	54.00	--	Avg
3	2400	H	72.09	-26.12	45.97	74.00	-28.03	Peak
4	2400	H	--	-26.12	--	54.00	--	Avg
1	2390	V	73.21	-21.47	51.74	74.00	-22.26	Peak
2	2390	V	--	-21.47	--	54.00	--	Avg
3	2400	V	72.27	-26.12	46.15	74.00	-27.85	Peak
4	2400	V	--	-26.12	--	54.00	--	Avg
Test Results					PASS			
Frequency Range					2450MHz~2550MHz			
Test Mode					GFSK Hopping			
1	2483.5	H	77.05	-25.29	51.76	74.00	-22.24	Peak
2	2483.5	H	--	-25.29	--	54.00	--	Avg
1	2483.5	V	77.12	-25.29	51.83	74.00	-22.17	Peak
2	2483.5	V	--	-25.29	--	54.00	--	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								


Test Results					PASS			
Frequency Range					2310MHz~2410MHz			
Test Mode					$\pi/4$ DQPSK Hopping			
N o.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	71.28	-21.47	49.81	74.00	-24.19	Peak
2	2390	H	--	-21.47	--	54.00	--	Avg
3	2400	H	72.47	-26.12	46.35	74.00	-27.65	Peak
4	2400	H	--	-26.12	--	54.00	--	Avg
1	2390	V	71.96	-21.47	50.49	74.00	-23.51	Peak
2	2390	V	--	-21.47	--	54.00	--	Avg
3	2400	V	70.27	-26.12	44.15	74.00	-29.85	Peak
4	2400	V	--	-26.12	--	54.00	--	Avg
Test Results					PASS			
Frequency Range					2450MHz~2550MHz			
Test Mode					$\pi/4$ DQPSK Hopping			
1	2483.5	H	77.21	-25.29	51.92	74.00	-22.08	Peak
2	2483.5	H	--	-25.29	--	54.00	--	Avg
1	2483.5	V	73.89	-25.29	48.60	74.00	-25.40	Peak
2	2483.5	V	--	-25.29	--	54.00	--	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								

Test Results					PASS			
Frequency Range					2310MHz~2410MHz			
Test Mode					8DPSK Hopping			
N o.	Freq MHz	Polarity	Reading (dBuV/m)	Correct Factor	Result (dBuV/m)	Limit (dBuV/m)	Margin	Remark
1	2390	H	74.01	-21.47	52.54	74.00	-21.46	Peak
2	2390	H	--	-21.47	--	54.00	--	Avg
3	2400	H	73.54	-26.12	47.42	74.00	-26.58	Peak
4	2400	H	--	-26.12	--	54.00	--	Avg
1	2390	V	73.25	-21.47	51.78	74.00	-22.22	Peak
2	2390	V	--	-21.47	--	54.00	--	Avg
3	2400	V	71.04	-26.12	44.92	74.00	-29.08	Peak
4	2400	V	--	-26.12	--	54.00	--	Avg
Test Results					PASS			
Frequency Range					2450MHz~2550MHz			
Test Mode					8DPSK Hopping			
1	2483.5	H	71.22	-25.29	45.93	74.00	-28.07	Peak
2	2483.5	H	--	-25.29	--	54.00	--	Avg
1	2483.5	V	72.27	-25.29	46.98	74.00	-27.02	Peak
2	2483.5	V	--	-25.29	--	54.00	--	Avg
Note: 1. Means other frequency and mode comply with standard requirements and at least have 20dB margin. 2. Correct Factor=Cable Loss+ Antenna Factor-Amplifier Gain. Result=Reading + Correct Factor. Margin= Result-Limit. 3. If the limits for the measurement with the average detector are met when using a receiver with a peak detector, the test unit shall be deemed to meet both limits and the measurement with the average detector need not be carried out.								

Reference level measurement


TestMode	Antenna	Freq(MHz)	Max.Point[MHz]	Result[dBm]
DH5	Ant1	2402	2402.15	3.59
		2441	2441.15	3.83
		2480	2479.84	3.01
2DH5	Ant1	2402	2402.15	2.58
		2441	2441.15	2.82
		2480	2479.84	2.07
3DH5	Ant1	2402	2402.16	2.45
		2441	2441.16	2.73
		2480	2480.16	1.83

DH5_Ant1_2402




Date: 16.JUL.2024 15:57:55

DH5_Ant1_2441




Date: 16.JUL.2024 15:59:34

DH5_Ant1_2480




Date: 16.JUL.2024 16:01:55

2DH5_Ant1_2402




Date: 16.JUL.2024 16:04:41


2DH5_Ant1_2441



2DH5_Ant1_2480




3DH5_Ant1_2402




Date: 16.JUL.2024 16:11:44

3DH5_Ant1_2441




Date: 16.JUL.2024 16:13:12


3DH5_Ant1_2480




Conducted Method

TestMode	Antenna	ChName	Freq(MHz)	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
DH5	Ant1	Low	2402	3.59	-48.04	≤-16.41	PASS
		High	2480	3.01	-47.02	≤-16.99	PASS
		Low	Hop_2402	4.13	-48.62	≤-15.87	PASS
		High	Hop_2480	3.84	-47.25	≤-16.16	PASS
2DH5	Ant1	Low	2402	2.58	-48.57	≤-17.42	PASS
		High	2480	2.07	-47.35	≤-17.93	PASS
		Low	Hop_2402	0.49	-48.14	≤-19.51	PASS
		High	Hop_2480	1.27	-47.05	≤-18.73	PASS
3DH5	Ant1	Low	2402	2.45	-48.39	≤-17.55	PASS
		High	2480	1.83	-47.73	≤-18.17	PASS
		Low	Hop_2402	1.79	-48.06	≤-18.21	PASS
		High	Hop_2480	0.28	-47.19	≤-19.72	PASS






DH5_Ant1_High_Hop_2480




2DH5_Ant1_Low_2402




Date: 16.JUL.2024 16:04:51

2DH5_Ant1_High_2480




Date: 16.JUL.2024 16:09:20

2DH5_Ant1_Low_Hop_2402




Date: 16.JUL.2024 16:22:51

2DH5_Ant1_High_Hop_2480




Date: 16.JUL.2024 16:25:48

3DH5_Ant1_Low_2402




Date: 16.JUL.2024 16:11:54

3DH5_Ant1_High_2480




Date: 16.JUL.2024 16:15:47

3DH5_Ant1_Low_Hop_2402



Date: 16.JUL.2024 16:26:58


3DH5_Ant1_High_Hop_2480



Date: 16.JUL.2024 16:35:11

10. POWER LINE CONDUCTED EMISSIONS

10.1. Block Diagram of Test Setup



10.2. Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.


10.3. Test Procedure

- (1) The EUT was placed on a non-metallic table, 80cm above the ground plane.
- (2) Setup the EUT and simulator as shown in 10.1
- (3) The EUT Power connected to the power mains through a power adapter and a line impedance stabilization network (L.I.S.N1). The other peripheral devices power cord connected to the power mains through a line impedance stabilization network (L.I.S.N2), this provided a 50-ohm coupling impedance for the EUT (Please refer to the block diagram of the test setup and photographs). Both sides of power line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10:2013 on conducted Emission test.
- (4) The bandwidth of test receiver is set at 10KHz.
- (5) The frequency range from 150 KHz to 30MHz is checked.

10.4.Test Result


Pass

Polarity: L



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1828	43.40	9.63	53.03	64.36	-11.33	QP	P	
2 *	0.1828	40.13	9.63	49.76	54.36	-4.60	AVG	P	
3	0.4408	36.26	9.63	45.89	57.05	-11.16	QP	P	
4	0.4408	19.30	9.63	28.93	47.05	-18.12	AVG	P	
5	0.5268	36.68	9.62	46.30	56.00	-9.70	QP	P	
6	0.5268	19.14	9.62	28.76	46.00	-17.24	AVG	P	
7	9.0649	37.17	9.72	46.89	60.00	-13.11	QP	P	
8	9.0649	28.57	9.72	38.29	50.00	-11.71	AVG	P	
9	14.7048	42.60	9.75	52.35	60.00	-7.65	QP	P	
10	14.7048	35.37	9.75	45.12	50.00	-4.88	AVG	P	
11	17.4446	37.98	9.76	47.74	60.00	-12.26	QP	P	
12	17.4446	29.00	9.76	38.76	50.00	-11.24	AVG	P	

Polarity: N



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.4407	36.64	9.62	46.26	57.05	-10.79	QP	P	
2	0.4407	18.85	9.62	28.47	47.05	-18.58	AVG	P	
3	0.5253	35.98	9.62	45.60	56.00	-10.40	QP	P	
4	0.5253	17.97	9.62	27.59	46.00	-18.41	AVG	P	
5	0.8272	36.73	9.62	46.35	56.00	-9.65	QP	P	
6	0.8272	22.38	9.62	32.00	46.00	-14.00	AVG	P	
7	8.8202	37.45	9.72	47.17	60.00	-12.83	QP	P	
8	8.8202	28.49	9.72	38.21	50.00	-11.79	AVG	P	
9	15.6312	42.87	9.76	52.63	60.00	-7.37	QP	P	
10 *	15.6312	35.83	9.76	45.59	50.00	-4.41	AVG	P	
11	17.8160	37.05	9.79	46.84	60.00	-13.16	QP	P	
12	17.8160	27.60	9.79	37.39	50.00	-12.61	AVG	P	

11. ANTENNA REQUIREMENTS

11.1.Limit


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2.Result

The EUT antenna is PIFA Antenna. It comply with the standard requirement.

12. TEST SETUP PHOTO

12.1.Photo of Radiated Emission test




12.2.Photo of Conducted Emission test



12.3.Conducted Test Photos







13. PHOTOS OF EUT




























-----END OF REPORT-----