



## RF Exposure Evaluation

For

The Gem Group, Inc.

EDEN COLLAPSIBLE DESK CHARGER

Test Model: 102462-021B

Prepared for : The Gem Group, Inc.  
Address : 9 International Way, Lawrence, MA 01843, USA

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street,  
Baoan District, Shenzhen, China  
Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : March 14, 2025  
Number of tested samples : 2  
Sample No. : A250313048-1, A250313048-2  
Serial number : Prototype  
Date of Test : March 14, 2025 ~ March 27, 2025  
Date of Report : March 28, 2025





<b>RF Exposure Evaluation</b>	
<b>Report Reference No.</b> : LCSA03135032EB	
<b>Date Of Issue</b> : March 28, 2025	
<b>Testing Laboratory Name</b> : Shenzhen LCS Compliance Testing Laboratory Ltd.	
<b>Address</b> : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street, Baoan District, Shenzhen, China	
<b>Testing Location/ Procedure</b> : Full application of Harmonised standards <input checked="" type="checkbox"/> Partial application of Harmonised standards <input type="checkbox"/> Other standard testing method <input type="checkbox"/>	
<b>Applicant's Name</b> : The Gem Group, Inc.	
<b>Address</b> : 9 International Way, Lawrence, MA 01843, USA	
<b>Test Specification</b>	
Standard : FCC KDB publication 680106 D01 Wireless Power Transfer v04 FCC CFR 47 part1 1.1310 FCC CFR 47 part2 2.1091 FCC CFR 47 part 18.107	
Test Report Form No. : TRF-4-E-214 A/0	
TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.	
Master TRF : Dated 2011-03	
<b>Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.</b> This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.	
<b>Test Item Description</b> : EDEN COLLAPSIBLE DESK CHARGER	
Trade Mark : Gemline	
Test Model : 102462-021B	
Ratings : Please Refer to Page 6	
<b>Result</b> : Positive	

Compiled by:

Supervised by:

Approved by:

Joker.Hu

Jack Liu

Gavin Liang

Joker Hu/Administrator

Jack Liu / Technique principal

Gavin Liang/ Manager



**FCC TEST REPORT**

<b>Test Report No. :</b> <b>LCSA03135032EB</b>	<u>March 28, 2025</u> Date of issue
--	--

Test Model.....	: 102462-021B
EUT.....	: EDEN COLLAPSIBLE DESK CHARGER
<b>Applicant.....</b>	<b>: The Gem Group, Inc.</b>
Address.....	: 9 International Way, Lawrence, MA 01843, USA
Telephone.....	: /
Fax.....	: /
<b>Manufacturer.....</b>	<b>: ShenzhenFuture chargerTechnologyCo..Ltd</b>
Address.....	: Yongfengtianindustiralpark, 3rd industrialzone, fenghuang, Fuyong, Bao'anDistrict, Shenzhen. China.51810
Telephone.....	: /
Fax.....	: /
<b>Factory.....</b>	<b>: ShenzhenFuture chargerTechnologyCo..Ltd</b>
Address.....	: Yongfengtianindustiralpark, 3rd industrialzone, fenghuang, Fuyong, Bao'anDistrict, Shenzhen. China.51810
Telephone.....	: /
Fax.....	: /

<b>Test Result</b>	<b>Positive</b>
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





Revision History

Report Version	Issue Date	Revision Content	Revised By
000	March 28, 2025	Initial Issue	--





TABLE OF CONTENTS

Description	Page
1. PRODUCT INFORMATION .....	6
2. EVALUATION METHOD .....	6
3. EVALUATION LIMIT .....	9
4. TEST SETUP DIAGRAM .....	11
5. TEST EQUIPMENT .....	11
6. MEASUREMENT PROCEDURE .....	11
7. EQUIPMENT APPROVAL CONSIDERATIONS .....	12
8. AND H FIELD STRENGTH .....	13
9. TEST SETUP PHOTOS .....	15
10. CONCLUSION .....	15
11. DESCRIPTION OF TEST FACILITY .....	15
12. MEASUREMENT UNCERTAINTY .....	15





## 1. Product Information

Product Name	EDEN COLLAPSIBLE DESK CHARGER
Model Number	102462-021B
Ratings	Input:DC 5V/2.0A, DC 9V/2.0A Wireless Output: 10W(Max)
Modulation Type	ASK
Frequency Range	110.1~205.0KHz
Antenna Type	Coil Antenna
Hardware version	/
Software version	/
Accessories	/
Exposure category	General population/uncontrolled environment
EUT Type	Production Unit
Device Type	Mobile Device

Note: For a more detailed antenna description, please refer to the antenna specifications or the antenna report provided by the customer.

## 2. Evaluation Method

Per KDB 680106 D01 Section 3. RF Exposure Requirements;

- 1) Wireless power transfer devices must comply with RF exposure requirements for all design configurations in which they can operate. At a minimum, RF exposure must be evaluated for the worst-case scenario, typically when the transmitter, while delivering energy to a client device, is operating at maximum output power. RF exposure compliance for equipment authorization must be determined following the guidance of KDB447498, which includes consideration of the different test requirements for *Mobile Device* and *Portable Device* exposure categories, as defined in §§ 2.1091 and 2.1093 of the Rules.
- 2) The RF exposure limits, as set forth in § 1.1310, do not cover the frequency range below 100 kHz for Specific Absorption Rate (SAR) and below 300 kHz for Maximum Permitted Exposure (MPE). In addition, present limitations of RF exposure evaluation systems prevent an accurate evaluation of SAR below 4 MHz. For these reasons, a specific MPE-based RF Exposure compliance procedure for devices operating in the aforementioned low-frequency ranges has been set in place. This procedure is applicable to Equipment Authorization of all RF devices, thus including, but not limited to, Part 18 and WPT devices. Accordingly, for § 2.1091-*Mobile* devices, the MPE limits between 100 kHz to 300 kHz are to be considered the same as those at 300 kHz in Table 1 of § 1.1310, that is, 614 V/m and 1.63 A/m, for the electric field and magnetic field, respectively. For § 2.1093-*Portable* devices below 4 MHz and down to 100 kHz, the MPE limits in § 1.1310 (with the 300 kHz limit applicable all the way down to 100 kHz) can be used for the purpose of equipment authorization in lieu of SAR evaluations.


Furthermore, consistent with FCC's equipment authorization RF exposure guidance, any device (both portable and mobile) operating at frequencies below 100 kHz is considered compliant for the purpose of equipment authorization when the external (unperturbed) temporal peak field strengths do not exceed the following reference levels:

83 V/m for the electric field strength ( $E$ )  
and 90 A/m for the magnetic field strength ( $H$ )











**a) Not considered as WPT  
"at-a-distance"**



**b) WPT "at-a-distance"  
because RX2 position**

**Figure 2-a)** For multiple-receiver systems (here shown with two receivers, indicated with RX1 and RX2) the one-meter distance limit must apply for all the receivers that are engaged in the charging process. **b)** The WPT system is considered "at-a-distance" because it can function when the RX2 is further away than one meter from the transmitter.



**Figure 3.** For multiple-coil transmitter systems, the one-meter distance limit is measured from the closest coil edge. A WPT within one meter operates with loads configured as those labeled in green font, if a load can be powered beyond one meter (in red), then it shall be considered "at-a-distance"

There might be situations where the WPT RF emissions are limited enough that even operations in a "crowded" environment, where many similar WPT devices are present, do not pose significant EMC and RF exposure concerns. In this scenario, and for devices operating within a one-meter distance from the receiver, as defined above, a manufacturer will not have to submit an "Equipment Compliance Review" KDB, and receive FCC concurrence before proceeding with equipment authorization. This exception to the requirement of submitting the ECR to obtain FCC concurrence only applies when all the following criteria (1) through (6) are met:







- (1) The power transfer frequency is below 1 MHz.
- (2) The output power from each transmitting element (e.g., coil) is less than or equal to 15 watts.
- (3) A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)
- (4) Only § 2.1091- Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093 – Portable exposure conditions).
- (5) The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios (i.e., the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.
- 5) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well. For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested

### 3. Evaluation Limit

#### 3.1 Refer evaluation method

[ANSI C95.1–1999](#): IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

[FCC KDB publication 680106 D01 Wireless Power Transfer v04](#): EQUIPMENT AUTHORIZATION OF WIRELESS POWER TRANSFER DEVICES

[FCC CFR 47 part1 1.1310](#): Radiofrequency radiation exposure limits.

[FCC CFR 47 part2 2.1091](#): Radiofrequency radiation exposure evaluation: mobile devices

[FCC CFR 47 part 18.107](#): Industrial, Scientific, and Medical Equipment





### 3.2 Limit

#### Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500	/	/	f/300	6
1,500-100,000	/	/	5	6

#### Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500	/	/	f/1500	30
1,500-100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

According to FCC KDB 680106 D01 Section 3. RF Exposure Requirements clause 3 the Emission-Limits in the frequency range from 100 KHz to 300 KHz should be assessed versus the limits at 300 KHz in Table 1 of CFR 47 – Section 1.310 as following (measured distance shall be 15cm from the center of the probe to the edge of the device):


	E-Field	*/*	B-Field
Frequency	V/m	A/m	uT
0.3 MHz – 3.0 MHz	614	1.613	2.0
3.0 MHz – 30 MHz	824/f (=27.5 <sub>30MHz</sub> )	2.19/f (=0.073 <sub>30MHz</sub> )	--

A KDB inquire was required to determine/confirm the applicable limits below 100 KHz.





#### 4. Test Setup Diagram



#### 5. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Exposure Level Tester	Narda	ELT-400	N-0713	2024-11-11	2025-11-10
2	B-Field Probe	Narda	ELT-400	M-1154	2024-10-08	2025-10-07
3	Electric field probe	Narda	EP601	611WX70332	N/A	N/A

#### 6. Measurement Procedure

- The RF exposure test was performed on 360 degree turn table in anechoic chamber.
- The measurement probe was placed at test distance (15cm and 20cm) which is between the edges of the charger and the geometric center of probe.
- The turn table was rotated 360d degree to search of highest strength.
- The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.
- The EUT were measured according to the dictates of KDB 680106D01v03.





## 7. Equipment Approval Considerations

The EUT does comply with item 5.2 of KDB 680106 D01v04 as follows table;

Requirements of KDB 680106 D01	Yes / No	Description
Power transfer frequency is less than 1 MHz	Yes	The device operates in the frequency range 110.1 KHz - 205 KHz
The output power from each transmitting element (e.g., coil) is less than or equal to 15 watts.	Yes	The maximum output power of the primary coil is 10W.
A client device providing the maximum permitted load is placed in physical contact with the transmitter (i.e., the surfaces of the transmitter and client device enclosures need to be in physical contact)	Yes	Client device is placed directly in contact with the transmitter.
Only § 2.1091- Mobile exposure conditions apply (i.e., this provision does not cover § 2.1093-Portable exposure conditions).	Yes	Mobile exposure conditions only
The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1. These measurements shall be taken along the principal axes of the device, with one axis oriented along the direction of the estimated maximum field strength, and for three points per axis or until a 1/d (inverse distance from the emitter structure) field strength decay is observed. Symmetry considerations may be used for test reduction purposes. The device shall be operated in documented worst-case compliance scenarios (i.e., the ones that lead to the maximum field components), and while all the radiating structures (e.g., coils or antennas) that by design can simultaneously transmit are energized at their nominal maximum power.	Yes	The EUT H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.
For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time, as per design conditions. If the design allows one or more radiating structures to be powered at a higher level while other radiating structures are not powered, then those cases must be tested as well.	Yes	Only one radiating structure and tested at maximum Output Power





For instance, a device may use three RF coils powered at 5 W, or one coil powered at 15 W: in this case, both scenarios shall be tested		
---	--	--

There might be situations where the WPT RF emissions are limited enough that even operations in a “crowded” environment, where many similar WPT devices are present, do not pose significant EMC and RF exposure concerns. In this scenario, and for devices operating within a one-meter distance from the receiver, as defined above, a manufacturer will not have to submit an “Equipment Compliance Review” KDB, and receive FCC concurrence before proceeding with equipment authorization. This exception to the requirement of submitting the ECR to obtain FCC concurrence only applies when all the following criteria (1) through (6) are met.

## 8. and H field Strength

Test Modes		
Mode 1	AC/DC Adapter(9V/2.0A)+EUT+mobile phone (Battery Status: <1%)	Record
Mode 2	AC/DC Adapter(9V/2.0A)+EUT+mobile phone (Battery Status: <50%)	Record
Mode 3	AC/DC Adapter(9V/2.0A)+EUT+mobile phone (Battery Status: 100%)	Record
Mode 4	AC/DC Adapter(5V/2.0A)+EUT+mobile phone (Battery Status: <1%)	Pre-tested
Mode 5	AC/DC Adapter(5V/2.0A)+EUT+mobile phone (Battery Status: <50%)	Pre-tested
Mode 6	AC/DC Adapter(5V/2.0A)+EUT+mobile phone (Battery Status: 100%)	Pre-tested
Note: All test modes were pre-tested, but we only recorded the worst case in this report.		







Field Strength at 15 cm from the edges surrounding the EUT and 15cm from the top surface of the EUT

Load mode	Frequency Range (kHz)	Field Strength	Measured Field Strength Values					50% Limits	Limits
			Test Position A	Test Position B	Test Position C	Test Position D	Test Position E		
Mode 1	110.1~205.0	uT	0.127	0.136	0.137	0.128	0.149	--	--
Mode 1	110.1~205.0	A/m	0.101	0.109	0.110	0.103	0.119	0.815	1.63
Mode 1	110.1~205.0	V/m	38.066	41.020	41.293	38.568	44.653	307.0	614.0
Mode 2	110.1~205.0	uT	0.125	0.130	0.135	0.125	0.143	--	--
Mode 2	110.1~205.0	A/m	0.100	0.104	0.108	0.100	0.114	0.815	1.63
Mode 2	110.1~205.0	V/m	37.477	39.031	40.719	37.553	42.865	307.0	614.0
Mode 3	110.1~205.0	uT	0.117	0.127	0.132	0.119	0.137	--	--
Mode 3	110.1~205.0	A/m	0.094	0.102	0.106	0.095	0.109	0.815	1.63
Mode 3	110.1~205.0	V/m	35.175	38.219	39.673	35.837	41.115	307.0	614.0

Field Strength at 20 cm from the edges surrounding the EUT and 20cm from the top surface of the EUT

Load mode	Frequency Range (kHz)	Field Strength	Measured Field Strength Values	50% Limits	Limits
			Test Position E		
Mode 1	110.1~205.0	uT	0.143	--	--
Mode 1	110.1~205.0	A/m	0.114	0.815	1.63
Mode 1	110.1~205.0	V/m	43.024	307	614
Mode 2	110.1~205.0	uT	0.140	--	--
Mode 2	110.1~205.0	A/m	0.112	0.815	1.63
Mode 2	110.1~205.0	V/m	42.067	307	614
Mode 3	110.1~205.0	uT	0.131	--	--
Mode 3	110.1~205.0	A/m	0.104	0.815	1.63
Mode 3	110.1~205.0	V/m	39.238	307	614

Note:  $V/m = 10(((20 \lg(A/m \cdot 10^6) + 51.5) - 120)/20)$

Note:  $A/m = uT/1.25$



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## 9. Test Setup Photos

Please refer to separated files for Test Setup Photos of the EUT.

## 10. Conclusion

A minimum safety distance of at 15 cm surrounding the device and 20 cm above the top surface of the device is required when the device is charging a smart phone. The detected emissions with a distance of 15 cm surrounding the device and 20 cm above the top surface of the device are below the limitations according to FCC KDB 680106 D01 Section 3. RF Exposure Requirement Clause 3.

## 11. Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

## 12. Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Field Strength Uncertainty :	1Hz~400KHz	1%	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

.....END OF REPORT.....

