

FCC PART 15.247 TEST REPORT

For

Shanghai Sunmi Technology Co.,Ltd.

Room 605, Block 7, KIC Plaza, No.388 Song Hu Road, Yang Pu District, Shanghai 200433
China

FCC ID: 2AH25TF700

Report Type: Original Report	Product Type: WIRELESS DATA TERMINAL
Project Engineer:	Chris Wang <i>Chris. wang</i>
Report Number:	RKSA200706002-00B
Report Date:	2020-11-04
Reviewed By:	Oscar Ye EMC Manager <i>Oscar.Ye</i>
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
TEST FACILITY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EUT EXERCISE SOFTWARE	7
SPECIAL ACCESSORIES	7
EQUIPMENT MODIFICATIONS	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST RESULTS.....	11
TEST EQUIPMENT LIST	12
FCC §1.1310 & §2.1093 - RF EXPOSURE.....	13
MEASUREMENT RESULT	13
FCC §15.203 – ANTENNA REQUIREMENT	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE	16
FACTOR & MARGIN CALCULATION	16
TEST RESULTS SUMMARY	16
TEST DATA	16
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	19
APPLICABLE STANDARD	19
EUT SETUP	19
EMI TEST RECEIVER SETUP.....	20
TEST PROCEDURE	20
CORRECTED AMPLITUDE & MARGIN CALCULATION	20
TEST RESULTS SUMMARY	20
TEST DATA	20
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36
TEST DATA	36
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH.....	42
APPLICABLE STANDARD	42
TEST PROCEDURE	42
TEST DATA	42
FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	48
APPLICABLE STANDARD	48

TEST PROCEDURE	48
TEST DATA	48
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	51
APPLICABLE STANDARD	51
TEST PROCEDURE	51
TEST DATA	51
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	67
APPLICABLE STANDARD	67
TEST PROCEDURE	67
TEST DATA	67
FCC §15.247(d) - BAND EDGES TESTING	74
APPLICABLE STANDARD	74
TEST PROCEDURE	74
TEST DATA	74

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant:	Shanghai Sunmi Technology Co.,Ltd.
Product Type:	WIRELESS DATA TERMINAL
Tested Model:	TF700
Power Supply:	DC 5.0/9.0/12.0/3.6~6.0/6.0~9.0/9.0~12.0V from adapter
RF Function:	Classic BT
Operating Band/Frequency:	2402-2480 MHz
Channel Number:	79
Channel Separation:	1 MHz
Modulation Type:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Antenna Type:	FPC Antenna
*Maximum Antenna Gain:	-1.3 dBi

Note: The antenna gain was provided by the applicant.

Adapter-1 Information:

Model: CK18W02U

Input: AC 100-240V 50/60Hz 0.5A

Output: 5.0V, 3.0A/9.0V, 2.0A/12.0V, 1.5A

Adapter-2 Information:

Model: TPA-10120150UU

Input: AC 100-240V 50/60Hz 0.6A

Output: 3.6~6.0V, 3.0A, /6.0~9.0V, 2.0A/9.0~12.0V, 1.5A

Adapter-3 Information:

Model: TPA-23A050200UU01

Input: AC100-240V 50/60Hz 0.3A

Output: 5.0V, 2000mA

Adapter-4 Information:

Model: UC13US

Input: AC100-240V 50/60Hz 0.35A

Output: 5.0V, 2000mA

*All measurement and test data in this report was gathered from production sample serial number: 20200706002.
(Assigned by the BACL. The EUT supplied by the applicant was received on 2020-07-06)

Objective

This test report is prepared on behalf of *Shanghai Sunmi Technology Co.,Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine Compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS submissions with FCC ID: 2AH25TF700

FCC Part 15.407 NII submissions with FCC ID: 2AH25TF700

FCC Part 15B JBP submissions with FCC ID: 2AH25TF700

FCC Part 15.225 DXX submissions with FCC ID: 2AH25TF700

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0℃
Humidity		6%

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01), the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	40	2442
1	2403	...	...
...	...	...	...
...	...	78	2480
39	2441	/	/

EUT was tested with Channel 0, 39 and 78.

Note: Pre-scanned the four adapters are for Conducted Emissions and Radiated Emissions items in the report No. RKSA200706002-00A, We chose the adapter 4 with the worst results for Conducted Emissions and Radiated Emissions items for testing in the RF report.

EUT Exercise Software

RF test software: QRCT

*GFSK, $\pi/4$ -DQPSK , 8DPSK Power level: 9.

Note: The power level setting was declared by the applicant.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable


Cable Description	Shielding Type	Length (m)	From Port	To
USB Cable	Un-shielding	2.0	EUT	Adapter
Power Cable	Un-shielding	1.0	Adapter	LISN/ AC Source

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1310 & §2.1093	RF EXPOSURE	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209 & §15.247(d)	Radiated Emissions & Restricted Bands Emissions	Compliant
§15.247(a)(1)	20 dB Emission Bandwidth	Compliant
§15.247(a)(1)	Channel Separation Test	Compliant
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliant
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliant
§15.247(b)(1)	Peak Output Power Measurement	Compliant
§15.247(d)	Band edges	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2019-12-14	2020-12-13
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2017-12-26	2020-12-25
Sonoma Instrunent	Pre-amplifier	310N	171205	2020-08-14	2021-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2020-08-15	2021-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2020-04-01	2021-03-31
ETS-LINDGREN	Horn Antenna	3115	6229	2020-01-10	2023-01-09
ETS-LINDGREN	Horn Antenna	3116	00084159	2019-10-18	2022-10-17
A.H.Systems,inc	Amplifier	PAM-0118P	512	2020-02-20	2021-02-19
EM Electronics Corporation	Amplifier	EM18G40G	060726	2020-03-22	2021-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2020-08-15	2021-08-14
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2019-12-12	2020-12-11
MICRO-COAX	Coaxial Cable	Cable-11	011	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2020-08-15	2021-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2019-12-14	2020-12-13
Rohde & Schwarz	Signal Analyzer	FSV40	101116	2020-08-05	2021-08-04
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
Sunmi	RF Cable	Sunmi 01	C01	Each Time	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	834115/007	2019-11-30	2020-11-29
Rohde & Schwarz	LISN	ENV216	3560655016	2019-11-30	2020-11-29
Audix	Test Software	e3	V9	--	--
Rohde & Schwarz	Pulse limiter	ESH3-Z2	0357.8810.54	2020-08-10	2021-08-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2020-08-15	2021-08-14

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1093 - RF EXPOSURE

Applicable Standard

According to FCC§1.1310,§2.1093.

Measurement Result

Compliance, please refer to SAR Report: RKSA200706002-20A.

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


Antenna Connector Construction

The EUT has an internal FPC antenna for Bluetooth, which the antenna gain is -1.3 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS**Applicable Standard**

FCC §15.207(a)

EUT Setup

- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

ANSI C63.10-2013 clause 6.2

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Margin Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation (dB). The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over Limit of 7dB means the emission is 7 dB above the limit. The equation for over Limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data


Environmental Conditions

Temperature:	24.5-26.3 °C
Relative Humidity:	51-55 %
ATM Pressure:	100.9-101.2 kPa

The testing was performed by Chris Wang from 2020-09-19 to 2020-09-20.


EUT operation mode: Transmitting in low channel of GFSK mode (Worst case)

AC 120V/60 Hz, Line



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.152	24.80	19.82	44.62	55.87	-11.25	Average
2	0.152	39.70	19.82	59.52	65.87	-6.35	QP
3	0.216	14.90	19.82	34.72	52.96	-18.24	Average
4	0.216	31.40	19.82	51.22	62.96	-11.74	QP
5	0.280	9.90	19.82	29.72	50.81	-21.09	Average
6	0.280	25.20	19.82	45.02	60.81	-15.79	QP
7	0.579	9.70	19.75	29.45	46.00	-16.55	Average
8	0.579	20.60	19.75	40.35	56.00	-15.65	QP
9	0.690	10.40	19.75	30.15	46.00	-15.85	Average
10	0.690	16.20	19.75	35.95	56.00	-20.05	QP
11	18.721	9.80	19.88	29.68	50.00	-20.32	Average
12	18.721	19.20	19.88	39.08	60.00	-20.92	QP



AC 120V/60 Hz, Neutral



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.203	19.00	19.82	38.82	53.49	-14.67	Average
2	0.203	34.70	19.82	54.52	63.49	-8.97	QP
3	0.249	5.20	19.82	25.02	51.78	-26.76	Average
4	0.249	21.00	19.82	40.82	61.78	-20.96	QP
5	0.479	3.80	19.76	23.56	46.36	-22.80	Average
6	0.479	18.70	19.76	38.46	56.36	-17.90	QP
7	0.576	5.00	19.75	24.75	46.00	-21.25	Average
8	0.576	20.60	19.75	40.35	56.00	-15.65	QP
9	0.665	1.10	19.75	20.85	46.00	-25.15	Average
10	0.665	14.40	19.75	34.15	56.00	-21.85	QP
11	21.830	10.10	19.85	29.95	50.00	-20.05	Average
12	21.830	18.60	19.85	38.45	60.00	-21.55	QP

FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS**Applicable Standard**

FCC §15.205; §15.209; §15.247(d)

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude (dB}\mu\text{V /m)} = \text{Meter Reading (dB}\mu\text{V)} + \text{Antenna Factor (dB/m)} + \text{Cable Loss (dB)} - \text{Amplifier Gain (dB)}$$

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin (dB)} = \text{Limit (dB}\mu\text{V/m)} - \text{Corrected Amplitude (dB}\mu\text{V /m)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data

Environmental Conditions


Temperature:	23.4°C~26.5°C
Relative Humidity:	49 %~56 %
ATM Pressure:	101.1kPa ~101.7kPa

The testing was performed by Chris Wang from 2020-07-09 to 2020-09-12.

EUT operation mode: Transmitting

Spurious Emission Test:**30MHz-1GHz:**

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case high channel of 8DPSK Mode in Z-axis of orientation was recorded




Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	Quasi-peak (dBμV/m)	Height (cm)	Polar (H/V)				
30.086370	25.48	100.0	V	94.0	-4.4	40.00	14.52
40.412950	24.15	100.0	V	99.0	-11.5	40.00	15.85
67.674250	17.59	100.0	V	109.0	-18.0	40.00	22.41
141.023000	17.90	100.0	V	234.0	-12.4	43.50	25.60
201.736000	16.76	100.0	V	353.0	-12.8	43.50	26.74
659.177100	18.51	100.0	V	104.0	-4.0	46.00	27.49

1GHz-18GHz:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case 8DPSK Mode in Z-axis of orientation was recorded

Note:


1. This test was performed with the 2.4-2.5 GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Low Channel: 2402MHz

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1595.000000	---	31.19	200.0	V	234.0	-16.0	54.00	22.81
1595.000000	38.22	---	200.0	V	234.0	-16.0	74.00	35.78
2130.500000	---	28.36	150.0	V	79.0	-13.9	54.00	25.64
2130.500000	34.44	---	150.0	V	73.0	-13.9	74.00	39.56
4804.000000	---	32.36	200.0	H	189.0	-5.6	54.00	21.64
4804.000000	40.00	---	200.0	H	189.0	-5.6	74.00	34.00
7208.400000	---	36.45	200.0	H	348.0	0.4	54.00	17.55
7208.400000	46.53	---	200.0	H	348.0	0.4	74.00	27.47
9607.100000	---	46.49	150.0	V	353.0	2.1	54.00	7.51
9607.100000	50.47	---	150.0	V	353.0	2.1	74.00	23.53
17605.600000	---	47.35	200.0	H	219.0	8.9	54.00	6.65
17605.600000	53.69	---	200.0	H	219.0	8.9	74.00	20.31

Middle Channel: 2441MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1062.900000	---	29.86	200.0	V	220.0	-18.7	54.00	24.14
1062.900000	38.62	---	200.0	V	220.0	-18.7	74.00	35.38
1311.100000	---	26.46	150.0	V	244.0	-17.4	54.00	27.54
1311.100000	35.65	---	150.0	V	244.0	-17.4	74.00	38.35
1596.700000	---	34.66	200.0	V	235.0	-16.0	54.00	19.34
1596.700000	39.11	---	200.0	V	235.0	-16.0	74.00	34.89
4882.000000	---	32.16	200.0	V	266.0	-5.4	54.00	21.84
4882.000000	40.58	---	200.0	V	266.0	-5.4	74.00	33.42
9763.500000	---	41.77	200.0	V	0.0	2.0	54.00	12.23
9763.500000	47.25	---	200.0	V	0.0	2.0	74.00	26.75
17763.700000	---	45.12	150.0	V	286.0	8.8	54.00	8.88
17763.700000	55.89	---	150.0	V	286.0	8.8	74.00	18.11

High Channel: 2480MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1593.300000	---	29.97	200.0	V	288.0	-16.0	54.00	24.03
1593.300000	39.11	---	200.0	V	288.0	-16.0	74.00	34.89
2123.700000	---	28.08	150.0	V	259.0	-14.0	54.00	25.92
2123.700000	35.47	---	150.0	V	259.0	-14.0	74.00	38.53
4960.000000	---	33.34	200.0	H	188.0	-5.3	54.00	20.66
4960.000000	39.78	---	200.0	H	188.0	-5.3	74.00	34.22
7330.800000	---	38.58	150.0	V	302.0	0.7	54.00	15.42
7330.800000	45.55	---	150.0	V	302.0	0.7	74.00	28.45
9919.900000	---	39.50	150.0	V	359.0	1.9	54.00	14.50
9919.900000	45.50	---	150.0	V	359.0	1.9	74.00	28.50
17699.100000	---	48.71	150.0	H	71.0	8.9	54.00	5.29
17699.100000	52.45	---	150.0	H	71.0	8.9	74.00	21.55

18GHz-25GHz:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case high channel of 8DPSK Mode in Z-axis of orientation was recorded

Horizontal

Date: 12.SEP.2020 13:02:06

Vertical

Date: 12.SEP.2020 13:13:41

Fundamental Test & Restricted Bands Emissions:

Pre-Scan with GFSK, $\pi/4$ -DQPSK, 8DPSK modes of operation in the X,Y and Z axes of orientation, the worst case 8DPSK Mode in Z-axis of orientation was recorded

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)


Corrected Amplitude (dB μ V /m) = Corrected Factor (dB/m) + Reading (dB μ V)

Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V /m)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2402MHz								
2390.00	---	37.10	150.0	V	272.0	-2.9	54.00	16.90
2390.00	44.25	---	150.0	V	272.0	-2.9	74.00	29.75
High Channel: 2480MHz								
2483.50	45.23	---	150.0	V	346.0	-2.5	74.00	28.77
2483.50	---	36.99	150.0	V	346.0	-2.5	54.00	17.01

Conducted Spurious Emissions at Antenna Port

BDR (GFSK): Low Channel




Date: 12.JUL.2020 21:26:16




Date: 12.JUL.2020 22:49:07

BDR (GFSK): Middle Channel




Date: 12.JUL.2020 21:40:28




Date: 12.JUL.2020 22:51:55

BDR (GFSK): High Channel




Date: 12.JUL.2020 21:42:14




Date: 12.JUL.2020 22:53:53

EDR ($\pi/4$ -DQPSK): Low Channel




Date: 12.JUL.2020 21:28:11




Date: 12.JUL.2020 22:58:48

EDR ($\pi/4$ -DQPSK): Middle Channel




Date: 12.JUL.2020 21:39:13




Date: 12.JUL.2020 23:05:27

EDR ($\pi/4$ -DQPSK): High Channel




Date: 12.JUL.2020 21:44:30




Date: 12.JUL.2020 23:11:00

EDR (8DPSK): Low Channel




Date: 12.JUL.2020 21:32:15




Date: 12.JUL.2020 23:47:03

EDR (8DPSK): Middle Channel




Date: 12.JUL.2020 21:34:33




Date: 12.JUL.2020 23:39:43

EDR (8DPSK): High Channel



Date: 12.JUL.2020 21:47:00



Date: 12.JUL.2020 23:35:01

FCC §15.247(a) (1)-CHANNEL SEPARATION TEST**Applicable Standard**

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: Wide enough to capture the peaks of two adjacent channels.
- b. RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c. Video (or average) bandwidth (VBW) $\geq$ RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

Test Data**Environmental Conditions**

Temperature:	25.7 °C
Relative Humidity:	56 %
ATM Pressure:	101.3 kPa

The testing was performed by Chris Wang on 2020-07-13.


EUT operation mode: Transmitting

Test Result: Compliant.

Mode	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)	Result
BDR (GFSK)	Low	2402	0.990	0.638	Pass
	Adjacent	2403			
	Middle	2441	1.000	0.635	Pass
	Adjacent	2442			
	High	2480	1.000	0.638	Pass
	Adjacent	2479			
EDR ($\pi/4$ -DQPSK)	Low	2402	1.010	0.875	Pass
	Adjacent	2403			
	Middle	2441	1.005	0.869	Pass
	Adjacent	2442			
	High	2480	1.000	0.885	Pass
	Adjacent	2479			
EDR (8DPSK)	Low	2402	1.005	0.878	Pass
	Adjacent	2403			
	Middle	2441	1.000	0.872	Pass
	Adjacent	2442			
	High	2480	1.005	0.875	Pass
	Adjacent	2479			


Note: For BDR mode and EDR mode, Limit = 20 dB bandwidth*2/3

BDR (GFSK): Low Channel




Date: 13.JUL.2020 20:56:19

BDR (GFSK): Middle Channel




Date: 13.JUL.2020 21:01:51

BDR (GFSK): High Channel




Date: 13.JUL.2020 21:10:18

EDR ($\pi/4$ -DQPSK): Low Channel




Date: 13.JUL.2020 21:18:36

EDR ($\pi/4$ -DQPSK): Middle Channel




Date: 13.JUL.2020 21:33:47

EDR ($\pi/4$ -DQPSK): High Channel




Date: 13.JUL.2020 21:49:19

EDR (8DPSK): Low Channel




Date: 13.JUL.2020 22:44:45

EDR (8DPSK): Middle Channel



Date: 13.JUL.2020 22:32:49

EDR (8DPSK): High Channel



Date: 13.JUL.2020 22:13:26

FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH**Applicable Standard**

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

Test Data**Environmental Conditions**

Temperature:	25.7 °C
Relative Humidity:	55 %
ATM Pressure:	101.3 kPa


The testing was performed by Chris Wang on 2020-07-11.

EUT operation mode: Transmitting

Test Result: Compliant.


Mode	Channel	Frequency (MHz)	20 dB Emission Bandwidth (MHz)
BDR (GFSK)	Low	2402	0.957
	Middle	2441	0.952
	High	2480	0.957
EDR ($\pi/4$-DQPSK)	Low	2402	1.313
	Middle	2441	1.303
	High	2480	1.327
EDR (8DPSK)	Low	2402	1.317
	Middle	2441	1.308
	High	2480	1.313

BDR (GFSK): Low Channel




Date: 11.JUL.2020 19:51:00

BDR (GFSK): Middle Channel




Date: 11.JUL.2020 19:55:30

BDR (GFSK): High Channel




Date: 11.JUL.2020 20:00:17

EDR ($\pi/4$ -DQPSK): Low Channel




Date: 11.JUL.2020 20:12:43


EDR($\pi/4$ -DQPSK): Middle Channel



Date: 11.JUL.2020 20:09:12


EDR ($\pi/4$ -DQPSK): High Channel

Date: 11.JUL.2020 20:04:22

EDR (8DPSK): Low Channel


Date: 11.JUL.2020 20:15:58

EDR (8DPSK): Middle Channel



Date: 11.JUL.2020 20:18:23

EDR (8DPSK): High Channel



Date: 11.JUL.2020 20:21:03

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST**Applicable Standard**

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a. Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c. VBW $\geq$ RBW.
- d. Sweep: Auto.
- e. Detector function: Peak.
- f. Trace: Max hold.
- g. Allow the trace to stabilize.

It might prove necessary to break the span up into subranges to show clearly all of the hopping frequencies.

Test Data**Environmental Conditions**

Temperature:	25.6 °C
Relative Humidity:	56 %
ATM Pressure:	101.3 kPa


The testing was performed by Chris Wang on 2020-07-13.

EUT operation mode: Hopping

Test Result: Compliant.


Mode	Frequency Range (MHz)	Number of Hopping Channel (CH)	Limit (CH)
BDR (GFSK)	2400-2483.5	79	≥ 15
EDR ($\pi/4$ -DQPSK)	2400-2483.5	79	≥ 15
EDR (8DPSK)	2400-2483.5	79	≥ 15

BDR (GFSK): Number of Hopping Channels




Date: 13.JUL.2020 23:08:00

EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



Date: 13.JUL.2020 23:04:42

EDR (8DPSK): Number of Hopping Channels



Date: 13.JUL.2020 22:57:56

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)**Applicable Standard**

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- a Span: Zero span, centered on a hopping channel.
- b RBW shall be $\leq$ channel spacing and where possible RBW should be set $\geq 1 / T$, where T is the expected dwell time per channel.
- c Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d Detector function: Peak.
- e Trace: Max hold.

Test Data**Environmental Conditions**


Temperature:	24.6 °C~25.7 °C
Relative Humidity:	49 %~50 %
ATM Pressure:	101.1 kPa ~101.3 kPa

The testing was performed by Chris Wang from 2020-07-13 to 2020-07-14.

EUT operation mode: Hopping


Mode		Channel	Pulse Width (ms)	Dwell Time (s)	Limit (s)	Result
BDR (GFSK)	DH1	Low	0.410	0.131	0.4	Pass
		Middle	0.410	0.131	0.4	Pass
		High	0.410	0.131	0.4	Pass
		Note: DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	DH3	Low	1.678	0.268	0.4	Pass
		Middle	1.678	0.268	0.4	Pass
		High	1.678	0.268	0.4	Pass
		Note: DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	DH5	Low	2.936	0.313	0.4	Pass
		Middle	2.936	0.313	0.4	Pass
		High	2.936	0.313	0.4	Pass
		Note: DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR ($\pi/4$ -DQPSK)	2DH1	Low	0.417	0.133	0.4	Pass
		Middle	0.417	0.133	0.4	Pass
		High	0.417	0.133	0.4	Pass
		Note: 2DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	2DH3	Low	1.678	0.268	0.4	Pass
		Middle	1.678	0.268	0.4	Pass
		High	1.678	0.268	0.4	Pass
		Note: 2DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	2DH5	Low	2.949	0.315	0.4	Pass
		Middle	2.949	0.315	0.4	Pass
		High	2.949	0.315	0.4	Pass
		Note: 2DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				
EDR (8DPSK)	3DH1	Low	0.415	0.133	0.4	Pass
		Middle	0.415	0.133	0.4	Pass
		High	0.415	0.133	0.4	Pass
		Note:3 DH1:Dwell time = Pulse time*(1600/2/79)*31.6S				
	3DH3	Low	1.678	0.268	0.4	Pass
		Middle	1.678	0.268	0.4	Pass
		High	1.678	0.268	0.4	Pass
		Note: 3DH3:Dwell time = Pulse time*(1600/4/79)*31.6S				
	3DH5	Low	2.942	0.314	0.4	Pass
		Middle	2.942	0.314	0.4	Pass
		High	2.942	0.314	0.4	Pass
		Note: 3DH5:Dwell time = Pulse time*(1600/6/79)*31.6S				

BDR (GFSK): Pulse time, Low Channel, DH1




Date: 13.JUL.2020 23:15:04

BDR (GFSK): Pulse time, Middle Channel, DH1




Date: 13.JUL.2020 23:17:36

BDR (GFSK): Pulse time, High Channel, DH1




Date: 13.JUL.2020 23:18:35

BDR (GFSK): Pulse time, Low Channel, DH3




Date: 13.JUL.2020 23:32:01

BDR (GFSK): Pulse time, Middle Channel, DH3




Date: 13.JUL.2020 23:33:09

BDR (GFSK): Pulse time, High Channel, DH3




Date: 13.JUL.2020 23:33:54

BDR (GFSK): Pulse time, Low Channel, DH5




Date: 13.JUL.2020 23:59:27


BDR (GFSK): Pulse time, Middle Channel, DH5



Date: 14.JUL.2020 00:01:06


BDR (GFSK): Pulse time, High Channel, DH5

Date: 14.JUL.2020 00:03:26

EDR ($\pi/4$ -DQPSK): Pulse time, Low Channel, 2DH1


Date: 13.JUL.2020 23:20:34

EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH1




Date: 13.JUL.2020 23:23:51

EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH1




Date: 13.JUL.2020 23:24:34

EDR ($\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH3




Date: 13.JUL.2020 23:35:35

EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH3




Date: 13.JUL.2020 23:36:16

EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH3




Date: 13.JUL.2020 23:39:49

EDR ($\pi/4$ -DQPSK):Pulse time, Low Channel, 2DH5




Date: 14.JUL.2020 00:08:03

EDR ($\pi/4$ -DQPSK):Pulse time, Middle Channel, 2DH5




Date: 14.JUL.2020 00:06:50

EDR ($\pi/4$ -DQPSK):Pulse time, High Channel, 2DH5




Date: 14.JUL.2020 00:04:58

EDR (8DPSK): Pulse time, Low Channel, 3DH1




Date: 13.JUL.2020 23:26:15

EDR (8DPSK): Pulse time, Middle Channel, 3DH1




Date: 13.JUL.2020 23:27:52

EDR (8DPSK): Pulse time, High Channel, 3DH1




Date: 13.JUL.2020 23:28:42


EDR (8DPSK): Pulse time, Low Channel, 3DH3



Date: 13.JUL.2020 23:40:54


EDR (8DPSK): Pulse time, Middle Channel, 3DH3

Date: 13.JUL.2020 23:41:38

EDR (8DPSK): Pulse time, High Channel, 3DH3


Date: 13.JUL.2020 23:42:45

EDR (8DPSK): Pulse time, Low Channel, 3DH5




Date: 14.JUL.2020 00:09:55

EDR (8DPSK): Pulse time, Middle Channel, 3DH5



Date: 14.JUL.2020 00:10:47

EDR (8DPSK): Pulse time, High Channel, 3DH5



Date: 14.JUL.2020 00:11:54

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT**Applicable Standard**

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

- a. Use the following spectrum analyzer settings:
 - 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
 - 2) RBW > 20 dB bandwidth of the emission being measured.
 - 3) VBW $\geq$ RBW.
 - 4) Sweep: Auto.
 - 5) Detector function: Peak.
 - 6) Trace: Max hold.
- b. Allow trace to stabilize.
- c. Use the marker-to-peak function to set the marker to the peak of the emission.
- d. The indicated level is the peak output power, after any corrections for external attenuators and cables.
- e. A plot of the test results and setup description shall be included in the test report.

Test Data**Environmental Conditions**

Temperature:	25.7 °C
Relative Humidity:	55 %
ATM Pressure:	101.3 kPa


The testing was performed by Chris Wang on 2020-07-11.

EUT operation mode: Transmitting

Test Result: Compliant.


Mode	Frequency (MHz)	Output Power		Limit (mW)
		(dBm)	(mW)	
BDR (GFSK)	2402	10.71	11.78	125
	2441	10.35	10.84	125
	2480	10.60	11.48	125
EDR ($\pi/4$-DQPSK)	2402	10.10	10.23	125
	2441	9.64	9.20	125
	2480	10.16	10.38	125
EDR (8DPSK)	2402	10.33	10.79	125
	2441	9.96	9.91	125
	2480	10.27	10.64	125

BDR (GFSK): 2402MHz




Date: 11.JUL.2020 20:36:23

BDR (GFSK): 2441MHz




Date: 11.JUL.2020 20:30:35

BDR (GFSK): 2480MHz




Date: 11.JUL.2020 20:29:30

EDR($\pi/4$ -DQPSK): 2402MHz




Date: 11.JUL.2020 20:35:04

EDR($\pi/4$ -DQPSK): 2441MHz




Date: 11.JUL.2020 20:32:01

EDR($\pi/4$ -DQPSK): 2480MHz




Date: 11.JUL.2020 20:27:45

EDR(8DPSK): 2402MHz




Date: 11.JUL.2020 20:34:23

EDR(8DPSK): 2441MHz



Date: 11.JUL.2020 20:33:07

EDR(8DPSK): 2480MHz



Date: 11.JUL.2020 20:25:39

FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	24.3-25.7 °C
Relative Humidity:	50-55 %
ATM Pressure:	100.9-101.3 kPa


The testing was performed by Chris Wang from 2020-07-12 to 2020-07-14.

EUT operation mode: Transmitting & Hopping


Test Result: Compliant.

Band Edge

BDR (GFSK): Left Side - Transmitting




Date: 12.JUL.2020 21:26:16




Date: 12.JUL.2020 23:58:20

BDR (GFSK): Right Side - Transmitting




Date: 12.JUL.2020 21:42:14




Date: 13.JUL.2020 00:10:07

EDR ($\pi/4$ -DQPSK): Left Side - Transmitting




Date: 12.JUL.2020 21:28:11




Date: 12.JUL.2020 23:55:43

EDR ($\pi/4$ -DQPSK): Right Side - Transmitting




Date: 12.JUL.2020 21:44:30




Date: 13.JUL.2020 00:05:14

EDR (8DPSK): Left Side - Transmitting




Date: 12.JUL.2020 21:32:15




Date: 12.JUL.2020 23:52:47

EDR (8DPSK): Right Side - Transmitting




Date: 12.JUL.2020 21:47:00




Date: 13.JUL.2020 00:07:37

BDR (GFSK): Left Side - Hopping




Date: 14.JUL.2020 00:24:22

BDR (GFSK): Right Side- Hopping




Date: 14.JUL.2020 00:54:46

EDR ($\pi/4$ -DQPSK): Left Side- Hopping




Date: 14.JUL.2020 00:30:24

EDR ($\pi/4$ -DQPSK): Right Side- Hopping




Date: 14.JUL.2020 00:51:54

EDR (8DPSK): Left Side- Hopping



Date: 14.JUL.2020 00:37:20

EDR (8DPSK): Right Side- Hopping



Date: 14.JUL.2020 00:47:54

Declarations

1: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

2: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

3: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

4: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

5: This report cannot be reproduced except in full, without prior written approval of the Company.

6: This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

******* END OF REPORT *******