

5473A Clouds Rest Road: Mariposa, CA 95338: Phone 209-966-5420: Fax 209-742-6133

Maximum Permissible Exposure Calculations

Date of Report: Aug 28, 2002

Calculations prepared for: Calculations prepared by:

IP Mobile Net Eddie Wong

11909 East Telegraph Road 110 N. Olinda Place Santa Fe Springs, CA 90670 Brea, CA 9283

Model Number: IP4HPV-GPS FCC Identification: MI7-IPMNIP4H

Fundamental Operating Frequency: 509-512MHz

Maximum Rated Output Power: 40.00 Watts Measured Output Power: 34.00 Watts

In accordance with 47CFR2.1093(d)(2), source based time averaging is allowed for this type of device:

Source Based Time Averaging = 20LOG(ON time/TOTAL time)

= 20LOG(389mS/(389+310 = 699mS)

= -5.09 dB

Therefore the Power Output = 46.02 dBm (40.00 W) - 5.09 dB = 40.93 dBm (12.39 W)

MPE Limit in accordance with 1.1310(b): Limits for general population/uncontrolled exposure

MPE Limit for 509 MHz = $509/1500 = 0.3393 \text{ mW/cm}^2 (3.339\text{W/M}^2)$ MPE Limit for $512 \text{ MHz} = 512/1500 = 0.3413 \text{ mW/cm}^2$

Power Output	Power Density	Minimum	
(Watts)	Limit	Distance	
	(mW/cm^2)	(Meters)	
12.39	0.3393	0.295	

Power Density $(W/M^2) = (30 * P_t * G) / (d^2 * Zo)$

 P_t = Power Delivered to the Antenna G = Antenna G = Antenna G = Antenna G = G

d = Distance in meters Zo = Impedance of Free Space

The typical vehicle used by police was measured, and a separation distance of 1 meter was found to be an appropriate distance. Under normal operating conditions, the antenna will maintain a separation of 1 meter from all persons. As can be seen from the MPE results, this device passes the limits specified in 1.1310 at a distance of 0.295 Meters (11.61 Inches).