

RF Exposure Report

Report No.: SA190319E02C

FCC ID: NKR-LVSK-IDU

Test Model: LVSKIDU

Received Date: May 19, 2019

Test Date: May 19, 2019

Issued Date: July 01, 2019

Applicant: Wistron NeWeb Corp.

Address: 20 Park Avenue II, Hsinchu Science Park, Hsinchu 308, Taiwan, R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

**FCC Registration /
Designation Number:** 723255 / TW2022

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	5
2.5 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA190319E02C	Original release.	July 01, 2019

1 Certificate of Conformity

Product: LVSKIDU

Brand: WNC

Test Model: LVSKIDU

Sample Status: ENGINEERING SAMPLE

Applicant: Wistron NeWeb Corp.

Test Date: May 19, 2019


Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1-1992

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.


Prepared by :


Phoenix Huang / Specialist

Date:

July 01, 2019

Approved by :


May Chen / Manager

Date:

July 01, 2019

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20 cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Frequency (MHz)	5500		5600		5700		5745		5785		5825		Antenna Type	Antenna Connector
	Directional Antenna Gain (dBi)													
Vertical-Pol	XZ	4.27	XZ	4.27	XZ	4.47	XZ	4.69	XZ	4.84	XZ	4.79	PCB	i-pex(MHF)
	YZ	3.35	YZ	2.70	YZ	2.73	YZ	2.93	YZ	2.60	YZ	2.49		
	XY	3.24	XY	3.58	XY	4.02	XY	4.12	XY	4.08	XY	4.20		
Horizontal-pol	XZ	4.53	XZ	4.44	XZ	4.34	XZ	4.41	XZ	4.67	XZ	4.36	PCB	i-pex(MHF)
	YZ	2.19	YZ	1.56	YZ	1.39	YZ	1.24	YZ	1.43	YZ	1.51		
	XY	4.47	XY	4.82	XY	4.89	XY	4.94	XY	5.09	XY	4.73		
Note: More detailed information, please refer to operating description.														

Note: More detailed information, please refer to operating description.

2.5 Calculation Result of Maximum Conducted Power

For 5GHz (U-NII-2C band) the Maximum power was refer to the FCC test report (Report No.: RF190319E02B-1)

For 5GHz (U-NII-3 band) data was copied from the original test report (Report No.: SA190319E02)

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
WLAN (U-NII-2C)	5610	248.291	4.89	20	0.15230	1
WLAN (U-NII-3)	5795	992.471	5.09	20	0.63745	1

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. 5GHz (U-NII-2C): The directional gain = 4.89dBi
5GHz (U-NII-3): The directional gain = 5.09dBi
3. The Max. Power = Max. tune up power including tolerance declared by client.

--- END ---