APPLICANT: RECOTON CORPORATION

FCC ID: CLVAW791

TEST REPORT CONTAINING:

PAGE	1TEST EQUIPMENT LIST & TEST PROCEDURE
PAGE	2TEST PROCEDURE CONTD.
PAGE	3-6RADIATED SPURIOUS EMISSIONS TEST DATA - DIGITAL
PAGE	7RADIATION INERFERENCE DATA -FUND. & HARMONICS
PAGE	8OCCUPIED BANDWIDTH
PAGE	9-10OCCUPIED BANDWIDTH PLOTS
PAGE	11POWERLINE CONDUCTED
PAGE	12-13POWERLINE CONDUCTED PLOTS

EXHIBIT ATTACHMENTS:

EXHIBIT	1FCC ID LABEL SAMPLE
EXHIBIT	2SKETCH OF FCC ID LABEL LOCATION
EXHIBIT	3 EXTERNAL PHOTO - FRONT VIEW
EXHIBIT	4EXTERNAL PHOTO - SIDE VIEW
EXHIBIT	5EXTERNAL PHOTO - REAR VIEW
EXHIBIT	6A-6B & COPPER VIEW - 1
EXHIBIT	7A-7B & COPPER VIEW - 2
EXHIBIT	8BLOCK DIAGRAM
EXHIBIT	9A-9BSCHEMATIC
EXHIBIT	10A-10FUSERS MANUAL
EXHIBIT	11TEST SET UP PHOTO - RADIATED
EXHIBIT	12TEST SET UP PHOTO - CONDUCTED
EXHIBIT	13CIRCUIT DESCRIPTION
EXHIBIT	14CONFIDENTIALITY REQUEST LETTER

APPLICANT: RECOTON CORPORATION FCC ID: CLVAW791 REPORT #: T:\R\REC\1080A\1080ATestReport.doc TABLE OF CONTENTS LIST

TEST EQUIPMENT LIST

<pre>1X_Spectrum Analyzer: HP 8566B-Opt 462, S/N 3138A07786, w/ preselector HP 85685A, S/N 3221A01400, Quasi-Peak Adapter HP 85650A, S/N 3303A01690 & Preamplifier HP 8449B-OPT H02, S/N 3008A00372 Cal. 8/31/01 Due 8/31/02</pre>
2X_Biconnical Antenna: Eaton Model 94455-1, S/N 1057, Cal. 10/1/01 Due 10/1/02
3. Biconnical Antenna: Electro-Metrics Model BIA-25, S/N 1171 Cal. 4/26/01 Due 4/26/03
4X_Log-Periodic Antenna: Electro-Metrics Model EM-6950, S/N 632 Char. 3/15/00 Due 3/15/01
5 Log-Periodic Antenna: Electro-Metrics Model LPA-30, S/N 409 Char. 3/15/00 Due 3/15/01
6X_Double-Ridged Horn Antenna: Electro-Metrics Model RGA-180, 1-18 GHz, S/N 2319 Cal. 4/27/99 Due 4/27/00
7 18-26.3GHz Systron Donner Standard Gain Horn #DBE-520-20 No Cal Reguired
8 Horn 40-60GHz: ATM Part #19-443-6R No Cal Required
9X_Line Impedance Stabilization Network: Electro-Metrics Model EM-7820, w/NEMA Adapter S/N 2682 Cal. 3/16/01 Due 3/16/02
10 Temperature Chamber: Tenney Engineering Model TTRC, S/N 11717-7 Char. 1/27/01 Due 1/27/02
11 Frequency Counter: HP Model 5385A, S/N 3242A07460 Char. 11/20/00 Due 11/20/01
12 Peak Power Meter: HP Model 8900C, S/N 2131A00545 Char. 1/26/01 Due 1/26/02
13. X Open Area Test Site #1-3meters Cal. 12/22/99
14Signal Generator: HP 8640B, S/N 2308A21464 Cal. 11/15/01 Due 11/15/02
15 Passive Loop Antenna: EMCO Model 6512, 9KHz to 30MHz, S/N 9706-1211 Char. 6/10/00 Due 6/10/01
<pre>16 Dipole Antenna Kit: Electro-Metrics Model TDA-30/1-4, S/N 153 Char. 11/24/00 Due 11/24/01</pre>
17 AC Voltmeter: HP Model 400FL, S/N 2213A14499 Cal. 10/9/01 Due 10/09/02
18X_Digital Multimeter: Fluke Model 77, S/N 43850817 Cal. 11/16/00 Due 11/16/01
19 Oscilloscope: Tektronix Model 2230, S/N 300572 Char. 2/1/01 Due 2/1/02

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC. The UUT was transmitting a test signal during the testing.

APPLICANT: RECOTON CORPORATION FCC ID: CLVAW791 REPORT #: T:\R\REC\1080A\1080ATestReport.doc Page 1 of 13

TEST PROCEDURES CONTINUED

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz up to 1.0GHz and 1.0MHz with a video BW of 3.0MHz above 1.0GHz. The ambient temperature of the UUT was 81 F with a humidity of 81%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example: Freq (MHz) METER READING + ACF = FS 33 20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STAN-DARD C63.4-1992 using a 50uH LISN. Both lines were observed. The bandwidth of the spectrum analyzer was 10kHz with an appropriate sweep speed. The ambient temperature of the UUT was 74.3°F with a humidity of 69%.

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The UUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The UUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSIC63.4-1992 with the EUT 40 cm from the vertical ground wall.

APPLICANT: RECOTON CORPORATION FCC ID: CLVAW791 REPORT #: T:\R\REC\1080A\1080ATestReport.doc Page 2 of 13

APPLICANT:	
------------	--

RECOTON CORPORATION

FCC ID: CLVAW791

NAME OF TEST: RADIATED SPURIOUS EMISSIONS

RULES PART NO.: 15.109(a) - Class B Computing Device REQUIREMENTS: 30-88 MHz 40.0 dBuV/m measured at 3 meters 88-216 MHz 43.5 dbuV/m 216-960 MHz 46.0 dbuV/m ABOVE 960 MHz 54.0 dbuV/m

TEST DATA FOR CLASS B DIGITAL DEVICE :

	Meter	Ant.	Coax		Field	
Emission	Reading	Polarity	Loss	Correction	Strength	Margin
Frequency	dBuv		dB	Factor	dBuv/m	dB
MHz				dB		
49.80	22.3	v	0.80	10.99	34.09	5.91
86.00	14.1	v	1.08	12.54	27.72	12.28
108.60	15.6	h	1.23	9.32	26.15	17.35
117.70	14.9	h	1.27	10.44	26.61	16.89
149.40	23.3	h	1.40	16.77	41.47	2.03
176.60	15.4	h	1.61	16.41	33.42	10.08
185.60	18.3	h	1.68	14.94	34.92	8.58
190.20	14.1	h	1.72	14.20	30.02	13.48
194.60	12.2	h	1.76	13.48	27.44	16.06
199.20	27.7	h	1.79	12.73	42.22	1.28
203.70	16.0	h	1.81	11.73	29.54	13.96
208.30	21.7	h	1.83	11.63	35.16	8.34
212.80	21.5	h	1.85	11.52	34.87	8.63
217.30	21.1	h	1.87	11.38	34.35	11.65
221.80	20.3	h	1.89	11.34	33.53	12.47
226.30	29.6	h	1.91	11.43	42.94	3.06
230.90	23.7	h	1.92	11.51	37.13	8.87
235.40	26.1	h	1.94	11.55	39.59	6.41
240.00	20.6	h	1.96	11.60	34.16	11.84
249.00	29.5	h	2.00	12.05	43.55	2.45

TEST PROCEDURE: ANSI STANDARD C63.4-1992 The spectrum was scanned from 30 to 1000 MHz. The unit was measured at Timco Engineering Inc. 849 N.W. State Road 45, Newberry, FL 32669.

TEST RESULTS: The unit DOES appear to meet the FCC requirements.

PERFORMED BY: JOE SCOGLIO

DATE: OCTOBER 24, 2001

APPLICANT: RECOTON CORPORATION FCC ID: CLVAW791 REPORT #: T:\R\REC\1080A\1080ATestReport.doc Page 3 of 13

APPLICANT:	RECOTON	CORPORATION
	112001011	00111 01111 1011

FCC ID: CLVAW791

NAME OF TEST: RADIATED SPURIOUS EMISSIONS

RULES PART NO.: 15.109(a) - Class B Computing Device 30-88 MHz 40.0 dBuV/m measured at 3 meters 88-216 MHz 43.5 dbuV/m 216-960 MHz 46.0 dbuV/m REQUIREMENTS: ABOVE 960 MHz 54.0 dbuV/m

TEST DATA FOR CLASS B DIGITAL DEVICE :

Emission	Meter	Ant.	Coax		Field	
Frequency	Reading	Polarity	Loss	Correction	Strength	Margin
MHz	dBuv		dB	Factor	dBuv/m	dB
				dB		
258.00	21.1	н	2.03	12.66	35.79	10.21
262.60	19.5	н	2.05	13.01	34.56	11.44
267.10	17.4	н	2.07	13.37	32.84	13.16
271.60	18.5	н	2.09	13.78	34.37	11.63
276.20	23.7	н	2.10	14.28	40.08	5.92
280.70	19.0	н	2.12	14.76	35.88	10.12
285.20	21.0	н	2.14	15.12	38.26	7.74
289.70	17.4	н	2.16	15.48	35.04	10.96
298.80	24.1	н	2.20	13.74	40.04	5.96
303.30	11.6	н	2.22	13.76	27.58	18.42
307.90	19.4	н	2.25	14.13	35.78	10.22
312.30	18.9	н	2.27	14.30	35.47	10.53
316.90	18.2	н	2.30	14.30	34.80	11.20
321.40	20.8	н	2.33	14.36	37.49	8.51
325.90	23.0	н	2.36	14.54	39.90	6.10
330.50	17.5	н	2.38	14.70	34.58	11.42
335.00	19.9	н	2.41	14.65	36.96	9.04

TEST PROCEDURE: ANSI STANDARD C63.4-1992 The spectrum was scanned from 30 to 1000 MHz. The unit was measured at Timco Engineering Inc. 849 N.W. State Road 45, Newberry, FL 32669.

TEST RESULTS: The unit DOES appear to meet the FCC requirements.

PERFORMED BY: JOE SCOGLIO DATE: OCTOBER 24, 2001

APPLICANT: RECOTON CORPORATION FCC ID: CLVAW791 REPORT #: T:\R\REC\1080A\1080ATestReport.doc Page 4 of 13

FCC ID:CLVAW791NAME OF TEST:RADIATED SPURIOUS EMISSIONSRULES PART NO.:15.109(a) - Class B Digital DeviceREQUIREMENTS:30-88 MHz 40.0 dBuV/m measured at 3 meters
88-216 MHz 43.5 dbuV/m
216-960 MHz 46.0 dbuV/m
ABOVE 960 MHz 54.0 dbuV/m

APPLICANT: RECOTON CORPORATION

TEST DATA FOR CLASS B DIGITAL DEVICE :

	Meter	Ant.	Coax		Field	
Emission	Reading	Polarity	Loss	Correction	Strength	Margin
Frequency	dBuv		dB	Factor	dBuv/m	dB
MHz				dB		
348.60	13.3	н	2.49	14.43	30.22	15.78
357.60	12.9	н	2.55	14.78	30.23	15.77
362.20	16.8	н	2.57	14.92	34.29	11.71
366.70	14.4	н	2.60	14.97	31.97	14.03
371.20	18.5	н	2.63	15.02	36.15	9.85
375.80	18.8	н	2.65	15.12	36.57	9.43
380.30	15.5	н	2.68	15.21	33.39	12.61
384.80	16.1	н	2.71	15.39	34.20	11.80
384.80	11.7	н	2.71	15.39	29.80	16.20
389.40	11.7	н	2.74	15.58	30.02	15.98
407.50	14.4	н	2.82	16.15	33.37	12.63
412.00	16.7	н	2.84	16.42	35.96	10.04
416.50	13.3	н	2.85	16.69	32.84	13.16
421.00	17.7	н	2.86	16.94	37.50	8.50
425.60	14.4	н	2.88	17.12	34.40	11.60
430.10	12.0	н	2.89	17.30	32.19	13.81
434.60	15.7	н	2.90	17.12	35.72	10.28
448.20	17.5	н	2.94	16.99	37.43	8.57

TEST PROCEDURE: ANSI STANDARD C63.4-1992 The spectrum was scanned from 30 to 1000 MHz. The unit was measured at Timco Engineering Inc. 849 N.W. State Road 45, Newberry, FL 32669.

TEST RESULTS: The unit DOES appear to meet the FCC requirements.

PERFORMED BY: JOE SCOGLIO

DATE: OCTOBER 24, 2001

APPLICANT: RECOTON CORPORATION FCC ID: CLVAW791 REPORT #: T:\R\REC\1080A\1080ATestReport.doc Page 5 of 13

RECOTON CORPORATION

FCC ID: CLVAW791

NAME OF TEST: RADIATED SPURIOUS EMISSIONS

RULES PART NO.: 15.109(a) - Class B Digital Device
 30-88
 MHz
 40.0
 dBuV/m
 measured at 3 meters

 88-216
 MHz
 43.5
 dbuV/m

 216-960
 MHz
 46.0
 dbuV/m
 REQUIREMENTS: ABOVE 960 MHz 54.0 dbuV/m

TEST DATA FOR CLASS B DIGITAL DEVICE :

	Meter	Ant.	Coax		Field	
Emission	Reading	Polarity	Loss	Correction	Strength	Margin
Frequency	dBuv		dB	Factor	dBuv/m	dB
MHz				dB		
470.80	15.5	н	3.01	17.52	36.03	9.97
475.40	14.8	н	3.03	17.66	35.49	10.51
484.40	12.5	н	3.05	17.71	33.26	12.74
520.60	14.5	н	3.16	18.77	36.43	9.57
525.20	14.5	н	3.18	18.54	36.22	9.78
570.40	14.2	н	3.31	19.20	36.71	9.29
597.60	17.7	н	3.39	18.93	40.02	5.98
611.20	15.2	н	3.43	19.30	37.93	8.07
615.70	13.9	н	3.45	19.30	36.65	9.35
620.30	17.3	н	3.46	19.30	40.06	5.94
624.70	17.2	н	3.47	19.35	40.02	5.98
633.80	11.4	н	3.50	19.55	34.45	11.55
638.40	15.7	н	3.52	19.74	38.96	7.04
642.80	13.0	н	3.53	19.68	36.21	9.79
656.40	13.3	н	3.57	19.97	36.84	9.16
674.60	15.3	н	3.62	20.78	39.70	6.30
719.90	13.6	н	3.76	21.40	38.76	7.24
724.30	14.5	н	3.77	21.49	39.76	6.24
796.80	15.4	н	3.99	21.43	40.82	5.18

TEST PROCEDURE: ANSI STANDARD C63.4-1992 The spectrum was scanned from 30 to 1000 MHz. The unit was measured at Timco Engineering Inc. 849 N.W. State Road 45, Newberry, FL 32669.

TEST RESULTS: The unit DOES appear to meet the FCC requirements.

PERFORMED BY: JOE SCOGLIO DATE: OCTOBER 24, 2001

APPLICANT: RECOTON CORPORATION FCC ID: CLVAW791 REPORT #: T:\R\REC\1080A\1080ATestReport.doc Page 6 of 13

APPLICANT:	RECOTON CORPORATION					
FCC ID:	CLVAW791					
NAME OF TEST:	RADIATION INTERFEREN	JCE				
RULES PART NUMBER:	15.249, 15.209					
REQUIREMENTS: FIELD STRENGTH	FIELD STRENGTH	S15.209				
of Fundamental: 902-928 MHZ 2.4-2.4835 GHz	of Harmonics	30 - 88 MHz 40 dBuV/m @3M 88 -216 MHz 43.5 216 -960 MHz 46				
94 dBuV/m @3m	54 dBuV/m @3m	ABOVE 960 MHz 54dBuV/m				

EMISSIONS RADIATED OUTSIDE OF THE SPECIFIED FREQUENCY BANDS, EXCEPT FOR HARMONICS, SHALL BE ATTENUATED BY AT LEAST 50 dB BELOW THE LEVEL OF THE FUNDAMENTAL OR TO THE GENERAL RADIATED EMISSION LIMITS IN 15.209, WHICHEVER IS THE LESSER ATTENUATION.

TEST RESULTS: This unit DOES meet the FCC requirements.

TEST DATA FOR RF FUNDAMENTAL AND HARMONICS:

Emission	Meter	Ant.	Coax		Field	
Frequency	Reading	Polarity	Loss	Correction	Strength	Margin
MHz	dBuv		dB	Factor	dBuv/m	dB
				dB		
913.00	57.6	v	3.91	23.40	84.91	9.09
911.50	57.4	v	3.94	23.40	84.74	9.26

TEST PROCEDURE: ANSI STANDARD C63.4-1992 using a Hewlett Packard Model 8566B spectrum analyzer, a Hewlett Packard Model 85685A Preselector, a Hewlett Packard Model 85650A Quasi-Peak adapter, and an appropriate antenna. The bandwidth of spectrum analyzer was 100 kHz with an appropriate sweep speed. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The spectrum was searched to at least the tenth(10) harmonic of the fundamental.

PERFORMED BY: JOE SCOGLIO

DATE: OCTOBER 24, 2001

APPLICANT: RECOTON CORPORATION FCC ID: CLVAW791 REPORT #: T:\R\REC\1080A\1080ATestReport.doc Page 7 of 13 APPLICANT: RECOTON CORPORATION

FCC ID: CLVAW791

NAME OF TEST: Occupied Bandwidth

RULES PART NO.: 15.249

REQUIREMENTS: The field strength of any emissions appearing outside the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 50 dB below the level of the carrier or to the general limits of 15.249.

THE PLOTS ON THE FOLLOWING PAGES REPRESENTS THE EMISSIONS TAKEN FOR THIS DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the attached plot was printed. The vertical scale is set to -10 dBm per division. The horizontal scale is set to 5 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: JOSEPH SCOGLIO DATE: OCTOBER 24, 2001

APPLICANT: RECOTON CORPORATION FCC ID: CLVAW791 REPORT #: T:\R\REC\1080A\1080ATestReport.doc Page 8 of 13



APPLICANT: RECOTON CORPORATION FCC ID: CLVAW791 REPORT #: T:\R\REC\1080A\1080ATestReport.doc Page 9 of 13



APPLICANT: RECOTON CORPORATION FCC ID: CLVAW791 REPORT #: T:\R\REC\1080A\1080ATestReport.doc Page 10 of 13 APPLICANT: RECOTON CORPORATION

FCC ID: CLVAW791

NAME OF TEST: POWER LINE CONDUCTED INTERFERENCE

RULES PART NUMBER: 15.107

MINIMUM	REQUIREMENTS:	FREQUENCY	LEVEL
		MHz	_uV_
		0.450-30	250

TEST PROCEDURE: ANSI STANDARD C63.4-1992

THE HIGHEST EMISSION READ FOR LINE 1 WAS 22.881 uV @ 12.33 MHz. THE HIGHEST EMISSION READ FOR LINE 2 WAS 18.385 uV @ 12.33 MHz.

THE PLOTS ON THE NEXT TWO PAGES REPRESENT THE EMISSIONS READ FOR POWERLINE CONDUCTED FOR THIS DEVICE.

TEST RESULTS: Both lines were observed. The measurements indicate that the unit DOES appear to meet the FCC requirements for this class of equipment.

PERFORMED BY: JOSEPH SCOGLIO DATE: OCTOBER 24, 2001

APPLICANT: RECOTON CORPORATION FCC ID: CLVAW791 REPORT #: T:\R\REC\1080A\1080ATestReport.doc Page 11 of 13



APPLICANT: RECOTON CORPORATION FCC ID: CLVAW791 REPORT #: T:\R\REC\1080A\1080ATestReport.doc Page 12 of 13



APPLICANT: RECOTON CORPORATION FCC ID: CLVAW791 REPORT #: T:\R\REC\1080A\1080ATestReport.doc Page 13 of 13