





TEST REPORT

Applicant Name: Address:

Report Number: FCC ID: Bytech NY Inc. 2585 West 13th Street, Brooklyn NY 11223, New York, United States 2401V85169E-RF-00 2AHN6-KBWS108

Test Standard (s)

FCC PART 15.249

Sample Description

Product Type: Model No.: Multiple Model(s) No.: Trade Mark: Date Received: Issue Date: Wireless Animal Keyboard-ASST BY-KB-WS-108-AC N/A N/A 2024/07/25 2024/08/29

Test Result:

Pass▲

▲ In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Gala Liu

Gala Liu RF Engineer

Approved By:

Michelle Zeng

Michelle Zeng RF Supervisor

Note: The information marked[#] is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government. This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "V".

Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

TR-EM-RF041

Page 1 of 35

Version 3.0

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	3
GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
MEASUREMENT UNCERTAINTY	
Test Facility	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	
Support Cable Descriptions	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
FCC§1.1307 (B) (1) & §2.1093- RF EXPOSURE	10
APPLICABLE STANDARD	10
Result	10
FCC§15.203 - ANTENNA REQUIREMENT	11
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	11
FCC§15.205, §15.209 & §15.249(D) - RADIATED EMISSIONS	12
APPLICABLE STANDARD	
EUT SETUP EMI Test Receiver & Spectrum Analyzer Setup	12
Test Procedure	14
FACTOR & OVER LIMIT/MARGIN CALCULATION	15
TEST DATA	15
FCC§15.215(C) - 20DB EMISSION BANDWIDTH	
APPLICABLE STANDARD	
TEST PROCEDURE	
EUT PHOTOGRAPHS	34
TEST SETUP PHOTOGRAPHS	35

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	2401V85169E-RF-00	Original Report	2024/08/29

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Wireless Animal Keyboard-ASST			
Tested Model	BY-KB-WS-108-AC			
Multiple Model(s)	N/A			
UPC number	805112127856, 805112127863, 805112127870, 805112127887			
SKU number	9148946			
Lot number	BY060324			
Frequency Range	2402-2480MHz			
Maximum E-field strength	68.27 dBuV/m@3m			
Modulation Technique	GFSK			
Antenna Specification [#]	2.34dBi (provided by the applicant)			
Voltage Range	DC 1.5 V from Battery			
Sample serial number	20WE-6 (Assigned by BACL, Shenzhen)			
Sample/EUT Status	Good condition			
Adapter Information	N/A			
Note: The model has 4 styles with different colors and appearances, the schematics are electrically identical, so				
Pink style was selected for testing, details please see $DoS^{\#}$				

Objective

This test report is in accordance with Part 2-Subpart J, and Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.249 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter			Uncertainty
Occupied Channel Bandwidth			$\pm 5\%$
RI	F Frequen	су	213.55 Hz(k=2, 95% level of confidence)
RF outpu	t power, c	onducted	0.72 dB(k=2, 95% level of confidence)
Unwanted	Emission,	conducted	1.75 dB(k=2, 95% level of confidence)
AC Power Lines Cond	ucted	9kHz-150kHz	3.94dB(k=2, 95% level of confidence)
Emissions		150kHz-30MHz	3.84dB(k=2, 95% level of confidence)
		9kHz - 30MHz	3.30dB(k=2, 95% level of confidence)
	30MHz~200MHz (Horizontal)		4.48dB(k=2, 95% level of confidence)
	30MHz~200MHz (Vertical)		4.55dB(k=2, 95% level of confidence)
Dedicted Emissions	200MHz~1000MHz (Horizontal)		4.85dB(k=2, 95% level of confidence)
Radiated Emissions	200MHz~1000MHz (Vertical)		5.05dB(k=2, 95% level of confidence)
		1GHz - 6GHz	5.35dB(k=2, 95% level of confidence)
		6GHz - 18GHz	5.44dB(k=2, 95% level of confidence)
	18GHz - 40GHz		5.16dB(k=2, 95% level of confidence)
Temperature		e	±1°C
Humidity			±1%
Sur	ply volta	ges	±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing by manufacturer.

Frequency Channel List:

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2402	11	2422	21	2442	31	2462
2	2404	12	2424	22	2444	32	2464
3	2406	13	2426	23	2446	33	2466
4	2408	14	2428	24	2448	34	2468
5	2410	15	2430	25	2450	35	2470
6	2412	16	2432	26	2452	36	2472
7	2414	17	2434	27	2454	37	2474
8	2416	18	2436	28	2456	38	2476
9	2418	19	2438	29	2458	39	2478
10	2420	20	2440	30	2460	40	2480

Note: Test on Channel 1, 20 and 40.

EUT Exercise Software

"FCC Test Tool V 2.4.0[#]" exercise software was used and the power level is $5^{#}$. The software and power level was provided by the manufacturer.

Equipment Modifications

No modifications were made to the unit tested.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

Support Cable Descriptions

Cable Description	Length (m)	From/Port	То
/	/	/	/

Report No.: 2401V85169E-RF-00

Block Diagram of Test Setup

Spurious emissions:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307 (b) (1) &§2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207(a)	Conduction Emissions	Not Applicable
15.205, §15.209, §15.249(d)	Radiated Emissions& Outside of Band Emission	Compliant
§15.215 (c)	20 dB Bandwidth	Compliant

Not Applicable: The device is only powered by battery.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
		Radiated Emissi	ions Test		
Rohde & Schwarz	EMI Test Receiver	ESR3	102455	2024/01/16	2025/01/15
Sonoma instrument	Pre-amplifier	310 N	186238	2024/05/21	2025/05/20
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2023/07/20	2026/07/19
Unknown	Cable	Chamber A Cable 1	N/A	2024/06/18	2025/06/17
Unknown	Cable	XH500C	J-10M-A	2024/06/18	2025/06/17
BACL	Active Loop Antenna	1313-1A	4031911	2024/05/14	2027/05/13
Audix	EMI Test software	E3	19821b(V9)	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40	101605	2024/03/27	2025/03/26
COM-POWER	Pre-amplifier	PA-122	181919	2024/06/18	2025/06/17
Schwarzbeck	Horn Antenna	BBHA9120D(12 01)	1143	2023/07/26	2026/07/25
Unknown	RF Cable	KMSE	735	2024/06/18	2025/06/17
Unknown	RF Cable	UFA147	219661	2024/06/18	2025/06/17
Unknown	RF Cable	XH750A-N	J-10M	2024/06/18	2025/06/17
JD	Multiplex Switch Test Control Set	DT7220FSU	DQ77926	2024/06/18	2025/06/17
A.H.System	Pre-amplifier	PAM-1840VH	190	2024/06/18	2025/06/17
Electro-Mechanics Co	Horn Antenna	3116	2026	2023/09/18	2026/09/17
UTIFLEX	RF Cable	NO. 13	232308-001	2024/06/18	2025/06/17
Audix	EMI Test software	E3	191218(V9)	NCR	NCR

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§1.1307 (b) (1) & §2.1093- RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \cdot [$\sqrt{f(GHz)}$] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. f(GHz) is the RF channel transmit frequency in GHz.

2. Power and distance are rounded to the nearest mW and mm before calculation.

3. The result is rounded to one decimal place for comparison.

4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Result

Mode	Frequency (MHz)	Maximum E- Field (dBuV/m@3 m)	Maximum EIRP(dBm)	Maximum EIRP (mW)	Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
GFSK	2402-2480	68.27	-26.93	0.002	5	0	3	Yes

Note: EIRP = E-Field -95.2 @3m

Result: Compliant.

FCC§15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

Antenna Connector Construction

The EUT has a PCB antenna which was permanently attached and the antenna gain[#] is 2.34dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Antenna Type	Antenna Gain [#] (dBi)	Impedance	Frequency Range	
PCB	2.34	50Ω	2402-2480MHz	

Result: Compliant.

FCC§15.205, §15.209 & §15.249(d) - RADIATED EMISSIONS

Applicable Standard

As per FCC§15.249 (a), except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
902–928 MHz	50	500
2400–2483.5 MHz	50	500
5725–5875 MHz	50	500
24.0–24.25 GHz	250	2500

As per FCC§15.249 (c), Field strength limits are specified at a distance of 3 meters.

As per FCC§15.249 (d), Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

EUT Setup

9 kHz-30MHz:



30MHz-1GHz:



Above 1GHz:



The radiated emission and out of band emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209/15.205 and FCC 15.249 limits.

EMI Test Receiver & Spectrum Analyzer Setup

Frequency Range	RBW	Video B/W	IF B/W	Measurement		
	/	/	200 Hz	QP		
9 кпz – 130 кпz	300 Hz	1 kHz	/	РК		
150 kHz 20 MHz	/	/	9 kHz	QP		
130 KHZ – 30 WHZ	10 kHz	30 kHz	/	РК		
30 MHz – 1000 MHz	/	/	120 kHz	QP		
	100 kHz	300 kHz	/	РК		
	Harmonics & Band Edge					
Above 1 GHz	1MHz	1MHz 3 MHz /		РК		
	Average Emission Level=Peak Emission Level+20*log(Duty cycle)					
	Other Emissions					
	1MHz	3 MHz	/	PK		
	1MHz	10 Hz	/	Average		

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

For Duty cycle measurement:

Use the duty cycle factor correction factor method per 15.35(c). Duty cycle=On time/100milliseconds, On time=N1*L1+N2*L2+...Nn-1*Ln-1+Nn*Ln, Where N1 is number of type 1 pulses, L1 is length of type 1 pulse, etc.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

The EUT is set 3 meter away from the testing antenna, which is varied from 1-4 meter, and the EUT is placed on a turntable, which is 0.8 meter above ground plane for below 1GHz or 1.5 meter for above 1GHz, the table shall be rotated for 360 degrees to find out the highest emission. The receiving antenna should be changed the polarization both of horizontal and vertical.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

All emissions under the average limit and under the noise floor have not recorded in the report.

Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

Factor = Antenna Factor + Cable Loss - Amplifier Gain

The "**Over Limit/Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

Over Limit = Level – Limit; Margin = Limit–Corrected Amplitude Level / Corrected Amplitude = Read Level + Factor

Test Data

Environmental Conditions

Temperature:	23~25.4 °C	
Relative Humidity:	49~53 %	
ATM Pressure:	99~101 kPa	

The testing was performed by Jack Liu on 2024-08-08 for below 1GHz and Sadow Tan from 2024-08-09 to 2024-08-15 for above 1GHz.

EUT operation mode: Transmitting

Note: Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded

9 kHz-30MHz: (Maximum output power mode, Middle channel)

The amplitude of spurious emissions attenuated more than 20 dB below the limit was not recorded.

30MHz-1GHz: (*Maximum output power mode, Middle channel*)

Horizontal



Site :	Chamber A
Condition :	3m Horizontal
Project Number:	2401V85169E-RF
Test Mode :	Transmitting
Tester :	Jack Liu

Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark	
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB		-
71.99	-17.87	35.28	17.41	40.00	-22.59	QP	
162.04	-12.80	37.68	24.88	43.50	-18.62	QP	
248.88	-13.09	46.07	32.98	46.00	-13.02	QP	
320.08	-10.79	44.42	33.63	46.00	-12.37	QP	
410.92	-8.22	35.13	26.91	46.00	-19.09	QP	
810.27	-2.05	29.18	27.13	46.00	-18.87	QP	
	Freq 71.99 162.04 248.88 320.08 410.92 810.27	Freq Factor MHz dB/m 71.99 -17.87 162.04 -12.80 248.88 -13.09 320.08 -10.79 410.92 -8.22 810.27 -2.05	Read Freq Factor Level MHz dB/m dBuV 71.99 -17.87 35.28 162.04 -12.80 37.68 248.88 -13.09 46.07 320.08 -10.79 44.42 410.92 -8.22 35.13 810.27 -2.05 29.18	Read Freq Factor Level Level MHz dB/m dBuV dBuV/m 71.99 -17.87 35.28 17.41 162.04 -12.80 37.68 24.88 248.88 -13.09 46.07 32.98 320.08 -10.79 44.42 33.63 410.92 -8.22 35.13 26.91 810.27 -2.05 29.18 27.13	Read Limit Freq Factor Level Level Line MHz dB/m dBuV dBuV/m dBuV/m 71.99 -17.87 35.28 17.41 40.00 162.04 -12.80 37.68 24.88 43.50 248.88 -13.09 46.07 32.98 46.00 320.08 -10.79 44.42 33.63 46.00 410.92 -8.22 35.13 26.91 46.00 810.27 -2.05 29.18 27.13 46.00	Read Limit Over Freq Factor Level Level Line Limit MHz dB/m dBuV dBuV/m dBuV/m dB 71.99 -17.87 35.28 17.41 40.00 -22.59 162.04 -12.80 37.68 24.88 43.50 -18.62 248.88 -13.09 46.07 32.98 46.00 -13.02 320.08 -10.79 44.42 33.63 46.00 -12.37 410.92 -8.22 35.13 26.91 46.00 -19.09 810.27 -2.05 29.18 27.13 46.00 -18.87	Read Limit Over Freq Factor Level Level Line Limit Remark MHz dB/m dBuV dBuV/m dBuV/m dB dB 71.99 -17.87 35.28 17.41 40.00 -22.59 QP 162.04 -12.80 37.68 24.88 43.50 -18.62 QP 248.88 -13.09 46.07 32.98 46.00 -13.02 QP 320.08 -10.79 44.42 33.63 46.00 -12.37 QP 410.92 -8.22 35.13 26.91 46.00 -19.09 QP 810.27 -2.05 29.18 27.13 46.00 -18.87 QP





:	Chamber A
:	3m Vertical
:	2401V85169E-RF
:	Transmitting
:	Jack Liu
	:::::::::::::::::::::::::::::::::::::::

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	47.97	-16.80	36.11	19.31	40.00	-20.69	QP
2	99.66	-15.96	41.04	25.08	43.50	-18.42	QP
3	111.01	-12.93	39.45	26.52	43.50	-16.98	QP
4	230.50	-13.07	40.15	27.08	46.00	-18.92	QP
5	424.10	-7.99	34.52	26.53	46.00	-19.47	QP
6	474.04	-6.69	39.94	33.25	46.00	-12.75	QP

Above 1GHz:

Engguerar	Rece	iver	Dolon	Factor	Absolute	I imit	Manain
(MHz)	Reading (dBµV)	PK/AV	(H/V)	(dB/m)	Level (dBµV/m)	(dBµV/m)	(dB)
			Low Channel				
2402.00	71.15	PK	Н	-3.13	68.02	114	-45.98
2402.00	70.84	PK	V	-3.13	67.71	114	-46.29
2317	54.3	PK	Н	-3.03	51.27	74	-22.73
2371.3	55.03	РК	V	-2.93	52.10	74	-21.90
4804.00	51.48	РК	Н	1.69	53.17	74	-20.83
4804.00	50.38	РК	V	1.69	52.07	74	-21.93
			Middle Channel				
2440.00	71.31	РК	Н	-3.13	68.18	114	-45.82
2440.00	71.40	РК	V	-3.13	68.27	114	-45.73
4880.00	51.78	РК	Н	1.69	53.47	74	-20.53
4880.00	50.89	РК	V	1.69	52.58	74	-21.42
			High Channel				
2480.00	68.96	РК	Н	-3.17	65.79	114	-48.21
2480.00	70.69	РК	V	-3.17	67.52	114	-46.48
2492.363	54.93	PK	Н	-3.18	51.75	74	-22.25
2488.953	55.18	PK	V	-3.18	52.00	74	-22.00
4960.00	51.52	PK	Н	2.77	54.29	74	-19.71
4960.00	50.42	РК	V	2.77	53.19	74	-20.81

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Absolute Level (Corrected Amplitude) = Factor + Reading

Margin = Absolute Level - Limit

The other spurious emission which is 20dB to the limit or in noise floor level was not recorded.

Report No.: 2401V85169E-RF-00

Field Strength of Average									
Frequency (MHz)	Peak Measurement @3m (dBµV/m)	Polar (H/V)	Duty Cycle Corrected Factor (dB)	Average Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Comment		
	Low Channel								
2402.00	68.02	Н	-55.92	12.10	94	-81.90	Mainwave		
2402.00	67.71	V	-55.92	11.79	94	-82.21	Mainwave		
2317.00	51.27	Н	-55.92	-4.65	54	-58.65	Bandedge		
2371.30	52.1	V	-55.92	-3.82	54	-57.82	Bandedge		
4804.00	53.17	Н	-55.92	-2.75	54	-56.75	Harmonic		
4804.00	52.07	V	-55.92	-3.85	54	-57.85	Harmonic		
			Middle (Channel					
2440.00	68.18	Н	-55.92	12.26	94	-81.74	Mainwave		
2440.00	68.27	V	-55.92	12.35	94	-81.65	Mainwave		
4880.00	53.47	Н	-55.92	-2.45	54	-56.45	Harmonic		
4880.00	52.58	V	-55.92	-3.34	54	-57.34	Harmonic		
			High C	hannel					
2480.00	65.79	Н	-55.92	9.87	94	-84.13	Mainwave		
2480.00	67.52	V	-55.92	11.60	94	-82.40	Mainwave		
2492.36	51.75	Н	-55.92	-4.17	54	-58.17	Bandedge		
2488.95	52	V	-55.92	-3.92	54	-57.92	Bandedge		
4960.00	54.29	Н	-55.92	-1.63	54	-55.63	Harmonic		
4960.00	53.19	V	-55.92	-2.73	54	-56.73	Harmonic		

Note:

Average level= Peak level+ Duty Cycle Corrected Factor Margin = Average level - Limit

For fundamental, the peak value compliance with the limit of Average.

Duty cycle = Ton/100ms = 0.16/100=0.0016 Duty Cycle Corrected Factor = 20lg (Duty cycle) = 20lg0.0016 = -55.92

Report No.: 2401V85169E-RF-00







Test plots for Band Edge Measurements (Radiated):





Listed with harmonic margin test plot:



Report No.: 2401V85169E-RF-00



Report No.: 2401V85169E-RF-00



Report No.: 2401V85169E-RF-00



Report No.: 2401V85169E-RF-00



Report No.: 2401V85169E-RF-00



FCC§15.215(c) - 20dB EMISSION BANDWIDTH

Applicable Standard

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.7 & Clause 6.9.2

The following conditions shall be observed for measuring the occupied bandwidth and 20 dB bandwidth:

• The transmitter shall be operated at its maximum carrier power measured under normal test conditions.

• The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.

• The detector of the spectrum analyzer shall be set to "Sample". However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or "Max Hold") may be necessary to determine the occupied / 20 dB bandwidth if the device is not transmitting continuously.

• The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW/ 20dB bandwidth and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.



Test Data

Environmental Conditions

Temperature:	25.4 °C
Relative Humidity:	49 %
ATM Pressure:	101 kPa

The testing was performed by Sadow Tan on 2024-08-29.

EUT operation mode: Transmitting

Please refer to the following table and plots.

Test Result

Test Mode	Frequency[MHz]	20dB EBW[MHz]
GFSK	2402	2.113
	2440	2.098
	2480	2.069

Test Graphs



Report No.: 2401V85169E-RF-00



EUT PHOTOGRAPHS

Please refer to the attachment 2401V85169E-RF External photo and 2401V85169E-RF Internal photo.

TEST SETUP PHOTOGRAPHS

Please refer to the attachment 2401V85169E-RF Test Setup photo.

***** END OF REPORT *****