

FCC Test Report

Report No.: AGC11775240905FR01

FCC ID	:	2A8K2MSWNM02-MSPKR
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Manta Sleep White Noise Machine
BRAND NAME	:	Manta Sleep
MODEL NAME	:	MSWHITENOISE02-MSPKR
APPLICANT	:	Manta Sleep LLC
DATE OF ISSUE	:	Oct. 30, 2024
STANDARD(S)	:	FCC Part 15 Subpart C §15.247
REPORT VERSION	:	V1.0







Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes	
V1.0	/	Oct. 30, 2024	Valid	Initial Release	



Table of Contents

1. General Information	5
2. Product Information	6
2.1 Product Technical Description	6
2.2 Test Frequency List	6
2.3 Related Submittal(S) / Grant (S)	7
2.4 Test Methodology	7
2.5 Receiver Input Bandwidth	
2.6 Equally Average Use of Frequencies and Behaviour	7
2.7 Pseudorandom Frequency Hopping Sequence	
2.8 Special Accessories	9
2.9 Equipment Modifications	
2.10 Antenna Requirement	9
3. Test Environment	
3.1 Address of The Test Laboratory	
3.2 Test Facility	
3.3 Environmental Conditions	11
3.4 Measurement Uncertainty	11
3.5 List of Equipment Used	
4. System Test Configuration	14
4.1 EUT Configuration	14
4.2 EUT Exercise	14
4.3 Configuration of Tested System	14
4.4 Equipment Used in Tested System	
4.5 Summary of Test Results	
5. Description of Test Modes	
6. RF Output Power Measurement	17
6.1 Provisions Applicable	
6.2 Measurement Procedure	
6.3 Measurement Setup (Block Diagram of Configuration)	
6.4 Measurement Result	
7. 20dB Bandwidth and 99% Occupied Bandwidth Measurement	
7.1 Provisions Applicable	
7.2 Measurement Procedure	
7.3 Measurement Setup (Block Diagram of Configuration)	24
7.4 Measurement Results	
8. Conducted Band Edge and Out-of-Band Emissions	
8.1 Provisions Applicable	
8.2 Measurement Procedure	
8.3 Measurement Setup (Block Diagram of Configuration)	
8.4 Measurement Results	



9. Radiated Spurious Emission	51
9.1 Measurement Limit	
9.2 Measurement Procedure	
9.3 Measurement Setup (Block Diagram of Configuration)	
9.4 Measurement Result	
10. Number of Hopping Frequency Measurement	
10.1 Provisions Applicable	
10.2 Measurement Procedure	
10.3 Measurement Setup (Block Diagram of Configuration)	
10.4 Measurement Result	
11. Time of Occupancy (Dwell Time) Measurement	
11.1 Provisions Applicable	
11.2 Measurement Procedure	
11.3 Measurement Setup (Block Diagram of Configuration)	
11.4 Measurement Result	
12. Frequency Separation Measurement	
12.1 Provisions Applicable	
12.2 Measurement Procedure	
12.3 Measurement Setup (Block Diagram of Configuration)	
12.4 Measurement Result	
13. AC Power Line Conducted Emission Test	
13.1 Measurement Limit	
13.2 Measurement Setup (Block Diagram of Configuration)	
13.3 Preliminary Procedure of Line Conducted Emission Test	
13.4 Final Procedure of Line Conducted Emission Test	
13.5 Measurement Results	
Appendix I: Photographs of Test Setup	
Appendix II: Photographs of Test EUT	



1. General Information

Applicant	Manta Sleep LLC
Address	680 S Cache Street Suite 100 Box 7403 Jackson, WY 83001 USA
Manufacturer	Manta Sleep LLC
Address	680 S Cache Street Suite 100 Box 7403 Jackson, WY 83001 USA
Factory	Mission Electronic Limited
Address	3F Building C, YUSHENG Industrial Area, LiaoKeng, ShiYan, Baoan, Shenzhen, China
Product Designation	Manta Sleep White Noise Machine
Brand Name	Manta Sleep
Test Model	MSWHITENOISE02-MSPKR
Series Model(s)	N/A
Difference Description	N/A
Date of receipt of test item	Sep. 27, 2024
Date of Test	Sep. 27, 2024 to Oct. 30, 2024
Deviation from Standard	No any deviation from the test method
Condition of Test Sample	Normal
Test Result	Pass
Test Report Form No	AGCER-FCC-BR_EDR-V1

Note: The test results of this report relate only to the tested sample identified in this report.

Prepared By

AS li

Cici Li (Project Engineer)

Oct. 30, 2024

Reviewed By

Calvin Liu (Reviewer)

Oct. 30, 2024

Approved By

Max Zhang

Max Zhang (Authorized Officer)

Oct. 30, 2024



2. Product Information

2.1 Product Technical Description

Frequency Band	2400MHz-2483.5MHz
Operation Frequency Range	2402MHz-2480MHz
Bluetooth Version	V5.4
Modulation Type	BR 🖾 GFSK, EDR 🖾 π /4-DQPSK, \boxtimes 8DPSK
Number of channels	79 Channels
Channel Separation	1 MHz
Maximum Transmitter Power	-2.745dBm
Hardware Version	V1.0
Software Version	V1.0
Antenna Designation	PCB Antenna
Antenna Gain	0.143dBi
Power Supply	DC 5V by adapter

2.2 Test Frequency List

Frequency Band	Channel Number	Frequency			
	0	2402 MHz			
	1	2403 MHz			
	:	:			
2400~2483.5MHz	39	2441MHz			
	:	:			
	77	2479 MHz			
	78	2480 MHz			
Note: f = 2402 + 1k MHz, k = 0,, 78 ; "f "is the operating frequency (MHz); "k" is the operating channel.					



2.3 Related Submittal(S) / Grant (S)

This submittal(s) (test report) is intended for FCC ID: **2A8K2MSWNM02-MSPKR**, filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.4 Test Methodology

The tests were performed according to following standards:

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	2 FCC 47 CFR Part 15 Radio Frequency Devices	
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum system, and Hybrid system devices operating under Section 15.247 of the FCC rules

2.5 Receiver Input Bandwidth

The input bandwidth of the receiver is 1.3MHz, in every connection one Bluetooth device is the master and the other one is slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master. Additionally, the type of connection (e.g. single of multi slot packet) is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also, the slave of the connection will use these settings. Repeating of a packet has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case. That means, a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.

2.6 Equally Average Use of Frequencies and Behaviour.

The generation of the hopping sequence in connection mode depends essentially on two input values:

1. LAP/UAP of the master of the connection.

2. Internal master clock.

The LAP (lower address part) are the 24 LSB's of the 48 BD_ADDRESS. The BD_ADDRESS is an unambiguous number of every Bluetooth unit. The UAP (upper address part) are the 24MSB's of the 48BD_ADDRESS

The internal clock of a Bluetooth unit is derived from a free running clock which is never adjusted and is never turned off. For behavior action with other units only offset is used. It has no relation to the time of the day. Its resolution is at least half the RX/TX slot length of 312.5us. The clock has a cycle of about one day(23h30).

In most case it is implemented as 28 bits counter. For the deriving of the hopping sequence the entire. LAP (24 bits),4LSB's(4bits) (Input 1) and the 27MSB's of the clock (Input 2) are used. With this input values different mathematical procedures (permutations, additions, XOR-operations) are performed to generate the Sequence. This will be done at the beginning of every new transmission.

Regarding short transmissions the Bluetooth system has the following behavior:


The first connection between the two devices is established, a hopping sequence was generated. For Transmitting the wanted data the complete hopping sequence was not used. The connection ended. The second connection will be established. A new hopping sequence is generated. Due to the fact the Bluetooth clock has a different value, because the period between the two transmission is longer (and it Cannot be shorter) than the minimum resolution of the clock(312.5us). The hopping sequence will always differ from the first one.



2.7 Pseudorandom Frequency Hopping Sequence

The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: 29 1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of The PRBS Sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:

44	35	78	03	20	76	02	19		2	1 64	75
						1		1			
				-							
					;				i i		
			└	i		<u>i</u>		1	i		

Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their Corresponding transmitters and shift frequencies in synchronization with the transmitted signals.



2.8 Special Accessories

Not available for this EUT intended for grant.

2.9 Equipment Modifications

Not available for this EUT intended for grant.

2.10 Antenna Requirement

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 0.143dBi.



3. Test Environment

3.1 Address of The Test Laboratory

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to follow CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories.)

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to follow ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842(CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



3.3 Environmental Conditions

	Normal Conditions
Temperature range (°C)	15 - 35
Relative humidity range	20 % - 75 %
Pressure range (kPa)	86 - 106
Power supply	DC 5V by adapter

3.4 Measurement Uncertainty

The reported uncertainty of measurement y \pm U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty		
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 2.9 \text{ dB}$		
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 3.9 \text{ dB}$		
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.9 \text{ dB}$		
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$		
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$		
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$		
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$		



3.5 List of Equipment Used

• R	RF Conducted Test System								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
\square	AGC-ER-E036	Spectrum Analyzer	Agilent	N9020A	MY49100060	2024-05-24	2025-05-23		
\boxtimes	AGC-ER-E062	Power Sensor	Agilent	U2021XA	MY54110007	2024-02-01	2025-01-31		
\boxtimes	AGC-ER-E063	Power Sensor	Agilent	U2021XA	MY54110009	2024-02-01	2025-01-31		
\boxtimes	AGC-EM-A001	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-09-21	2025-09-20		
	AGC-ER-E083	Signal Generator	Agilent	E4421B	US39340815	2024-05-23	2025-05-22		
\boxtimes	N/A	RF Connection Cable	N/A	1#	N/A	Each time	N/A		
\boxtimes	N/A	RF Connection Cable	N/A	2#	N/A	Each time	N/A		

• F	Radiated Spurious Emission								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
\square	AGC-EM-E046	EMI Test Receiver	R&S	ESCI	10096	2024-02-01	2025-01-31		
	AGC-EM-E116	EMI Test Receiver	R&S	ESCI	100034	2024-05-24	2025-05-23		
\square	AGC-EM-E061	Spectrum Analyzer	Agilent	N9010A	MY53470504	2024-05-28	2025-05-27		
\boxtimes	AGC-EM-E086	Loop Antenna	ZHINAN	ZN30900C	18051	2024-03-05	2026-03-04		
\boxtimes	AGC-EM-E001	Wideband Antenna	SCHWARZBECK	VULB9168	D69250	2023-05-11	2025-05-10		
	AGC-EM-E029	Broadband Ridged Horn Antenna	ETS	3117	00034609	2024-03-31	2025-03-30		
\square	AGC-EM-E082	Horn Antenna	SCHWARZBECK	BBHA 9170	#768	2023-09-24	2025-09-23		
\square	AGC-EM-E146	Pre-amplifier	ETS	3117-PA	00246148	2024-07-24	2026-07-23		
\square	AGC-EM-A119	2.4GHz Filter	SongYi	N/A	N/A	2024-05-23	2025-05-22		
\square	AGC-EM-A138	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08		
	AGC-EM-A139	6dB Attenuator	Eeatsheep	LM-XX-6-5W	N/A	2023-06-09	2025-06-08		

• A	AC Power Line Conducted Emission								
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)		
\boxtimes	AGC-EM-E045	EMI Test Receiver	R&S	ESPI	101206	2024-05-28	2025-05-27		
\square	AGC-EM-A130	6dB Attenuator	Eeatsheep	LM-XX-6-5W	DC-6GZ	2023-06-09	2025-06-08		
\square	AGC-EM-E023	AMN	R&S	100086	ESH2-Z5	2024-05-28	2025-05-27		



• Tes	Test Software						
Used	Equipment No.	Test Equipment	Manufacturer	Model No.	Version Information		
\boxtimes	AGC-EM-S001	CE Test System	R&S	ES-K1	V1.71		
\boxtimes	AGC-EM-S003	RE Test System	FARA	EZ-EMC	V.RA-03A		
\boxtimes	AGC-EM-S004	RE Test System	Tonscend	TS ⁺ Ver2.1(JS32-RE)	4.0.0.0		
\boxtimes	AGC-ER-S012	BT/WIFI Test System	Tonscend	JS1120-2	2.6		
\square	AGC-EM-S011	RSE Test System	Tonscend	TS+-Ver2.1(JS36-RSE)	4.0.0.0		



4. System Test Configuration

4.1 EUT Configuration


The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT Exercise


The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 Configuration of Tested System

Radiated Emission Configure:



Conducted Emission Configure:



4.4 Equipment Used in Tested System

The following peripheral devices and interface cables were connected during the measurement:

☑ Test Accessories Come From The Laboratory

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	Control Box	RISYM	USB-TTL	-	

☑ Test Accessories Come From The Manufacturer

No.	Equipment	Manufacturer	Model No.	Specification Information	Cable
1	Adapter	Guangdong Sangu Technology Co., LTD	5G-0502000AUC	Input: 100-240V~50/60Hz 0.6A MAX Output: 5.0V 2.0A 10.0W	2.46m,unshielded



4.5 Summary of Test Results

Item	FCC Rules	Description of Test	Result
1	§15.203&15.247(b)(4)	Antenna Equipment	Pass
2	§15.247 (b)(1)	RF Output Power	Pass
3	§15.247 (a)(1)	20 dB Bandwidth	Pass
4	§15.247 (d)	Conducted Band Edge and Out-of-Band Emissions	Pass
5	§15.209	Radiated Spurious Emission	Pass
6	§15.247 (a)(1)(iii)	Number of Hopping Frequency	Pass
7	§15.247 (a)(1)(iii)	Time of Occupancy	Pass
8	§15.247 (a)(1)	Frequency Separation	Pass
9	§15.207	AC Power Line Conducted Emission	Pass



5. Description of Test Modes

Data Rate / ModulationData Rate / ModulationBluetooth – BR_EDR (GFSK/π /4-DQPSK/8DPSK)Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps (AC/DC adapter) Mode 2: Bluetooth Tx CH39_2441 MHz_1Mbps (AC/DC adapter) Mode 3: Bluetooth Tx CH78_2480 MHz_1Mbps (AC/DC adapter) Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps (AC/DC adapter) Mode 5: Bluetooth Tx CH39_2441 MHz_2Mbps (AC/DC adapter) Mode 5: Bluetooth Tx CH39_2441 MHz_2Mbps (AC/DC adapter) Mode 6: Bluetooth Tx CH78_2480 MHz_2Mbps (AC/DC adapter) Mode 6: Bluetooth Tx CH78_2480 MHz_3Mbps (AC/DC adapter) Mode 7: Bluetooth Tx CH39_2441 MHz_3Mbps (AC/DC adapter) Mode 8: Bluetooth Tx CH39_2441 MHz_3Mbps (AC/DC adapter) Mode 9: Bluetooth Tx CH78_2480 MHz_3Mbps (AC/DC adapter)
Bluetooth – BR_EDR (GFSK/π /4-DQPSK/8DPSK)Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps (AC/DC adapter) Mode 2: Bluetooth Tx CH39_2441 MHz_1Mbps (AC/DC adapter) Mode 3: Bluetooth Tx CH78_2480 MHz_1Mbps (AC/DC adapter) Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps (AC/DC adapter) Mode 5: Bluetooth Tx CH39_2441 MHz_2Mbps (AC/DC adapter) Mode 5: Bluetooth Tx CH39_2441 MHz_2Mbps (AC/DC adapter) Mode 6: Bluetooth Tx CH78_2480 MHz_2Mbps (AC/DC adapter) Mode 6: Bluetooth Tx CH78_2480 MHz_2Mbps (AC/DC adapter) Mode 6: Bluetooth Tx CH78_2480 MHz_3Mbps (AC/DC adapter) Mode 8: Bluetooth Tx CH39_2441 MHz_3Mbps (AC/DC adapter) Mode 8: Bluetooth Tx CH39_2441 MHz_3Mbps (AC/DC adapter) Mode 9: Bluetooth Tx CH78_2480 MHz_3Mbps (AC/DC adapter)
Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps (AC/DC adapter) Mode 2: Bluetooth Tx CH39_2441 MHz_1Mbps (AC/DC adapter) Mode 3: Bluetooth Tx CH78_2480 MHz_1Mbps (AC/DC adapter) Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps (AC/DC adapter) Mode 5: Bluetooth Tx CH39_2441 MHz_2Mbps (AC/DC adapter) Mode 5: Bluetooth Tx CH39_2441 MHz_2Mbps (AC/DC adapter) Mode 6: Bluetooth Tx CH78_2480 MHz_2Mbps (AC/DC adapter) Mode 6: Bluetooth Tx CH78_2480 MHz_2Mbps (AC/DC adapter) Mode 7: Bluetooth Tx CH00_2402 MHz_3Mbps (AC/DC adapter) Mode 8: Bluetooth Tx CH39_2441 MHz_3Mbps (AC/DC adapter) Mode 9: Bluetooth Tx CH78_2480 MHz_3Mbps (AC/DC adapter)
Mode10: Bluetooth Tx Hopping-1Mbps (AC/DC adapter) Mode11: Bluetooth Tx Hopping-2Mbps (AC/DC adapter) Mode12: Bluetooth Tx Hopping-3Mbps (AC/DC adapter)
AC Conducted Emission Mode 1: Bluetooth Link + USB Cable (Powered from AC Adapter)
 Only the result of the worst case was recorded in the report, if no other cases. For Radiated Emission, 3axis were chosen for testing for each applicable mode. For Conducted Test method, a temporary antenna connector is provided by the manufacture. Software Setting Diagram
return code: 0x0 配置数据发送成功:
清除曰志



6. RF Output Power Measurement

6.1 Provisions Applicable

The maximum out power permissible output power is 1 Watt for all frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels.

The maximum out power permissible output power is 0.125 watts for all other frequency hopping systems in the 2400-2483.5 MHz band.


6.2 Measurement Procedure

⊠For Peak power test:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- 3. RBW > 20 dB bandwidth of the emission being measured.
- 4. VBW \geq RBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.
- 8. Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

6.3 Measurement Setup (Block Diagram of Configuration)

For peak power test setup






6.4 Measurement Result


Test Data of Conducted Output Power						
Test Mode	Test Frequency (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail		
	2402	-4.808	≤21	Pass		
GFSK	2441	-4.035	≤21	Pass		
	2480	-3.760	≤21	Pass		
	2402	-3.954	≤21	Pass		
π/4-DQPSK	2441	-3.153	≤21	Pass		
	2480	-2.911	≤21	Pass		
	2402	-3.683	≤21	Pass		
8DPSK	2441	-2.846	≤21	Pass		
	2480	-2.745	≤21	Pass		






Test Graphs of Conducted Output Power





















7. 20dB Bandwidth and 99% Occupied Bandwidth Measurement

7.1 Provisions Applicable


There is no corresponding limit requirement for this test item.

7.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 6.9.2 (20dB BW).

- The 20dB bandwidth spectrum analyzer setting reference is as follows:
- 1. Set RBW \geq 1% to 5% of the 20dB bandwidth
- 2. VBW = Approximately three times RBW
- 3. Span = Approximately 2 to 5 times the 20dB bandwidth, centered on a hopping channel
- 4. Detector = Peak
- 5. Trace mode = Max hold
- 6. Sweep = Auto couple
- 7. Allow the trace to stabilize
- 8. Measure the maximum width of the emission that is constrained by the frequencies associated
- 9. with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20
- 10. dB relative to the maximum level in the fundamental emission.
- The 99% bandwidth spectrum analyzer setting reference is as follows:
- 1. Span = 1.5 times to 5 times the OBW
- 2. Set RBW = 1% to 5% the OBW
- 3. VBW \geq 3 × RBW
- 4. Detector = Peak
- 5. Trace mode = Max hold
- 6. Sweep = Auto couple
- 7. Allow the trace was allowed to stabilize

7.3 Measurement Setup (Block Diagram of Configuration)






7.4 Measurement Results

Test Data of Occupied Bandwidth and -20dB Bandwidth							
Test Mode	Test Frequency (MHz)	99% Occupied Bandwidth (MHz)	-20dB Bandwidth (MHz)	Limits	Pass or Fail		
	2402	0.864	0.953	N/A	Pass		
GFSK	2441	0.867	0.955	N/A	Pass		
	2480	0.870	0.952	N/A	Pass		
	2402	1.170	1.283	N/A	Pass		
π /4-DQPSK	2441	1.170	1.281	N/A	Pass		
	2480	1.170	1.281	N/A			
	2402	1.172	1.293	N/A	Pass		
8DPSK	2441	1.172	1.294	N/A	Pass		
	2480	1.173	1.293	N/A	Pass		

Test Graphs of Occupied Bandwidth and -20 Bandwidth





















8. Conducted Band Edge and Out-of-Band Emissions

8.1 Provisions Applicable


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

8.2 Measurement Procedure

The testing follows the ANSI C63.10 Section 6.10.4 and 7.8.8:

- Reference level measurement
- 1. Span = Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Sweep time = Auto couple
- 6. Trace mode = Max hold
- 7. Allow the trace to stabilize. Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission.
- Emission level measurement
- 1. Span = Wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
- 2. RBW = 100kHz
- 3. VBW = 300kHz
- 4. Detector = Peak
- 5. Sweep time = Auto couple
- 6. Trace mode = Max hold
- 7. Trace was allowed to stabilize
- 8. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.

8.3 Measurement Setup (Block Diagram of Configuration)






8.4 Measurement Results




Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands

































Report No.: AGC11775240905FR01 Page 39 of 76



































Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands




























9. Radiated Spurious Emission

9.1 Measurement Limit

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

9.2 Measurement Procedure

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average



absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.

- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Spectrum Parameter	Setting			
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP			
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP			
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP			
Start ~Stop Frequency	1GHz~26.5GHz			
	1MHz/3MHz for Peak, 1MHz/3MHz for Average			

The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP



• Quasi-Peak Measurements below 1GHz

- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. Span was set greater than 1MHz
- 3. RBW = as shown in the table above
- 4. Detector = CISPR quasi-peak
- 5. Sweep time = auto couple
- 6. Trace was allowed to stabilize

• Peak Measurements above 1GHz


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW = 3MHz
- 4. Detector = peak
- 5. Sweep time = auto couple
- 6. Trace mode = max hold
- 7. Trace was allowed to stabilize

<u>Average Measurements above 1GHz</u>


- 1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
- 2. RBW = 1MHz
- 3. VBW \geq [3 × RBW]
- 4. Detector = Power averaging (rms)
- 5. Averaging type = power (i.e., rms)
- 6. Sweep time = auto
- 7. Perform a trace average of at least 100 traces.
- 8. The applicable correction factor is [10*log (1 / D)], where D is the duty cycle. The factor had been edited in the "Input Correction" of the Spectrum Analyzer.




9.3 Measurement Setup (Block Diagram of Configuration)



Radiated Emission Test Setup 30MHz-1000MHz



Radiated Emission Test Setup Above 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com

 Web: http://www.agccert.com/




9.4 Measurement Result

Radiated Emission Below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

	Radiated Emission Test Results at 30MHz-1GHz														
EUT	Name	Ма	Manta Sleep White Noise Machine				Model	Model Name M			MSWHITENOISE02-MSPKR				
Temp	erature	23.	2 °C					Relativ	∕e ⊦	lumidity	5	8.6%	6		
Press	sure	960	DhPa					Test Vo	olta	ige	١	lorm	al Vo	oltag	je
Test M	Node	Мо	de 9					Antenr	na I	Polarity	ŀ	loriz	onta	I	
	72.0	dBu\	//m												
													nit: argin:	_	
	-								_						
	_														F
									_						
	-													Ŷ	H
	32						2			A A A A A A A A A A A A A A A A A A A		here the set	مجلس المسالمة	part 4	<u>~</u>
						Aller	M.A.	3		and the south work	Mar .	an a c Bas			
		M water	nondernon	nahaman ang kang kang kang kang kang kang kan	MAN WAR	(MM)	Mr. And Marine M	Marthan Hold Marthan	4						
	-						,		_						
	-8 30.	000	40	50 60	70 8	0	(MHz)		30	0 400	500	600	700	100	0.000
Final															
Final	Data List Freq			evel	- Ea	ctor	Limit	Margin		Height		۸n	gle	<u> </u>	
NO.	[MHz			uV/m]		B]	[dBµV/m]	[dB]		[cm]			°]		Polarity
1	99.877	77	31	.11	16	6.18	43.50	12.39		100		1	14		Horizontal
2	113.71	43	30	.02	16	6.34	43.50	13.48		100		2	17		Horizontal
3	185.78	82	22	.55	12	2.87	43.50	20.95		100		8	36		Horizontal
4	268.48	53	24	.12	14	1.84	46.00	21.88		100		1	63		Horizontal
5	449.55	58	31	.37	24	1.77	46.00	14.63		100		2	35		Horizontal
6	893.85	67	37	.28	31	.03	46.00	8.72		100		1	24		Horizontal





	Radiated Emission Test Results at 30MHz-1GHz								
EUT Name	Ma	anta Sleep V	hite Noise N	<i>l</i> achine	Model Na	ame	OISE02-MSPKR		
Temperatu	re 23	.2 ℃			Relative	Humidity	58.6%		
Pressure	96	0hPa			Test Volt	age	Normal Volta	ige	
Test Mode	M	ode 9			Antenna	Polarity	Vertical		
	72.0 dBu	.₩/m							
	32			MM Martin M					
	30.000	40 50 6	0 70 80	(MHz)	E	800 400 9	500 600 700 10	000.000	
Final Data		T		1					
	req. IHz]	Level [dBµV/m]	Factor [dB]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	
	3992	35.56	14.06	40.00	4.44	100	172	Vertical	
2 61.	3462	35.33	17.09	40.00	4.67	100	86	Vertical	
3 102	.3597	39.55	14.61	43.50	3.95	100	142	Vertical	
4 174	.4241	32.59	18.42	43.50	10.91	100	215	Vertical	
5 446	.4141	32.17	25.81	46.00	13.83	100	135	Vertical	
6 763	.3757	34.97	28.06	46.00	11.03	100	187	Vertical	
		<u>I</u>	1			1		L	

RESULT: Pass

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Limit-Level.

2. All test modes had been pre-tested. The mode 9 is the worst case and recorded in the report.



EUT Name	Manta Sleep Machine	White Noise	Model	Name	MSWHITENOISE02-MSPKR				
Temperature	23.2 ℃		Relativ	ve Humidity	58.6%				
Pressure	960hPa		Test V	oltage	Normal Vo	oltage			
Test Mode	Mode 7		Anten	na Polarity	Horizonta				
			•		·				
Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	- Value Type			
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type			
4804.000	45.25	0.08	45.33	74	-28.67	peak			
4804.000	38.86	0.08	38.94	54	-15.06	AVG			
7206.000	41.23	2.21	43.44	74	-30.56	peak			
7206.000	32.96	2.21	35.17	54	-18.83	AVG			
Remark:									
Factor = Antenna Factor + Cable Loss – Pre-amplifier.									
-									
EUT Name	Manta Sleep Machine			Name	MSWHITE	ENOISE02-MSPK			
EUT Name Temperature			Model	Name ve Humidity	MSWHITE 58.6%	ENOISE02-MSPK			
	Machine		Model	ve Humidity	-				
Temperature Pressure	Machine 23.2℃		Model Relativ Test V	ve Humidity	58.6%				
Temperature Pressure Test Mode	Machine 23.2℃ 960hPa Mode 7	White Noise	Model Relativ Test V Anten	ve Humidity oltage na Polarity	58.6% Normal Vo Vertical				
Temperature Pressure Test Mode Frequency	Machine 23.2°C 960hPa Mode 7 Meter Reading	White Noise Factor	Model Relativ Test V Anten Emission Level	ve Humidity oltage na Polarity	58.6% Normal Vo Vertical				
Temperature Pressure Test Mode Frequency (MHz)	Machine 23.2℃ 960hPa Mode 7 Meter Reading (dBµV)	White Noise Factor (dB)	Model Relativ Test V Anten Emission Level (dBµV/m)	ve Humidity oltage na Polarity Limits (dBµV/m)	58.6% Normal Vo Vertical Margin (dB)	Ditage Value Type			
Temperature Pressure Test Mode Frequency (MHz) 4804.000	Machine 23.2℃ 960hPa Mode 7 Meter Reading (dBµV) 45.57	White Noise Factor (dB) 0.08	Model Relativ Test V Anten Emission Level (dBµV/m) 45.65	ve Humidity oltage na Polarity Limits (dBµV/m) 74	58.6% Normal Vo Vertical Margin (dB) -28.35	Value Type peak			
Temperature Pressure Test Mode Frequency (MHz) 4804.000 4804.000	Machine 23.2°C 960hPa Mode 7 Meter Reading (dBµV) 45.57 36.82	White Noise Factor (dB) 0.08 0.08	Model Relativ Test V Anten Emission Level (dBµV/m) 45.65 36.9	ve Humidity oltage na Polarity Limits (dBµV/m) 74 54	58.6% Normal Vo Vertical Margin (dB) -28.35 -17.1	Value Type peak AVG			
Temperature Pressure Test Mode Frequency (MHz) 4804.000 4804.000 7206.000	Machine 23.2℃ 960hPa Mode 7 Meter Reading (dBµV) 45.57 36.82 41.45	White Noise Factor (dB) 0.08 0.08 2.21	Model Relative Test V Anten Emission Level (dBµV/m) 45.65 36.9 43.66	ve Humidity oltage na Polarity Limits (dBµV/m) 74 54 74	58.6% Normal Vo Vertical Margin (dB) -28.35 -17.1 -30.34	Value Type peak AVG peak			
Temperature Pressure Test Mode Frequency (MHz) 4804.000 4804.000	Machine 23.2°C 960hPa Mode 7 Meter Reading (dBµV) 45.57 36.82	White Noise Factor (dB) 0.08 0.08	Model Relativ Test V Anten Emission Level (dBµV/m) 45.65 36.9	ve Humidity oltage na Polarity Limits (dBµV/m) 74 54	58.6% Normal Vo Vertical Margin (dB) -28.35 -17.1	Value Type peak AVG			
Temperature Pressure Test Mode Frequency (MHz) 4804.000 7206.000 7206.000	Machine 23.2℃ 960hPa Mode 7 Meter Reading (dBµV) 45.57 36.82 41.45	White Noise Factor (dB) 0.08 0.08 2.21	Model Relative Test V Anten Emission Level (dBµV/m) 45.65 36.9 43.66	ve Humidity oltage na Polarity Limits (dBµV/m) 74 54 74	58.6% Normal Vo Vertical Margin (dB) -28.35 -17.1 -30.34	Value Type peak AVG peak			
Temperature Pressure Test Mode Frequency (MHz) 4804.000 4804.000 7206.000 7206.000 Remark:	Machine 23.2℃ 960hPa Mode 7 Meter Reading (dBµV) 45.57 36.82 41.45	White Noise Factor (dB) 0.08 0.08 2.21 2.21	Моdel Relativ Test V Anten Emission Level (dBµV/m) 45.65 36.9 43.66 34.9	ve Humidity oltage na Polarity Limits (dBµV/m) 74 54 74	58.6% Normal Vo Vertical Margin (dB) -28.35 -17.1 -30.34	Value Type peak AVG peak			

Radiated Emissions Test Results Above 1GHz

RESULT: Pass



EUT	⁻ Name		Manta Slee Machine	p White No	ise	Mod	Model Name			MSWHITENOISE02-MSPKR		
Tem	perature		23.2℃			Rela	tive Humidi	ity	58.6%			
Pres	ssure		960hPa			Test	Voltage		Normal Voltage			
Tes	t Mode		Mode 8			Ante	enna Polarit	y	Horizoi	ntal		
	Frequenc	су	Meter Reading	Factor	. Emiss	sion Lev	el Limits		Margin	Value Typ	~	
	(MHz)		(dBµV)	(dB)	(dE	3µV/m)	(dBµV/m	ı)	(dB)	value Typ	e	
	4882.000	C	46.94	0.14	4	7.08	74		-26.92	peak		
	4882.000	C	37.56	0.14	:	37.7	54		-16.3	AVG		
	7323.000)	42.71	2.36	4	5.07	74		-28.93	peak		
	7323.000	5	33.32	2.36	3	5.68	54		-18.32	AVG		
	Remark:											
	Factor = A	ntenna	a Factor + Ca	ble Loss – F	Pre-amplifier	<u>.</u>						
EUT	Name		Manta Slee Machine	p White No	ise	Mod	el Name		MSWH	IITENOISE02-	MSPKR	
Tem	perature		23.2 ℃		Relative Humidity			ity	58.6%			
Pres	ssure		960hPa			Test Voltage			Normal Voltage			
Test	t Mode		Mode 8			Ante	enna Polarit	y	Vertical			
	_			_	1							
- F	requency		er Reading	Factor	Emission L		Limits		argin	Value Type		
	(MHz)		(dBµV)	(dB)	(dBµV/m	1)	(dBµV/m)		dB)	nack		
	1882.000		45.25	0.14	45.39		74		8.61	peak		
	1882.000		37.74	0.14	37.88		54		6.12	AVG		
-	7323.000 7323.000		42.49	2.36 44.85 74 2.36 35.97 54			9.15 8.03	peak AVG				
<u> </u>	323.000	33.61 2.36 35.97 54		-1	0.03	AvG						
Por	nark:											
		na Fa	ctor + Cable I	oss – Pre-a	molifier							
. 40												

RESULT: Pass



EUT	Name	IameManta Sleep White Noise Machine			Model	Name	MSWHITE	MSWHITENOISE02-MSPKR			
Tem	perature	23.2°C Relative Humidity			58.6%						
Pre	ssure	960hPa			Test Vo	oltage	Normal Vo	oltage			
Tes	t Mode	Mode 9			Antenn	a Polarity	Horizonta				
	Frequency	Meter Reading	Factor	Emiss	ion Level	Limits	Margin				
	(MHz)	(dBµV)	(dB)	(dB	µV/m)	(dBµV/m)	(dB)	Value Type			
	4960.000	45.84	0.22	46	5.06	74	-27.94	peak			
	4960.000	37.47	0.22	37	7.69	54	-16.31	AVG			
	7440.000	42.49	2.64	48	5.13	74	-28.87	peak			
	7440.000	33.58	2.64	36	6.22	54	-17.78	AVG			
	Remark:										
	Factor = Anten	na Factor + Cabl	e Loss – Pre-	amplifier.							
EUT	Name	Manta Sleep Machine	White Noise		Model	Name	MSWHITE	NOISE02-MSPKF			
Ten	perature	23.2 ℃			Relative Humidity 58.6%						
Pre	ssure	960hPa			Test Voltage		Normal Vo	oltage			
Tes	t Mode	Mode 9			Antenn	a Polarity	Vertical				
								1 1			
	Frequency	Meter Reading	Factor		ion Level	Limits	Margin	Value Type			
	(MHz)	(dBµV)	(dB)	`	µV/m)	(dBµV/m)	(dB)				
	4960.000	46.25	0.22		6.47	74	-27.53	peak			
	4960.000	38.41	0.22		3.63	54	-15.37	AVG			
	7440.000	42.64	2.64		5.28	74	-28.72	peak			
	7440.000	440.000 32.38 2.64 3		35	5.02	54	-18.98	AVG			
I		02.00		Remark:							
	Remark:	na Factor + Cabl		•				·			

Radiated Emissions Test Results for Above 1GHz

RESULT: Pass


Note:

- 1. The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.
- 2. Factor = Antenna Factor + Cable loss Pre-amplifier gain, Margin = Emission Level-Limit.
- 3. The "Factor" value can be calculated automatically by software of measurement system.
- 4. All mode rates are tested and evaluated, 8DPSK modulated 3DH5 mode is the worst case and documented in the report.




EUT Name	Manta Sleep White Noise Machine	Model Name	MSWHITENOISE02-MSPKR
Temperature	25.8 ℃	Relative Humidity	46.0%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 7	Antenna Polarity	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: Pass




EUT Name	Manta Sleep White Noise Machine	Model Name	MSWHITENOISE02-MSPKR
Temperature	25.8 ℃	Relative Humidity	46.0%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 7	Antenna Polarity	Vertical

Band Edge Emission Test Results for Restricted Bands

Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: Pass




EUT Name Manta Sleep White Noise Machine		Model Name	MSWHITENOISE02-MSPKR	
Temperature	25.8 ℃	Relative Humidity	46.0%	
Pressure	960hPa	Test Voltage	Normal Voltage	
Test Mode	Mode 9	Antenna Polarity	Horizontal	

Band Edge Emission Test Results for Restricted Bands

Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: Pass




EUT Name	Manta Sleep White Noise Machine	Model Name	MSWHITENOISE02-MSPKR	
Temperature	25.8 ℃	Relative Humidity	46.0%	
Pressure	960hPa	Test Voltage	Normal Voltage	
Test Mode	Mode 9	Antenna Polarity	Vertical	

Band Edge Emission Test Results for Restricted Bands





Test Graph for Average Measurement



RESULT: Pass

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer. All mode rates are tested and evaluated, 8DPSK modulated 3DH5 mode is the worst case and documented in the report.



10. Number of Hopping Frequency Measurement

10.1 Provisions Applicable

This frequency hopping system must employ a minimum of 15 hopping channels.


10.2 Measurement Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

1. Span = The frequency band of operation. Depending on the number of channels the device

- 2. supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- 3. RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- 4. VBW \geq RBW
- 5. Sweep time = Auto couple
- 6. Detector = Peak
- 7. Trace mode = Max hold
- 8. Allow the trace to stabilize

10.3 Measurement Setup (Block Diagram of Configuration)



10.4 Measurement Result

Test Data of Number of Hopping Frequency								
Test Mode Number of Hopping Frequency Limits Pass or Fail								
8DPSK Hopping	79	>=15	Pass					



200 Center Freq 201 Center Freq 202 Center Freq 203 Center Freq 204 Center Freq 205 Center Freq 206 Center Freq 207 Center Freq 208 Center Freq 209 Center Freq 200 Center Freq 201 Center Freq 2100 Center Freq						Tambol	<u></u>	-ping -	10940		
Center Freq 2.441750000 GHz Trig: Free Run #Atten: 40 dB Avg Type: Log-Pwr Avg Hoid: 100/100 Trig: Frequency 10 dB/div Ref 30.00 dBm -3.848 dBm Center Freq 2.441750000 GHz Center Freq 2.441750000 GHz 200		· · · · · · · · · · · · · · · · · · ·		CODDEC		OFNOT JUT			10.40.00.01	10-100 2024	
Open Hild Open Hild Trig: Free Run #Atten: 40 dB Avgihidi: 100/100 Trig: Free Run #Atten: 40 dB Avgihidi: 100/100 Trig: Free Run #Atten: 40 dB Avgihidi: 12:468 87 GHz -3.848 dBm Auto Tune 10 dB/div Ref 30.00 dBm -3.848 dBm -3.848 dBm Center Freq 2.441750000 GHz -3.848 dBm Center Freq 2.441750000 GHz -4.41750000 GHz -4.41750000 GHz -4.41750000 GHz -4.41750000 GHz -4.41750000 GHz -4.41750000 GHz -4.4175 GHz -5.5180 MHz -5.5180 MHz <t< td=""><td></td><td></td><td></td><td></td><td></td><td>SENSE:INT</td><td>Ava Tva</td><td></td><td></td><td></td><td>Frequency</td></t<>						SENSE:INT	Ava Tva				Frequency
IF GainLow #Atten: 40 dB Der parturer Mkr1 2.468 87 GHz -3.848 dBm Auto Tune Center Freq 2.44175000 GHz Center Freq 2.44175000 GHz Mulp Amage And	Center F	rey 2.44 17 3	0000		Trig	: Free Run			TYP	E M WWWWW	
Mikr 2.408 87 GH2 Center Freq -3.848 dBm -3.848 dBm -00 -3.848 dBm -01 -3.848 dBm -02 -3.848 dBm -03 -3.848 dBm -04 -3.848 dBm -05 -3.848 dBm -06 -4.10 -07 -4.11 -08 -3.848 dBm -09 -4.11 -01 -4.11 -02 -4.11 -03 -4.11 -04 -4.11 -05 -4.11 -06 -4.11 -07 -4.11 -08 -4.11 -09 -4.11 -01 -4.11 -01 -4.11 -01 -4.11 -01 -4.11 -01 -4.11 -01 -4.11 -01 -4.11 -01 -4.11 -01 -4.11 -01 -4.11 -01 -4.11 -01 -4.11 -						en: 40 dB			DE		
100 dB/div Ref 30.00 dBm -3.848 dBm 200 -9 -9 -2 100 -9 -9 -2 100 -9 -9 -1 100 -9 -1 -1 100 -9 -1 -1 100 -1 -1 -1 100 -1 -1 -1 100 -1 -1 -1 100 -1 -1 -1 100 -1 -1 -1 100 -1 -1 -1 100 -1 -1 -1 100 -1 -1 -1 100 -1 -1 -1 100 -1 -1 -1 100 -1 -1 -1 100 -1 -1 -1 100 -1 -1 -1 200 -1 -1 -1 200 -1 -1 -1 200 -1 -1 -1								Mkr	1 2 468	87 GHz	Auto Tune
200 2	10 40/404	Bof 20.00 c	1Bm						-3.8	48 dBm	
200 201 201 201 201 201 201 201	Log	Kei 30.00 0									
200 201 201 201 201 201 201 201											Center Fred
100 1	20.0										
000 1	20.0										2.441750000 GHZ
000 1											
0.00 1 2.40000000 GHz 100 1 1 1 100 1 1 1 200 1 1 1 1 300 1 1 1 1 1 400 1 1 1 1 1 1 500 1 1 1 1 1 1 1 600 1 <td< td=""><td>10.0</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>Oto at Ease</td></td<>	10.0										Oto at Ease
100 1											
Stop Freq 2.483500000 GHz 2.483500000 GHz 2.483500000 GHz 2.483500000 GHz 2.483500000 GHz 8.350000 MHz Auto Man Freq Offset 0 Hz 60.0 CEnter 2.44175 GHz #Res BW 200 kHz #VBW 620 kHz Sweep 1.998 ms (1000 pts) STATUS	0.00								 1		2.40000000 GHz
Stop Freq 2.483500000 GHz 2.483500000 GHz 2.483500000 GHz 2.483500000 GHz 2.483500000 GHz 8.350000 MHz Auto Man Freq Offset 0 Hz 60.0 CEnter 2.44175 GHz #Res BW 200 kHz #VBW 620 kHz Sweep 1.998 ms (1000 pts) STATUS		nin dia Al-Lisa M			a 0 - 4	6606808080808	N 101 101	መአጠራስ ሸሩ	NO OR NO	14444	
Stop Freq 2.48350000 GHz 2.48350000 GHz 2.48350000 GHz 2.48350000 GHz 2.48350000 GHz 8.350000 Hz 8.350000 Hz 8.350000 Hz 8.350000 Hz 8.350000 Hz 8.350000 Hz 8.350000 Hz 8.350000 Hz 8.350000 Hz 9.40 9.40 9.40 9.40 9.40 9.40 9.40 9.40		I I I I I I I I I I I I I I I I I I I	MANAN VAN	MYYVWYY	and the second	ϞͽϐϐϠͽ	NN YYYYY VM	IN NAM AN	/YUYUYYY	VVYVY	
200 200 200 200 200 200 200 200 200 200	- 10.0										Stop Freq
30.0 40.0 50.0											2.483500000 GHz
Auto Society Span 83.50 MHz Scenter 2.44175 GHz #Res BW 200 kHz #VBW 620 kHz Sweep 1.998 ms (1000 pts) Status	-20.0										
Auto Society Span 83.50 MHz Scenter 2.44175 GHz #Res BW 200 kHz #VBW 620 kHz Sweep 1.998 ms (1000 pts) Status											
40.0 60.0 60.0 Center 2.44175 GHz #VBW 620 kHz Sweep 1.998 ms (1000 pts) STATUS	-30.0										
40.0 50.0											
50.0 50.0	(0.0										Auto Man
500 600 <td>-40.0</td> <td></td>	-40.0										
500 600 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>հո</td> <td>Freg Offset</td>										հո	Freg Offset
60.0 Center 2.44175 GHz #Res BW 200 kHz #VBW 620 kHz Sweep 1.998 ms (1000 pts) Status	-50.0										
Center 2.44175 GHz #Res BW 200 kHz #VBW 620 kHz Sweep 1.998 ms (1000 pts) Isg status											0 H2
#Res BW 200 kHz #VBW 620 kHz Sweep 1.998 ms (1000 pts) Isg status	-60.0										
#Res BW 200 kHz #VBW 620 kHz Sweep 1.998 ms (1000 pts) Isg status											
#Res BW 200 kHz #VBW 620 kHz Sweep 1.998 ms (1000 pts) Isg status											
#Res BW 200 kHz #VBW 620 kHz Sweep 1.998 ms (1000 pts) Isg Isg Isg	Center 2.	44175 GHz							Span 8	3.50 MHz	
ASG STATUS				#V	BW 620	kHz		Sweep 1	.998 ms (1000 pts)	
Test_Graph_EDR_HOP_ANT1_NA_3Mbps_Number of Hopping	MSG										

Test Graphs of Number of Hopping Frequency

Note: All mode rates are tested and evaluated, 8DPSK modulated 3DH5 mode is the worst case and documented in the report.



11. Time of Occupancy (Dwell Time) Measurement

11.1 Provisions Applicable


The maximum permissible time of occupancy is 400ms within a period of 400ms multiplied by the number of hopping channels employed.

11.2 Measurement Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:

- 1. Span = Zero span, centered on a hopping channel.
- 2. RBW shall be \leq channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
- 3. VBW \geq RBW
- 4. Sweep time = As necessary to capture the entire dwell time per hopping channel
- 5. Detector = Peak
- 6. Trace mode = Free Run
- 7. Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time. An oscilloscope may be used instead of a spectrum analyzer. The EUT shall show compliance with the appropriate regulatory limit for the number of hopping channels. A plot of the data shall be included in the test report.


11.3 Measurement Setup (Block Diagram of Configuration)



11.4 Measurement Result

Test Data of Dwell Time								
Channel	Time of Pulse for 3DH5 (ms)	Number of hops in the period specified in the requirements	Dwell Time (ms)	Limit (ms)	Pass or Fail			
2402	2.892	25.0*4	289.200	400	Pass			
2441	2.892	30.0*4	347.040	400	Pass			
2480	2.892	27.0*4	312.336	400	Pass			







Test Graphs of Dwell Time











Note: All mode rates are tested and evaluated, 8DPSK modulated 3DH5 mode is the worst case and documented in the report.