

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a LumiTek Neon Beast Monster Truck/LumiTek 1:10 Neon Giant operating at 2.4G Band. The EUT can be powered by DC 3.0V (2 x 1.5V AA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Modulation Type: GFSK

Antenna Gain: 0dBi

The nominal conducted output power specified: -25.0 dBm (± 3 dB)

The nominal radiated output power (e.i.r.p) specified: -25.0 dBm (± 3 dB)

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 71.0 dB μ V/m at 3m in the frequency 2410MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -24.23dBm

which is within the production variation.

The Minimum peak radiated emission for the EUT is 69.7 dB μ V/m at 3m in the frequency 2470MHz

The EIRP = $[(FS \cdot D)^2 / 30]$ mW = -25.53dBm

which is within the production variation.

The maximum conducted output power specified is -22dBm= 0.006mW

The source- based time-averaging conducted output power
=0.006* Duty cycle mW <0.006 mW(Duty cycle <100%)

The SAR Exclusion Threshold Level:

$$\begin{aligned} P_{th}(\text{mW}) &= ERP_{20\text{cm}} * (d/20\text{cm})^X \quad (X = -\log_{10} \left(\frac{60}{ERP_{20\text{cm}} \sqrt{f}} \right)) \\ &= 3060 * (0.5/20)^{1.9} \text{ mW} \\ &= 2.72 \text{ mW} \end{aligned}$$

Since max. power of the source-based time-averaging conducted output power and effective radiated power (ERP) is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 29.5652ms

Effective period of the cycle = 1.8841ms

DC = 1.8841ms / 29.5652ms = 0.0637 or 6.37%