

FCC 47 CFR PART 15 SUBPART C

CERTIFICATION TEST REPORT

For

Air Purifier

Model No.: Kilo, Miro, Gala, Oly, Alan

FCC ID: 2ATIZKILO

Trademark: N/A

REPORT NO.: ES190806013E

ISSUE DATE: August 30, 2019

Prepared for

Zhongshan Invitop Electrical Co.,Ltd.

B-6F, NO.6, Xinhua Road, Sanjiao Town, Zhongshan, Guandong P.R.C

Prepared by

EMTEK (SHENZHEN) CO., LTD.

Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen,
Guangdong, China

TEL: 86-755-26954280

FAX: 86-755-26954282

TABLE OF CONTENTS

1	TEST RESULT CERTIFICATION	3
2	EUT TECHNICAL DESCRIPTION	4
3	SUMMARY OF TEST RESULT	6
4	TEST METHODOLOGY	7
4.1	GENERAL DESCRIPTION OF APPLIED STANDARDS	7
4.2	MEASUREMENT EQUIPMENT USED	7
4.3	DESCRIPTION OF TEST MODES	8
5	FACILITIES AND ACCREDITATIONS	9
5.1	FACILITIES.....	9
5.2	LABORATORY ACCREDITATIONS AND LISTINGS	9
6	TEST SYSTEM UNCERTAINTY	10
7	SETUP OF EQUIPMENT UNDER TEST	11
7.1	RADIO FREQUENCY TEST SETUP 1.....	11
7.2	RADIO FREQUENCY TEST SETUP 2.....	11
7.3	CONDUCTED EMISSION TEST SETUP	12
7.4	SUPPORT EQUIPMENT.....	12
8	TEST REQUIREMENTS	13
8.1	DTS (6DB) BANDWIDTH.....	13
8.2	MAXIMUM PEAK CONDUCTED OUTPUT POWER	19
8.3	MAXIMUM POWER SPECTRAL DENSITY	20
8.4	UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS.....	26
8.5	RADIATED SPURIOUS EMISSION	31
8.6	CONDUCTED EMISSION TEST	43

1 TEST RESULT CERTIFICATION

Applicant:	Zhongshan Invitop Electrical Co.,Ltd. B-6F, NO.6, Xinhua Road, Sanjiao Town, Zhongshan, Guandong P.R.C
Manufacturer:	Zhongshan Invitop Electrical Co.,Ltd. B-6F, NO.6, Xinhua Road, Sanjiao Town, Zhongshan, Guandong P.R.C
Product Description:	Air Purifier
Model Number:	Kilo, Miro, Gala, Oly, Alan (Note: All models are the same except the appearance and structure. Here Kilo was selected for full test.)
Trade Mark:	N/A
File Number:	ES190806013E
Date of Test:	August 01, 2019 to August 23, 2019

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2, Subpart J:2018 FCC 47 CFR Part 15, Subpart C:2018	PASS

The above equipment was tested by EMTEK (SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 2018 and Part 15.247 2018

The test results of this report relate only to the tested sample identified in this report.

Date of Test : August 01, 2019 to August 23, 2019

Abel Wu

Prepared by:

Abel Wu /Editor

Yaping Shen

Reviewer:

Yaping Shen /Supervisor



[Signature]

Approve & Authorized Signer :

Lisa Wang/Manager

2 EUT TECHNICAL DESCRIPTION

Characteristics	Description
IEEE 802.11 WLAN Mode Supported:	<input checked="" type="checkbox"/> 802.11b(20MHz channel bandwidth) <input checked="" type="checkbox"/> 802.11g(20MHz channel bandwidth) <input checked="" type="checkbox"/> 802.11n(20MHz channel bandwidth) <input type="checkbox"/> 802.11n(40MHz channel bandwidth)
Data Rate:	<input checked="" type="checkbox"/> 802.11 b:1,2,5.5,11Mbps; <input checked="" type="checkbox"/> 802.11 g:6,9,12,18,24,36,48,54Mbps; <input checked="" type="checkbox"/> 802.11n(HT20):MCS0-MCS7; <input type="checkbox"/> 802.11n(HT40):MCS0-MCS7;
Modulation:	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;
Operating Frequency Range:	<input checked="" type="checkbox"/> 2412-2462MHz for 802.11b/g; <input checked="" type="checkbox"/> 2412-2462MHz for 802.11n(HT20); <input type="checkbox"/> 2422-2452MHz for 802.11n(HT40);
Number of Channels:	<input checked="" type="checkbox"/> 11 channels for 802.11b/g; <input checked="" type="checkbox"/> 11 channels for 802.11n(HT20); <input type="checkbox"/> 7 channels for 802.11n(HT40);
Transmit Power Max:	17.99dBm
Antenna Type:	PCB Antenna
Antenna Gain:	3dBi
Power supply:	Switching Adapter Model: GQ24-240120-AG Input: AC 100-240V, 50/60Hz, 1.0A Max Output: DC 24V, 1.2A
Smart system	SISO for 802.11b/g/n

Note: for more details, please refer to the User's manual of the EUT.

Modified Information

Version.	Summary	Date of Rev.	Report No.
Ver.1.0	Original Report	\	ES190806013E

3 SUMMARY OF TEST RESULT

FCC Part Clause	Test Parameter	Verdict	Remark
15.247(a)(2)	DTS (6dB) Bandwidth	PASS	
15.247(b)(3)	Maximum Peak Conducted Output Power	PASS	
15.247(e)	Maximum Power Spectral Density Level	PASS	
15.247(d)	Unwanted Emission Into Non-Restricted Frequency Bands	PASS	
15.247(d) 15.209	Unwanted Emission Into Restricted Frequency Bands	PASS	
15.247(d) 15.209	Radiated Spurious Emission	PASS	
15.207	Conducted Emission Test	PASS	
15.247(b)	Antenna Application	PASS	
NOTE1: N/A (Not Applicable) NOTE2: According to FCC OET KDB 558074, the report use radiated measurements in the restricted frequency bands. In addition, the radiated test is also performed to ensure the emissions emanating from the device cabinet also comply with the applicable limits.			

RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2ATIZKILO filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

4 TEST METHODOLOGY

4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart C

FCC KDB 558074 D01 15.247 Meas Guidance V05r02

FCC KDB 662911 D01 Multiple Transmitter Output v02or01

FCC KDB 662911 D02 MIMO With Cross Polarized Antenna V01

4.2 MEASUREMENT EQUIPMENT USED

4.2.1 Conducted Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	DUE CAL.
Test Receiver	Rohde & Schwarz	ESCS30	828985/018	05/18/2019	May 17, 2020
L.I.S.N.	Schwarzbeck	NNLK8129	8129203	05/18/2019	May 17, 2020
50Ω Coaxial Switch	Anritsu	MP59B	M20531	05/18/2019	May 17, 2020
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100006	05/18/2019	May 17, 2020
Voltage Probe	Rohde & Schwarz	TK9416	N/A	05/18/2019	May 17, 2020
I.S.N	Rohde & Schwarz	ENY22	1109.9508.02	05/18/2019	May 17, 2020

4.2.2 Radiated Emission Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	DUE CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	May 19, 2019	May 18, 2020
Pre-Amplifier	HP	8447F	2944A07999	May 18, 2019	May 17, 2020
Bilog Antenna	Schwarzbeck	VULB9163	142	May 18, 2019	May 17, 2020
Loop Antenna	ARA	PLA-1030/B	1029	May 18, 2019	May 17, 2020
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170399	May 19, 2019	May 18, 2020
Horn Antenna	Schwarzbeck	BBHA 9120	D143	May 18, 2019	May 17, 2020
Cable	Schwarzbeck	AK9513	ACRX1	May 19, 2019	May 18, 2020
Cable	Rosenberger	N/A	FP2RX2	May 19, 2019	May 18, 2020
Cable	Schwarzbeck	AK9513	CRPX1	May 19, 2019	May 18, 2020
Cable	Schwarzbeck	AK9513	CRRX2	May 19, 2019	May 18, 2020

4.2.3 Radio Frequency Test Equipment

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LASTCAL.	DUE CAL.
EMI Test Receiver	Rohde & Schwarz	ESU	1302.6005.26	May 19, 2019	May 18, 2020
Spectrum Analyzer	Agilent	E4407B	88156318	May 19, 2019	May 18, 2020
Signal Analyzer	Agilent	N9010A	My53470879	May 19, 2019	May 18, 2020
Power meter	Anritsu	ML2495A	0824006	May 19, 2019	May 18, 2020
Power sensor	Anritsu	MA2411B	0738172	May 19, 2019	May 18, 2020

Remark: Each piece of equipment is scheduled for calibration once a year.

4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Those data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0) were used for all test.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The Y-plane results were found as the worst case and were shown in this report.

Frequency and Channel list for 802.11b/g/n (HT20):

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

Test Frequency and Channel for 802.11b/g/n (HT20):

Lowest Frequency		Middle Frequency		Highest Frequency	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	6	2437	11	2462

Note:Duty cycle>98%

5 FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

Bldg 69, Majialong Industry Zone District, Nanshan District, Shenzhen, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

5.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab. : Accredited by CNAS, 2018.11.30
The certificate is valid until 2022.10.28
The Laboratory has been assessed and proved to be in compliance with
CNAS-CL01:2018 (identical to ISO/IEC 17025:2017)
The Certificate Registration Number is L2291.

Accredited by TUV Rheinland Shenzhen 2016.5.19
The Laboratory has been assessed according to the requirements
ISO/IEC 17025.

Accredited by FCC, August 06, 2018
The certificate is valid until August 07, 2020
Designation Number: CN1204
Test Firm Registration Number: 882943

Accredited by A2LA, August 08, 2018
The certificate is valid until August 31, 2020
The Certificate Number is 4321.01.

Name of Firm : EMTEK (SHENZHEN) CO., LTD.
Site Location : Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen,
Guangdong, China

TEST SOFTWARE

Item	Software
Conducted Emission	: EMTEK(Ver.CON-03A1)-Shenzhen
Radiated Emission	: EMTEK(Ver.RA-03A1)-Shenzhen

6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:


Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-5}$
Maximum Peak Output Power Test	$\pm 1.0\text{dB}$
Conducted Emissions Test	$\pm 2.0\text{dB}$
Radiated Emission Test	$\pm 2.0\text{dB}$
Power Density	$\pm 2.0\text{dB}$
Occupied Bandwidth Test	$\pm 1.0\text{dB}$
Band Edge Test	$\pm 3\text{dB}$
All emission, radiated	$\pm 3\text{dB}$
Antenna Port Emission	$\pm 3\text{dB}$
Temperature	$\pm 0.5^{\circ}\text{C}$
Humidity	$\pm 3\%$

Measurement Uncertainty for a level of Confidence of 95%

7 SETUP OF EQUIPMENT UNDER TEST

7.1 RADIO FREQUENCY TEST SETUP 1

The WLAN component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.




7.2 RADIO FREQUENCY TEST SETUP 2


The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




7.3 CONDUCTED EMISSION TEST SETUP

The mains cable of the EUT (Air Purifier) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



7.4 SUPPORT EQUIPMENT

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	iPhone	Apple	iPhone 5C/A1526	N/A	

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

8 TEST REQUIREMENTS

8.1 DTS (6DB) BANDWIDTH

8.1.1 Applicable Standard

According to FCC Part 15.247(a)(2) and 558074 D01 15.247 Meas Guidance V05r02

8.1.2 Conformance Limit

The minimum -6 dB bandwidth shall be at least 500 kHz.

8.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.1.4 Test Procedure

The EUT was operating in IEEE 802.11b/g/n mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 100 kHz.

Set the video bandwidth (VBW) =300 kHz.

Set Span=2 times OBW

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

Allow the trace to stabilize.

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Measure and record the results in the test report.

8.1.5 Test Results

Temperature: 24°C
Humidity: 53 %


Test Date: Aug 20, 2019
Test By: XW

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Bandwidth (MHz)	Limit (kHz)	Verdict
802.11b	1	2412	8.122	>500	PASS
	6	2437	8.132	>500	PASS
	11	2462	8.130	>500	PASS
802.11g	1	2412	16.38	>500	PASS
	6	2437	16.38	>500	PASS
	11	2462	16.38	>500	PASS
802.11n (HT20)	1	2412	17.62	>500	PASS
	6	2437	17.59	>500	PASS
	11	2462	17.22	>500	PASS


Test Model	DTS (6dB) Bandwidth
	802.11b
	Channel 1: 2412MHz




Test Model	DTS (6dB) Bandwidth
	802.11b
	Channel 6: 2437MHz




Test Model	DTS (6dB) Bandwidth
	802.11b
	Channel 11: 2462MHz




Test Model	DTS (6dB) Bandwidth
	802.11g
	Channel 1: 2412MHz




Test Model	DTS (6dB) Bandwidth
	802.11g
	Channel 6: 2437MHz




Test Model	DTS (6dB) Bandwidth
	802.11g
	Channel 11: 2462MHz




Test Model	DTS (6dB) Bandwidth
	802.11n (HT20)
	Channel 1: 2412MHz



Test Model	DTS (6dB) Bandwidth
	802.11n (HT20)
	Channel 6: 2437MHz





8.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER

8.2.1 Applicable Standard

According to FCC Part 15.247(b)(3) and 558074 D01 15.247 Meas Guidance V05r02

8.2.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm).

8.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.2.4 Test Procedure

■ According to FCC Part 15.247(b)(3)

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum output power setting and enable the EUT transmit continuously.

Measure the conducted output power with cable loss and record the results in the test report.

Measure and record the results in the report.

■ According to FCC Part 15.247(b)(4):

Conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note: If antenna Gain exceeds 6 dBi, then Output power Limit = 30 (Gain - 6)

8.2.5 Test Results

Temperature: 24°C
Humidity: 53 %

Test Date: Aug 20, 2019
Test By: XW

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm)	Limit (dBm)	Verdict
802.11b	1	2412	17.64	30	PASS
	6	2437	16.69	30	PASS
	11	2462	17.03	30	PASS
802.11g	1	2412	17.39	30	PASS
	6	2437	16.55	30	PASS
	11	2462	16.91	30	PASS
802.11n (HT20)	1	2412	17.39	30	PASS
	6	2437	16.53	30	PASS
	11	2462	16.86	30	PASS

8.3 MAXIMUM POWER SPECTRAL DENSITY

8.3.1 Applicable Standard

According to FCC Part 15.247(e) and 558074 D01 15.247 Meas Guidance V05r02

8.3.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

8.3.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.3.4 Test Procedure

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance

The transmitter output (antenna port) was connected to the spectrum analyzer

Set analyzer center frequency to DTS channel center frequency.

Set the span to 1.5 times the DTS bandwidth.

Set the RBW to: 3 kHz

Set the VBW to: 10 kHz.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum amplitude level within the RBW.

Note: If antenna Gain exceeds 6 dBi, then PSD Limit=8 (Gain- 6)


8.3.5 Test Results

Temperature: 24°C
Humidity: 53 %


Test Date: Aug 20, 2019
Test By: XW

Operation Mode	Channel Number	Channel Frequency (MHz)	Measurement Level (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
802.11b	1	2412	-9.99	8	PASS
	6	2437	-11.084	8	PASS
	11	2462	-10.748	8	PASS
802.11g	1	2412	-14.795	8	PASS
	6	2437	-15.698	8	PASS
	11	2462	-15.373	8	PASS
802.11n (HT20)	1	2412	-16.053	8	PASS
	6	2437	-16.877	8	PASS
	11	2462	-16.521	8	PASS


Test Model	Power Spectral Density
	802.11b
	Channel 1: 2412MHz




Test Model	Power Spectral Density
	802.11b
	Channel 6: 2437MHz




Test Model	Power Spectral Density
	802.11b
	Channel 11: 2462MHz




Test Model	Power Spectral Density
	802.11g
	Channel 1: 2412MHz




Test Model	Power Spectral Density
	802.11g
	Channel 6: 2437MHz




Test Model	Power Spectral Density
	802.11g
	Channel 11: 2462MHz




Test Model	Power Spectral Density
	802.11n (HT20)
	Channel 1: 2412MHz



Test Model	Power Spectral Density
	802.11n (HT20)
	Channel 6: 2437MHz





8.4 UNWANTED EMISSIONS INTO NON-RESTRICTED FREQUENCY BANDS

8.4.1 Applicable Standard

According to FCC Part 15.247(d) and 558074 D01 15.247 Meas Guidance V05r02

8.4.2 Conformance Limit

According to FCC Part 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

8.4.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

8.4.4 Test Procedure

The transmitter output (antenna port) was connected to the spectrum analyzer

■ Reference level measurement

Establish a reference level by using the following procedure:

Set instrument center frequency to DTS channel center frequency.

Set the span to ≥ 1.5 times the DTS bandwidth.

Set the RBW = 100 kHz.

Set the VBW $\geq 3 \times$ RBW.

Set Detector = peak.

Set Sweep time = auto couple.

Set Trace mode = max hold.

Allow trace to fully stabilize.

Use the peak marker function to determine the maximum PSD level.

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.

■ Emission level measurement

Set the center frequency and span to encompass frequency range to be measured.

Set the RBW = 100 kHz.

Set the VBW = 300 kHz.

Set Detector = peak

Sweep time = auto couple.

Trace mode = max hold.


Allow trace to fully stabilize.


Use the peak marker function to determine the maximum amplitude level.


Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements. Report the three highest emissions relative to the limit.

8.4.5 Test Results

All the modulation modes were tested, the data of the worst mode(802.11b) are described in the following table








Test Model	Band edge
	802.11b
	Channel 1: 2412MHz



Test Model	Band edge
	802.11b
	Channel 11: 2462MHz



8.5 RADIATED SPURIOUS EMISSION

8.5.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and 558074 D01 15.247 Meas Guidance V05r02

8.5.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

According to FCC Part 15.205, Restricted bands

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

According to FCC Part 15.205, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBμV/m)	Measurement Distance
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300
0.490~1.705	2400/F(KHz)	20 log (uV/m)	30
1.705~30.0	30	29.5	30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Remark: 1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. Distance extrapolation factor =40log(Specific distance/ test distance)(dB);

Limit line=Specific limits(dBuV) + distance extrapolation factor.

for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10*lg(100 [kHz]/narrower RBW [kHz]). , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.

8.5.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

8.5.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

For Above 1GHz:

The EUT was placed on a turn table which is 1.5m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz

VBW \geq RBW for peak measurement

VBW = 10Hz for Average measurement

Sweep = auto

Detector function = peak

Trace = max hold

For Below 1GHz:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 100 kHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from $20\log(\text{dwell time}/100 \text{ ms})$, in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

8.5.5 Test Results


■ Spurious Emission below 30MHz (9KHz to 30MHz)

Test mode: TX Mode

Freq. (MHz)	Ant. Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
--	--	--	--	--	--	--	--

■ Spurious Emission Below 1GHz (30MHz to 1GHz)

All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11b recorded was report as below:



Site Radiated Emission 3m #1

Polarization: **Horizontal**

Temperature: 24

Limit: FCC Part15 Class B 3M Radiation


Power: AC 120V/60Hz

Humidity: 55 %

Mode:TX (802.11g, 2412MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		56.0007	41.59	-20.04	21.55	40.00	-18.45	QP		
2		87.4175	47.03	-24.34	22.69	40.00	-17.31	QP		
3		90.2202	47.18	-23.25	23.93	43.50	-19.57	QP		
4		116.1320	47.43	-22.85	24.58	43.50	-18.92	QP		
5	*	119.8555	52.36	-23.57	28.79	43.50	-14.71	QP		
6		168.4137	49.15	-25.34	23.81	43.50	-19.69	QP		



Site Radiated Emission 3m #1

Polarization: **Vertical**

Temperature: 24

Limit: FCC Part15 Class B 3M Radiation


Power: AC 120V/60Hz

Humidity: 55 %


Mode:TX (802.11g, 2412MHz)

Note:


No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		39.9941	46.76	-20.68	26.08	40.00	-13.92	QP		
2	*	56.0007	49.04	-20.04	29.00	40.00	-11.00	QP		
3		70.5835	48.33	-24.26	24.07	40.00	-15.93	QP		
4		104.1701	47.28	-21.20	26.08	43.50	-17.42	QP		
5		116.1320	48.23	-22.85	25.38	43.50	-18.12	QP		
6		120.2766	53.02	-23.62	29.40	43.50	-14.10	QP		




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		56.0007	41.39	-20.04	21.35	40.00	-18.65	QP		
2		85.5975	45.32	-25.12	20.20	40.00	-19.80	QP		
3		87.7246	47.21	-24.22	22.99	40.00	-17.01	QP		
4		89.9046	47.77	-23.29	24.48	43.50	-19.02	QP		
5	*	119.8555	52.45	-23.57	28.88	43.50	-14.62	QP		
6		184.4898	47.65	-23.87	23.78	43.50	-19.72	QP		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		39.9941	47.02	-20.68	26.34	40.00	-13.66	QP		
2	*	56.0007	48.79	-20.04	28.75	40.00	-11.25	QP		
3		70.8315	48.59	-24.34	24.25	40.00	-15.75	QP		
4		104.1701	46.76	-21.20	25.56	43.50	-17.94	QP		
5		119.8555	52.64	-23.57	29.07	43.50	-14.43	QP		
6		147.9214	51.98	-25.32	26.66	43.50	-16.84	QP		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		56.0007	42.08	-20.04	22.04	40.00	-17.96	QP		
2		87.4176	46.08	-24.34	21.74	40.00	-18.26	QP		
3		104.1701	45.37	-21.20	24.17	43.50	-19.33	QP		
4	*	119.8556	52.54	-23.57	28.97	43.50	-14.53	QP		
5		168.4137	49.09	-25.34	23.75	43.50	-19.75	QP		
6		793.3958	35.61	-8.24	27.37	46.00	-18.63	QP		



Site Radiated Emission 3m #1

Polarization: **Vertical**

Temperature: 24

Limit: FCC Part15 Class B 3M Radiation

Power: AC 120V/60Hz

Humidity: 55 %

Mode: TX (802.11g, 2462MHz)

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		39.9942	46.36	-20.68	25.68	40.00	-14.32	QP		
2	*	56.0007	49.63	-20.04	29.59	40.00	-10.41	QP		
3		69.8449	47.50	-24.02	23.48	40.00	-16.52	QP		
4		104.1701	47.09	-21.20	25.89	43.50	-17.61	QP		
5		116.1321	47.62	-22.85	24.77	43.50	-18.73	QP		
6		119.8556	54.27	-23.57	30.70	43.50	-12.80	QP		

■ Spurious Emission Above 1GHz (1GHz to 25GHz)

All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11b recorded was report as below:

Temperature: 24°C Test Date: Aug 05, 2019
 Humidity: 53 % Test By: XW
 Test mode: 802.11b Frequency: Channel 1: 2412MHz

Freq. (MHz)	Ant.Po l. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4824.000	V	47.59	42.58	74.00	54.00	-26.41	-11.42
5522.000	V	41.29	26.40	74.00	54.00	-32.71	-27.60
9772.000	V	50.00	34.50	74.00	54.00	-24.00	-19.50
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4824.000	H	46.03	41.01	74.00	54.00	-27.97	-12.99
7970.000	H	47.23	32.50	74.00	54.00	-26.77	-21.50
10639.000	H	52.75	37.40	74.00	54.00	-21.25	-16.60

Test mode: 802.11b Frequency: Channel 6: 2437MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4874.00	V	43.94	38.86	74.00	54.00	-30.06	-15.14
7766.00	V	46.97	31.60	74.00	54.00	-27.03	-22.40
10622.00	V	52.04	36.90	74.00	54.00	-21.96	-17.10
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4874.000	H	45.09	39.05	74.00	54.00	-28.91	-14.95
5777.000	H	41.81	26.80	74.00	54.00	-32.19	-27.20
10639.00	H	52.75	37.50	74.00	54.00	-21.25	-16.50

Test mode: 802.11b Frequency: Channel 11: 2462MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level(dBuV/m)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4924.000	V	46.78	41.68	74.00	54.00	-27.22	-12.32
8004.000	V	46.74	30.20	74.00	54.00	-27.26	-23.80
10826.00	V	53.59	39.80	74.00	54.00	-20.41	-14.20
--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--
4924.000	H	46.73	41.67	74.00	54.00	-27.27	-12.33
7392.000	H	45.13	29.80	74.00	54.00	-28.87	-24.20
10350.00	H	51.40	36.40	74.00	54.00	-22.60	-17.60

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

(2) Emission Level= Reading Level+Probe Factor +Cable Loss.

(3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

■ All modes 2.4G 802.11b/g/n have been tested, and the worst result 802.11b recorded was report as below:

Temperature : 28°C Test Date : Aug 05, 2019
Humidity : 55 % Test By: XW
Test mode: 802.11b Frequency: Channel 1: 2412MHz

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Margin (dB)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)	Margin (dB)
2386.480	H	53.56	74.00	-20.44	39.63	54.00	-14.37
2386.240	V	53.74	74.00	-20.26	37.91	54.00	-16.09

Temperature : 28°C Test Date : Aug 05, 2019
Humidity : 55 % Test By: XW
Test mode: 802.11b Frequency: Channel 11: 2462MHz

Frequency (MHz)	Polarity	PK(dBuV/m) (VBW=3MHz)	Limit 3m (dBuV/m)	Margin (dB)	AV(dBuV/m) (VBW=10Hz)	Limit 3m (dBuV/m)	Margin (dB)
2483.682	H	51.84	74.00	-22.16	38.10	54.00	-15.90
2488.202	V	50.93	74.00	-23.07	36.33	54.00	-17.67


- Note:** (1) All Readings are Peak Value (VBW=3MHz) and Average Value (VBW=10Hz).
(2) Emission Level= Reading Level+Probe Factor +Cable Loss.
(3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

Test Model

Spurious Emission in Restricted Band 2310-2390MHz
802.11b

Channel 1: 2412MHz

H




Test Model

Spurious Emission in Restricted Band 2483.5-2500MHz
802.11b

Channel 1: 2412MHz


V



Test Model

Spurious Emission in Restricted Band 2310-2390MHz
802.11b
Channel 11: 2462MHz


H



Test Model

Spurious Emission in Restricted Band 2483.5-2500MHz
802.11b
Channel 11: 2462MHz

V



8.6 CONDUCTED EMISSION TEST

8.6.1 Applicable Standard

According to FCC Part 15.207(a)

8.6.2 Conformance Limit

Conducted Emission Limit		
Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50
Note: 1. The lower limit shall apply at the transition frequencies 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.		

8.6.3 Test Configuration


Test according to clause 7.3 conducted emission test setup

8.6.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.
 Maximum procedure was performed on the highest emissions to ensure EUT compliance.
 Repeat above procedures until all frequency measured were complete.

8.6.5 Test Results

PASS.



Site site #1

Phase: **L1**

Temperature: 24

Limit: (CE)FCC PART 15 class B_QP


Power: AC 120V/60Hz

Humidity: 55 %

Mode: Wifi Working


Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1500	43.90	10.10	54.00	66.00	-12.00	QP	
2		0.1500	16.60	10.10	26.70	56.00	-29.30	AVG	
3		0.1900	40.90	10.09	50.99	64.04	-13.05	QP	
4		0.1900	23.90	10.09	33.99	54.04	-20.05	AVG	
5		0.2580	39.10	10.09	49.19	61.50	-12.31	QP	
6		0.2580	19.90	10.09	29.99	51.50	-21.51	AVG	
7		0.5060	29.00	10.07	39.07	56.00	-16.93	QP	
8		0.5060	14.20	10.07	24.27	46.00	-21.73	AVG	
9		2.5420	27.00	10.15	37.15	56.00	-18.85	QP	
10		2.5420	10.00	10.15	20.15	46.00	-25.85	AVG	
11	*	15.8920	37.80	10.56	48.36	60.00	-11.64	QP	
12		15.8920	23.50	10.56	34.06	50.00	-15.94	AVG	



Site site #1 Phase: **N** Temperature: 24
 Limit: (CE)FCC PART 15 class B_QP Power: AC 120V/60Hz Humidity: 55 %
 Mode: Wifi Working
 Note:

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1540	43.60	10.10	53.70	65.78	-12.08	QP	
2	0.1540	17.60	10.10	27.70	55.78	-28.08	AVG	
3	0.1860	41.80	10.09	51.89	64.21	-12.32	QP	
4	0.1860	19.20	10.09	29.29	54.21	-24.92	AVG	
5	0.2540	36.90	10.09	46.99	61.63	-14.64	QP	
6	0.2540	18.70	10.09	28.79	51.63	-22.84	AVG	
7	0.3700	31.30	10.08	41.38	58.50	-17.12	QP	
8	0.3700	10.70	10.08	20.78	48.50	-27.72	AVG	
9	3.8020	26.40	10.25	36.65	56.00	-19.35	QP	
10	3.8020	9.90	10.25	20.15	46.00	-25.85	AVG	
11 *	15.5200	38.50	10.55	49.05	60.00	-10.95	QP	
12	15.5200	24.20	10.55	34.75	50.00	-15.25	AVG	



Site site #1

Phase: **N**

Temperature: 24

Limit: (CE)FCC PART 15 class B_QP


Power: AC 240V/50Hz

Humidity: 55 %

Mode: Wifi Working

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1820	43.20	10.09	53.29	64.39	-11.10	QP	
2		0.1820	17.70	10.09	27.79	54.39	-26.60	AVG	
3	*	0.1980	43.90	10.09	53.99	63.69	-9.70	QP	
4		0.1980	23.50	10.09	33.59	53.69	-20.10	AVG	
5		0.4660	30.30	10.07	40.37	56.58	-16.21	QP	
6		0.4660	12.50	10.07	22.57	46.58	-24.01	AVG	
7		0.7540	27.50	10.03	37.53	56.00	-18.47	QP	
8		0.7540	6.80	10.03	16.83	46.00	-29.17	AVG	
9		3.9580	28.10	10.27	38.37	56.00	-17.63	QP	
10		3.9580	11.50	10.27	21.77	46.00	-24.23	AVG	
11		15.4840	39.50	10.55	50.05	60.00	-9.95	QP	
12		15.4840	27.00	10.55	37.55	50.00	-12.45	AVG	



Site site #1

Phase: L1

Temperature: 24

Limit: (CE)FCC PART 15 class B_QP

Power: AC 240V/50Hz

Humidity: 55 %

Mode: Wifi Working

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1660	43.20	10.10	53.30	65.16	-11.86	QP	
2		0.1660	18.20	10.10	28.30	55.16	-26.86	AVG	
3		0.1820	43.30	10.09	53.39	64.39	-11.00	QP	
4		0.1820	22.60	10.09	32.69	54.39	-21.70	AVG	
5		0.2500	39.60	10.09	49.69	61.76	-12.07	QP	
6		0.2500	23.10	10.09	33.19	51.76	-18.57	AVG	
7		0.5380	33.70	10.06	43.76	56.00	-12.24	QP	
8		0.5380	17.90	10.06	27.96	46.00	-18.04	AVG	
9		0.7980	29.10	10.02	39.12	56.00	-16.88	QP	
10		0.7980	8.20	10.02	18.22	46.00	-27.78	AVG	
11	*	15.9120	39.60	10.56	50.16	60.00	-9.84	QP	
12		15.9120	25.30	10.56	35.86	50.00	-14.14	AVG	

8.7 ANTENNA APPLICATION

8.7.1 Antenna Requirement

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

For intentional device, according to IC RSS-Gen 8.3, testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level.⁹ When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.

8.7.2 Result

The EUT'S antenna is a PCB antenna. The antenna's gain is 3 dBi, which in accordance to section 15.203, please refer to the internal photos.

END OF REPORT