

**Prüfbericht - Nr.:****14041785 001****Seite 1 von 1**

Test Report No.:

Page 1 of 1

**Maximum transmitter power:**

Frequency (MHz)	Maximum peak output power (dBuV/m)	Output power (mW)
49.860	72.4	0.0052

According to KDB 447498 D01:

For frequencies below 100 MHz, the following may be considered for SAR test exclusion:

- 1) For test separation distances > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by  $[1 + \log(100/f(\text{MHz}))]$
- 2) For test separation distances  $\leq 50$  mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by  $\frac{1}{2}$
- 3) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any SAR test results below 100 MHz to be acceptable.

**Result:**

$$\begin{aligned}\text{Exclusion threshold} &= 3 \times [1 + \log(100/f(\text{MHz}))] \times 0.5 \\ &= 3 \times [1 + \log(100/49.86)] \times 0.5 \\ &= 1.9536\text{mW}\end{aligned}$$

**Conclusion:**

SAR test is not required due to maximum peak output power of the RF channel below the exclusion threshold as calculated above.