

Test Report No.: FCC2021-0013-EX

TEST REPORT

FCC ID		2AWMK-BTP-MK
Applicant	:	Guangzhou Pinzhong Electronic Technology CO., Ltd.
Product Name	:	BEITONG IOS GAME CONTROLLER EX
Mode No.	:	BTP-iG6

CVC Testing Technology Co., Ltd.

Applicant		Name: Guangzhou Pinzhong Electronic Technology CO., Ltd. Address: Room 611-612, Greenland Center of Financial City, No. 662, Huangpu Avenue Middle Road, Tianhe District, Guangzhou City, Guangdong Province, China					
Manufacturer	Name: Guangzhou Pinzhong Electronic Technology CO., Ltd. Address: Room 611-612, Greenland Center of Financial City, No. 662, Huangpu Avenue Middle Road, Tianhe District, Guangzhou City, Guangdong Province, China						
Equipment Under Test		Product Name : BEITONG IOS GAME CONTROLLER EX Model No. : BTP-IG6 Trade mark : FEBEITONG Serial no. : 430-624-010					
Date of Receipt.	.08	<u> </u>	Date of Testing	2021.06.08	-2021.07.26		
Test Specification				Test Result			
FCC Part 2 (Section 2.1093) KDB 447498 D01 IEEE C95.1				PASS			
Evaluation of Te	The equipment under test was found to comply with the requirements of the standards applied. Seal of CVC Issue Date: 2021.07.26				with the VC 2021.07.26		
Tested by:		Reviewed by:		Approved by:			
Xu Zhenfei		Liu Yonghai		Chen Huawen			
Xu Zhanfei		Lin yonghai			Chenturan		
Other Aspects: NO	NE.						
Abbreviations:OK, Pas	ss= passed	Fail = failed	I/A= not appl	licable EUT= equ	iipment, sample(s) u	nder tested	
This test report relates o	nly to the EUT, a	nd shall not be repr	roduced ex	cept in full, without wri	tten approval of	CVC.	

TABLE OF CONTENTS

1.	GEN	ERAL PRODUCT INFORMATION	4
	1.1	GENERAL INFORMATION	4
2.	HUM	IAN EXPOSURE ASSESSMENT	5
	2.1 2.2	RF EXPOSURE DEFINE	5 5
3.	RF C	DUTPUT POWER	6
4.	TES	T RESULTS	7

1. General Product Information 1.1 General information

Product Name	BEITONG IOS GAME CONTROLLER EX			
Model No.	BTP-iG6			
Power Supply	Adapter	DC 5V		
	Battery	DC 3.7V		
Antenna Type	PCB antenna			
Antenna Gain	Antenna 1: 1.5 dBi (provided by client)			
Beamforming gain	Unsupported			
Frequency Range	2402~2480MHz			
Operate Temp.Range	-20°C to +60°C			
Note:				
 The information of the EUT is declared by the manufacturer. 				

2. The laboratory is not responsible for the product technical specification provided by the client.

2. Human Exposure Assessment

2.1 RF EXPOSURE DEFINE

The corresponding SAR Exclusion Threshold condition, listed below:

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance,

mm)] $\left[\sqrt{f(GHz)}\right] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,16 where

- f(GHz) is the RF channel transmit frequency in GHz
- > Power and distance are rounded to the nearest mW and mm before calculation
- > The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

- 2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following:
 - a) [Threshold at 50 mm in step 1) + (test separation distance 50 mm)·(f(MHz)/150)] mW, at 100MHz to 1500 MHz
 - b) [Threshold at 50 mm in step 1) + (test separation distance 50 mm) \cdot 10] mW at > 1500 MHz and ≤ 6 GHz
- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.
 - a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by [1 + log(100/f(MHz))] for test separation distances > 50 mm and < 200 mm.
 - b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by ½ for test separation distances ≤ 50 mm.
 - c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

2.2 CLASSIFICATION

The antenna of this product, under normal use condition, is at less than 20cm away from the body of the user. So, this device is classified as Portable Device.

3. RF Output Power

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
BT(DH5)	2402-2480MHz	-1.50	+-2	-3.50	0.50
BT(2DH5)	2402-2480MHz	-5.00	+-2	-7.00	-3.00
BT(3DH5)	2402-2480MHz	-4.50	+-2	-6.50	-2.50

The conducted power turn-up tolerance reference manufacturer specification.

Test Mode	Antenna	Center Frequency[MHz]	Result[dBm]	Limit[dBm]	Verdict
		2402	-3.41	<=30	PASS
DH5	Ant1	2441	-0.1	<=30	PASS
		2480	0.13	<=30	PASS
	Ant1	2402	-6.45	<=20.97	PASS
2DH5		2441	-3.26	<=20.97	PASS
		2480	-3.16	<=20.97	PASS
	Ant1	2402	-6.46	<=20.97	PASS
3DH5		2441	-3.02	<=20.97	PASS
		2480	-2.74	<=20.97	PASS

Note: The relevant measured result has the offset with cable loss already.

4. Test Results

Frequency (MHz)	Maximum source-based time averaged conducted output power (dBm)	Minimum separation distance (mm)	Result of Eq. 1	Limit for 1-g SAR	Limit for 10-g extremity SAR	Verdict
2402-2480	0.50	5	0.353	3.0	7.5	Exempt from SAR

Therefore this device complies with FCC's RF radiation exposure limits for general population without SAR evaluation.