

FCC Test Report

FCC ID : SWX-AF60

Equipment : airFiber 60

Model No. : AF60

Brand Name : UBIQUITI

Applicant : Ubiquiti Inc.

Address : 685 Third Avenue, 27th Floor New York, New

York 10017 USA

Standard : 47 CFR FCC Part 15.249

Received Date : Aug. 01, 2019
Tested Date : Aug. 14, 2019

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by: Approved by:

Along Cheld/ Assistant Manager Gary Chang / Manager

Testing Laboratory

Page: 1 of 26

Report No.: FR981302AE



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information	5
1.2	Local Support Equipment List	7
1.3	Test Setup Chart	7
1.4	The Equipment List	
1.5	Test Standards	9
1.6	Deviation from Test Standard and Measurement Procedure	9
1.7	Measurement Uncertainty	g
2	TEST CONFIGURATION	10
2.1	Testing Condition	10
2.2	The Worst Test Modes and Channel Details	10
3	TRANSMITTER TEST RESULTS	11
3.1	Conducted Emissions	11
3.2	Radiated Emission	14
3.3	20dB and Occupied Bandwidth	25
4	TEST LABORATORY INFORMATION	26



Release Record

Report No.	Version	Description	Issued Date
FR981302AE	Rev. 01	Initial issue	Aug. 20, 2019
FR981302AE	Rev. 02	Revised applicant name	Sep. 05, 2019

Report No.: FR981302AE Page: 3 of 26

Report Version: Rev. 02



Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	AC Power Line Conducted Emissions	[dBuV]: 0.177MHz 57.38 (Margin -7.26dB) - QP	Pass
15.249(a)	Field Strength of Fundamental	Meet the requirement of limit	Pass
15.249(a)(d)	Field Strength of Harmonics and Emissions Radiated outside of the Specified Frequency Bands	Meet the requirement of limit	Pass
15.215(c)	20dB bandwidth	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Report No.: FR981302AE

Page: 4 of 26

Report Version: Rev. 02



General Description 1

Information 1.1

1.1.1 **Specification of the Equipment under Test (EUT)**

RF General Information						
Frequency Range (MHz) Bluetooth Ch. Freq. (MHz) Channel Number Data Rate						
2400-2483.5 V4.1 LE 2402-2480 0-39 [40] 1 Mbps						
Note 1: Bluetooth LE (Low energy) uses GFSK modulation.						

1.1.2 Antenna Details

Ant. No.	Туре	Gain (dBi)	Connector	Remark
1	Internal	0	N/A	

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	24Vdc from POE
-------------------	----------------

1.1.4 Accessories

	Accessories					
No.	Equipment	Description				
1	POE	Brand: UBIQUITI Model: GP-A240-050G Power Rating: I/P: 100-240Vac, 50/60Hz 0.3A O/P: 24Vdc, 0.5A Power Line: 0.6m non-shielded without core				

Report No.: FR981302AE

Report Version: Rev. 02



1.1.5 Channel List

	Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	
37	2402	9	2422	18	2442	28	2462	
0	2404	10	2424	19	2444	29	2464	
1	2406	38	2426	20	2446	30	2466	
2	2408	11	2428	21	2448	31	2468	
3	2410	12	2430	22	2450	32	2470	
4	2412	13	2432	23	2452	33	2472	
5	2414	14	2434	24	2454	34	2474	
6	2416	15	2436	25	2456	35	2476	
7	2418	16	2438	26	2458	36	2478	
8	2420	17	2440	27	2460	39	2480	

1.1.6 Test Tool and Duty Cycle


Test Tool	Putty, Version: V0.60.0			
Duty Cycle and Duty Factor	Duty Cycle (%)	Duty Factor (dB)		
Duty Cycle and Duty Factor	63.84%	1.95		



1.2 Local Support Equipment List

	Support Equipment List						
No.	No. Equipment Brand Model FCC ID Remarks						
1	Notebook	DELL	Latitude E6440	DoC			

1.3 Test Setup Chart





1.4 The Equipment List

Test Item	Conducted Emission							
Test Site	Conduction room 1 / (Conduction room 1 / (CO01-WS)						
Instrument	Manufacturer Model No. Serial No. Calibration Date Calibration Until							
Receiver	R&S	ESR3	101657	Jan. 08, 2019	Jan. 07, 2020			
LISN	R&S	ENV216	101579	Mar. 08, 2019	Mar. 07, 2020			
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Oct. 23, 2018	Oct. 22, 2019			
Measurement Software AUDIX e3 6.120210k NA NA NA								

Test Item	Radiated Emission						
Test Site	966 chamber 3 / (03C	:H03-WS)					
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until		
Spectrum Analyzer	R&S	FSV40	101499	Jan. 07, 2019	Jan. 06, 2020		
Receiver	R&S	ESR3	101658	Dec. 11, 2018	Dec. 10, 2019		
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-685	Apr. 17, 2019	Apr. 16, 2020		
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1206	Jan. 07, 2019	Jan. 06, 2020		
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 15, 2018	Nov. 14, 2019		
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 09, 2018	Nov. 08, 2019		
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 08, 2018	Oct. 07, 2019		
Preamplifier	EMC	EMC02325	980187	Aug. 24, 2018	Aug. 23, 2019		
Preamplifier	Agilent	83017A	MY53270013	Dec. 27, 2018	Dec. 26, 2019		
Preamplifier	EMC	EMC184045B	980192	Aug. 01, 2019	Jul. 31, 2020		
RF cable-3M	HUBER+SUHNER	SUCOFLEX104	MY22620/ 4	Oct. 01, 2018	Sep. 30, 2019		
RF cable-8M	EMC	EMC104-SM-SM-80 00	181107	Oct. 01, 2018	Sep. 30, 2019		
RF cable-1M	HUBER+SUHNER	SUCOFLEX104	MY22624/4	Oct. 01, 2018	Sep. 30, 2019		
LF cable-0.8M	EMC	EMC8D-NM-NM-800	EMC8D-NM-NM-800 -001	Oct. 01, 2018	Sep. 30, 2019		
LF cable-3M	EMC	EMC8D-NM-NM-300 0	131103	Oct. 01, 2018	Sep. 30, 2019		
LF cable-13M	EMC	EMC8D-NM-NM-130 00	131104	Oct. 01, 2018	Sep. 30, 2019		
Measurement Software	AUDIX	e3	6.120210g	NA	NA		
Note: Calibration Inter	val of instruments liste	d above is one year.					

Report No.: FR981302AE

Page: 8 of 26

Report Version: Rev. 02



1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.249

ANSI C63.10-2013

1.6 Deviation from Test Standard and Measurement Procedure

None

1.7 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty							
Parameters Uncertain							
Bandwidth	±34.130 Hz						
AC conducted emission	±2.92 dB						
Radiated emission ≤ 1GHz	±3.96 dB						
Radiated emission > 1GHz	±4.51 dB						



2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	24°C / 64%	Alex Tsai
Radiated Emissions	03CH03-WS	24°C / 65%	Akun Chung

FCC Designation No.: TW0009FCC site registration No.: 207696

➤ ISED#: 10807A

➤ CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate	Test Configuration
AC Power Line Conducted Emissions	BT LE	2440	1 Mbps	
Field Strength of Fundamental	BT LE	2402, 2440, 2480	1 Mbps	
Radiated Emissions ≤ 1GHz	BT LE	2440	1 Mbps	
Radiated Emissions > 1GHz	BT LE	2402, 2440, 2480	1 Mbps	
20dB bandwidth	BT LE	2402, 2440, 2480	1 Mbps	

Report No.: FR981302AE

Report Version: Rev. 02



3 Transmitter Test Results

3.1 Conducted Emissions


3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit									
Frequency Emission (MHz) Quasi-Peak Average									
0.15-0.5	66 - 56 *	56 - 46 *							
0.5-5	56	46							
5-30	60	50							
Note 1: * Decreases with the logarith	nm of the frequency.								

3.1.2 Test Procedures

- 1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
- 2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
- 3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
- 4. This measurement was performed with AC 120V / 60Hz.

3.1.3 Test Setup




Note: 1. Support units were connected to second LISN.

Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

Report No.: FR981302AE Page: 11 of 26




Test Result of Conducted Emissions



Report No.: FR981302AE

Page: 12 of 26





Report No.: FR981302AE Page: 13 of 26



3.2 Radiated Emission

This section includes field strength of fundamental, field strength of harmonics and emissions radiated outside of the operating frequency bands.

3.2.1 Limit of field strength of fundamental and field strength of harmonics

Fundamental Frequency	Field strength of fundamental (millivolts/meter)	Field strength of harmonics (microvolts/meter)
2400-2483.5 MHz	50	500

3.2.2 Limit of Unwanted Emissions

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in below table, whichever is the lesser attenuation.

Radiated emission limits										
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)							
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300							
0.490~1.705	24000/F(kHz)	33.8 - 23	30							
1.705~30.0	30	29	30							
30~88	100	40	3							
88~216	150	43.5	3							
216~960	200	46	3							
Above 960	500	54	3							

Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit **Note 2:**

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

Page: 14 of 26

Report No.: FR981302AE



3.2.3 Test Procedures

- 1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
- Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- 3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.


Note:

- Radiated emission below 1GHz
 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission
- Radiated emission above 1GHz / Peak value except fundamental RBW=1MHz, VBW=3MHz and Peak detector
- Radiated emission above 1GHz / Average value RBW=1MHz, VBW=10Hz and Peak detector
- Radiated emission Peak value for fundamental RBW=2MHz, VBW=10MHz and Peak detector

Page: 15 of 26




3.2.4 Test Setup





3.2.5 Transmitter Radiated Unwanted Emissions (Below 1GHz)



Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Report Version: Rev. 02

Report No.: FR981302AE Page: 17 of 26



Modulation	GFS	GFSK Test Freq. (MHz) 2440									
Polarization		Verti	cal					•			
		(dDest/free)									
ç	90 Level	(dBuV/m)									
	30										
,	30										
7	70										
	60										
`	~								FCC	CLAS	S-B
5	50										
4	10 1 2	456									
	1	3 111									
3	30										
2	20										
1	10										
	030 1	00. 20	0. 30	0. 40	0. 50	0. 600	0. 700.	800.	90	ın	1000
	50 1	20	. 50	0. 40		ncy (MHz)	. 700.	000.	-		1000
		Freq. E	mission	Limit	Margin	SA	Factor	Remark	Al	NT	Turn
			level			reading			H:	igh	Table
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB		CI	m	deg
1		38.65	39.01	40.00	-0.99	48.32	-9.31	QP		100	66
2		63.84		40.00	-2.31	47.32	-9.63	ÕР		100	185
3		85.33	34.82	40.00	-5.18	49.09	-14.27	QР		100	108
4		151.31	35.76	43.50	-7.74	44.11	-8.35	Peak			
5		161.85	36.81	43.50	-6.69	45.25	-8.44	Peak			
6		172.62	35.75	43.50	-7.75	44.81	-9.06	Peak			

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.


Page: 18 of 26

Report No.: FR981302AE

Report Version: Rev. 02



3.2.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK




Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		




	Freq.	Emission level	Limit	Margin	SA reading	Factor	Remark	ANT High	Turn Table
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	39.77	54.00	-14.23	39.35	0.42	Average	103	91
2	2390.00	51.47	74.00	-22.53	51.05	0.42	Peak	103	91
3	2400.00	40.76	54.00	-13.24	40.36	0.40	Average	103	91
4	2400.00	51.74	74.00	-22.26	51.34	0.40	Peak	103	91
5	2402.00	87.79	94.00	-6.21	87.39	0.40	Average	103	91
6	2402.00	88.20	114.00	-25.80	87.80	0.40	Peak	103	91
7	4804.00	52.05	54.00	-1.95	45.73	6.32	Average	253	355
8	4804.00	57.57	74.00	-16.43	51.25	6.32	Peak	253	355
9	7206.00	47.53	54.00	-6.47	35.81	11.72	Average	102	261
10	7206.00	57.64	74.00	-16.36	45.92	11.72	Peak	102	261

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).






*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).





*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR981302AE

Report Version: Rev. 02



Modulation		GFSK				Test Fre	2480			
Polarization		Horiz	Horizontal							
90	Level (dBuV	/m)								
80										
00								FC	C 15C 249(2	.4G)
70		+								-
60			8	10) .	_				
00	+	6			1	2		FCC 1	5C 249(2.4G	AV)
50		+ +	1	9						
	3				1	1				
40										
30										
20										
10										
0	1000 40	000. 6	000. 8	000. 100	00. 1200	0. 14000. 1	16000. 180	00. 20000.	22000.	25000
					Frequ	ency (MHz)				
	_	_								
	Fre	eq. En	nissior	n Limit	Margi	n SA	Factor	Remark	ANT	Turn
	Fre	eq. En	missior level	l Limit	Margi	n SA reading		Remark	ANT High	
		•	level	dBuV/n				Remark		
	Mi	Hz o	level dBuV/m	dBuV/n	ı dB	reading dBuV	dB		High cm	Table deg
1	MI 	Hz 0	level dBuV/m 87.92	dBuV/n	-6.08	reading dBuV 87.65	dB 0.27	Average	High cm 130	Table deg 21
2	Mi 2480 2480	Hz 0	level dBuV/m 87.92 89.46	dBuV/n 94.00 114.00	-6.08 -24.54	reading dBuV 87.65 89.19	dB 0.27 0.27	Average Peak	High cm 130 130	Table deg 21 21
2	2480 2480 2481	Hz 0 0.00 0.00 0.00 3.50	level dBuV/m 87.92 89.46 43.32	dBuV/n 94.00 114.00 54.00	-6.08 -24.54 -10.68	87.65 89.19 43.06	dB 0.27 0.27 0.26	Average Peak Average	High cm 130 130 130	Table deg 21 21 21
2 3 4	2480 2480 2480 2480 2480	Hz 0 0.00 0.00 3.50 3.50	87.92 89.46 43.32 55.58	dBuV/n 94.00 114.00 54.00 74.00	-6.08 -24.54 -10.68 -18.42	87.65 89.19 43.06 55.32	dB 0.27 0.27 0.26 0.26	Average Peak Average Peak	High cm 130 130 130 130	Table deg 21 21 21 21 21
2 3 4 5	2486 2486 248 248 248 4966	Hz 0 0.00 0.00 3.50 3.50 0.00	87.92 89.46 43.32 55.58 46.00	94.00 114.00 54.00 74.00 54.00	-6.08 -24.54 -10.68 -18.42 -8.00	87.65 89.19 43.06 55.32 39.29	0.27 0.27 0.26 0.26 6.71	Average Peak Average Peak Average	High cm 130 130 130 130 122	Table deg 21 21 21 21 356
2 3 4 5 6	2486 2486 248. 248. 4966 4966	0.00 0.00 0.00 3.50 3.50 0.00	87.92 89.46 43.32 55.58 46.00 52.43	dBuV/n 94.00 114.00 54.00 74.00 54.00 74.00	-6.08 -24.54 -10.68 -18.42 -8.00 -21.57	87.65 89.19 43.06 55.32 39.29 45.72	dB 0.27 0.27 0.26 0.26 6.71 6.71	Average Peak Average Peak Average Peak	High cm 130 130 130 130 122 122	Table deg 21 21 21 21 21 356 356
2 3 4 5 6 7	2480 2480 2480 2480 2480 4960 7440	Hz 0 0.00 0.00 3.50 3.50 0.00 0.00	87.92 89.46 43.32 55.58 46.00 52.43 50.86	dBuV/n 94.00 114.00 54.00 74.00 54.00 54.00	-6.08 -24.54 -10.68 -18.42 -8.00 -21.57 -3.14	87.65 89.19 43.06 55.32 39.29 45.72 39.04	dB 0.27 0.27 0.26 0.26 6.71 6.71 11.82	Average Peak Average Peak Average Peak Average	High cm 130 130 130 130 122 122 122 119	Table deg 21 21 21 21 356 356 293
2 3 4 5 6 7 8	2480 2480 2480 2480 2480 4960 4960 7440	Hz 0 0.00 0.00 3.50 3.50 0.00 0.00 0.00	87.92 89.46 43.32 55.58 46.00 52.43 50.86 60.37	dBuV/n 94.00 114.00 54.00 74.00 54.00 74.00 74.00	-6.08 -24.54 -10.68 -18.42 -8.00 -21.57 -3.14 -13.63	87.65 89.19 43.06 55.32 39.29 45.72 39.04 48.55	dB 0.27 0.27 0.26 0.26 6.71 6.71 11.82 11.82	Average Peak Average Peak Average Peak Average Peak	High cm 130 130 130 122 122 119 119	Table deg 21 21 21 21 356 356 293 293
2 3 4 5 6 7 8 9	2480 2480 2480 2480 2480 4960 4960 7444 7444	Hz 0 0.00 0.00 3.50 3.50 0.00 0.00 0.00 0.0	87.92 89.46 43.32 55.58 46.00 52.43 50.86 60.37 46.61	dBuV/n 94.00 114.00 54.00 74.00 54.00 74.00 54.00 54.00	-6.08 -24.54 -10.68 -18.42 -8.00 -21.57 -3.14 -13.63 -7.39	87.65 89.19 43.06 55.32 39.29 45.72 39.04 48.55 30.35	dB 0.27 0.27 0.26 0.26 6.71 6.71 11.82 11.82 16.26	Average Peak Average Peak Average Peak Average Peak Average	High cm 130 130 130 122 122 119 119 100	Table deg 21 21 21 21 356 356 293 293 358
2 3 4 5 6 7 8	2480 2480 2480 2480 2480 4960 4960 7444 7444 9920 9920	Hz 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.	87.92 89.46 43.32 55.58 46.00 52.43 50.86 60.37 46.61 58.54	dBuV/n 94.00 114.00 54.00 74.00 54.00 74.00 74.00	-6.08 -24.54 -10.68 -18.42 -8.00 -21.57 -3.14 -13.63 -7.39 -15.46	87.65 89.19 43.06 55.32 39.29 45.72 39.04 48.55 30.35 42.28	dB 0.27 0.27 0.26 0.26 6.71 6.71 11.82 11.82	Average Peak Average Peak Average Peak Average Peak	High cm 130 130 130 122 122 119 119 100 100	Table deg 21 21 21 21 356 356 293 293

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) - Limit (dBuV/m).

Report No.: FR981302AE

Report Version: Rev. 02

The previous version of the test report has been cancelled and replaced by new version.

Page: 23 of 26



Modulation		GFS	GFSK Test Freq. (MHz) 2480							
Polarization Vertical						•				
	90 Level	(dBuV/m)								
	80							FC	C 15C 249(2	.4G)
	70								,	
			8	10	,					
	60	4 4	1	İ	1	2		FCC 15	5C 249(2.4G	AV)
	50			9						
		3			1	1				
	40									
	30									
	20									
	10									
	⁰ 1000	4000.	6000. 8	000. 100		0. 14000. 1	16000. 180	00. 20000.	22000.	25000
						ency (MHz)				
		Freq.	Emissior	l Limit	Margi		Factor	Remark	ANT	Turn
		MHz	level dBuV/m	dBuV/ı	JD	reading dBuV	dB		High	Table
		MUZ	ubuv/m	ubuv/i	II UD	abuv	uБ		cm	deg
	1	2480.00	89.18	94.00	-4.82	88.91	0.27	Average	122	94
	2	2480.00			-23.45		0.27	Peak	122	94
:	3	2483.50	44.07	54.00	-9.93	43.81	0.26	Average	122	94
	4	2483.50			-17.97		0.26	Peak	122	94
	5	4960.00		54.00			6.71	Average		348
	6	4960.00			-15.75		6.71	Peak	238	348
	7	7440.00		54.00			11.82	Average		262
	8 9	7440.00 9920.00			-11.39 -5.30		11.82 16.26	Peak	129 181	262 344
	2	3320.00	40.70	34.00	-5.50	32.44	10.20	Average	101	544

16.26

15.92

15.92

Peak

Peak

Average

344

88

88

Page: 24 of 26

181

100

100

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

9920.00 59.35 74.00 -14.65 43.09

12400.00 44.27 54.00 -9.73 28.35

12400.00 56.90 74.00 -17.10 40.98

*Factor includes antenna factor, cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Report No.: FR981302AE

10

11

12

Report Version: Rev. 02




3.3 20dB and Occupied Bandwidth

3.3.1 Test Procedures


- 1. Set resolution bandwidth (RBW) = 20 kHz, Video bandwidth = 100 kHz.
- 2. Detector = Peak, Trace mode = max hold
- 3. Sweep = auto couple, Allow the trace to stabilize.
- 4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 20dB relative to the maximum level measured in the fundamental emission.
- 5. Use the occupied measurement function of specturm analyzer to measure 99% occupied bandwidth.

3.3.2 Test Setup



3.3.3 20dB and Occupied Bandwidth

Freq. (MHz)	20dB Bandwidth (MHz)	Occupied Bandwidth (MHz)
2402	1.064	1.013
2440	1.064	1.027
2480	1.078	1.020



Page: 25 of 26

Report No.: FR981302AE



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website http://www.icertifi.com.tw.

Linkou

Tel: 886-2-2601-1640 No. 30-2, Ding Fwu Tsuen, Lin Kou District, New Taipei City,

Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666 No. 3-1, Lane 6, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd St., Kwei Shan District, Tao Yuan City 333, Taiwan, R.O.C.

Page: 26 of 26

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666 Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==

Report No.: FR981302AE Report Version: Rev. 02