

FCC TEST REPORT

For

Shenzhen Feelstorm Technology Co., Ltd

Digital Video Baby Monitor

Test Model: VB607-T

Additional Model No.:N/A

Prepared for : Shenzhen Feelstorm Technology Co., Ltd
Address : 5F Block C, HuaWan industrial Park, No.119, BaoAn DaDao, BaoAn District, ShenZhen CHINA

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 101,601, Xingyuan Industrial Park, Tongda Road, Bao'an Avenue, Bao'an District, Shenzhen, Guangdong, China
Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : June 18, 2019
Number of tested samples : 1
Serial number : Prototype
Date of Test : June 18, 2019 ~ June 24, 2019
Date of Report : June 28, 2019

**ISED TEST REPORT
FCC CFR 47 PART 15 C (15.247)****Report Reference No. : LCS190611048AEA**

Date of Issue : June 28, 2019

Testing Laboratory Name..... : Shenzhen LCS Compliance Testing Laboratory Ltd.Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,
Bao'an District, Shenzhen, Guangdong, ChinaTesting Location/ Procedure : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □**Applicant's Name..... : Shenzhen Feelstorm Technology Co., Ltd**Address : 5F Block C, HuaWan industrial Park, No.119, BaoAn DaDao,
BaoAn District, ShenZhen CHINA**Test Specification**

Standard..... : FCC CFR 47 PART 15 C (15.247)

Test Report Form No. : LCSEMC-1.0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

EUT Description. : Digital Video Baby Monitor

Trade Mark..... : N/A

Model/ Type reference : VB607-T


Ratings : 5V DC,1000mAh by adapter,

Result : **Positive****Compiled by:**

Jack Liu/ File administrators

Supervised by:

Aking Jin/ Technique principal

Approved by:

Gavin Liang/ Manager

FCC -- TEST REPORT

| | |
|-----------------------------------|--------------------------------|
| Test Report No. : LCS190611047AEA | June 28, 2019 Date of issue |
|-----------------------------------|--------------------------------|

| | |
|--------------------------|--|
| Type / Model..... | : VB607-T |
| EUT..... | : Digital Video Baby Monitor |
| Applicant..... | : Shenzhen Feelstorm Technology Co., Ltd |
| Address..... | : 5F Block C, HuaWan industrial Park, No.119, BaoAn DaDao, BaoAn District, ShenZhen CHINA |
| Telephone..... | : / |
| Fax..... | : / |
| Manufacturer..... | : Shenzhen Feelstorm Technology Co., Ltd |
| Address..... | : 5F Block C, HuaWan industrial Park, No.119, BaoAn DaDao, BaoAn District, ShenZhen CHINA |
| Telephone..... | : / |
| Fax..... | : / |
| Factory..... | : Shenzhen Feelstorm Technology Co., Ltd |
| Address..... | : 5F Block C, HuaWan industrial Park, No.119, BaoAn DaDao, BaoAn District, ShenZhen CHINA |
| Telephone..... | : / |
| Fax..... | : / |

| | |
|-------------|----------|
| Test Result | Positive |
|-------------|----------|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

| Revision | Issue Date | Revisions | Revised By |
|----------|---------------|---------------|-------------|
| 000 | June 28, 2019 | Initial Issue | Gavin Liang |
| | | | |
| | | | |

TABLE OF CONTENTS

| | |
|--|-----------|
| 1. GENERAL INFORMATION | 6 |
| 1.1. DESCRIPTION OF DEVICE (EUT) | 6 |
| 1.2. HOST SYSTEM CONFIGURATION LIST AND DETAILS | 7 |
| 1.3. EXTERNAL I/O CABLE | 7 |
| 1.4. DESCRIPTION OF TEST FACILITY | 7 |
| 1.5. STATEMENT OF THE MEASUREMENT UNCERTAINTY | 7 |
| 1.6. MEASUREMENT UNCERTAINTY | 7 |
| 1.7. DESCRIPTION OF TEST MODES | 8 |
| 1.8. FREQUENCY OF CHANNELS | 8 |
| 2. TEST METHODOLOGY | 9 |
| 2.1. EUT CONFIGURATION | 9 |
| 2.2. EUT EXERCISE | 9 |
| 2.3. GENERAL TEST PROCEDURES | 9 |
| 3. SYSTEM TEST CONFIGURATION..... | 10 |
| 3.1. JUSTIFICATION | 10 |
| 3.2. EUT EXERCISE SOFTWARE..... | 10 |
| 3.3. SPECIAL ACCESSORIES | 10 |
| 3.4. BLOCK DIAGRAM/SCHEMATICS..... | 10 |
| 3.5. EQUIPMENT MODIFICATIONS | 10 |
| 3.6. TEST SETUP | 10 |
| 4. SUMMARY OF TEST RESULTS..... | 11 |
| 5. TEST RESULT | 12 |
| 5.1. ON TIME AND DUTY CYCLE | 12 |
| 5.2. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT..... | 13 |
| 5.3. POWER SPECTRAL DENSITY MEASUREMENT | 15 |
| 5.4. 6 dB AND 99% SPECTRUM BANDWIDTH MEASUREMENT | 17 |
| 5.5. RADIATED EMISSIONS MEASUREMENT..... | 19 |
| 5.6. CONDUCTED SPURIOUS EMISSIONS AND BAND EDGES TEST..... | 29 |
| 5.7. AC POWER LINE CONDUCTED EMISSIONS (NOT APPLICABLE)..... | 32 |
| 5.8. BAND-EDGE MEASUREMENTS FOR RADIATED EMISSIONS | 35 |
| 5.9. ANTENNA REQUIREMENTS..... | 39 |
| 6. LIST OF MEASURING EQUIPMENTS | 41 |
| 7. TEST SETUP PHOTOGRAPHS OF EUT..... | 42 |
| 8. EXTERIOR PHOTOGRAPHS OF THE EUT | 42 |
| 9. INTERIOR PHOTOGRAPHS OF THE EUT | 42 |

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

| | | |
|--------------------------------|---|---|
| EUT | : | Digital Video Baby Monitor |
| Test Model | : | VB607-T |
| Additional Model No. | : | / |
| Model Declaration | : | / |
| Power Supply | : | 5V DC,1000mAh by adapter, |
| Hardware Version | : | A02 |
| Software Version | : | V6.3 |
| For Digital Video Baby Monitor | | |
| Frequency Range | : | 2415MHz-2460MHz (2415MHz, 2418MHz, 2421MHz, 2424MHz, 2427MHz, 2430MHz, 2433MHz, 2436MHz, 2439MHz, 2442MHz, 2445MHz, 2448MHz, 2451MHz, 2454MHz, 2457MHz, 2460MHz) |
| Channel Number | : | 16 channels |
| Channel Spacing | : | 3MHz |
| Modulation Type | : | GFSK |
| Antenna Description | : | Internal Antenna, 2dBi(max.) |

1.2. Host System Configuration List and Details

| Manufacturer | Description | Model | Serial Number | Certificate |
|--------------|-------------|-------|---------------|-------------|
| -- | -- | -- | --- | -- |

1.3. External I/O Cable

| I/O Port Description | Quantity | Cable |
|----------------------|----------|-------|
| -- | -- | -- |

1.4. Description of Test Facility

FCC Registration Number is 254912.
 Industry Canada Registration Number is 9642A-1.
 EMSD Registration Number is ARCB0108.
 UL Registration Number is 100571-492.
 TUV SUD Registration Number is SCN1081.
 TUV RH Registration Number is UA 50296516-001.
 NVLAP Accreditation Code is 600167-0.
 FCC Designation Number is CN5024
 CAB identifier: CN0071

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

1.5. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.6. Measurement Uncertainty

| Test Item | | Frequency Range | Uncertainty | Note |
|------------------------|---|-----------------|-------------|------|
| Radiation Uncertainty | : | 9KHz~30MHz | ±3.10dB | (1) |
| | | 30MHz~200MHz | ±2.96dB | (1) |
| | | 200MHz~1000MHz | ±3.10dB | (1) |
| | | 1GHz~26.5GHz | ±3.80dB | (1) |
| | | 26.5GHz~40GHz | ±3.90dB | (1) |
| Conduction Uncertainty | : | 150kHz~30MHz | ±1.63dB | (1) |
| Power disturbance | : | 30MHz~300MHz | ±1.60dB | (1) |

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.7. Description of Test Modes

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position.

Worst-case mode and channel used for 150 KHz-30 MHz power line conducted emissions was the mode and channel with the highest output power that was determined to be TX.

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be SRD mode(HCH).

Pre-test AC conducted emission at charge from adapter mode, recorded worst case.

Pre-test AC conducted emission at both voltage AC 120V/60Hz and AC 240V/50Hz, recorded worst case.

Worst-Case data rates were utilized from preliminary testing of the Chipset, worst-case data rates used during the testing are as follows:

1.8. Frequency of Channels

| Modulation Technology | Channel No. | Frequency | Channel No. | Frequency |
|-----------------------|-------------|-----------|-------------|-----------|
| | | (MHz) | | (MHz) |
| GFSK | 0 | 2415 | 8 | 2439 |
| | 1 | 2418 | 9 | 2442 |
| | 2 | 2421 | 10 | 2445 |
| | 3 | 2424 | 11 | 2448 |
| | 4 | 2427 | 12 | 2451 |
| | 5 | 2430 | 13 | 2454 |
| | 6 | 2433 | 14 | 2457 |
| | 7 | 2436 | 15 | 2460 |

2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd.

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to FCC's request, Test Procedure KDB558074 D01 15.247 Meas Guidance v05 Meas. Guidance is required to be used for this kind of FCC 15.247 digital modulation device.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

2.3. General Test Procedures

2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013.

3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a continuous transmits condition. The duty cycle is 100% and the average correction factor is 0.

The EUT After the power is switched on, By manually operating the keys, and the Signal continuous transmission.

3.2. EUT Exercise Software

N/A

3.3. Special Accessories

N/A

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST RESULTS

| Applied Standard: RSS-247 Issue 2 / RSS-Gen Issue 5 | | | |
|---|---|-----------|--------|
| ISED Rules | Description of Test | Result | Remark |
| / | On Time and Duty Cycle | Compliant | Note 1 |
| §15.247(b) | Maximum Conducted Output Power | Compliant | Note 1 |
| §15.247(e) | Power Spectral Density | Compliant | Note 1 |
| §15.247(a)(2) | 6dB Bandwidth | Compliant | Note 1 |
| §15.209, §15.247(d) | Occupied Bandwidth | Compliant | Note 1 |
| §15.209, §15.247(d) | Radiated and Conducted Spurious Emissions | Compliant | Note 1 |
| §15.205 | Emissions at Restricted Band | Compliant | Note 1 |
| §15.207(a) | AC Conducted Emissions | Compliant | Note 1 |
| §15.203 | Antenna Requirements | Compliant | Note 1 |
| §15.247(i)§2.1091 | RF Exposure | Compliant | Note 2 |

Remark:

1. Note 1 – Test results inside test report;
2. Note 2 – Test results in other test report (RF Exposure Evaluation);

5. TEST RESULT

5.1. On Time and Duty Cycle

5.1.1. Standard Applicable

None; for reporting purpose only.


5.1.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of the spectrum analyzer.

5.1.3. Test Procedures

1. Set the center frequency of the spectrum analyzer to the transmitting frequency;
2. Set the span=0MHz, RBW=8MHz, VBW=50MHz, Sweep time=5ms;
3. Detector = peak;
4. Trace mode = Single hold.

5.1.4. Test Setup Layout




5.1.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.1.6. Test result

| Mode | On Time B (ms) | Period (ms) | Duty Cycle x (Linear) | Duty Cycle (%) | Duty Cycle Correction Factor (dB) | 1/B Minimum VBW (KHz) |
|------|----------------------|----------------|--------------------------|-------------------|--|--------------------------------|
| GFSK | 5.0 | 5.0 | 1 | 100 | 0 | 0.01 |

On Time and Duty Cycle



Channel 7 / 2436 MHz

5.2. Maximum Conducted Output Power Measurement

5.2.1. Standard Applicable

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

5.2.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of the spectrum analyzer.

5.2.3. Test Procedures


The transmitter output (antenna port) was connected to the spectrum analyzer.

According to KDB558074 D01 15.247 Measurement Guidance Section 9.1 Maximum peak conducted output power 9.1.1.

This procedure shall be used when the measurement instrument has available a resolution bandwidth that is greater than the DTS bandwidth.

- Set the RBW \geq DTS bandwidth.
- Set VBW $\geq 3 \times$ RBW.
- Set span $\geq 3 \times$ RBW
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

5.2.4. Test Setup Layout



5.2.5. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.


5.2.6. Test Result of Maximum Conducted Output Power

| Channel | Frequency (MHz) | Measured Maximum Peak Power (dBm) | Limits (dBm) | Verdict |
|---------|-----------------|-----------------------------------|--------------|---------|
| 0 | 2415 | 3.479 | 30 | PASS |
| 7 | 2436 | 4.216 | | |
| 15 | 2460 | 4.638 | | |

Remark:

- Test results including cable loss;
- Please refer to following plots;





5.3. Power Spectral Density Measurement

5.3.1. Standard Applicable

According to §15.247(e): For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


5.3.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of Spectrum Analyzer.

5.3.3. Test Procedures

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. The power was Digital Video Baby Monitored at the coupler port with a Spectrum Analyzer. The power level was set to the maximum level.
3. Set the RBW = 3 kHz.
4. Set the VBW $\geq 3 \times$ RBW
5. Set the span to 1.5 times the DTS channel bandwidth.
6. Detector = peak.
7. Sweep time = auto couple.
8. Trace mode = max hold.
9. Allow trace to fully stabilize.
10. Use the peak marker function to determine the maximum power level.
11. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
12. The resulting peak PSD level must be 8 dBm.

5.3.4. Test Setup Layout



5.3.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


5.3.6. Test Result of Power Spectral Density


PASS

Remark:

1. Test results including cable loss;
2. Please refer to following plots;

| Channel | Frequency (MHz) | Peak Power Spectral Density (dBm/3kHz) | Limits (dBm/3kHz) | Verdict |
|---------|-----------------|--|-------------------|---------|
| 0 | 2415 | 1.569 | 8 | PASS |
| 7 | 2436 | 1.720 | | |
| 15 | 2460 | 3.175 | | |





Channel 15/ 2460 MHz

5.4. 6 dB and 99% Spectrum Bandwidth Measurement

5.4.1. Standard Applicable

According to §15.247(a) (2): For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

5.4.2. Measuring Instruments and Setting


Please refer to equipment list in this report. The following table is the setting of the Spectrum Analyzer.

| Spectrum Parameter | Setting |
|--------------------|----------|
| Attenuation | Auto |
| Span Frequency | > RBW |
| Detector | Peak |
| Trace | Max Hold |
| Sweep Time | 100ms |

5.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth and the video bandwidth were set according to KDB558074.
3. Measured the spectrum width with power higher than 6dB below carrier.

5.4.4. Test Setup Layout



5.4.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


5.4.6. Test Result of 6dB and 99% Spectrum Bandwidth


| Channel | Frequency (MHz) | 6dB Bandwidth (KHz) | 99% Bandwidth (KHz) | Limits (KHz) | Verdict |
|---------|-----------------|---------------------|---------------------|--------------|---------|
| 0 | 2415 | 1243 | 2023.3 | ≥500 | PASS |
| 7 | 2436 | 701.9 | 2003.6 | | |
| 15 | 2460 | 248.0 | 2003.5 | | |

Remark:

1. Test results including cable loss;
2. Please refer to following plots;

6dB and 99% Bandwidth





Channel 15 2460Hz

5.5. Radiated Emissions Measurement

5.5.1. Standard Applicable

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

| MHz | MHz | MHz | GHz |
|-------------------|---------------------|---------------|-------------|
| 0.090-0.110 | 16.42-16.423 | 399.9-410 | 4.5-5.15 |
| \1\ 0.495-0.505 | 16.69475-16.69525 | 608-614 | 5.35-5.46 |
| 2.1735-2.1905 | 16.80425-16.80475 | 960-1240 | 7.25-7.75 |
| 4.125-4.128 | 25.5-25.67 | 1300-1427 | 8.025-8.5 |
| 4.17725-4.17775 | 37.5-38.25 | 1435-1626.5 | 9.0-9.2 |
| 4.20725-4.20775 | 73-74.6 | 1645.5-1646.5 | 9.3-9.5 |
| 6.215-6.218 | 74.8-75.2 | 1660-1710 | 10.6-12.7 |
| 6.26775-6.26825 | 108-121.94 | 1718.8-1722.2 | 13.25-13.4 |
| 6.31175-6.31225 | 123-138 | 2200-2300 | 14.47-14.5 |
| 8.291-8.294 | 149.9-150.05 | 2310-2390 | 15.35-16.2 |
| 8.362-8.366 | 156.52475-156.52525 | 2483.5-2500 | 17.7-21.4 |
| 8.37625-8.38675 | 156.7-156.9 | 2690-2900 | 22.01-23.12 |
| 8.41425-8.41475 | 162.0125-167.17 | 3260-3267 | 23.6-24.0 |
| 12.29-12.293 | 167.72-173.2 | 3332-3339 | 31.2-31.8 |
| 12.51975-12.52025 | 240-285 | 3345.8-3358 | 36.43-36.5 |
| 12.57675-12.57725 | 322-335.4 | 3600-4400 | (2\) |
| 13.36-13.41 | | | |

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

According to §15.247 (d): 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

5.5.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter | Setting |
|---|---|
| Attenuation | Auto |
| Start Frequency | 1000 MHz |
| Stop Frequency | 10 th carrier harmonic |
| RB / VB (Emission in restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average |
| RB / VB (Emission in non-restricted band) | 1MHz / 1MHz for Peak, 1 MHz / 1/B kHz for Average |

| Receiver Parameter | Setting |
|------------------------|--|
| Attenuation | Auto |
| Start ~ Stop Frequency | 9kHz~150kHz / RB/VB 200Hz/1KHz for QP/AVG |
| Start ~ Stop Frequency | 150kHz~30MHz / RB/VB 9kHz/30KHz for QP/AVG |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB/VB 120kHz/1MHz for QP |

5.5.3. Test Procedures

1) Sequence of testing 9 kHz to 30 MHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 0.8 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

2) Sequence of testing 30 MHz to 1 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

3) Sequence of testing 1 GHz to 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ($\pm 45^\circ$) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

4) Sequence of testing above 18 GHz

Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.


Premeasurement:

- The antenna is moved spherical over the EUT in different polarizations of the antenna.


Final measurement:

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.


5.5.4. Test Setup Layout



Below 30MHz



Below 1GHz



Above 1GHz

Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

5.5.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.5.6. Results of Radiated Emissions (9 KHz~30MHz)

| | | | |
|---------------|-----------|----------------|-------|
| Temperature | 24.5℃ | Humidity | 53.7% |
| Test Engineer | David Luo | Configurations | GFSK |

| Freq. (MHz) | Level (dBuV) | Over Limit (dB) | Over Limit (dBuV) | Remark |
|-------------|--------------|-----------------|-------------------|----------|
| - | - | - | - | See Note |

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

5.5.7. Results of Radiated Emissions (30MHz~1GHz)

| | | | |
|---------------|-----------|----------------|-------|
| Temperature | 24.5℃ | Humidity | 53.7% |
| Test Engineer | David Luo | Configurations | GFSK |

Vertical



Env./Ins: 24.5℃/53.7%
pol: VERTICAL


| | Freq | Reading | CabLos | Antfac | Measured | Limit | Over | Remark |
|---|--------|---------|--------|--------|----------|--------|--------|--------|
| | MHz | dBuV | dB | dB/m | dBuV/m | dBuV/m | dB | |
| 1 | 39.30 | 15.35 | 0.38 | 13.40 | 29.13 | 40.00 | -10.87 | QP |
| 2 | 51.66 | 14.21 | 0.54 | 13.17 | 27.92 | 40.00 | -12.08 | QP |
| 3 | 119.86 | 13.86 | 0.64 | 10.51 | 25.01 | 43.50 | -18.49 | QP |
| 4 | 216.02 | 20.04 | 0.88 | 11.07 | 31.99 | 46.00 | -14.01 | QP |
| 5 | 312.18 | 19.77 | 1.09 | 13.22 | 34.08 | 46.00 | -11.92 | QP |
| 6 | 504.71 | 22.30 | 1.29 | 16.67 | 40.26 | 46.00 | -5.74 | QP |

Note: 1. All readings are Quasi-peak values.

2. Measured= Reading + Antenna Factor + Cable Loss

3. The emission that are 20db below the official limit are not reported

Horizontal



Env./Ins: 24.5°C/53.7%
 pol: HORIZONTAL

| | Freq | Reading | CabLos | Antfac | Measured | Limit | Over | Remark |
|---|--------|---------|--------|--------|----------|--------|--------|--------|
| | MHz | dBuV | dB | dB/m | dBuV/m | dBuV/m | dB | |
| 1 | 39.30 | 2.94 | 0.38 | 13.40 | 16.72 | 40.00 | -23.28 | QP |
| 2 | 191.75 | 18.28 | 0.86 | 10.56 | 29.70 | 43.50 | -13.80 | QP |
| 3 | 216.02 | 27.17 | 0.88 | 11.07 | 39.12 | 46.00 | -6.88 | QP |
| 4 | 360.45 | 24.79 | 1.18 | 14.43 | 40.40 | 46.00 | -5.60 | QP |
| 5 | 504.71 | 23.60 | 1.29 | 16.67 | 41.56 | 46.00 | -4.44 | QP |
| 6 | 552.88 | 20.65 | 1.46 | 17.57 | 39.68 | 46.00 | -6.32 | QP |

Note: 1. All readings are Quasi-peak values.
 2. Measured= Reading + Antenna Factor + Cable Loss
 3. The emission that are 20db below the official limit are not reported

Note:

- 1). Pre-scan all modes and recorded the worst case results in this report.
- 2). Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 3). Corrected Reading: Antenna Factor + Cable Loss + Read Level = Level.

5.5.8. Results for Radiated Emissions (Above 1GHz)

Channel 0/ 2415Hz

| Freq. MHz | Reading dBuV | Ant. Fac dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|-----------|--------------|---------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4830.3 | 59.40 | 32.14 | 34.12 | 3.53 | 60.95 | 74.00 | -13.05 | Peak | Horizontal |
| 4830.3 | 41.58 | 32.14 | 34.12 | 3.53 | 43.13 | 54.00 | -10.87 | Average | Horizontal |
| 7245.3 | 54.62 | 32.17 | 34.15 | 3.55 | 56.19 | 74.00 | -17.81 | Peak | Horizontal |
| 7245.3 | 39.18 | 32.17 | 34.15 | 3.55 | 40.75 | 54.00 | -13.25 | Average | Horizontal |
| 4830.3 | 51.60 | 32.21 | 34.19 | 3.58 | 53.20 | 74.00 | -20.80 | Peak | Vertical |
| 4830.3 | 41.80 | 32.21 | 34.19 | 3.58 | 43.40 | 54.00 | -10.60 | Average | Vertical |
| 7245.6 | 54.20 | 33.16 | 35.06 | 3.96 | 56.26 | 74.00 | -17.74 | Peak | Vertical |
| 7245.6 | 42.01 | 33.16 | 35.06 | 3.96 | 44.07 | 54.00 | -9.93 | Average | Vertical |

Channel 7/ 2436Hz

| Freq. MHz | Reading dBuV | Ant. Fac dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|-----------|--------------|---------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4872.3 | 50.40 | 33.06 | 35.04 | 3.94 | 52.36 | 74.00 | -21.64 | Peak | Horizontal |
| 4872.3 | 40.40 | 33.06 | 35.04 | 3.94 | 42.36 | 54.00 | -11.64 | Average | Horizontal |
| 7308.3 | 49.03 | 33.16 | 35.15 | 3.96 | 51.00 | 74.00 | -23.00 | Peak | Horizontal |
| 7308.3 | 38.47 | 33.16 | 35.15 | 3.96 | 40.44 | 54.00 | -13.56 | Average | Horizontal |
| 4872.3 | 51.20 | 33.26 | 35.14 | 3.98 | 53.30 | 74.00 | -20.70 | Peak | Vertical |
| 4872.3 | 37.02 | 33.26 | 35.14 | 3.98 | 39.12 | 54.00 | -14.88 | Average | Vertical |
| 7308.6 | 53.73 | 33.26 | 35.17 | 3.98 | 55.80 | 74.00 | -18.20 | Peak | Vertical |
| 7308.6 | 37.21 | 33.26 | 35.17 | 3.98 | 39.28 | 54.00 | -14.72 | Average | Vertical |

Channel 15/ 2460 MHz

| Freq. MHz | Reading dBuV | Ant. Fac dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark | Pol. |
|-----------|--------------|---------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 4920.2 | 51.28 | 33.26 | 35.14 | 3.98 | 53.38 | 74.00 | -20.62 | Peak | Horizontal |
| 4920.2 | 39.63 | 33.26 | 35.14 | 3.98 | 41.73 | 54.00 | -12.27 | Average | Horizontal |
| 7380.6 | 49.97 | 33.36 | 35.16 | 4.00 | 52.17 | 74.00 | -21.83 | Peak | Horizontal |
| 7380.6 | 38.04 | 33.36 | 35.16 | 4.00 | 40.24 | 54.00 | -13.76 | Average | Horizontal |
| 4920.4 | 51.46 | 33.26 | 35.14 | 3.98 | 53.56 | 74.00 | -20.44 | Peak | Vertical |
| 4920.4 | 37.04 | 33.26 | 35.14 | 3.98 | 39.14 | 54.00 | -14.86 | Average | Vertical |
| 7380.2 | 52.93 | 33.36 | 35.16 | 4.00 | 55.13 | 74.00 | -18.87 | Peak | Vertical |
| 7380.2 | 37.58 | 33.36 | 35.16 | 4.00 | 39.78 | 54.00 | -14.22 | Average | Vertical |

Notes:

- 1). Measuring frequencies from 9 KHz~10th harmonic or 26.5GHz (which is less), No emission found between lowest internal used/generated frequency to 30MHz.
- 2). Radiated emissions measured in frequency range from 9 KHz~10th harmonic or 26.5GHz (which is less) were made with an instrument using Peak detector mode.
- 3). Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4). Measured radiated emission used 900-930 MHz band filter in order to avoid spectrum overload.

5.6. Conducted Spurious Emissions and Band Edges Test

5.6.1. Standard Applicable

According to §15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

5.6.2. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of the spectrum analyzer.

| Spectrum Parameter | Setting |
|---|---------------|
| Detector | Peak |
| Attenuation | Auto |
| RB / VB (Emission in restricted band) | 100KHz/300KHz |
| RB / VB (Emission in non-restricted band) | 100KHz/300KHz |

5.6.3. Test Procedures

The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 300 kHz

The spectrum from 9 KHz to 10 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

5.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 5.4.4.

5.6.5. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

5.6.6. Test Results of Conducted Spurious Emissions

| | | | |
|---------------|-----------|----------------|-------|
| Temperature | 24.6°C | Humidity | 53.3% |
| Test Engineer | David Luo | Configurations | GFSK |

RF Conducted Spurious Emissions


Channel 0 / 2415 MHz



2415MHz

30 MHz – 25 GHz


Channel 7 / 2436 MHz



2436MHz

30 MHz – 25 GHz


Channel 15 / 2460 MHz



2460MHz

30 MHz – 25 GHz

Band-edge measurements for conducted emissions



5.7. AC Power Line Conducted Emissions (Not Applicable)


5.7.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

| Frequency Range (MHz) | Limits (dB μ V) | |
|-----------------------|---------------------|----------|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56 | 56 to 46 |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |

* Decreasing linearly with the logarithm of the frequency

5.7.2 Block Diagram of Test Setup




5.7.3 Test Results

PASS

The test data please refer to following page.

AC Conducted Emission of powered by charge power Adapter mode @ AC 120V/60Hz (worst case)


Line



| Freq | Reading | LISNFac | CabLos | Aux2Fac | Measured | Limit | Over | Remark |
|------|---------|---------|--------|---------|----------|-------|-------|----------------|
| MHz | dBuV | dB | dB | dB | dBuV | dBuV | dB | |
| 1 | 0.17 | 40.08 | 9.59 | 0.02 | 10.00 | 59.69 | 65.16 | -5.47 QP |
| 2 | 0.17 | 19.99 | 9.59 | 0.02 | 10.00 | 39.60 | 55.16 | -15.56 Average |
| 3 | 0.55 | 30.45 | 9.63 | 0.04 | 10.00 | 50.12 | 56.00 | -5.88 QP |
| 4 | 0.55 | 19.93 | 9.63 | 0.04 | 10.00 | 39.60 | 46.00 | -6.40 Average |
| 5 | 0.87 | 27.12 | 9.63 | 0.04 | 10.00 | 46.79 | 56.00 | -9.21 QP |
| 6 | 0.87 | 12.38 | 9.63 | 0.04 | 10.00 | 32.05 | 46.00 | -13.95 Average |
| 7 | 1.14 | 25.44 | 9.63 | 0.05 | 10.00 | 45.12 | 56.00 | -10.88 QP |
| 8 | 1.14 | 10.44 | 9.63 | 0.05 | 10.00 | 30.12 | 46.00 | -15.88 Average |
| 9 | 1.84 | 24.09 | 9.64 | 0.05 | 10.00 | 43.78 | 56.00 | -12.22 QP |
| 10 | 1.84 | 8.12 | 9.64 | 0.05 | 10.00 | 27.81 | 46.00 | -18.19 Average |
| 11 | 17.47 | 26.29 | 9.74 | 0.11 | 10.00 | 46.14 | 60.00 | -13.86 QP |
| 12 | 17.48 | 10.07 | 9.74 | 0.11 | 10.00 | 29.92 | 50.00 | -20.08 Average |

Remarks: 1. Measured = Reading + LISNFac + Cable Loss + Aux2 Fac.
2. The emission levels that are 20dB below the official limit are not reported.

Neutral



Trace: 22

Env. Ins: 23.8*/54.1%

Pol: NEUTRAL

| | Freq | Reading | LISNFac | CabLos | Aux2Fac | Measured | Limit | Over | Remark |
|----|-------|---------|---------|--------|---------|----------|-------|--------|---------|
| | MHz | dBuV | dB | dB | dB | dBuV | dBuV | dB | |
| 1 | 0.15 | 40.13 | 9.69 | 0.02 | 10.00 | 59.84 | 65.78 | -5.94 | QP |
| 2 | 0.15 | 18.87 | 9.69 | 0.02 | 10.00 | 38.58 | 55.77 | -17.19 | Average |
| 3 | 0.20 | 36.31 | 9.59 | 0.02 | 10.00 | 55.92 | 63.54 | -7.62 | QP |
| 4 | 0.20 | 15.84 | 9.59 | 0.02 | 10.00 | 35.45 | 53.53 | -18.08 | Average |
| 5 | 0.53 | 28.89 | 9.62 | 0.04 | 10.00 | 48.55 | 56.00 | -7.45 | QP |
| 6 | 0.54 | 17.34 | 9.62 | 0.04 | 10.00 | 37.00 | 46.00 | -9.00 | Average |
| 7 | 0.74 | 23.04 | 9.63 | 0.04 | 10.00 | 42.71 | 56.00 | -13.29 | QP |
| 8 | 0.74 | 11.85 | 9.63 | 0.04 | 10.00 | 31.52 | 46.00 | -14.48 | Average |
| 9 | 1.10 | 22.26 | 9.63 | 0.05 | 10.00 | 41.94 | 56.00 | -14.06 | QP |
| 10 | 1.10 | 4.59 | 9.63 | 0.05 | 10.00 | 24.27 | 46.00 | -21.73 | Average |
| 11 | 15.55 | 23.63 | 9.75 | 0.10 | 10.00 | 43.48 | 60.00 | -16.52 | QP |
| 12 | 15.55 | 3.09 | 9.75 | 0.10 | 10.00 | 22.94 | 50.00 | -27.06 | Average |

Remarks: 1. Measured = Reading + LISNFac + Cable Loss + Aux2 Fac.

2. The emission levels that are 20dB below the official limit are not reported.


***Note: Pre-scan all modes and recorded the worst case results in this report

5.8. Band-edge Measurements for Radiated Emissions

5.8.1 Standard Applicable

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

5.8.2. Test Setup Layout



5.8.3. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of Spectrum Analyzer.

5.8.4. Test Procedures

According to KDB558074 D01 15.247 for Antenna-port conducted measurement. Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to an EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, for Radiated emissions restricted band RBW=1MHz, VBW=3MHz for peak detector and RBW=1MHz, VBW=1/B for Peak detector.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.
6. Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency (see 12.2.2, 12.2.3, and 12.2.4 for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
7. Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see 12.2.5 for guidance on determining the applicable antenna gain)
8. Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
9. For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
10. Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:

$$E = \text{EIRP} - 20\log D + 104.8$$

Where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

11. Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.
12. Compare the resultant electric field strength level to the applicable regulatory limit.
13. Perform radiated spurious emission test duress until all measured frequencies were complete.

5.8.5 Test Results


PASS

Remark:


- 1). Test results including cable loss;
- 2). “---”means that the fundamental frequency not for 15.209 limits requirement;
- 3). The average measurement was not performed when the peak measured data under the limit of average detection.
- 4). Detector AV is setting spectrum/receiver. RBW=1MHz/VBW=10Hz/Sweep time=Auto/Detector=Peak.
- 5). Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.

| Test Mode | Test Channel | Ant | Freq. | Power [dBm] | Gain | Ground Factor | E [dBuV/m] | Detector | Limit [dBuV/m] | Verdict |
|-----------|--------------|------|--------|-------------|------|---------------|------------|----------|----------------|---------|
| GFSK | 2415 | Ant1 | 2310.0 | -48.39 | 2.0 | 0 | 54.15 | PEAK | 74 | PASS |
| | | Ant1 | 2310.0 | -72.11 | 2.0 | 0 | 37.82 | AV | 54 | PASS |
| | | Ant1 | 2390.0 | -36.86 | 2.0 | 0 | 58.15 | PEAK | 74 | PASS |
| | | Ant1 | 2390.0 | -71.45 | 2.0 | 0 | 51.35 | AV | 54 | PASS |
| | 2460 | Ant1 | 2483.5 | -32.38 | 2.0 | 0 | 58.41 | PEAK | 74 | PASS |
| | | Ant1 | 2483.5 | -70.46 | 2.0 | 0 | 39.25 | AV | 54 | PASS |
| | | Ant1 | 2500.0 | -35.30 | 2.0 | 0 | 56.15 | PEAK | 74 | PASS |
| | | Ant1 | 2500.0 | -70.85 | 2.0 | 0 | 36.65 | AV | 54 | PASS |


Restrict-band band-edge measurements_GFSK_2415_PEAK




Restrict-band band-edge measurements_GFSK_2415_AV



Restrict-band band-edge measurements_GFSK_2460_PEAK



Restrict-band band-edge measurements_GFSK_2460_AV



5.9. Antenna Requirements

5.9.1 Standard Applicable

According to RSS-Gen Issue 5,

The applicant for equipment certification, as per RSP-100, must provide a list of all antenna types that may be used with the licence-exempt transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna.

Licence-exempt transmitters that have received equipment certification may operate with different types of antennas. However, it is not permissible to exceed the maximum equivalent isotropically radiated power (e.i.r.p.) limits specified in the applicable standard (RSS) for the licence-exempt apparatus.

Testing shall be performed using the highest gain antenna of each combination of licence-exempt transmitter and antenna type, with the transmitter output power set at the maximum level.9 When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna manufacturer.

5.9.2 Antenna Connected Construction

5.9.2.1. Standard Applicable

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

5.9.2.2. Antenna Connector Construction

The directional gains of antenna used for transmitting 2dBi, and the antenna is an internal antenna connect to PCB board and no consideration of replacement. Please see EUT photo for details.\

5.9.2.3. Results: Compliance.

Measurement

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

Conducted power refers ANSI C63.10:2013 Output power test procedure for DTS devices.

Radiated power refers to ANSI C63.10:2013 Radiated emissions tests.

Measurement parameters

| Measurement parameter | |
|-----------------------|----------|
| Detector: | Peak |
| Sweep Time: | Auto |
| Resolution bandwidth: | 1MHz |
| Video bandwidth: | 3MHz |
| Trace-Mode: | Max hold |

Note: The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

Limits

| FCC | | ISED | | |
|---|------|---------------------------|------------------------------------|-----------------------------|
| Antenna Gain | | | | |
| 6 dBi | | | | |
| Tnom | Vnom | lowest channel 2415MHz | middle channel 2436 MHz | highest channel 2460 MHz |
| Conducted power [dBm] Measured with GFSK modulation | | 1.479 | 2.216 | 3.938 |
| Radiated power [dBm] Measured with GFSK modulation | | 3.479 | 4.216 | 5.938 |
| Gain [dBi] Calculated | | 2.00 | 2.00 | 2.00 |
| Measurement uncertainty | | | ± 1.6 dB (cond.) / ± 3.8 dB (rad.) | |

6. LIST OF MEASURING EQUIPMENTS

| Item | Equipment | Manufacturer | Model No. | Serial No. | Cal Date | Due Date |
|------|--------------------------|----------------|--------------|-----------------|------------|------------|
| 1 | Power Meter | R&S | NRVS | 100444 | 2019-06-11 | 2020-06-10 |
| 2 | Power Sensor | R&S | NRV-Z81 | 100458 | 2019-06-11 | 2020-06-10 |
| 3 | Power Sensor | R&S | NRV-Z32 | 10057 | 2019-06-11 | 2020-06-10 |
| 4 | Test Software | Tonscend | JS1120-2 | N/A | N/A | N/A |
| 5 | RF Control Unit | Tonscend | JS0806-2 | N/A | 2019-06-11 | 2020-06-10 |
| 6 | MXA Signal Analyzer | Agilent | N9020A | MY50510140 | 2019-06-11 | 2020-06-10 |
| 7 | DC Power Supply | Agilent | E3642A | N/A | 2018-11-15 | 2019-11-14 |
| 8 | EMI Test Software | AUDIX | E3 | N/A | N/A | N/A |
| 9 | 3m Semi Anechoic Chamber | SIDT FRANKONIA | SAC-3M | 03CH03-HY | 2019-06-12 | 2020-06-11 |
| 10 | Positioning Controller | MF | MF-7082 | N/A | 2019-06-12 | 2020-06-11 |
| 11 | Active Loop Antenna | SCHWARZBECK | FMZB 1519B | 00005 | 2018-07-26 | 2019-07-25 |
| 12 | By-log Antenna | SCHWARZBECK | VULB9163 | 9163-470 | 2018-07-26 | 2019-07-25 |
| 13 | Horn Antenna | SCHWARZBECK | BBHA 9120D | 9120D-1925 | 2018-07-02 | 2019-07-01 |
| 14 | Broadband Horn Antenna | SCHWARZBECK | BBHA 9170 | 791 | 2018-09-20 | 2019-09-19 |
| 15 | Broadband Preamplifier | SCHWARZBECK | BBV 9719 | 9719-025 | 2018-09-20 | 2019-09-19 |
| 16 | EMI Test Receiver | R&S | ESR 7 | 101181 | 2019-06-12 | 2020-06-11 |
| 17 | RS SPECTRUM ANALYZER | R&S | FSP40 | 100503 | 2018-11-15 | 2019-11-14 |
| 18 | AMPLIFIER | QuieTek | QTK | CHM/0809065 | 2018-11-15 | 2019-11-14 |
| 19 | RF Cable-R03m | Jye Bao | RG142 | CB021 | 2019-06-12 | 2020-06-11 |
| 20 | RF Cable-HIGH | SUHNER | SUCOFLEX 106 | 03CH03-HY | 2019-06-12 | 2020-06-11 |
| 21 | 6dB Attenuator | / | 100W/6dB | 1172040 | 2019-06-11 | 2020-06-10 |
| 22 | 3dB Attenuator | / | 2N-3dB | / | 2019-06-11 | 2020-06-10 |
| 23 | EMI Test Receiver | R&S | ESPI | 101840 | 2019-06-11 | 2020-06-10 |
| 24 | Artificial Mains | R&S | ENV216 | 101288 | 2019-06-12 | 2020-06-11 |
| 25 | 10dB Attenuator | SCHWARZBECK | MTS-IMP-136 | 261115-001-0032 | 2019-06-11 | 2020-06-10 |

Note: All equipment is calibrated through GUANGZHOU LISAI CALIBRATION AND TEST CO.,LTD.

7. TEST SETUP PHOTOGRAPHS OF EUT

Please refer to separated files for Test Setup Photos of the EUT.

8. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

9. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----