

SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	Broadcom Corporation
Applicant Address	190 Mathilda Place Sunnyvale CA 94086 U.S.A.
FCC ID	QDS-BRCM1075
Manufacturer's company	Broadcom Corporation
Manufacturer Address	190 Mathilda Place Sunnyvale CA 94086 U.S.A.

Product Name	Broadcom 802.11a/b/g/n/ac WLAN + Bluetooth 4.0 NGFF2230 Mini Card
Brand Name	Broadcom
Model No.	BCM943162ZP
Test Rule	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2402 ~ 2480MHz
Received Date	Dec. 25, 2013
Final Test Date	Apr. 18, 2014
Submission Type	Class II Change

Statement

Test result included is only for the Bluetooth LE part of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in ANSI C63.4-2003, 47 CFR FCC Part 15 Subpart C and KDB 558074 D01 v03r01.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.





Table of Contents

1.	CER	RTIFICATE OF COMPLIANCE	. 1
2.	SUN	IMARY OF THE TEST RESULT	. 2
3.	GEN	NERAL INFORMATION	. 3
	3.1.	Product Details	3
	3.2.	Accessories	3
	3.3.	Table for Filed Antenna	4
	3.4.	Table for Carrier Frequencies	5
	3.5.	Table for Test Modes	5
	3.6.	Table for Testing Locations	5
	3.7.	Table for Class II Change	6
	3.8.	Table for Supporting Units	6
	3.9.	Test Configurations	7
4.	TEST	r Result	. 8
	4.1.	Radiated Emissions Measurement	8
	4.2.	Antenna Requirements	.14
5.	LIST	OF MEASURING EQUIPMENTS	15
6.	MEA	ASUREMENT UNCERTAINTY	16
AF	PEN	IDIX A. TEST PHOTOS	44



History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR3D2546-02AD	Rev. 01	Initial issue of report	Apr. 30, 2014
		Revising the model name of antenna to	
FR3D2546-02AD	Rev. 02	"PCA-4077-25GC1-A1" from	May 05, 2014
		"PCA-4077-25GC1-A1-RT".	



Certificate No.: CB10301257

1. CERTIFICATE OF COMPLIANCE

- Product Name : Broadcom 802.11a/b/g/n/ac WLAN + Bluetooth 4.0 NGFF2230 Mini Card
 - Brand Name : Broadcom
 - Model No. : BCM943162ZP
 - Applicant : Broadcom Corporation
- Test Rule Part(s) :
- 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Dec. 25, 2013 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

Sam Chen SPORTON INTERNATIONAL INC.



2. SUMMARY OF THE TEST RESULT

	Applied Standard: 47 CFR FCC Part 15 Subpart C					
Part	Rule Section	Result	Under Limit			
4.1	15.247(d)	Radiated Emissions	Complies	3.06 dB		
4.2	15.203	Antenna Requirements	Complies	-		



3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Power Type	From host system
Modulation	DSSS
Data Rate (Mbps)	GFSK: 1
Frequency Range	2402 ~ 2480MHz
Channel Number	40 (37 hopping + 3 advertising channel)
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

3.2. Accessories

N/A



3.3. Table for Filed Antenna

Set		Ant. Brand	Brand Model Name	Antonna		Gain (dBi)				
	Ant.			Type Connector		5GHz	5GHz	5GHz	5GHz	
						2.4962	B1	B2	B3	B4
1	1	MAG.LAYERS	PCA-4077-25GC1-A1	WLAN/BT antenna	IPEX A13	3.33	5.85	5.85	6.21	6.21
	2	MAG.LAYERS	PCA-4077-25GC1-A1	WLAN/BT antenna	IPEX A13	3.33	5.85	5.85	6.21	6.21

Note1: The each set has two antennas.

For 2.4GHz:

For IEEE 802.11b/g/n mode (1TX/1RX)

The EUT supports the antenna with TX/RX diversity function.

Both Chain 1 and Chain 2 can be used as transmitting/receiving antenna, but only one antenna can be used as transmitting/receiving antenna at the same time.

Chain 1 generated the worst case than Chain 2, so it tested and recorded in the report.

For 5GHz:

For IEEE 802.11a/n/ac mode (1TX/1RX)

The EUT supports the antenna with TX/RX diversity function.

Both Chain 1 and Chain 2 can be used as transmitting/receiving antenna, but only one antenna can be used as transmitting/receiving antenna at the same time.

Chain 1 generated the worst case than Chain 2, so it tested and recorded in the report.

For Bluetooth mode (1TX/1RX)

Only Chain 1 can be used as transmitting/receiving antenna.





3.4. Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
	0	2402 MHz	20	2442 MHz
	1	2404 MHz	:	:
2400 2482 EMU-	2	2406 MHz	37	2476 MHz
2400~2403.5IVIH2	:	:	38	2478 MHz
	18	2438 MHz	39	2480 MHz
	19	2440 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Chain
Radiated Emissions 9kHz~1GHz	Normal Link	-	-	-

The following test modes were performed for all tests:

For Radiated Emission Below 1GHz test:

Mode 1. Normal Link -2.4GHz WLAN function + Bluetooth function

Mode 2. Normal Link -5GHz WLAN function + Bluetooth function

Mode 2 is the worst case, so it was selected to record in this test report.

3.6. Table for Testing Locations

Test Site Location						
Address:	No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.					
TEL:	886-3-656-9065					
FAX:	886-3-656-9085					
Test Site No. Site Category Location FCC Reg. No. IC File No.					IC File No.	
03CH01	03CH01-CB SAC Hsin Chu 262045 IC 4086D					

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).



3.7. Table for Class II Change

This product is an extension of original one reported under Sporton project number: FR3D2546AD Below is the table for the change of the product with respect to the original one.

	Modifications	Performance Checking
1.	Adding a new antenna (Brand: MAG. LAYERS, Model	
	No.: PCA-4077-25GC1-A1) for this device.	
2.	The application of this module increases to portable	
	host equipment. The module is limited to use the new	Radiated Emissions Below 1GHz
	antenna (Brand: MAG. LAYERS, Model No.:	
	PCA-4077-25GC1-A1) when it is defined as portable	
	device.	

Note: New antenna and original antenna are the same type, but the gain of new antenna is higher than the original one in 5GHz. Thus, we checked the test items above.

3.8. Table for Supporting Units

For Test Site No: 03CH01-CB (Below 1GHz)

Support Unit	Brand	Model	FCC ID
Wireless AP	Planex	GW-AP54SGX	N/A
NB	DELL	E6220	DoC
NB	DELL	E6430	DoC
Mouse	Logitech	M-U0026	DoC
Earphone	SHYARO CHI	MIC-04	N/A
Test fixture*2	Broadcom	BCM9NGFF2EC_1	N/A
Broadcom 802.11a/b/g/n/ac WLAN + Bluetooth 4.0 NGFF2230 Mini Card (Device)	Broadcom	BCM943162ZP	QDS-BRCM1075



3.9. Test Configurations

3.9.1. Radiation Emissions Below 1GHz Test Configuration





Item	Connection	Length	
1	Power cable	No	2.6m
2	ANT cable	Yes	0.2m
3	ANT cable	Yes	0.2m
4	ANT cable	Yes	0.2m
5	ANT cable	Yes	0.2m
6	USB cable	Yes	1.8m
7	Audio cable	No	1.1m



4. TEST RESULT

4.1. Radiated Emissions Measurement

4.1.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies	Field Strength	Measurement Distance		
(MHz)	(micorvolts/meter)	(meters)		
0.009~0.490	2400/F(kHz)	300		
0.490~1.705	24000/F(kHz)	30		
1.705~30.0	30	30		
30~88	100	3		
88~216	150	3		
216~960	200	3		
Above 960	500	3		

4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak

Receiver Parameter	Setting		
Attenuation	Auto		
Start \sim Stop Frequency	9kHz~150kHz / RBW 200Hz for QP		
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP		
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP		



4.1.3. Test Procedures

- 1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



4.1.4. Test Setup Layout

For Radiated Emissions: $9kHz \sim 30MHz$



For Radiated Emissions: 30MHz~1GHz



4.1.5. Test Deviation

There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.





4.1.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	21°C	Humidity	61%
Test Engineer	YC Chen	Configurations	Normal Link
Test Date	Apr. 18, 2014	Test Mode	Mode 2

Freq.	Level	Over Limit	Limit Line	Remark
(MHz)	(dBuV)	(dB)	(dBuV)	
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = 40 log (specific distance / test distance) (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.



4.1.8. Results of Radiated Emissions (30MHz~1GHz)

Temperature	21°C	Humidity	61%
Test Engineer	YC Chen	Configurations	Normal Link
Test Mode	Mode 2		



CableAntenna Preamp Loss Factor Factor Remark Read Limit Line Over Read Limit Level T/Pos A/Pos Pol/Phase Freq Level MHz dBuV/m dBuV/m dB dB/m dB deg dBuV dB Cm -13.09 -7.12 -3.06 -8.65 -12.96 -14.65 1.50 2.06 2.09 2.51 3.37 4.38 99.84 191.99 199.75 275.41 497.54 812.79 30.41 36.38 40.44 37.35 33.04 31.35 43.50 43.50 43.50 46.00 46.00 46.00 52.27 56.24 58.70 54.11 46.84 39.21 27.82 Peak 27.30 Peak 27.25 QP 26.89 Peak 27.93 Peak 26.89 Peak 11.40 10.08 10.40 13.85 17.76 100 HORIZONTAL 100 HORIZONTAL 0 0 123456 252 0 0 0 100 HORIZONTAL 100 HORIZONTAL 100 HORIZONTAL 21.30 100 HORIZONTAL





Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableA Loss	ntenna Factor	Preamp Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		deg	Cm	
1 2 3 4 5 6	54.25 98.87 268.62 497.54 699.30 798.24	26.71 25.84 30.07 27.74 26.99 29.85	40.00 43.50 46.00 46.00 46.00 46.00	-13.29 -17.66 -15.93 -18.26 -19.01 -16.15	52.39 47.93 47.03 41.54 36.94 37.42	1.12 1.49 2.48 3.37 4.16 4.35	8.00 11.20 13.91 17.76 19.90 21.18	27.90 27.82 26.90 27.93 27.09 26.90	Peak Peak Peak Peak Peak Peak	360 360 360 360 360 360	400 400 400 400 400 400	VERTICAL VERTICAL VERTICAL VERTICAL VERTICAL VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = $20 \log Emission level (uV/m)$.

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.



4.2. Antenna Requirements

4.2.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.2.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.



5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
BILOG ANTENNA	Schaffner	CBL6112D	2888	20MHz ~ 2GHz	Jan. 15, 2014	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 12, 2013	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100019	9kHz~40GHz	Dec. 02, 2013	Radiation (03CH01-CB)
EMI Test Receiver	Agilent	N9038A	MY52260123	9kHz ~ 8GHz	Dec. 12, 2013	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO 2000	N/A	1 m - 4 m	N.C.R	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2013	Radiation (03CH01-CB)

Note: Calibration Interval of instruments listed above is one year.

"*" Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.



6. MEASUREMENT UNCERTAINTY

Uncertainty of Radiated Emission Measurement (30MHz ~ 1,000MHz)

	Un	certain		
Contribution	Value	Unit	Probability Distribution k	$u(x_i)$
Receiver reading	±0.173	dB	K=1	0.086
Cable loss	±0.174	dB	K=2	0.087
Antenna gain	±0.169	dB	K=2	0.084
Site imperfection	±0.433	dB	Triangular	0.214
Pre-amplifier gain	±0.366	dB	K=2	0.183
Transmitter antenna	±1.200	dB	Rectangular	0.600
Signal generator	±0.461	dB	Rectangular	0.231
Mismatch	±0.080	dB	U-shape	0.040
Spectrum analyzer	±0.500	dB	Rectangular	0.250
Combined standard uncertainty Uc(y)	1.778			
Measuring uncertainty for a level of confidence	3.555			