

February 19, 2016

## **Declaration – MIF for HAC RF Interference Evaluation**

To Whom It May Concern,

This device, with FCC ID: NM82PS6500, Hearing Aid Compatibility Requirement is going to be certified under ANSI C63.19-2011 version per Part 20.19.


The M rating was determined by measuring the maximum steady state average E-field values in dB (V/m) as documented in the HAC report and adding the MIF value in dB (V/m) using pre-determined values provided by Speag under :

**UID 10021 DAB (06.02.2014) / UID 10011 CAB (16.01.2014) / UID10295 AAB (16.01.2014) / UID 10170 CAB (13.05.2013) / UID 10077 CAB (26.11.2014) / UID 10069 CAB (26.11.2014).**

The Speag-reference documentation for supporting the pre-determined MIF value is Schmid & Partner Engineering AG, **UID SUMMARY (Communication Systems for Calibration, Issued Date 2013/05/31).**

We confirm that the Speag simulation provided represents all the air interface modes applicable for a HAC rating for this handset.

Sincerely Yours,



**Ivan Li / Project Manager**

**Jeff.CF Chu / Project Manager**

**HTC Corporation**

**Tel: 886-2-8912-4138**

**Fax: 886-2-8912-6307**

**E-mail: Jeff.CF Chu @htc.com**