FCC ID: 2A4TK-BH63020

## **RF Exposure Evaluation**

FCC KDB publication 447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

#### Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)	
The state of the	(A) Limits	for Occupational/Controlled	Exposures	TELLINE OF ST	
0.3–3.0	614	1.63	*(100)	6	
3.0–30	1842/f	4.89/f	*(900/f²)	6	
30–300	61.4	0.163	1.0	6 6	
300–1500			f/300	6	
1500–100,000	St. Bulling		5	6	
De St. Land	(B) Limits for	General Population/Uncontro	olled Exposure	The state of the s	
0.3–1.34	614	1.63	*(100)	30	
1.34–30	824/f	2.19/f	*(180/f²)	30	
30–300	27.5	0.073	0.2	30	
300–1500	STATE OF THE A		f/1500	30	
1500–100,000	A CONTRACTOR	A CONTRACTOR OF A	1.0	30	

f = frequency in MHz

Friis transmission formula:  $Pd = (Pout*G)/(4*pi*r^2)$ 

#### Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### **Test Procedure**

Software provided by client enabled the EUT to transmit and receive data at lowest, and highest channel individually.



# Shenzhen QC Testing Laboratory Co., Ltd.

### **Test Result of RF Exposure Evaluation**

Antenna gain=-0.68dBi

For BLE worst case

Test Frequency (MHz)	Minimum Separation Distance (cm)	Output Power (dBm)	Target power (dBm)	Target power (mW)	Antenna Gain (Numeric)	Power Density Limit (mW/cm²)	Power Density At 20 cm (mW/cm²)	Test Results
2402	20.00	2.37	3±1	2.512	0.86	1,50	0.0004	Pass
2440	20.00	2.88	3±1	2.512	0.86	d 1 6	0.0004	Pass
2480	20.00	2.4	3±1	2.512	0.86	and the second	0.0004	Pass

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure.