

FCC RF EXPOSURE EVALUATION REPORT

APPLICANT: Shanghai Flydigi Electronics Technology Co.,Ltd.

PRODUCT NAME: Flydigi Wasp One-handed Gamepad

MODEL NAME : FeiZhi Wasp-N

BRAND NAME: Flydigi

FCC ID : 2AORE-WASP-N

STANDARD(S) : 47CFR 2.1093

KDB 447498

ISSUE DATE : 2018-09-27

Reviewed by:

Gan Yueming
Gan yueming (Reviewer)

Approved by:

Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.





DIRECTORY

1	Technical Information	-
١.		•
1.1	Applicant and Manufacturer Information	3
1.2	Equipment Under Test (EUT) Description	3
1.3	Photographs of the EUT	4
1.4	Identification of all used EUT	5
1.5	Applied Reference Documents	5
2.	Device Category and RF Exposure Limit	E
3.	Measurement of RF Output Power ······	7
4.	RF Exposure Evaluation	8
Anı	nex A General Information······	٥

Change History			
Issue	Date	Reason for change	
1.0	2018-09-27	First edition	

Tel: 86-755-36698555

Http://www.morlab.cn



1. Technical Information

Note: Provide by manufacturer.

1.1 Applicant and Manufacturer Information

Applicant:	Shanghai Flydigi Electronics Technology Co.,Ltd.	
Applicant Address: Rm1108, No.258 Guoxia Rd, Yangpu District,Shanghai		
Manufacturer:	Shanghai Flydigi Electronics Technology Co.,Ltd.	
Manufacturer Address:	Rm1108, No.258 Guoxia Rd, Yangpu District, Shanghai	

1.2 Equipment Under Test (EUT) Description

EUT Type:	Flydigi WASP-N Single-Handed Controller
Hardware Version:	FeiZhi Wasp-V1.1
Software Version:	FeiZhi Wasp-V1.0.1
Frequency Bands:	Bluetooth: 2402MHz-2480MHz
Modulation Mode:	BLE: GFSK
Antenna Gain:	-4.41dBi





1.3 Photographs of the EUT

1. EUT front view



2. EUT rear view





1.4 Identification of all used EUT

The EUT identity consists of numerical and letter characters, the letter character indicates the test sample, and the following two numerical characters indicate the software version of the test sample.

EUT Identity	Hardware Version	Software Version
1#	FeiZhi Wasp-V1.1	FeiZhi Wasp-V1.0.1

1.5 Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	47 CFR§2.1093	Radio frequency Radiation Exposure Evaluation: portable
		devices
2	KDB 447498 D01v06	General RF Exposure Guidance

FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,



2. Device Category and RF Exposure Limit

Per user manual, this device is a Flydigi WASP-N Single-Handed Controller. Based on 47CFR 2.1093, this device belongs to portable device category with General Population/Uncontrolled exposure.

Portable Devices:

47CFR 2.1093(b)

For purposes of this section, a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

GENERAL POPULATION / UNCONTROLLED EXPOSURE

47CFR 2.1093(d) (2)

Limits for General Population/Uncontrolled exposure: 0.08 W/kg as averaged over the whole-body and spatial peak SAR not exceeding 1.6 W/kg as averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the hands, wrists, feet and ankles where the spatial peak SAR shall not exceed 4 W/kg, as averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). General Population/Uncontrolled limits apply when the general public may be exposed, or when persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or do not exercise control over their exposure. Warning labels placed on consumer devices such as cellular telephones will not be sufficient reason to allow these devices to be evaluated subject to limits for occupational/controlled exposure in paragraph (d)(1) of this section.





3. Measurement of RF Output Power

Bluetooth

	Channel	Frequency (MHz)	Peak Power	Tune-up Limit
Band			(dBm)	(dBm)
			GFSK	
	CH 00	2402	0.67	1.0
BLE	CH 19	2440	1.74	2.0
	CH 39	2480	3.01	3.5

Note:

According to KDB 447498, time-averaged maximum conducted output power applies to SAR and, as required by § 2.1091(c), time-averaged effective radiated power applies to MPE.





4. RF Exposure Evaluation

The device only incorporates a Bluetooth transmitter, so standalone SAR evaluation is required for Bluetooth and simultaneous SAR is not required.

Standalone transmission SAR evaluation:

According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation Distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f(GHz)}$] ≤ 3.0

The maximum tune-up limit power is 2.24mW @ 2.48GHz

When the Flydigi WASP-N Single-Handed Controller is used on the hand/head, so use **5mm** as the most conservative minimum test separation distance,

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]·[$\sqrt{f(GHz)}$] =0.71 > 3.0

Therefore the standalone SAR evaluation are not required for this device.





Annex A General Information

1. Identification of the Responsible Testing Laboratory

- monument of the responding recining amortanery			
Company Name:	Shenzhen Morlab Communications Technology Co., Ltd.		
Department:	Morlab Laboratory		
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang		
	Road, Block 67, BaoAn District, ShenZhen, GuangDong		
	Province, P. R. China		
Responsible Test Lab Manager:	Mr. Su Feng		
Telephone:	+86 755 36698555		
Facsimile:	+86 755 36698525		

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
	Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang
	Road, Block 67, BaoAn District, ShenZhen, GuangDong
	Province, P. R. China

 END OF REPORT	
 END OF REPORT	

