



# TEST REPORT

**FCC ID: 2AIZN-X609B****Product: Mobile Phone****Model No.: X609B****Additional Model No.: N/A****Trade Mark: Infinix****Report No.: FCC18080068A-BLE****Issued Date: Oct. 16, 2018**

Issued for:

**INFINIX MOBILITY LIMITED****RMS 05-15, 13A/F SOUTH TOWER WORLD FINANCE CTR HARBOUR CITY 17  
CANTON RD TST KLN HONG KONG**

Issued By:

**World Standardization Certification & Testing Group Co., Ltd.  
Building A-B, Baoshi Science & Technology Park, Baoshi Road,  
Bao'an District, Shenzhen, Guangdong, China****TEL: +86-755-26996192****FAX: +86-755-86376605**

**Note:** The results contained in this report pertain only to the tested sample. This report shall not be reproduced, except in full, without written approval of World Standardization Certification & Testing Group Co., Ltd. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.







## TABLE OF CONTENTS

1. GENERAL INFORMATION .....	3
2. GENERAL DESCRIPTION OF EUT .....	4
3. Facilities and Accreditations .....	5
3.1. ACCREDITATIONS .....	5
3.2. TEST DESCRIPTION .....	6
3.3. DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE) .....	9
3.4. SUMMARY OF TEST RESULTS .....	10
4. MEASUREMENT INSTRUMENTS .....	11
5. ANTENNA REQUIREMENT .....	12
5.1. STANDARD APPLICABLE .....	12
5.2. ANTENNA CONNECTOR CONSTRUCTION .....	12
6. CONDUCTED EMISSIONS .....	13
7. SPURIOUS EMISSIONS .....	16
8. -6dB BANDWIDTH TESTING .....	25
9. MAXIMUM PEAK OUTPUT POWER .....	28
10. 100 kHz Bandwidth of Frequency Band Edge .....	31
11. MAXIMUM CONDUCTED POWER SPECTRAL DENSITY .....	36







For Question,  
Please Contact with WSCT  
www.wsct-cert.com

## 1. GENERAL INFORMATION

<b>Product:</b>	Mobile Phone
<b>Model No.:</b>	X609B
<b>Additional Model:</b>	N/A
<b>Applicant:</b>	INFINIX MOBILITY LIMITED
<b>Address:</b>	RMS 05-15, 13A/F SOUTH TOWER WORLD FINANCE CTR HARBOUR CITY 17 CANTON RD TST KLN HONG KONG
<b>Manufacturer:</b>	SHENZHEN TECNO TECHNOLOGY CO., LTD.
<b>Address:</b>	1/F-4/F, 7/F, BUILDING 3, TAIPINGYANG INDUSTRIAL ZONE, NO.2088, SHENYAN ROAD, YANTIAN DISTRICT, SHENZHEN CITY, GUANGDONG PROVINCE, P.R.C
<b>Data of receipt:</b>	Sep. 26, 2018
<b>Date of Test:</b>	Sep. 26, 2018 to Oct. 15, 2018
<b>Applicable Standards:</b>	FCC CFR Title 47 Part 15 Subpart C Section 15.247

The above equipment has been tested by World Standardization Certification & Testing Group Co., Ltd. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By: \_\_\_\_\_

Pu Shixi

( Pu Shixi)

Date: \_\_\_\_\_

Oct. 16, 2018

Check By: \_\_\_\_\_

Qin Shuiquan

( Qin Shuiquan)

Date: \_\_\_\_\_

Oct. 16, 2018

Approved By: \_\_\_\_\_

Wang Fengbing

(Wang Fengbing)

Date: \_\_\_\_\_

Oct. 16, 2018



世标检测认证股份  
World Standardization Certification & Testing Group Co., Ltd.

ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China  
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com





## 2. GENERAL DESCRIPTION OF EUT

Equipment Type:	Mobile Phone
Test Model:	X609B
Additional Model:	N/A
Trade Mark:	Infinix
Applicant:	INFINIX MOBILITY LIMITED
Address:	RMS 05-15, 13A/F SOUTH TOWER WORLD FINANCE CTR HARBOUR CITY 17 CANTON RD TST KLN HONG KONG
Manufacturer:	SHENZHEN TECNO TECHNOLOGY CO.,LTD.
Address:	1/F-4/F,7/F, BUILDING 3, TAIPINGYANG INDUSTRIAL ZONE, NO.2088, SHENYAN ROAD, YANTIAN DISTRICT, SHENZHEN CITY, GUANGDONG PROVINCE, P.R.C
Hardware version:	V2.0
Software version:	X609B-H8025C-GO-180911V46
Extreme Temp. Tolerance:	-10°C to +65°C
Battery information:	Li-Polymer Battery : BL-34BX Voltage: 3.8V Rated Capacity:3400mAh/12.92Wh Typical Capacity:3500mAh/13.30Wh Limited Charge Voltage: 4.35V
Adapter Information:	Adapter: CU-52JT Input: AC 100-240V 50/60Hz 200mA Output: DC 5V 1.2A
Operating Frequency:	2402-2480MHz
Channels:	40
Channel Spacing:	2MHz
Modulation Type:	GFSK
Antenna Type:	Integral Antenna
Antenna gain:	1.26dBi





### 3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at **Building A-B, Baoshi Science & Technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China of the World Standardization Certification & Testing Group Co., Ltd**

The sites are constructed in conformance with the requirements of ANSI C63.4 and CISPR Publication 22. All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

**Registration Number: 366353**

#### 3.1. ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

**USA**

**NVLAP** (The certificate registration number is NVLAP LAB CODE:600142-0)

**Japan**

**VCCI** (The certificate registration number is C-4790, R-3684, G-837)

**Canada**

**INDUSTRY CANADA**

(The certificated registration number is 7700A-1)

**China**

**CNAS** (The certificated registration number is L3732)

Copies of granted accreditation certificates are available for downloading from our web site, <http://www.wsct-cert.com>







### 3.2. TEST DESCRIPTION

#### 3.2.1. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 3.2\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.7\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.7\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$







### 3.2.2. DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH20
Mode 3	CH39
Mode 4	Normal

For Conducted Emission	
Final Test Mode	Description
Mode 4	Normal

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH20
Mode 3	CH39

Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) Record the worst case of each test item in this report.
- (3) When we test it, the duty cycle  $\geq 98\%$








### 3.2.3. Table of Parameters of Text Software Setting

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters.

Test software Version	N/A
-----------------------	-----

Frequency	2402 MHz	2440 MHz	2480 MHz
Parameters(1Mbps)	DEF	DEF	DEF

### 3.2.4. CONFIGURATION OF SYSTEM UNDER TEST



(EUT: Mobile Phone)





### 3.3. DESCRIPTION OF SUPPORT UNITS (CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	Adapter	/	CU-52JT	/	/
2	Earphone	/	N/A	/	/

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.







### 3.4. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.203	Antenna Requirement	PASS	
15.207	Conducted Emission	PASS	
15.209, 15.205, 15.247(d)	Spurious Emission	PASS	
15.247(a) (2)	6dB Bandwidth Testing	PASS	
15.247(b) (3)	Maximum Peak Output Power	PASS	
15.247(d)	100 KHz Bandwidth of Frequency Band Edge	PASS	
15.247(e)	Maximum Conducted Power Spectral Density	PASS	

#### NOTE:

(1) "N/A" denotes test is not applicable in this test report.







#### 4. MEASUREMENT INSTRUMENTS

NAME OF EQUIPMENT	MANUFACTURER	MODEL	SERIAL NUMBER	Calibration Date	Calibration Due.
EMI Test Receiver	R&S	ESCI	100005	08/19/2018	08/18/2019
LISN	AFJ	LS16	16010222119	08/19/2018	08/18/2019
LISN(EUT)	Mestec	AN3016	04/10040	08/19/2018	08/18/2019
Universal Radio Communication Tester	R&S	CMU 200	1100.0008.02	08/19/2018	08/18/2019
Coaxial cable	Megalon	LMR400	N/A	08/12/2018	08/11/2019
GPIO cable	Megalon	GPIO	N/A	08/12/2018	08/11/2019
Spectrum Analyzer	R&S	FSU	100114	08/19/2018	08/18/2019
Pre Amplifier	H.P.	HP8447E	2945A02715	10/13/2017	10/12/2018
Pre-Amplifier	CDSI	PAP-1G18-38	--	10/13/2017	10/12/2018
Bi-log Antenna	SUNOL Sciences	JB3	A021907	09/13/2018	09/12/2019
9*6*6 Anechoic	--	--	--	08/21/2018	08/20/2019
Horn Antenna	COMPLIANCE ENGINEERING	CE18000	--	09/13/2018	09/12/2019
Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-631	08/23/2018	08/22/2019
Cable	TIME MICROWAVE	LMR-400	N-TYPE04	04/25/2018	04/24/2019
System-Controller	CCS	N/A	N/A	N.C.R	N.C.R
Turn Table	CCS	N/A	N/A	N.C.R	N.C.R
Antenna Tower	CCS	N/A	N/A	N.C.R	N.C.R
RF cable	Murata	MXHQ87WA3000	-	08/21/2018	08/20/2019
Loop Antenna	EMCO	6502	00042960	08/22/2018	08/21/2019
Horn Antenna	SCHWARZBECK	BBHA 9170	1123	08/19/2018	08/18/2019
Power meter	Anritsu	ML2487A	6K00003613	08/23/2018	08/22/2019
Power sensor	Anritsu	MX248XD	--	08/19/2018	08/18/2019







## 5. ANTENNA REQUIREMENT

### 5.1. Standard Applicable

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### 5.2. Antenna Connector Construction

The EUT's antenna integrated on PCB, The antenna's gain is 1.26dBi and meets the requirement.







## 6. CONDUCTED EMISSIONS

### 6.1.1. Applicable Standard

The specification used was with the FCC Part 15.207 limits.

### 6.1.2. Test Procedure

During the conducted emission test, the EUT was connected to the outlet of the LISN. Maximizing procedure was performed on the six (6) highest emissions of the EUT. All data was recorded in the Quasi-peak and average detection mode.

### 6.1.3. Test Conditions

Temperature:	26 °C
Relative Humidity:	60%
ATM Pressure:	100.0kPa
Voltage	120V/60Hz

### 6.1.4. TEST RESULTS

Plot(s) of Test Data is presented hereinafter as reference.








For Question,  
Please Contact with WSCT  
www.wsct-cert.com

Phase: L



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.4700	37.41	10.40	47.81	56.51	-8.70	QP
2	*	0.4700	32.36	10.40	42.76	46.51	-3.75	AVG
3		0.8380	37.29	10.36	47.65	56.00	-8.35	QP
4		0.8900	31.03	10.35	41.38	46.00	-4.62	AVG
5		1.2579	33.51	10.33	43.84	56.00	-12.16	QP
6		1.2579	28.67	10.33	39.00	46.00	-7.00	AVG
7		1.6740	27.70	10.31	38.01	46.00	-7.99	AVG
8		1.7300	31.05	10.30	41.35	56.00	-14.65	QP
9		2.1099	26.15	10.29	36.44	46.00	-9.56	AVG
10		3.5220	28.36	10.26	38.62	56.00	-17.38	QP
11		23.7620	20.09	10.10	30.19	50.00	-19.81	AVG
12		24.0500	25.26	10.10	35.36	60.00	-24.64	QP

Remark: All of the Tx modes have been investigated, and only worst mode is presented in this report.



世标检测认证股份  
World Standardization Certification & Testing Group Co., Ltd.

ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China  
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com


Member of the WSCT INC.





For Question,  
Please Contact with WSCT  
www.wsct-cert.com

Phase: N



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1620	28.99	10.44	39.43	65.36	-25.93	QP
2		0.2620	21.52	10.43	31.95	51.36	-19.41	AVG
3	*	0.4700	26.02	10.40	36.42	46.51	-10.09	AVG
4		0.5740	32.19	10.39	42.58	56.00	-13.42	QP
5		0.7260	27.78	10.37	38.15	56.00	-17.85	QP
6		0.8900	23.18	10.35	33.53	46.00	-12.47	AVG
7		1.3580	31.69	10.32	42.01	56.00	-13.99	QP
8		1.3619	22.93	10.32	33.25	46.00	-12.75	AVG
9		2.1099	22.13	10.29	32.42	46.00	-13.58	AVG
10		2.8980	28.28	10.27	38.55	56.00	-17.45	QP
11		23.8220	25.25	10.10	35.35	60.00	-24.65	QP
12		23.9220	16.53	10.10	26.63	50.00	-23.37	AVG

Remark: All of the Tx modes have been investigated, and only worst mode is presented in this report.



世标检测认证股份  
World Standardization Certification & Testing Group Co., Ltd.

ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China  
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.





## 7. SPURIOUS EMISSIONS

### 7.1.1. Test Equipment

Please refer to section 4 this report.

### 7.1.2. Test Procedure

The out of band emission tests were performed in the 3-meter chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part Subpart C limits.

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

**Both horizontal and vertical antenna polarities were tested**

**And performed pretest to three orthogonal axis. The worst case emissions were reported**

### 7.1.3. Environmental Conditions

Temperature:	26 °C
Relative Humidity:	55%
ATM Pressure:	100.0kPa








#### 7.1.4. Radiated Test Setup

The system was investigated from 9 KHz to 25 GHz.


During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	Detector
9KHz-30MHz	9kHz	30 kHz	QP
30 MHz – 1000 MHz	100 kHz	300 kHz	QP
1000 MHz – 25 GHz	1 MHz	3 MHz	PK
1000 MHz – 25 GHz	1 MHz	10 Hz	Ave

##### (A) Radiated Emission Test-Up Frequency Below 30MHz




##### (B) Radiated Emission Test-Up Frequency 30MHz~1GHz







(C) Radiated Emission Test-Up Frequency Above 1GHz



For the accrual test configuration, please refer to the related items-photos of Testing.





For Question,  
Please Contact with WSCT  
www.wsct-cert.com

### 7.1.5. Radiated Emission Limit

Applicable Standard  
FCC §15.247 (d); §15.209; §15.205;  
Radiated Emission Test Result  
Test Mode: Transmitting

Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100**	3
88–216	150**	3
216–960	200**	3
Above 960	500	3

Note:

*Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported*

### 7.1.6. Test result:

From 9KHz to 30MHz

NOTE: 9KHz-30MHz the measurements were greater than 20dB below the limit.








For Question,  
Please Contact with WSCT  
www.wsct-cert.com

Frequency from 30MHz to 1GHz

Horizontal:

80.0 dBuV/m



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	32.1795	26.79	3.96	30.75	40.00	-9.25	QP
2		54.8348	26.43	-5.59	20.84	40.00	-19.16	QP
3		113.7143	23.06	-2.23	20.83	43.50	-22.67	QP
4		229.2931	24.46	-5.67	18.79	46.00	-27.21	QP
5		392.0951	26.41	-1.56	24.85	46.00	-21.15	QP
6		839.1818	25.19	4.57	29.76	46.00	-16.24	QP

Remark: All of the TX modes have been investigated, and only worst mode is presented in this report.



世标检测认证股份  
World Standardization Certification & Testing Group Co., Ltd.

ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China  
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com


Member of the WSCT INC.



For Question,  
Please Contact with WSCT  
t-cert.com

Vertical:

80.0 dBuV/m



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	32.2925	27.95	3.91	31.86	40.00	-8.14	QP
2		42.3022	26.92	-0.98	25.94	40.00	-14.06	QP
3		58.2030	33.49	-6.00	27.49	40.00	-12.51	QP
4		104.1701	24.77	-3.01	21.76	43.50	-21.74	QP
5		504.7062	24.17	0.66	24.83	46.00	-21.17	QP
6		836.2443	25.31	4.53	29.84	46.00	-16.16	QP

Remark: All of the TX modes have been investigated, and only worst mode is presented in this report.







### 7.1.7. From 1GHz to 25GHz:

Operation Mode:	Channel 0	Measured Distance:	3m
Frequency Range:	Above 1GHz	Temperature :	28℃
Test Result:	PASS	Humidity :	65 %

Freq. (MHz)	Ant.Pol .	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4804	V	59.00	40.75	74	54	-15.00	-13.25
7206	V	59.25	40.65	74	54	-14.75	-13.35
4804	H	59.34	39.29	74	54	-14.66	-14.71
7206	H	58.26	39.26	74	54	-15.74	-14.74

**All emissions not reported were more than 20dB below the specified limit or in the noise floor.**

- Note:**
- (1) All Readings are Peak Value and AV.
  - (2) Emission Level= Reading Level+ Probe Factor +Cable Loss.
  - (3) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.







For Question,  
Please Contact with WSCT  
www.wsct-cert.com

Operation Mode:	Channel 20	Measured Distance:	3m
Frequency Range:	Above 1GHz	Temperature :	28℃
Test Result:	PASS	Humidity :	65 %

Freq. (MHz)	Ant.Pol .	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4880	V	60.35	39.47	74	54	-13.65	-14.53
7320	V	60.00	39.65	74	54	-14.00	-14.35
4880	H	58.85	39.31	74	54	-15.15	-14.69
7320	H	59.90	40.90	74	54	-14.10	-13.10

**All emissions not reported were more than 20dB below the specified limit or in the noise floor.**

**Note:**

- (1) All Readings are Peak Value and AV.
- (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
- (3) Data of measurement within this frequency range shown "--" in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.







For Question,  
Please Contact with WSCT  
www.wsct-cert.com

Operation Mode:	Channel 39	Measured Distance:	3m
Frequency Range:	Above 1GHz	Temperature :	28℃
Test Result:	PASS	Humidity :	65 %

Freq. (MHz)	Ant.Po. H/V	Emission Level(dBuV)		Limit 3m(dBuV/m)		Over(dB)	
		PK	AV	PK	AV	PK	AV
4960	V	59.68	40.28	74	54	-14.32	-13.72
7440	V	59.19	39.48	74	54	-14.81	-14.52
4960	H	58.66	40.88	74	54	-15.34	-13.12
7440	H	59.94	40.94	74	54	-14.06	-13.06

**All emissions not reported were more than 20dB below the specified limit or in the noise floor.**

- Note:**
- (1) All Readings are Peak Value and AV.
  - (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
  - (3) Data of measurement within this frequency range shown “ -- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.







## 8. -6dB BANDWIDTH TESTING

### 8.1.1. Test Equipment

Please refer to Section 4 this report.

### 8.1.2. Test Procedure

1. Set EUT in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=100KHz, VBW≥RBW, Span=3MHz, Sweep=auto.
4. Mark the peak frequency and -6dB(upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

**Note :** The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

### 8.1.3. Environmental Conditions

Temperature:	26 °C
Relative Humidity:	55%
ATM Pressure:	100.0kPa

### 8.1.4. Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.








### 8.1.5. Test Result: Pass.

Please refer to the following tables

Channel Frequency (MHz)	Data Rate (Mbps)	6dB Bandwidth (kHz)	Limit (kHz)	Ref. Plot
2402	1	740.38	>500	PLOT 1
2440	1	745.19	>500	PLOT 2
2480	1	735.58	>500	PLOT 3

Low Channel









For Question,  
Please Contact with WSCT  
www.wsct-cert.com

### Middle channel



### High Channel







## 9. MAXIMUM PEAK OUTPUT POWER

### 9.1.1. Test Equipment

Please refer to Section 4 this report.

### 9.1.2. Test Procedure

1. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set the RBW =1MHz, VBW  $\geq$  3RBW, span  $\geq$  1.5\*6dbbandwith.  
Sweep time = auto couple, Detector = peak, Trace mode = max hold.
4. Record the maximum power from the spectrum analyzer.
5. The maximum peak power shall be less 1 Watt (30dBm).

**Note :** The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

### 9.1.3. Environmental Conditions

Temperature:	26 °C
Relative Humidity:	55%
ATM Pressure:	100.0kPa

### 9.1.4. Applicable Standard

According to §15.247(b) (3), for systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.








### 9.1.5. Test Result

Channel	Frequency (MHz)	Data Rate (Mbps)	Conducted Power (dBm)	Limit (dBm)
Low	2402	1	1.00	30
Middle	2440	1	1.73	30
High	2480	1	2.11	30

#### Low channel









For Question,  
Please Contact with WSCT  
www.wsct-cert.com

### Middle channel



Date: 4.OCT.2018 09:41:24

### High channel



Date: 4.OCT.2018 09:42:08



世标检测认证股份  
World Standardization Certification & Testing Group Co., Ltd.

ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China  
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.





## 10. 100 kHz Bandwidth of Frequency Band Edge

### 10.1.1. Test Equipment

Please refer to Section 4 this report.

### 10.1.2. Test Procedure

The out of band emission tests were performed in the 3-meter chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part Subpart C limits.

### 10.1.3. Environmental Conditions

Temperature:	26 °C
Relative Humidity:	55%
ATM Pressure:	100.0kPa

### 10.1.4. Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).







For Question,  
Please Contact with WSCT  
www.wsct-cert.com

### 10.1.5. Test Result: PASS

#### Radiated measurement:

Indicated		result (PK/AV)	Table Angle degree	Antenna		Correction Factor			FCC Part 15.247		
Frequency (MHz)	Receiver Reading (dBμV/m)			Height (m)	Polar (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dBμV/m)	Limit (dBμV/m)	Margin (dB)
Low Channel (2402MHz)											
2390	40.23	AV	225	1.5	V	30.3	4.1	33.1	41.53	54	12.47
2390	41.68	AV	90	2	H	30.3	4.1	33.1	42.98	54	11.02
2390	61.21	PK	180	1.5	V	30.3	4.1	33.1	41.53	74	11.49
2390	61.92	PK	270	2	H	30.3	4.1	33.1	63.22	74	10.78
High Channel (2480MHz)											
2483.5	41.12	AV	360	1	V	31	4.4	32.7	43.82	54	10.18
2483.5	41.20	AV	90	2	H	31	4.4	32.7	43.9	54	10.1
2483.5	60.35	PK	180	1	V	31	4.4	32.7	63.05	74	10.95
2483.5	62.31	PK	225	2	H	31	4.4	32.7	65.01	74	8.99









For Question,  
Please Contact with WSCT  
www.wsct-cert.com

## Conducted Emission Measurement:

### Low channel



### High channel



世标检测认证股份

World Standardization Certification & Testing Group Co., Ltd.

ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China  
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com


Member of the WSCT INC.






## Conducted spurious emissions

### Channel Low



Date: 4.OCT.2018 09:46:55

### Channel Mid




Date: 4.OCT.2018 09:47:54







For Question,  
Please Contact with WSCT  
www.wsct-cert.com



世标检测认证股份  
World Standardization Certification & Testing Group Co., Ltd.

ADD: Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China  
TEL: 86-755-26996143/26996144/26996145/26996192 FAX: 86-755-86376605 E-mail: Fengbing.Wang@wsct-cert.com Http: www.wsct-cert.com

Member of the WSCT INC.





## 11. MAXIMUM CONDUCTED POWER SPECTRAL DENSITY

### 11.1.1. Test Equipment

Please refer to Section 4 this report.

### 11.1.2. Test Procedure

- 1, This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.
- 2, Set analyzer center frequency to DTS channel center frequency.
- 3, Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ , Set the VBW  $\geq 3 \text{ RBW}$ , Detector = peak. Sweep time = auto couple
- 4, Trace mode = max hold, Allow trace to fully stabilize.

**Note :** The EUT was tested according to KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

### 11.1.3. Environmental Conditions

Temperature:	25 °C
Relative Humidity:	55%
ATM Pressure:	100.0kPa

### 11.1.4. Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.








### 11.1.5. Test Result

PASS

Channel Frequency (MHz)	Data Rate (Mbps)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	RESULT
2402	1	-14.10	8	Compliant
2440	1	-13.61	8	Compliant
2480	1	-12.90	8	Compliant

Low Channel









For Question,  
Please Contact with WSCT  
www.wsct-cert.com

### Middle Channel



Date: 4.OCT.2018 09:52:24

### High Channel



Date: 4.OCT.2018 09:53:04

---END OF REPORT---



世标检测认证股份  
World Standardization Certification & Testing Group Co.,Ltd.

ADD:Building A-B Baoshi Science & technology Park, Baoshi Road, Bao'an District, Shenzhen, Guangdong, China  
TEL:86-755-26996143/26996144/26996145/26996192 FAX:86-755-86376605 E-mail:Fengbing.Wang@wsct-cert.com Http:www.wsct-cert.com

Member of the WSCT INC.