

RF Exposure Evaluation

REQUIREMENT

KDB447498 D01 General RF Exposure Guidance v06, Clause 4.3.1(a)

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

Where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

TEST RESULT

☒ Passed ☐ Not Applicable

Radio Type	Frequency range (MHz)	Conducted Power (dBm)	Maximum Tune-up (dBm)	Calculating data	Limit	Result
Bluetooth	2402	-1.39	-1.00	0.246	3.00	Pass
Bluetooth	2440	-1.45	-1.00	0.248	3.00	Pass
Bluetooth	2480	-1.83	-1.00	0.250	3.00	Pass

Note:

- 1) The maximum antenna gain is 0dBi
- 2) The exposure evaluation safety distance is 0mm.