



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V03
Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No. : CQASZ20181000025E-02

Applicant: ZAGG Inc.

Address of Applicant: 910 West Legacy Center Way, Midvale, Utah, United States, 84047

Manufacturer: ZAGG Inc.

Address of Manufacturer: 910 West Legacy Center Way, Midvale, Utah, United States, 84047

Factory: Dongguan Kailai Eletronic Co.,Ltd

Address of Factory: No 36# Industrial Main Road, 2nd District (Shahukou), Eastern Industrial Park, Changping Town, Dongguan City, Guangdong Province, China

Equipment Under Test (EUT):

Product: Little Rockerz Wireless Headphones

All Model No.: IFOEW29-I, 304101849, 304101850

Test Model No.: IFOEW29-I

Brand Name: IFROGZ

FCC ID: QTG-IFAYLR

Standards: 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06

Date of Test: 2018-10-17 to 2018-10-23

Date of Issue: 2018-10-23

Test Result : PASS*

Tested By:

Tiny You

(Tiny You)

Reviewed By:

Aaron Ma

(Aaron Ma)

Approved By:

Jack Ai

(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20181000025E-02	Rev.01	Initial report	2018-10-23

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT	4
4 SAR EVALUATION	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
4.1.1 <i>Standard Requirement</i>	5
4.1.2 <i>Limits</i>	5
4.1.3 <i>EUT RF Exposure</i>	5

3 General Information

3.1 Client Information

Applicant:	ZAGG Inc.
Address of Applicant:	910 West Legacy Center Way, Midvale, Utah, United States, 84047
Manufacturer:	ZAGG Inc.
Address of Manufacturer:	910 West Legacy Center Way, Midvale, Utah, United States, 84047
Factory:	Dongguan Kailai Eletronic Co.,Ltd
Address of Factory:	No 36# Industrial Main Road, 2nd District (Shahukou), Eastern Industrial Park, Changping Town, Dongguan City, Guangdong Province, China

3.2 General Description of EUT

Product Name:	Little Rockerz Wireless Headphones
All Model No.:	IFOEW29-I, 304101849, 304101850
Test Model No.:	IFOEW29-I
Brand Name:	IFROGZ
Hardware Version:	V1.0
Software Version:	V1.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.1
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	portable production
Test Software of EUT:	Blue test (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	0dBi
Power Supply:	lithium battery: DC3.7V, 180mAh, Charge by USB

Note:

All model: IFOEW29-I, 304101849, 304101850

Only the model IFOEW29-I was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{[\sqrt{f(\text{GHz})}]} \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where} \right.$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure

For BT:

Measurement Data

GFSK mode	
Test channel	Peak Output Power (dBm)
Lowest	-0.080
Middle	-0.480
Highest	-0.890
$\pi/4$ DQPSK mode	
Test channel	Peak Output Power (dBm)
Lowest	0.140
Middle	-0.190
Highest	-0.600
8DPSK mode	
Test channel	Peak Output Power (dBm)
Lowest	0.720
Middle	0.340
Highest	-0.140

The Max Conducted Peak Output Power is 0.72dBm in Lowest channel(2.402GHz);

The best case gain of the antenna is 0dBi.

EIRP= 0.72dBm + 0dBi = 0.72dBm

0.72dBm logarithmic terms convert to numeric result is nearly 1.18mW

According to the formula. calculate the EIRP test result:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$$

General RF Exposure = $(1.18\text{mW} / 5 \text{ mm}) \times \sqrt{2.402\text{GHz}} = 0.37$ ①

SAR requirement:

S= 3.0

② ;

① < ②.

So the SAR report is not required.

Remark: The Max Conducted Peak Output Power data refer to report Report No.:CQASZ20181000025E-01