



## TEST REPORT

**Application No.:** GZCR2103000023AT  
**Applicant:** The House of Marley. LLC  
**Address of Applicant:** 3000 Pontiac Trail, Commerce Township, Michigan 48390 United States  
**Manufacturer:** The House of Marley. LLC  
**Address of Manufacturer:** 3000 Pontiac Trail, Commerce Township, Michigan 48390 United States  
**Factory:** Cosonic Intelligent Technologies Co., Ltd.  
**Address of Factory:** Room 506 building 1, No.6, South Industrial Road, Songshan Lake High-tech Industrial Development Zone, Dongguan City, Guangdong, P.R. China 523808

**Equipment Under Test (EUT):**

**FCC ID:** PVB-EMJA015

**EUT Name:** No Bounds  
**Model No.:** EM-JA015  
**Trade Mark:** Marley  
**Standard(s) :** 47 CFR Part 15, Subpart C 15.247  
**Date of Receipt:** 2021-03-10  
**Date of Test:** 2021-03-15 to 2021-03-24  
**Date of Issue:** 2021-03-26

<b>Test Result:</b>	<b>Pass*</b>
---------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.

Kobe Jian  
EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2021-03-26		Original

Authorized for issue by				
Tested By		Kevin Zhang		
		Kevin Zhang/Project Engineer		
Reviewed By		Ricky Liu		
		Ricky Liu/Reviewer		

## 2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass

**Note:** E.U.T./EUT means Equipment Under Test.

Pass means the test result passed the test standard requirement, please find the detailed decision rule in the report relative section.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

### 3 Contents

	Page
<b>1 Cover Page .....</b>	<b>1</b>
<b>2 Test Summary.....</b>	<b>3</b>
<b>3 Contents .....</b>	<b>4</b>
<b>4 General Information.....</b>	<b>6</b>
4.1 Details of E.U.T. ....	6
4.2 Description of Support Units .....	6
4.3 Measurement Uncertainty .....	6
4.4 Test Location .....	6
4.5 Test Facility.....	7
4.6 Deviation from Standards.....	8
4.7 Abnormalities from Standard Conditions.....	8
4.8 Duty cycle of the EUT.....	8
<b>5 Equipment List .....</b>	<b>9</b>
<b>6 Radio Spectrum Technical Requirement.....</b>	<b>11</b>
6.1 Antenna Requirement .....	11
6.1.1 Test Requirement: .....	11
6.1.2 Conclusion .....	11
<b>7 Radio Spectrum Matter Test Results.....</b>	<b>12</b>
7.1 Conducted Peak Output Power .....	12
7.1.1 E.U.T. Operation .....	12
7.1.2 Test Mode Description .....	12
7.1.3 Test Setup Diagram .....	12
7.1.4 Measurement Procedure and Data.....	12
7.2 Minimum 6dB Bandwidth.....	13
7.2.1 E.U.T. Operation .....	13
7.2.2 Test Mode Description .....	13
7.2.3 Test Setup Diagram .....	13
7.2.4 Measurement Procedure and Data.....	13
7.3 Power Spectrum Density .....	14
7.3.1 E.U.T. Operation .....	14
7.3.2 Test Mode Description .....	14
7.3.3 Test Setup Diagram .....	14
7.3.4 Measurement Procedure and Data.....	14
7.4 Conducted Band Edges Measurement .....	15
7.4.1 E.U.T. Operation .....	15
7.4.2 Test Mode Description .....	15
7.4.3 Test Setup Diagram .....	15
7.4.4 Measurement Procedure and Data.....	15
7.5 Conducted Spurious Emissions .....	16
7.5.1 E.U.T. Operation .....	16
7.5.2 Test Mode Description .....	16



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Guangzhou Branch EEC Laboratory

No. 198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 [www.sgsgroup.com.cn](http://www.sgsgroup.com.cn)  
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 [sgs.china@sgs.com](mailto:sgs.china@sgs.com)

7.5.3	Test Setup Diagram .....	16
7.5.4	Measurement Procedure and Data .....	16
7.6	Radiated Emissions which fall in the restricted bands .....	17
7.6.1	E.U.T. Operation .....	17
7.6.2	Test Mode Description .....	17
7.6.3	Test Setup Diagram .....	17
7.6.4	Measurement Procedure and Data .....	18
7.7	Radiated Spurious Emissions .....	23
7.7.1	E.U.T. Operation .....	23
7.7.2	Test Mode Description .....	23
7.7.3	Test Setup Diagram .....	23
7.7.4	Measurement Procedure and Data .....	24
<b>8</b>	<b>Appendix .....</b>	<b>33</b>
8.1	Appendix A: DTS Bandwidth .....	33
8.1.1	Test Result .....	33
8.1.2	Test Graphs .....	33
8.2	Appendix B: Maximum conducted output power .....	35
8.2.1	Test Result .....	35
8.2.2	Test Graphs .....	35
8.3	Appendix C: Maximum power spectral density .....	37
8.3.1	Test Result .....	37
8.3.2	Test Graphs .....	37
8.4	Appendix D: Band edge measurements .....	39
8.4.1	Test Result .....	39
8.4.2	Test Graphs .....	39
8.5	Appendix E: Conducted Spurious Emission .....	40
8.5.1	Test Result .....	40
8.5.2	Test Graphs .....	40
8.6	Appendix F: Duty Cycle .....	45
8.6.1	Test Result .....	45
8.6.2	Test Graphs .....	45



## 4 General Information

### 4.1 Details of E.U.T.

Power supply:	DC 5V, 1.0A
Cable(s):	DC input cable (unshielded, 1.2 m)
Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Antenna Type:	PCB Antenna
Antenna Gain:	1.18 dBi declared by applicant.
Function:	No bounds Portable Speaker with BT Function.
S/N	208569
Hardware Version	V1.5
Firmware	V2.8
Test Software	FCC Test tools v1.08
Power Setting	-5dBm can't be changed by user.

### 4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Note Book Computer	LENOVO	Lenovo Xiaoxinchao 5000	PF0TNMG8

### 4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Peak Output Power	$\pm 0.75\text{dB}$
Minimum 6dB Bandwidth	$\pm 3\%$
Power Spectrum Density	$\pm 2.84\text{dB}$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 4.5\text{dB}$ (Below 1GHz); $\pm 4.8\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions	$\pm 4.5\text{dB}$ (Below 1GHz); $\pm 4.8\text{dB}$ (Above 1GHz)

### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou Branch EMC Laboratory,  
198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District,  
Guangzhou, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Guangzhou Branch EMC Laboratory

No. 198 Kezhu Road, Sciencetech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgs.com.cn  
中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

#### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP (Lab Code: 200611-0)**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government.

- **ACMA**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory can also perform testing for the Australian/New Zealand Regulatory Compliance Mark (RCM).

- **SGS UK(Certificate No.: 32), SGS-TUV SAARLAND and SGS-FIMKO**

Have approved SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory as a supplier of EMC TESTING SERVICES and SAFETY TESTING SERVICES.

- **CNAS (Lab Code: L0167)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been assessed and in compliance with CNAS-CL01:2018 accreditation criteria for testing laboratories (identical to ISO/IEC 17025:2017 General Requirements) for the Competence of Testing Laboratories.

- **FCC Recognized Accredited Test Firm(Registration No.: 486818)**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been accredited and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Designation Number: CN5016, Test Firm Registration Number: 486818.

- **ISED (Registration No.: 4620B, CAB identifier: CN0052)**

SGS-CSTC Standards Technical Services Co., Ltd., has been registered by Innovation Science and Economic Development Canada for Wireless Device Testing laboratories to test to Canadian radio equipment requirements. Registration No. 4620B, CAB identifier: CN0052.

- **VCCI (Registration No.: R-12460, C-12584, G-20107 and T-11179)**

The 10m Semi-anechoic chamber, 966 Anechoic Chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-12460, C-12584, G-20107 and T-11179 respectively.

- **CBTL (Lab Code: TL129)**

SGS-CSTC Standards Technical Services Co., Ltd., E&E Laboratory has been assessed and fully comply with the requirements of ISO/IEC 17025:2017, the Basic Rules, IECEE 01 and Rules of procedure IECEE 02, and the relevant IECEE CB-Scheme Operational documents.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

**4.6 Deviation from Standards**

None

**4.7 Abnormalities from Standard Conditions**

None

**4.8 Duty cycle of the EUT**

Pre-analysis Check: While conducting average power measurement, duty cycle of each mode shall be checked to ensure its duty cycle in order to compensate for the loss due to insufficient ratio of duty cycle.

All duty cycle is pre-scanned and result as obtained below shows only the most representative ones where duty cycle is conducted as the given transmission with given virtual operation that expresses the percent.

Formula:

Duty Cycle =  $\text{Ton}/(\text{Ton}+\text{Toff})$ 

Measurement Procedure:

1. Set span = Zero
2. RBW=8MHz
3. VBW=8MHz
4. Detector=Peak

Mode	Channel(MHz)	Duty Cycle(%)	Correction Factor(dB)*
DH5	2402	16.40	7.85
	2440	16.50	7.85
	2480	16.50	7.85

\*Correction Factor(dB) =  $10\log(1/\text{Duty Cycle})$ 

Please refer to appendix for details.



## 5 Equipment List

Conducted Peak Output Power					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer (N9010A)	Agilent Technologies	N9010A	EMC2138	2020-09-17	2021-09-16
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
Test Software JS1120-3	HangTianXing	V2.6	GZE100-69	N/A	N/A
MI CABLE	SGS-EMC	0.8M	EMC2136	2019-11-02	2021-11-01

Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer (N9010A)	Agilent Technologies	N9010A	EMC2138	2020-09-17	2021-09-16
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
Test Software JS1120-3	HangTianXing	V2.6	GZE100-69	N/A	N/A
MI CABLE	SGS-EMC	0.8M	EMC2136	2019-11-02	2021-11-01

Power Spectrum Density					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer (N9010A)	Agilent Technologies	N9010A	EMC2138	2020-09-17	2021-09-16
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
Test Software JS1120-3	HangTianXing	V2.6	GZE100-69	N/A	N/A
MI CABLE	SGS-EMC	0.8M	EMC2136	2019-11-02	2021-11-01

Conducted Band Edges Measurement					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer (N9010A)	Agilent Technologies	N9010A	EMC2138	2020-09-17	2021-09-16
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
Test Software JS1120-3	HangTianXing	V2.6	GZE100-69	N/A	N/A
MI CABLE	SGS-EMC	0.8M	EMC2136	2019-11-02	2021-11-01

Conducted Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
EXA Signal Analyzer (N9010A)	Agilent Technologies	N9010A	EMC2138	2020-09-17	2021-09-16
6dB Attenuator	HP	8491A	EMC2062	2020-04-15	2022-04-14
Test Software JS1120-3	HangTianXing	V2.6	GZE100-69	N/A	N/A
MI CABLE	SGS-EMC	0.8M	EMC2136	2019-11-02	2021-11-01



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd. No. 198 Kezhu Road, Science Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgs.com.cn  
Guangzhou Branch Testing Laboratory 中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Chamber cable	HangTianXing	N/A	EMC0542	2019-06-28	2021-06-27
Horn Antenna(BBHA 9120D)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2019-09-25	2022-09-24
1GHz-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2021-01-08	2022-01-07
2.4GHz Filter	Micro-Tronics	BRM 50702	EMC2069	2021-01-08	2022-01-07
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2020-12-20	2023-12-19
MXE EMI Receiver(N9038A)	Keysight	N9038A	EMC2139	2020-11-13	2021-11-12
EXA Signal Analyzer(N9010A)	Keysight	N9010A	EMC2138	2020-09-17	2021-09-16
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A

Radiated Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Chamber cable	HangTianXing	N/A	EMC0542	2019-06-28	2021-06-27
Horn Antenna(BBHA 9120D)	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120D	EMC2026	2019-09-25	2022-09-24
1GHz-26.5 GHz Pre-Amplifier	Agilent	8449B	EMC0521	2021-01-08	2022-01-07
2.4GHz Filter	Micro-Tronics	BRM 50702	EMC2069	2021-01-08	2022-01-07
966 Anechoic Chamber	C.R.T	9m x 6m x 6m	EMC2142	2020-12-20	2023-12-19
MXE EMI Receiver(N9038A)	Keysight	N9038A	EMC2139	2020-11-13	2021-11-12
EXA Signal Analyzer(N9010A)	Keysight	N9010A	EMC2138	2020-09-17	2021-09-16
Test Software E3	Audix	Ver.6.120110a	GZE100-61	N/A	N/A

General used equipment					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
DMM	Fluke	73	EMC0006	2020-07-09	2021-07-08
DMM	Fluke	73	EMC0007	2020-07-09	2021-07-08

## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

#### 6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 1.18 dBi.

Antenna phot please refer to Internal photo.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2013) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq$ hopping channels $< 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

#### 7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 27.0 °C


Humidity: 60.8 % RH

Atmospheric Pressure: 1010 mbar

#### 7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	03	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

#### 7.1.3 Test Setup Diagram



#### 7.1.4 Measurement Procedure and Data

Please Refer To Appendix For Details



### 7.2 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)  
Test Method: ANSI C63.10 (2013) Section 11.8.1  
Limit:  $\geq 500$  kHz


#### 7.2.1 E.U.T. Operation

Operating Environment:  
Temperature: 27.0 °C Humidity: 60.8 % RH Atmospheric Pressure: 1010 mbar

#### 7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	03	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

#### 7.2.3 Test Setup Diagram



#### 7.2.4 Measurement Procedure and Data

Please Refer To Appendix For Details



### 7.3 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)  
 Test Method: ANSI C63.10 (2013) Section 11.10.2  
 Limit: ≤8dBm in any 3 kHz band during any time interval of continuous transmission


#### 7.3.1 E.U.T. Operation

Operating Environment:  
 Temperature: 27.0 °C Humidity: 60.8 % RH Atmospheric Pressure: 1010 mbar

#### 7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	03	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

#### 7.3.3 Test Setup Diagram



#### 7.3.4 Measurement Procedure and Data

Please Refer To Appendix For Details

### 7.4 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)  
Test Method: ANSI C63.10 (2013) Section 11.13.3.2  
Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### 7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 27.0 °C Humidity: 60.8 % RH Atmospheric Pressure: 1010 mbar

#### 7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	03	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

#### 7.4.3 Test Setup Diagram



#### 7.4.4 Measurement Procedure and Data

Please Refer To Appendix For Details

### 7.5 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2013) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### 7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 27.0 °C


Humidity: 60.8 % RH

Atmospheric Pressure: 1010 mbar

#### 7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	03	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

#### 7.5.3 Test Setup Diagram



#### 7.5.4 Measurement Procedure and Data

Please Refer To Appendix For Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)  
SGS-CSTC Standards Technical Services Co., Ltd. No. 198 Kezhu Road, Sciotech Park, Guangzhou Economic & Technology Development District, Guangzhou, China 510663 t (86-20) 82155555 f (86-20) 82075058 www.sgs.com.cn  
Guangzhou Branch Testing Laboratory 中国·广州·经济技术开发区科学城科珠路198号 邮编: 510663 t (86-20) 82155555 f (86-20) 82075058 sgs.china@sgs.com



### 7.6 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.10.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

#### 7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 25.1 °C


Humidity: 63.3 % RH

Atmospheric Pressure: 1010 mbar

#### 7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	03	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

#### 7.6.3 Test Setup Diagram



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

#### 7.6.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Remark 3: Antenna: 3 denotes the type of antenna for above 1000MHz.




Test Mode: 03; Polarity: Horizontal; Modulation:GFSK; ; Channel:High; Antenna: 3



		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2310.000	35.49	27.15	3.32	37.62	28.34	54.00	-25.66	HORIZONTAL	Average
2	2310.000	45.82	27.15	3.32	37.62	38.67	74.00	-35.33	HORIZONTAL	Peak
3	2390.000	34.38	27.33	3.48	37.59	27.60	54.00	-26.40	HORIZONTAL	Average
4	2390.000	44.75	27.33	3.48	37.59	37.97	74.00	-36.03	HORIZONTAL	Peak
5	2483.500	37.59	27.48	3.53	37.57	31.03	54.00	-22.97	HORIZONTAL	Average
6	2483.500	47.24	27.48	3.53	37.57	40.68	74.00	-33.32	HORIZONTAL	Peak
7	2500.000	34.03	27.50	3.40	37.56	27.37	54.00	-26.63	HORIZONTAL	Average
8	2500.000	44.53	27.50	3.40	37.56	37.87	74.00	-36.13	HORIZONTAL	Peak


Test Mode: 03; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low; Antenna: 3



Trace: (Discrete)

	Read	Antenna	Cable	Preamp	Limit	Over			
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2310.000	34.49	27.15	3.32	37.62	27.34	54.00	-26.66	HORIZONTAL Average
2	2310.000	44.54	27.15	3.32	37.62	37.39	74.00	-36.61	HORIZONTAL Peak
3	2390.000	35.04	27.33	3.48	37.59	28.26	54.00	-25.74	HORIZONTAL Average
4	2390.000	44.64	27.33	3.48	37.59	37.86	74.00	-36.14	HORIZONTAL Peak
5	2483.500	34.05	27.48	3.53	37.57	27.49	54.00	-26.51	HORIZONTAL Average
6	2483.500	43.81	27.48	3.53	37.57	37.25	74.00	-36.75	HORIZONTAL Peak
7	2500.000	33.24	27.50	3.40	37.56	26.58	54.00	-27.42	HORIZONTAL Average
8	2500.000	44.76	27.50	3.40	37.56	38.10	74.00	-35.90	HORIZONTAL Peak

Test Mode: 03; Polarity: Vertical; Modulation: GFSK; ; Channel: High; Antenna: 3




Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark	
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	2310.000	34.59	27.15	3.32	37.62	27.44	54.00	-26.56	VERTICAL	Average
2	2310.000	44.48	27.15	3.32	37.62	37.33	74.00	-36.67	VERTICAL	Peak
3	2390.000	32.72	27.33	3.48	37.59	25.94	54.00	-28.06	VERTICAL	Average
4	2390.000	43.82	27.33	3.48	37.59	37.04	74.00	-36.96	VERTICAL	Peak
5	2483.500	33.62	27.48	3.53	37.57	27.06	54.00	-26.94	VERTICAL	Average
6	2483.500	44.45	27.48	3.53	37.57	37.89	74.00	-36.11	VERTICAL	Peak
7	2500.000	34.31	27.50	3.40	37.56	27.65	54.00	-26.35	VERTICAL	Average
8	2500.000	44.68	27.50	3.40	37.56	38.02	74.00	-35.98	VERTICAL	Peak



Test Mode: 03; Polarity: Vertical; Modulation:GFSK; ; Channel:Low; Antenna: 3



	Freq	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Level	Limit	Over	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	2310.000	33.62	27.15	3.32	37.62	26.47	54.00	-27.53	Average
2	2310.000	44.18	27.15	3.32	37.62	37.03	74.00	-36.97	Peak
3	2390.000	33.60	27.33	3.48	37.59	26.82	54.00	-27.18	Average
4	2390.000	44.94	27.33	3.48	37.59	38.16	74.00	-35.84	Peak
5	2483.500	34.16	27.48	3.53	37.57	27.60	54.00	-26.40	Average
6	2483.500	44.78	27.48	3.53	37.57	38.22	74.00	-35.78	Peak
7	2500.000	34.59	27.50	3.40	37.56	27.93	54.00	-26.07	Average
8	2500.000	44.56	27.50	3.40	37.56	37.90	74.00	-36.10	Peak

### 7.7 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

#### 7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 25.1 °C


Humidity: 63.3 % RH

Atmospheric Pressure: 1010 mbar

#### 7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	03	TX mode_Keep the EUT in continuously transmitting mode with GFSK modulation.

#### 7.7.3 Test Setup Diagram





**7.7.4 Measurement Procedure and Data**

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


**Remark:**

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
- 5) Antenna: 2 denotes the type of antenna for 30-1000MHz; Antenna: 3 denotes the type of antenna for above 1000MHz.




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

Test Mode: 03; Polarity: Horizontal; Modulation:GFSK; ; Channel:Low; Antenna: 2




Test Mode: 03; Polarity: Horizontal; Modulation:GFSK; ; Channel:High; Antenna: 3



	ReadAntenna	Cable	Preamp		Limit	Over			
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1315.985	40.04	25.24	2.60	38.29	29.59	54.00	-24.41	HORIZONTAL Average
2	1315.985	47.16	25.24	2.60	38.29	36.71	74.00	-37.29	HORIZONTAL Peak
3	2973.293	41.72	28.38	3.78	37.28	36.60	54.00	-17.40	HORIZONTAL Average
4	2973.293	47.74	28.38	3.78	37.28	42.62	74.00	-31.38	HORIZONTAL Peak
5	4960.946	38.35	31.65	5.65	36.84	38.81	54.00	-15.19	HORIZONTAL Average
6	4960.946	43.70	31.65	5.65	36.84	44.16	74.00	-29.84	HORIZONTAL Peak
7	7440.300	36.03	36.27	6.22	37.47	41.05	54.00	-12.95	HORIZONTAL Average
8	7440.300	41.67	36.27	6.22	37.47	46.69	74.00	-27.31	HORIZONTAL Peak
9	9920.464	36.71	38.65	6.96	37.40	44.92	54.00	-9.08	HORIZONTAL Average
10	9920.464	42.05	38.65	6.96	37.40	50.26	74.00	-23.74	HORIZONTAL Peak
11	12400.810	40.84	38.57	7.97	36.88	50.50	74.00	-23.50	HORIZONTAL Peak
12	12400.810	36.23	38.57	7.97	36.88	45.89	54.00	-8.11	HORIZONTAL Average




Test Mode: 03; Polarity: Horizontal; Modulation: GFSK; ; Channel: Low; Antenna: 3



	Read	Antenna	Cable	Preamp	Limit	Over			
Freq	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1189.368	38.84	24.63	2.36	38.39	27.44	54.00	-26.56	HORIZONTAL Average
2	1189.368	47.16	24.63	2.36	38.39	35.76	74.00	-38.24	HORIZONTAL Peak
3	1845.516	37.85	25.99	2.95	37.78	29.01	54.00	-24.99	HORIZONTAL Average
4	1845.516	45.63	25.99	2.95	37.78	36.79	74.00	-37.21	HORIZONTAL Peak
5	4804.821	35.11	31.42	5.40	36.83	35.10	54.00	-18.90	HORIZONTAL Average
6	4804.821	40.61	31.42	5.40	36.83	40.60	74.00	-33.40	HORIZONTAL Peak
7	7206.542	35.19	35.54	5.98	37.38	39.33	54.00	-14.67	HORIZONTAL Average
8	7206.542	40.67	35.54	5.98	37.38	44.81	74.00	-29.19	HORIZONTAL Peak
9	9608.879	35.21	38.37	7.07	37.42	43.23	54.00	-10.77	HORIZONTAL Average
10	9608.879	40.26	38.37	7.07	37.42	48.28	74.00	-25.72	HORIZONTAL Peak
11	12010.950	39.70	38.90	8.19	37.10	49.69	74.00	-24.31	HORIZONTAL Peak
12	12010.950	34.98	38.90	8.19	37.10	44.97	54.00	-9.03	HORIZONTAL Average


Test Mode: 03; Polarity: Horizontal; Modulation:GFSK; ; Channel:middle; Antenna: 3



	Freq	ReadAntenna Level	Cable Preamp Factor	Loss	Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1323.614	40.55	25.26	2.60	38.29	30.12	54.00	-23.88	HORIZONTAL	Average
2	1323.614	47.42	25.26	2.60	38.29	36.99	74.00	-37.01	HORIZONTAL	Peak
3	3132.079	38.06	28.51	3.95	37.14	33.38	54.00	-20.62	HORIZONTAL	Average
4	3132.079	44.73	28.51	3.95	37.14	40.05	74.00	-33.95	HORIZONTAL	Peak
5	4884.760	37.32	31.56	5.52	36.84	37.56	54.00	-16.44	HORIZONTAL	Average
6	4884.760	43.40	31.56	5.52	36.84	43.64	74.00	-30.36	HORIZONTAL	Peak
7	7326.443	35.09	36.00	6.13	37.43	39.79	54.00	-14.21	HORIZONTAL	Average
8	7326.443	40.32	36.00	6.13	37.43	45.02	74.00	-28.98	HORIZONTAL	Peak
9	9768.942	35.51	38.53	7.01	37.41	43.64	54.00	-10.36	HORIZONTAL	Average
10	9768.942	40.23	38.53	7.01	37.41	48.36	74.00	-25.64	HORIZONTAL	Peak
11	12210.260	38.91	38.74	8.08	37.00	48.73	74.00	-25.27	HORIZONTAL	Peak
12	12210.260	32.88	38.74	8.08	37.00	42.70	54.00	-11.30	HORIZONTAL	Average



Test Mode: 03; Polarity: Vertical; Modulation: GFSK; ; Channel: Low; Antenna: 2




Trace: (Discrete)

Site : SGS  
Condition : FCC PART15 C (3M) VERTICAL  
Job :  
Model :  
Power :  
Test Mode : AC



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.


Test Mode: 03; Polarity: Vertical; Modulation: GFSK; ; Channel: High; Antenna: 3



Trace: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1278.492	39.69	25.14	2.50	38.33	29.00	54.00	-25.00	VERTICAL	Average
2	1278.492	47.09	25.14	2.50	38.33	36.40	74.00	-37.60	VERTICAL	Peak
3	2359.478	39.29	27.27	3.42	37.61	32.37	54.00	-21.63	VERTICAL	Average
4	2359.478	45.84	27.27	3.42	37.61	38.92	74.00	-35.08	VERTICAL	Peak
5	4960.978	36.77	31.65	5.65	36.84	37.23	54.00	-16.77	VERTICAL	Average
6	4960.978	43.82	31.65	5.65	36.84	44.28	74.00	-29.72	VERTICAL	Peak
7	7440.200	36.40	36.27	6.22	37.47	41.42	54.00	-12.58	VERTICAL	Average
8	7440.200	41.96	36.27	6.22	37.47	46.98	74.00	-27.02	VERTICAL	Peak
9	9920.375	36.98	38.65	6.96	37.40	45.19	54.00	-8.81	VERTICAL	Average
10	9920.375	40.94	38.65	6.96	37.40	49.15	74.00	-24.85	VERTICAL	Peak
11	12400.910	33.09	38.57	7.97	36.88	42.75	54.00	-11.25	VERTICAL	Average
12	12400.910	38.71	38.57	7.97	36.88	48.37	74.00	-25.63	VERTICAL	Peak


Test Mode: 03; Polarity: Vertical; Modulation: GFSK; ; Channel: Low; Antenna: 3



		Read	Antenna	Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1350.667	37.30	25.31	2.60	38.27	26.94	54.00	-27.06	VERTICAL	Average
2	1350.667	46.52	25.31	2.60	38.27	36.16	74.00	-37.84	VERTICAL	Peak
3	2188.663	36.26	26.56	3.20	37.65	28.37	54.00	-25.63	VERTICAL	Average
4	2188.663	45.41	26.56	3.20	37.65	37.52	74.00	-36.48	VERTICAL	Peak
5	4804.781	37.88	31.42	5.40	36.83	37.87	54.00	-16.13	VERTICAL	Average
6	4804.781	44.14	31.42	5.40	36.83	44.13	74.00	-29.87	VERTICAL	Peak
7	7206.436	34.20	35.54	5.98	37.38	38.34	54.00	-15.66	VERTICAL	Average
8	7206.436	41.21	35.54	5.98	37.38	45.35	74.00	-28.65	VERTICAL	Peak
9	9608.860	34.29	38.37	7.07	37.42	42.31	54.00	-11.69	VERTICAL	Average
10	9608.860	40.05	38.37	7.07	37.42	48.07	74.00	-25.93	VERTICAL	Peak
11	12010.500	39.51	38.90	8.19	37.10	49.50	74.00	-24.50	VERTICAL	Peak
12	12010.500	33.07	38.90	8.19	37.10	43.06	54.00	-10.94	VERTICAL	Average



Test Mode: 03; Polarity: Vertical; Modulation:GFSK; ; Channel:middle; Antenna: 3



		Read	Antenna	Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1346.769	40.04	25.31	2.60	38.27	29.68	54.00	-24.32	VERTICAL	Average
2	1346.769	47.23	25.31	2.60	38.27	36.87	74.00	-37.13	VERTICAL	Peak
3	2838.921	38.21	28.21	3.70	37.38	32.74	54.00	-21.26	VERTICAL	Average
4	2838.921	45.78	28.21	3.70	37.38	40.31	74.00	-33.69	VERTICAL	Peak
5	4884.257	37.85	31.56	5.52	36.84	38.09	54.00	-15.91	VERTICAL	Average
6	4884.257	43.27	31.56	5.52	36.84	43.51	74.00	-30.49	VERTICAL	Peak
7	7326.047	36.03	36.00	6.13	37.43	40.73	54.00	-13.27	VERTICAL	Average
8	7326.047	42.33	36.00	6.13	37.43	47.03	74.00	-26.97	VERTICAL	Peak
9	9768.762	33.67	38.53	7.01	37.41	41.80	54.00	-12.20	VERTICAL	Average
10	9768.762	39.96	38.53	7.01	37.41	48.09	74.00	-25.91	VERTICAL	Peak
11	12210.820	39.16	38.74	8.08	37.00	48.98	74.00	-25.02	VERTICAL	Peak
12	12210.820	33.62	38.74	8.08	37.00	43.44	54.00	-10.56	VERTICAL	Average



## 8 Appendix


(Cable loss=0.9dB)

### 8.1 Appendix A: DTS Bandwidth


#### 8.1.1 Test Result

TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.508	2401.652	2402.160	0.5	PASS
		2442	0.552	2441.632	2442.184	0.5	PASS
		2480	0.528	2479.640	2480.168	0.5	PASS

#### 8.1.2 Test Graphs



### BLE\_1M\_Ant1\_2442



### BLE\_1M\_Ant1\_2480



## 8.2 Appendix B: Maximum conducted output power


### 8.2.1 Test Result

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	-5.09	<=30	PASS
		2442	-3.93	<=30	PASS
		2480	-4.39	<=30	PASS

### 8.2.2 Test Graphs



### BLE\_1M\_Ant1\_2442



### BLE\_1M\_Ant1\_2480





### 8.3 Appendix C: Maximum power spectral density


#### 8.3.1 Test Result

TestMode	Antenna	Channel	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-15.67	<=8	PASS
		2442	-14.61	<=8	PASS
		2480	-14.85	<=8	PASS

#### 8.3.2 Test Graphs



### BLE\_1M\_Ant1\_2442



### BLE\_1M\_Ant1\_2480




### 8.4 Appendix D: Band edge measurements

#### 8.4.1 Test Result

TestMode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	Low	2402	-5.40	-42.47	<=-25.4	PASS
		High	2480	-4.74	-47.54	<=-24.74	PASS

#### 8.4.2 Test Graphs




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

### 8.5 Appendix E: Conducted Spurious Emission

#### 8.5.1 Test Result


TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	Reference	-5.53	-5.53	---	PASS
			30~1000	30~1000	-63.919	<=-25.526	PASS
			1000~26500	1000~26500	-57.533	<=-25.526	PASS
		2442	Reference	-4.24	-4.24	---	PASS
			30~1000	30~1000	-65.08	<=-24.235	PASS
			1000~26500	1000~26500	-54.545	<=-24.235	PASS
		2480	Reference	-4.97	-4.97	---	PASS
			30~1000	30~1000	-65.596	<=-24.973	PASS
			1000~26500	1000~26500	-55.587	<=-24.973	PASS

#### 8.5.2 Test Graphs






### BLE\_1M\_Ant1\_2402\_30~1000




### BLE\_1M\_Ant1\_2402\_1000~26500




### BLE\_1M\_Ant1\_2442\_0~Reference



### BLE\_1M\_Ant1\_2442\_30~1000




### BLE\_1M\_Ant1\_2442\_1000~26500




### BLE\_1M\_Ant1\_2480\_0~Reference



### BLE\_1M\_Ant1\_2480\_30~1000



### BLE\_1M\_Ant1\_2480\_1000~26500






### 8.6 Appendix F: Duty Cycle


#### 8.6.1 Test Result

TestMode	Antenna	Channel	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
BLE_1M	Ant1	2402	0.10	0.63	16.40
		2442	0.10	0.63	16.50
		2480	0.10	0.63	16.50


#### 8.6.2 Test Graphs



### BLE\_1M\_Ant1\_2442



### BLE\_1M\_Ant1\_2480



- End of the Report -