

***Electromagnetic Emissions Test Report
and
Request for Class II Permissive Change
pursuant to
FCC Part 15, Subpart E (UNII Devices) and
Industry Canada RSS 210 Issue 5 (LELEAN Devices)
Intentional Radiator on the
Axxcelera
Model: AB-access Unit***

FCC ID: OJBAB-ACCESS-SU01

UPN: 4570A-1032091A


GRANTEE: Axxcelera Wireless
2144 Brighton Henrietta Town Line Rd.
Rochester, NY 14623

TEST SITE: Elliott Laboratories, Inc.
684 W. Maude Avenue
Sunnyvale, CA 94086

REPORT DATE: June 18, 2004

FINAL TEST DATE: June 16, 2004

AUTHORIZED SIGNATORY:



Juan Martinez
Senior EMC Engineer



Elliott Laboratories, Inc. is accredited by the A2LA, certificate number 2016-01, to perform the test(s) listed in this report. This report shall not be reproduced, except in its entirety, without the written approval of Elliott Laboratories, Inc.

DECLARATIONS OF COMPLIANCE

Equipment Name and Model:
AB-access Unit

Manufacturer:
Axxcelera Wireless
2144 Brighton Henrietta Town Line Rd.
Rochester, NY 14623


Tested to applicable standards:
RSS-210, Issue 5, November 2001 (Low Power License-Exempt Radiocommunication Devices)
FCC Part 15.407 (UNII)

Measurement Facility Description Filed With Department of Industry:

Departmental Acknowledgement Number: IC2845 SV2, Dated August 12, 2001

I declare that the testing was performed or supervised by me; that the test measurements were made in accordance with the above mentioned departmental standards (through the use of ANSI C63.4 as detailed in section 5.3 of RSS-210, Issue 5); and that the equipment performed in accordance with the data submitted in this report.

Signature



Name

Juan Martinez

Title

Senior EMC Engineer

Company

Elliott Laboratories Inc.

Address

684 W. Maude Ave
Sunnyvale, CA 94086
USA

Date: June 18, 2004

Maintenance of compliance with the above standards is the responsibility of the manufacturer. Any modification of the product which may result in increased emissions should be checked to ensure compliance has been maintained (i.e., printed circuit board layout changes, different line filter, different power supply, harnessing or I/O cable changes, etc.).

TABLE OF CONTENTS

APPLICATION AND AGREEMENT FOR CERTIFICATION SERVICES.....	1
DECLARATIONS OF COMPLIANCE.....	2
TABLE OF CONTENTS	3
SCOPE.....	5
OBJECTIVE	5
SUMMARY OF RESULTS	6
MEASUREMENT UNCERTAINTIES.....	7
EQUIPMENT UNDER TEST (EUT) DETAILS.....	8
GENERAL.....	8
OTHER EUT DETAILS.....	8
ENCLOSURE.....	8
MODIFICATIONS.....	8
SUPPORT EQUIPMENT.....	8
EUT INTERFACE PORTS.....	9
EUT OPERATION DURING TESTING.....	9
ANTENNA REQUIREMENTS	9
TEST SITE.....	10
GENERAL INFORMATION.....	10
CONDUCTED EMISSIONS CONSIDERATIONS	10
RADIATED EMISSIONS CONSIDERATIONS	10
MEASUREMENT INSTRUMENTATION	11
RECEIVER SYSTEM	11
INSTRUMENT CONTROL COMPUTER.....	11
LINE IMPEDANCE STABILIZATION NETWORK (LISN)	11
POWER METER.....	12
FILTERS/ATTENUATORS	12
ANTENNAS.....	12
ANTENNA MAST AND EQUIPMENT TURNTABLE.....	12
INSTRUMENT CALIBRATION.....	12
TEST PROCEDURES	13
EUT AND CABLE PLACEMENT	13
CONDUCTED EMISSIONS.....	13
RADIATED EMISSIONS.....	13
CONDUCTED EMISSIONS FROM ANTENNA PORT	14
SPECIFICATION LIMITS AND SAMPLE CALCULATIONS.....	15
FCC 15.407 (A)AND RSS 210 (O) OUTPUT POWER LIMITS.....	16
RSS 210 (O) AND FCC 15.247 SPURIOUS RADIATED EMISSIONS LIMITS.....	16
FCC 15.205 AC POWER PORT CONDUCTED EMISSIONS LIMITS	17
RSS-210 SECTION 6.6 AC POWER PORT CONDUCTED EMISSIONS LIMITS	17
SAMPLE CALCULATIONS - CONDUCTED EMISSIONS	18
SAMPLE CALCULATIONS - RADIATED EMISSIONS	19
EXHIBIT 1: Test Equipment Calibration Data.....	1
EXHIBIT 2: Test Data Log Sheets	2
EXHIBIT 3: Test Configuration Photographs	3
EXHIBIT 4: Proposed FCC ID Label & Label Location	6
EXHIBIT 5: Detailed Photographs of.....	7

<i>Axxcelera Model AB-access Unit Construction</i>	7
<i>EXHIBIT 6: Operator's Manual for</i>	8
<i>Axxcelera Model AB-access Unit</i>	8
<i>EXHIBIT 7: Block Diagram of</i>	9
<i>Axxcelera Model AB-access Unit</i>	9
<i>EXHIBIT 8: Schematic Diagrams for</i>	10
<i>Axxcelera Model AB-access Unit</i>	10
<i>EXHIBIT 9: Theory of Operation for</i>	11
<i>Axxcelera Model AB-access Unit</i>	11
<i>EXHIBIT 10: Advertising Literature</i>	12
<i>EXHIBIT 11: RF Exposure Information</i>	13

SCOPE

An electromagnetic emissions test has been performed on the Axxcelera model AB-access Unit pursuant to Subpart E of Part 15 of FCC Rules for Unlicensed National Information Infrastructure (UNII) devices and RSS-210 Issue 5 for licence-exempt local area network (LELAN) devices. Conducted and radiated emissions data has been collected, reduced, and analyzed within this report in accordance with measurement guidelines set forth in ANSI C63.4-2001 as outlined in Elliott Laboratories test procedures.

The intentional radiator above has been tested in a simulated typical installation to demonstrate compliance with the relevant FCC performance and procedural standards.

Final system data was gathered in a mode that tended to maximize emissions by varying orientation of EUT, orientation of power and I/O cabling, antenna search height, and antenna polarization.

Every practical effort was made to perform an impartial test using appropriate test equipment of known calibration. All pertinent factors have been applied to reach the determination of compliance.

The test results recorded herein are based on a single type test of the Axxcelera model AB-access Unit and therefore apply only to the tested sample. The sample was selected and prepared by Dennis McCarthy of Axxcelera

OBJECTIVE

The primary objective of the manufacturer is compliance with Subpart E of Part 15 of FCC Rules for the radiated and conducted emissions of intentional radiators. Certification of these devices is required as a prerequisite to marketing as defined in Part 2 the FCC Rules.

Certification is a procedure where the manufacturer or a contracted laboratory makes measurements and submits the test data and technical information to the FCC. The FCC issues a grant of equipment authorization upon successful completion of their review of the submitted documents. Once the equipment authorization has been obtained, the label indicating compliance must be attached to all identical units, which are subsequently manufactured.

SUMMARY OF RESULTS

FCC Part 15 Section	RSS 210 Section	Description	Comments	Result
Operation in the 5.725 – 5.805 GHz Band				
		Maximum Antenna Gain	Detachable, point-to-point operation	COMPLIES
15.407(a) (3)	6.2.2 q1 (iii)	Output Power	12.87 dBm	COMPLIES
15.407(b) (3)	6.2.2 q1 (iii)	Spurious Emissions above 1GHz	-11.7 dB @ 11,500 MHz	COMPLIES
General requirements for all bands				
15.407 (f)	6.2.2 q(iv)(g)	RF Exposure Requirements	Refer to MPE calculations in Exhibit 11	COMPLIES

EIRP calculated using antenna gain of dBi (37.6) for the highest EIRP point-to-point system.

MEASUREMENT UNCERTAINTIES

ISO Guide 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level and were calculated in accordance with NAMAS document NIS 81.

Measurement Type	Frequency Range (MHz)	Calculated Uncertainty (dB)
Conducted Emissions	0.15 to 30	± 2.4
Radiated Emissions	30 to 1000	± 3.6

EQUIPMENT UNDER TEST (EUT) DETAILS**GENERAL**

The Axxcelera model AB-access Unit is a 5 GHz radio transceiver and 6 foot dish antenna which together is designed to transmit and receive data. Normally, the EUT would be mounted to a pole. The EUT was treated as table-top equipment during testing to simulate the end-user environment. The electrical rating of the EUT is 48VDC, 625mA.

The sample was received on June 16, 2004 and tested on June 16, 2004. The EUT consisted of the following component(s):

Manufacturer	Model	Description	Serial Number	FCC ID
Axxcelera	AB-access Unit	U-NII ISM Transceiver	SW1600135H	OJBAB-ACC-SU02ESS
Radio Waves	SP6-5.2	6' dish antenna	N/A	N/A

OTHER EUT DETAILS**ENCLOSURE**

The transceiver enclosure is primarily constructed of molded plastic and measures approximately 25 cm wide by 6 cm deep by 27 cm high.

The dish antenna does not have an enclosure. It measures 6 foot in diameter.

MODIFICATIONS

The EUT did not require modifications during testing in order to comply with the emission specifications.

SUPPORT EQUIPMENT

No equipment was used as local support equipment for emissions testing:

The following equipment was used as remote support equipment for emissions testing:

Manufacturer/Model/Description	Serial Number	FCC ID Number
Dell Inspiron 3800 Laptop computer	1213-104-1	LNQUSA-34552-M5-E

EUT INTERFACE PORTS

The I/O cabling configuration during emissions testing was as follows:

Port	Connected To	Cable(s)		
		Description	Shielded or Unshielded	Length(m)
Transceiver RF	dish antenna RF	coax	shielded	1.3
Transceiver Ethernet	POE converter box	CAT5	Unshielded	2
POE converter box	Laptop Computer	CAT5	Unshielded	30

Note: The 2nd RF transceiver and dish antenna ports were not connected as the manufacturer stated that it is for receiving diversity purpose.

EUT OPERATION DURING TESTING

The transceiver was set up to continuously transmit through the dish antenna at the recorded transmit frequencies.

ANTENNA REQUIREMENTS

The antenna port is a standard, N-type connector, which is permitted as the system is intended to be professionally installed.

TEST SITE**GENERAL INFORMATION**

Final test measurements were taken on June 16, 2004 at the Elliott Laboratories Open Area Test Site #2 located at 684 West Maude Avenue, Sunnyvale, California. The test site contains separate areas for radiated and conducted emissions testing. Pursuant to section 2.948 of the Rules, construction, calibration, and equipment data has been filed with the Federal Communications Commission. In accordance with Industry Canada rules detailed in RSS 210 Issue 5 and RSS-212, construction, calibration, and equipment data for the test sites have been filed with the Federal Communications Commission.

The FCC recommends that ambient noise at the test site be at least 6 dB below the allowable limits. Ambient levels are below this requirement with the exception of predictable local TV, radio, and mobile communications traffic. The test site contains separate areas for radiated and conducted emissions testing. Considerable engineering effort has been expended to ensure that the facilities conform to all pertinent FCC requirements.

CONDUCTED EMISSIONS CONSIDERATIONS

Conducted emissions testing is performed in conformance with ANSI C63.4-1992. Measurements are made with the EUT connected to the public power network through a nominal, standardized RF impedance, which is provided by a line impedance stabilization network, known as a LISN. A LISN is inserted in series with each current-carrying conductor in the EUT power cord.

RADIATED EMISSIONS CONSIDERATIONS

The FCC has determined that radiation measurements made in a shielded enclosure are not suitable for determining levels of radiated emissions. Radiated measurements are performed in an open field environment. The test site is maintained free of conductive objects within the CISPR defined elliptical area incorporated in ANSI C63.4 guidelines.

MEASUREMENT INSTRUMENTATION**RECEIVER SYSTEM**

An EMI receiver as specified in CISPR 16-1 is used for emissions measurements. The receivers used can measure over the frequency range of 9 kHz up to 2000 MHz. These receivers allow both ease of measurement and high accuracy to be achieved. The receivers have Peak, Average, and CISPR (Quasi-peak) detectors built into their design so no external adapters are necessary. The receiver automatically sets the required bandwidth for the CISPR detector used during measurements.

For measurements above the frequency range of the receivers, a spectrum analyzer is utilized because it provides visibility of the entire spectrum along with the precision and versatility required to support engineering analysis. Average measurements above 1000MHz are performed on the spectrum analyzer using the linear-average method with a resolution bandwidth of 1 MHz and a video bandwidth of 10 Hz.

INSTRUMENT CONTROL COMPUTER

The receivers utilize either a Rohde and Schwarz EZM Spectrum Monitor/Controller or contain an internal Spectrum Monitor/Controller to view and convert the receiver measurements to the field strength at an antenna or voltage developed at the LISN measurement port, which is then compared directly with the appropriate specification limit. This provides faster, more accurate readings by performing the conversions described under Sample Calculations within the Test Procedures section of this report. Results are printed in a graphic and/or tabular format, as appropriate. A personal computer is used to record all measurements made with the receivers.

The Spectrum Monitor provides a visual display of the signal being measured. In addition, the controller or a personal computer run automated data collection programs which control the receivers. This provides added accuracy since all site correction factors, such as cable loss and antenna factors are added automatically.

LINE IMPEDANCE STABILIZATION NETWORK (LISN)

Line conducted measurements utilize a fifty microhenry Line Impedance Stabilization Network as the monitoring point. The LISN used also contains a 250 uH CISPR adapter. This network provides for calibrated radio frequency noise measurements by the design of the internal low pass and high pass filters on the EUT and measurement ports, respectively.

POWER METER

A power meter and peak power sensor are used for all direct output power measurements from transmitters as they provide a broadband indication of the power output.

FILTERS/ATTENUATORS

External filters and precision attenuators are often connected between the receiving antenna or LISN and the receiver. This eliminates saturation effects and non-linear operation due to high amplitude transient events.

ANTENNAS

A biconical antenna is used to cover the range from 30 MHz to 300 MHz and a log periodic antenna is utilized from 300 MHz to 1000 MHz. Narrowband tuned dipole antennas are used over the entire 30 to 1000 MHz range for precision measurements of field strength. Above 1000 MHz, a horn antenna is used. The antenna calibration factors are included in site factors programmed into the test receivers.

ANTENNA MAST AND EQUIPMENT TURNTABLE

The antennas used to measure the radiated electric field strength are mounted on a non-conductive antenna mast equipped with a motor-drive to vary the antenna height.

ANSI C63.4 specifies that the test height above ground for table mounted devices shall be 80 centimeters. Floor mounted equipment shall be placed on the ground plane if the device is normally used on a conductive floor or separated from the ground plane by insulating material from 3 to 12 mm if the device is normally used on a non-conductive floor. During radiated measurements, the EUT is positioned on a motorized turntable in conformance with this requirement.

INSTRUMENT CALIBRATION

All test equipment is regularly checked to ensure that performance is maintained in accordance with the manufacturer's specifications. All antennas are calibrated at regular intervals with respect to tuned half-wave dipoles. An exhibit of this report contains the list of test equipment used and calibration information.

TEST PROCEDURES**EUT AND CABLE PLACEMENT**

The FCC requires that interconnecting cables be connected to the available ports of the unit and that the placement of the unit and the attached cables simulate the worst case orientation that can be expected from a typical installation, so far as practicable. To this end, the position of the unit and associated cabling is varied within the guidelines of ANSI C63.4, and the worst case orientation is used for final measurements.

CONDUCTED EMISSIONS

Conducted emissions are measured at the plug end of the power cord supplied with the EUT. Excess power cord length is wrapped in a bundle between 30 and 40 centimeters in length near the center of the cord. Preliminary measurements are made to determine the highest amplitude emission relative to the specification limit for all the modes of operation. Placement of system components and varying of cable positions are performed in each mode. A final peak mode scan is then performed in the position and mode for which the highest emission was noted on all current carrying conductors of the power cord.

RADIATED EMISSIONS

Radiated emissions measurements are performed in two phases as well. A preliminary scan of emissions is conducted in which all significant EUT frequencies are identified with the system in a nominal configuration. At least two scans are performed from 30 MHz up to the frequency required by the regulation specified on page 1. One or more of these is with the antenna polarized vertically while the one or more of these is with the antenna polarized horizontally. During the preliminary scans, the EUT is rotated through 360°, the antenna height is varied and cable positions are varied to determine the highest emission relative to the limit.

A speaker is provided in the receiver to aid in discriminating between EUT and ambient emissions. Other methods used during the preliminary scan for EUT emissions involve scanning with near field magnetic loops, monitoring I/O cables with RF current clamps, and cycling power to the EUT.

Final maximization is a phase in which the highest amplitude emissions identified in the spectral search are viewed while the EUT azimuth angle is varied from 0 to 360 degrees relative to the receiving antenna. The azimuth which results in the highest emission is then maintained while varying the antenna height from one to four meters. The result is the identification of the highest amplitude for each of the highest peaks. Each recorded level is corrected in the receiver using appropriate factors for cables, connectors, antennas, and preamplifier gain. Emissions which have values close to the specification limit may also be measured with a tuned dipole antenna to determine compliance.

CONDUCTED EMISSIONS FROM ANTENNA PORT

Direct measurements are performed with the antenna port of the EUT connected to either the power meter or spectrum analyzer via a suitable attenuator and/or filter. These are used to ensure that the front end of the measurement instrument is not overloaded by the fundamental transmission.

Measurement bandwidths (video and resolution) are set in accordance with FCC procedures for the type of radio being tested.

SPECIFICATION LIMITS AND SAMPLE CALCULATIONS

The limits for conducted emissions from the AC power port are given in units of microvolts, the limits for radiated electric field emissions are given in units of microvolts per meter at a specified test distance and the output power limits are given in terms of Watts, milliwatts or dBm. Data is measured in the logarithmic form of decibels relative to one microvolt, or dB microvolts (dBuV). For radiated emissions, the measured data is converted to the field strength at the antenna in dB microvolts per meter (dBuV/m). The results are then converted to the linear forms of uV and uV/m for comparison to published specifications.

Where the radiated electric field strength is expressed in terms of the equivalent isotropic radiated power (eirr) the following formula is used to determine the field strength limit in terms of microvolts per meter at a distance of 3m from the equipment under test:

$$E = \frac{1000000 \sqrt{30 P}}{3} \quad \text{microvolts per meter}$$

where P is the eirr (Watts)

For reference, converting the voltage and electric field strength specification limits from linear to decibel form is accomplished by taking the base ten logarithm, then multiplying by 20. Conversion of power specification limits from linear units (in milliwatts) to decibel form (in dBm) is accomplished by taking the base ten logarithm, then multiplying by 10.

FCC 15.407 (a) and RSS 210 (o) OUTPUT POWER LIMITS

The table below shows the limits for output power and output power density. Where the signal bandwidth is less than 20 MHz the maximum output power is reduced to the power spectral density limit plus 10 times the log of the bandwidth (in MHz).

Operating Frequency (MHz)	Output Power	Power Spectral Density
902 – 928	1 Watts (30 dBm)	8 dBm/3kHz
2400 – 2483.5	1 Watts (30 dBm)	8 dBm/3kHz
5725 – 5850	1 Watts (30 dBm)	8 dBm/3kHz

The maximum permitted output power is reduced by 1dB for every dB the antenna gain exceeds 6dBi. Fixed point-to-point applications using the 5725 – 5850 MHz band are not subject to this restriction.

RSS 210 (o) AND FCC 15.247 SPURIOUS RADIATED EMISSIONS LIMITS

T limits for unwanted (spurious) emissions from the transmitter falling in the restricted bands detailed in Part 15.205 and for all spurious emissions from the receiver are:

Frequency Range (MHz)	Limit (uV/m @ 3m)	Limit (dBuV/m @ 3m)
30 to 88	100	40
88 to 216	150	43.5
216 to 960	200	46.0
Above 960	500	54.0

All other unwanted (spurious) emissions shall be at least 20dB below the level of the highest in-band signal level.

FCC 15.205 AC POWER PORT CONDUCTED EMISSIONS LIMITS

The table below shows the limits for emissions on the AC power line as detailed in FCC Part 15.205.

Frequency (MHz)	Average Limit (dBuV)	Quasi Peak Limit (dBuV)
0.150 to 0.500	Linear decrease on logarithmic frequency axis between 56.0 and 46.0	Linear decrease on logarithmic frequency axis between 66.0 and 56.0
0.500 to 5.000	46.0	56.0
5.000 to 30.000	50.0	60.0

RSS-210 SECTION 6.6 AC POWER PORT CONDUCTED EMISSIONS LIMITS

The table below shows the limits for emissions on the AC power line as detailed in Industry Canada RSS-210 section 6.6.

Frequency Range (MHz)	Limit (uV)	Limit (dBuV)
0.450 to 30.000	250	48

SAMPLE CALCULATIONS - CONDUCTED EMISSIONS

Receiver readings are compared directly to the conducted emissions specification limit (decibel form) as follows:

$$R_r - B = C$$

and

$$C - S = M$$

where:

R_r = Receiver Reading in dBuV

B = Broadband Correction Factor*

C = Corrected Reading in dBuV

S = Specification Limit in dBuV

M = Margin to Specification in +/- dB

* Broadband Level - Per ANSI C63.4, 13 dB may be subtracted from the quasi-peak level if it is determined that the emission is broadband in nature. If the signal level in the average mode is six dB or more below the signal level in the peak mode, the emission is classified as broadband.

SAMPLE CALCULATIONS - RADIATED EMISSIONS

Receiver readings are compared directly to the specification limit (decibel form). The receiver internally corrects for cable loss, preamplifier gain, and antenna factor. The calculations are in the reverse direction of the actual signal flow, thus cable loss is added and the amplifier gain is subtracted. The Antenna Factor converts the voltage at the antenna coaxial connector to the field strength at the antenna elements. A distance factor, when used for electric field measurements, is calculated by using the following formula:

$$F_d = 20 * \text{LOG}_{10} (D_m/D_s)$$

where:

$$F_d = \text{Distance Factor in dB}$$

$$D_m = \text{Measurement Distance in meters}$$

$$D_s = \text{Specification Distance in meters}$$

Measurement Distance is the distance at which the measurements were taken and Specification Distance is the distance at which the specification limits are based. The antenna factor converts the voltage at the antenna coaxial connector to the field strength at the antenna elements.

The margin of a given emission peak relative to the limit is calculated as follows:

$$R_c = R_r + F_d$$

and

$$M = R_c - L_s$$

where:

$$R_r = \text{Receiver Reading in dBuV/m}$$

$$F_d = \text{Distance Factor in dB}$$

$$R_c = \text{Corrected Reading in dBuV/m}$$

$$L_s = \text{Specification Limit in dBuV/m}$$

$$M = \text{Margin in dB Relative to Spec}$$

EXHIBIT 1: Test Equipment Calibration Data

1 Page

Radiated Emissions, 5 - 18 GHz, 16-Jun-04**Engineer: Adam LaCourse**

<u>Manufacturer</u>	<u>Description</u>	<u>Model #</u>	<u>Asset #</u>	<u>Cal Due</u>
Hewlett Packard	Microwave Preamplifier, 1-26.5GHz	8449B	785	23-Jan-05
EMCO	Horn Antenna, D. Ridge 1-18GHz	3115	786	29-Oct-04
Hewlett Packard	High Pass filter, 8.2GHz	P/N-84300-80039	1156	19-Apr-05
Hewlett Packard	EMC Spectrum Analyzer, 9KHz - 22GHz	8593EM	1319	20-Nov-04

EXHIBIT 2: Test Data Log Sheets

ELECTROMAGNETIC EMISSIONS

TEST LOG SHEETS

AND

MEASUREMENT DATA

T56034 5 Pages



EMC Test Data

Client:	Axxcelera Wireless	Job Number:	J55674
Model:	AB-access Unit	T-Log Number:	T56034
		Account Manager:	Christine Vu
Contact:	Dennis Mc Carthy		
Emissions Spec:	FCC Part 15.205 / 15.401	Class:	II Permissive
Immunity Spec:		Environment:	Radio

EMC Test Data

For The

Axxcelera Wireless

Model

AB-access Unit

Date of Last Test: 6/16/2004



EMC Test Data

Client:	Axxcelera Wireless	Job Number:	J55674
Model:	AB-access Unit	T-Log Number:	T56034
		Account Manager:	Christine Vu
Contact:	Dennis Mc Carthy		
Emissions Spec:	FCC Part 15.205 / 15.401	Class:	
Immunity Spec:	Enter immunity spec on cover	Environment:	Radio

EUT INFORMATION

General Description

The EUT is a 5 GHz radio transceiver and 6 foot dish antenna which together is designed to transmit and receive data. Normally, the EUT would be mounted to a pole. The EUT was treated as table-top equipment during testing to simulate the end-user environment. The electrical rating of the EUT is 48VDC, 625mA.

Equipment Under Test

Manufacturer	Model	Description	Serial Number	FCC ID
Axxcelera	AB-Access	U-NII ISM Transceiver	SW1600135H	OJBAB-ACC-SU02ESS
Radio Waves	SP6-5.2	6', 2 pol, dish antenna	N/A	N/A

Other EUT Details

EUT Enclosure

The transceiver enclosure is primarily constructed of molded plastic and measures approximately 25 cm wide by 6 cm deep by 27 cm high.

The dish antenna does not have an enclosure. It measures 6 foot in diameter.

Modification History

Mod. #	Test	Date	Modification
1	-	-	None

Modifications applied are assumed to be used on subsequent tests unless otherwise stated as a further modification.



EMC Test Data

Client:	Axxcelera Wireless	Job Number:	J55674
Model:	AB-access Unit	T-Log Number:	T56034
		Account Manager:	Christine Vu
Contact:	Dennis Mc Carthy		
Emissions Spec:	FCC Part 15.205 / 15.401	Class:	II Permissive
Immunity Spec:	Enter immunity spec on cover	Environment:	Radio

Test Configuration #1

Local Support Equipment

Manufacturer	Model	Description	Serial Number	FCC ID
None				

Remote Support Equipment

Manufacturer	Model	Description	Serial Number	FCC ID
Dell	Inspiron 3800	Laptop Computer	1213-104-18	LNQUSA-34552-M5-E

Interface Cabling and Ports

Port	Connected To	Cable(s)		
		Description	Shielded or Unshielded	Length(m)
Transceiver RF	dish antenna RF	coax	shielded	1.3
Transceiver Ethernet	POE converter box	CAT5	Unshielded	2
POE converter box	Laptop Computer	CAT5	Unshielded	30

Note: The 2nd RF transceiver and dish antenna ports were not connected as the manufacturer stated that it is for ??? purpose and therefore would not normally be connected.

EUT Operation During Emissions

The transceiver was set up to continuously transmit through the dish antenna at the recorded transmit frequencies.



EMC Test Data

Client:	Axxcelera Wireless	Job Number:	J55674
Model:	AB-access Unit	T-Log Number:	T56034
Contact:	Dennis Mc Carthy	Account Manager:	Christine Vu
Spec:	FCC Part 15.205 / 15.401	Class:	N/A

Radiated Emissions

Test Specifics

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above for a Class II Permissive change.

Date of Test: 6/16/2004
Test Engineer: Adam LaCourse
Test Location: SVOATS #2

Config. Used: 1
Config Change: none
EUT Voltage: 120V/60Hz

General Test Configuration

The EUT and all local support equipment were located on the turntable for radiated spurious emissions testing. All remote support equipment was located off of the turntable with the ethernet connection routed in overhead in the cable gantry.

For radiated emissions testing the measurement antenna was located 3 meters from the EUT.

Ambient Conditions:

Temperature:	23.9 °C
Rel. Humidity:	55 %

Summary of Results

Run #	Test Performed	Limit	Result	Margin
1a - c	CH 10, 12 and 14 Harmonics measured	FCC Part 15.205 / 15.401	Pass	-11.7dB @ 1155.01155

Modifications Made During Testing:

No modifications were made to the EUT during testing

Deviations From The Standard

No deviations were made from the requirements of the standard.



EMC Test Data

Client:	Axxcelera Wireless	Job Number:	J55674
Model:	AB-access Unit	T-Log Number:	T56034
Contact:	Dennis Mc Carthy	Account Manager:	Christine Vu
Spec:	FCC Part 15.205 / 15.401	Class:	N/A

Run #1a: Radiated Spurious Emissions, Low Channel @ 5745 MHz, Power Output = 12.87dBm

Spurious Radiated Emissions:

Frequency	Level	Pol	15.209 / 15E		Detector	Azimuth	Height	Comments
MHz	dBuV/m	v/h	Limit	Margin	Pk/QP/Avg	degrees	meters	
11490.00	54.5	-	74.0	-19.5	PK	0	1.0	Noise Floor
11490.00	42.0	-	54.0	-12.0	Avg	0	1.0	Noise Floor
17240.00	-	-	74.0	-	PK	0	1.0	Noise Floor
17240.00	-	-	54.0	-	Avg	0	1.0	Noise Floor

Note 1: For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit was set to -27dBm/MHz (68dBuV/m).

Note 2: No other emissions detected after the second harmonic of the fundamental, close to 20 dB of the limit.

Run #1b: Radiated Spurious Emissions, @ 5775 MHz, Power Output = 12.80dBm

Spurious Radiated Emissions:

Frequency	Level	Pol	15.209 / 15.247		Detector	Azimuth	Height	Comments
MHz	dBuV/m	v/h	Limit	Margin	Pk/QP/Avg	degrees	meters	
11550.00	54.7	-	74.0	-19.3	Pk	0	1.0	Noise Floor
11550.00	42.3	-	54.0	-11.7	Avg	0	1.0	Noise Floor
17330.00	-	-	74.0	-	Pk	0	1.0	Noise Floor
17330.00	-	-	54.0	-	Avg	0	1.0	Noise Floor

Note 1: For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit was set to -27dBm/MHz (68dBuV/m).

Note 2: No other emissions detected after the second harmonic of the fundamental, close to 20 dB of the limit.

Run #1c: Radiated Spurious Emissions, @ 5805 MHz, Power Output = 12.75dBm

Other Spurious Radiated Emissions:

Frequency	Level	Pol	15.209 / 15.247		Detector	Azimuth	Height	Comments
MHz	dBuV/m	v/h	Limit	Margin	Pk/QP/Avg	degrees	meters	
11610.00	55.2	-	74.0	-18.8	Pk	0	1.0	Noise Floor
11610.00	42.2	-	54.0	-11.8	Avg	0	1.0	Noise Floor
23220.00	-	-	74.0	-	Pk	0	1.0	Noise Floor
23220.00	-	-	54.0	-	Avg	0	1.0	Noise Floor

Note 1: For emissions in restricted bands, the limit of 15.209 was used. For all other emissions, the limit was set to -27dBm/MHz (68dBuV/m).

Note 2: No other emissions detected after the second harmonic of the fundamental, close to 20 dB of the limit.