

TEST REPORT

Product Name : Wireless Communication Headset

Brand Mark : KOSS

Model No. : KOSS CS340BT QZ FCC ID : L76-CS340BTQZ-X

Report Number : BLA-EMC-202111-A5303

Date of Sample Receipt : 2021/11/10

Date of Test : 2021/11/10 to 2021/11/19

Date of Issue : 2021/11/19

Test Standard 47 CFR Part 1.1307, Part 2.1093, KDB

447498

Test Result : Pass

Jozu Blue Zhong

Prepared for:

Koss Corporation 4129 N. Port Washington Rd Milwaukee, WI 53212

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China

TEL: +86-755-23059481

Compiled by:

Approved by:

Review by:

Date:







Page 2 of6

REPORT REVISE RECORD

| Version No. | Date | Description |
|-------------|------------|-------------|
| 00 | 2021/11/19 | Original |





Page 3 of6



TABLE OF CONTENTS

| 1 | TE | EST SUMMARY | 4 |
|---|----|-----------------------------------|---|
| 2 | GI | ENERAL INFORMATION | 5 |
| 3 | GI | ENERAL DESCRIPTION OF E.U.T | 5 |
| 4 | L/ | ABORATORY LOCATION | 5 |
| 5 | RI | F EXPOSURE COMPLIANCE REQUIREMENT | 6 |
| 5 | .1 | Standard Requirement | 6 |
| 5 | .2 | LIMITS | 6 |
| 5 | .3 | EUT RF Exposure | 6 |



Page 4 of6

1 TEST SUMMARY

| Test item | Test Requirement | Test Method | Class/Severity | Result |
|-------------|------------------------------------------------------|-----------------------|--------------------|--------|
| RF Exposure | 47 CFR Part 1.1307, Part 2.1093, KDB 447498 | CFR 47 Part 2.1093 | CFR 47 Part 2.1093 | PASS |





Page 5 of6

2 GENERAL INFORMATION

| Applicant | Koss Corporation | |
|----------------|----------------------------------------------------------------------------------------------------|--|
| Address | 4129 N. Port Washington Rd Milwaukee, WI 53212 | |
| Manufacturer | ASKA Electronics Co. Ltd. | |
| Address | No.5 Puxin Road, Keyuancheng Industrial Park, Tangxia Town, Dongguan, Guangdong, China PRC. 523725 | |
| Factory | ASKA Electronics Co. Ltd. | |
| Address | No.5 Puxin Road, Keyuancheng Industrial Park, Tangxia Town, Dongguan, Guangdong, China PRC. 523725 | |
| Product Name | ct Name Wireless Communication Headset | |
| Test Model No. | KOSS CS340BT QZ | |

3 GENERAL DESCRIPTION OF E.U.T.

| Hardware Version | MB_PCB_V51_210112 | |
|----------------------|---------------------------------|--|
| Software Version | C060_koss_V07_20210730 | |
| Operation Frequency: | 2402MHz-2480MHz | |
| Modulation Type: | GFSK, pi/4DQPSK, 8DPSK | |
| Channel Spacing: | 1MHz | |
| Number of Channels: | 79 | |
| Antenna Type: | PCB Antenna | |
| Antenna Gain: | 1dBi(Provided by the applicant) | |

4 LABORATORY LOCATION

All tests were performed at:

BlueAsia of Technical Services(Shenzhen) Co., Ltd.

Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China

Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673

No tests were sub-contracted.



Page 6 of6

5 RF EXPOSURE COMPLIANCE REQUIREMENT

5.1 STANDARD REQUIREMENT

According to KDB447498D01 General RF Exposure Guidance v06

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.2 LIMITS

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\sqrt{f(GHz)} \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is \leq 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.3 EUT RF EXPOSURE

| Operational Mode;BT | | | | | | |
|---------------------------------------------------------|------------------------------|-------------------|-----------------------|------|------------|-----------|
| Channel | Maximum Peak annel Conducted | Tune up tolerance | Maximum tune-up Power | | Calculated | Exclusion |
| Chamilei | Output Power (dBm) | (dB) | (dBm) | (mW) | value | threshold |
| 2402 MHz | 0.296 | ±1 | 1.296 | 1.35 | 0.42 | 0.0 |
| 2441 MHz | 0.279 | ±1 | 1.279 | 1.34 | 0.42 | 3.0 |
| 2480 MHz | 0.225 | ±1 | 1.225 | 1.33 | 0.42 | |
| Conclusion: the calculated value ≤3.0, SAR is exempted. | | | | | | |

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.