



Certificate #5376.01



EUROFINS ELECTRICAL TESTING SERVICE (SHENZHEN) CO., LTD.

RADIO TEST - REPORT

FCC&ISED Compliance Test Report

Product name: AMP Bridge

Model name: AMP USB Bridge WiFi and RF

FCC ID: 2AU29AMPRFWIFIUSBV3

IC: 25624-AMPRFWIFIV3

Test Report Number: EFGX23090181-IE-01-E03

Content

1	General Information	3
1.1	Notes	3
1.2	Testing laboratory	4
1.3	Details of approval holder	4
1.4	Details of Manufacturer	4
1.5	Application details	4
1.6	Test item	4
1.7	Test standards	6
2	Technical test	7
2.1	Summary of test results	7
2.2	Test environment	7
2.3	Measurement uncertainty	7
2.4	Test mode	7
2.5	Test equipment utilized	8
2.6	Auxiliary Equipment Used during Test:	8
2.7	Test software information	8
2.8	Customized Configurations	8
2.9	Test Environments	8
2.10	Test results	9
3	Technical Requirement	10
3.1	Conducted Emission	10
3.2	Automatically Deactivate	13
3.3	20dB bandwidth	15
3.4	Field strength of fundamental , Field strength of spurious emission for transmitter and Restricted bands	17

1 General Information

1.1 Notes

The results of this test report relate exclusively to the item tested as specified in chapter "Description of test item" and are not transferable to any other test items.

Eurofins Product Testing Service (Shenzhen) Co., Ltd. is not responsible for any generalisations and conclusions drawn from this report. Any modification of the test item can lead to invalidity of test results and this test report may therefore be not applicable to the modified test item.

The test report may only be reproduced or published in full. Reproducing or publishing extracts of the report requires the prior written approval of the Eurofins Product Testing Service (Shenzhen) Co., Ltd.

This document is subject to the General Terms and Conditions and the Testing and Certification System of Eurofins Product Testing Service (Shenzhen) Co., Ltd., available on request or accessible at www.eurofins.com.

Operator:

2024-01-09		Bruce Zheng / Project Engineer	
Date	Eurofins-Lab.	Name / Title	Signature

Technical responsibility for area of testing:

2024-01-09		Albert Xu / Lab Manager	
Date	Eurofins-Lab.	Name / Title	Signature

1.2 Testing laboratory

Eurofins Electrical Testing Service (Shenzhen) Co., Ltd.

1st Floor, Building 2, Chungu, Meisheng Huigu Science and Technology Park, No. 83 Dabao Road, Bao'an District, Shenzhen. P.R.China.

Telephone : +86-755-82911867

Fax : +86-755-82910749

The Laboratory has passed the Accreditation by the American Association for Laboratory Accreditation (A2LA). The Accreditation number is 5376.01

The Laboratory has been listed by industry Canada to perform electromagnetic emission measurements, The CAB identifier is CN0088

1.3 Details of approval holder

Name : Turnils North America
Address : 1750 Satellite Blvd, Suite 100, Buford GA 30518,
United States
Telephone : ./.
Fax : ./.

1.4 Details of Manufacturer

Name : Turnils North America
Address : 1750 Satellite Blvd, Suite 100, Buford GA 30518,
United States
Telephone : ./.
Fax : ./.

1.5 Application details

Date of receipt of application : 2023-09-14
Date of receipt of test item : 2023-09-14
Date of test : 2023-09-14 to 2024-01-09
Date of issue : 2024-01-09

1.6 Test item

Product type : AMP Bridge
Model name : AMP USB Bridge WiFi and RF
Sample ID : 230915-02-001
Brand : ./.
Serial number : ./.
Ratings : USB 5V DC
Test voltage : USB 5V DC
FCC ID : 2AU29AMPFRWIFIUSBV3
IC : 25624-AMPFRWIFIV3
PMN : AMP Bridge
HVIN : AMP USB Bridge WiFi and RF V3
Additional information : ./.

RadioTechnical data

Frequency range	: 433.92MHz
Radio Tech.	: N/A
Frequency channel	: 1 Channel
Modulation	: GFSK
Antenna type	: Patch antenna

1.7 Test standards

Test Standards	
FCC Part 15 Subpart C	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators
RSS-210 Issue 10 December 2019	Licence-Exempt Radio Apparatus: Category I Equipment
RSS-GEN Issue 5 February 2021	RSS-Gen — General Requirements for Compliance of Radio Apparatus

Test Method

- 1: ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
- 2: ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices.

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.



or

The deviations as specified were ascertained in the course of the tests performed.



2.2 Test environment

Temperature : 20 ... 25°C
 Relative humidity content : 30 ... 60%
 Air pressure : 100 ... 101kPa

2.3 Measurement uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Conducted RF test	RF Power Conducted: 1.16dB Frequency test involved: 1.05×10 ⁻⁷ or 1%
Uncertainty in conducted measurements	1.96dB
Uncertainty for Radiated Spurious Emission 25MHz-3000MHz	Horizontal: 4.46dB; Vertical: 4.54dB;
Uncertainty for Radiated Spurious Emission 3000MHz-18000MHz	Horizontal: 4.42dB; Vertical: 4.41dB;
Uncertainty for Radiated Spurious Emission 18000MHz-40000MHz	Horizontal: 4.63dB; Vertical: 4.62dB;

2.4 Test mode

The EUT was set at continuously transmitting during the test.

2.5 Test equipment utilized

EQUIPMENT ID	EQUIPMENT NAME	MODEL NO.	CAL. DUE DATE
23-2-13-05	EMI Test Receiver	ESR3	2024-03-21
23-2-13-06	LISN	NNLK 8127 RC	2024-03-21
23-2-10-16	Attenuator	VTSD 9561-F	2024-03-21
23-2-13-01	EMI Test Receiver	ESR7	2024-03-22
23-2-13-02	Signal Analyzer	N9020B-544	2024-03-22
23-2-12-01	Active Loop Antenna	FMZB 1519B	2024-03-22
23-2-12-02	TRILOG Broadband Antenna	VULB9168	2024-05-29
23-2-12-03	Horn Antenna	3117	2024-05-29
23-2-12-04	Horn Antenna	BBHA 9170	2024-05-29
23-2-10-01	Preamplifier	BBV9745	2024-03-22
23-2-10-02	Preamplifier	EMC001330	2024-03-22
23-2-10-03	Preamplifier	EMC051845SE	2024-03-22
23-2-10-14	Switch and Control Unit	ERIT-E-JS0806-SF1	N/A

2.6 Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.	S/N
N/A	N/A	N/A	N/A

2.7 Test software information

Test Software Version	N/A		
Modulation	Setting TX Power	TX Pattern	Packet Type
FSK	Default	Default	Default

2.8 Customized Configurations

EUT Conf.	Signal Description	Operating Frequency	Duty Cycle
TM1	GFSK	433.92MHz	100%

2.9 Test Environments

Environment Parameter	Temperature	Voltage	Relative Humidity
101.7Kpa	26.5℃	5Vdc	68.3%

2.10 Test results

☒ 1st test

☐ test after modification

☐ production test

Technical Requirements					
FCC Part 15 Subpart C/ RSS-210 Issue 9/RSS-Gen Issue 5					
Test Condition			Test Result	Verdict	Test Site
§15.207	RSS-GEN 8.8	Conducted emission AC power port	See page 10	Pass	Site 1
§15.231(a)(1)	RSS-210 A1.1	Automatically Deactivate	See page 13	Pass	Site 1
§15.231(b)(3)	RSS-210 A1.2	Field strength of fundamental	See page 21	Pass	Site 1
§15.231(b)(3) §15.209 & §15.205	RSS-210 A1.2 RSS-GEN 6.13 RSS-GEN 8.9 RSS-GEN 8.10	Field strength of spurious emission	See page 21	Pass	Site 1
§15.231(c)	--	-20dB Bandwidth	See page 15	Pass	Site 1
--	RSS-GEN 6.7	99% Occupied Bandwidth	See page 15	Pass	Site 1
§15.203	RSS-GEN 6.8	Antenna requirement	See note 1	Pass	--

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses internal antenna, According to §15.203/ RSS-GEN 6.8, it is considered sufficiently to comply with the provisions of this section.

3 Technical Requirement

3.1 Conducted Emission

Test Method:


The test method was referred to the subclause 5.2 of ANSI C63.4-2014.

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line

Test Setup:

The mains cable of the EUT (per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.




Limit:

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50


Decreasing linear.

Test Result:



Final Data List										
NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Type	Verdict
1	0.1680	10.26	52.38	65.06	12.68	28.41	55.06	26.65	L1	PASS
2	0.1764	10.26	51.88	64.65	12.77	32.22	54.65	22.43	L1	PASS
3	0.1903	10.26	50.26	64.02	13.76	32.72	54.02	21.30	L1	PASS
4	0.2260	10.26	40.19	62.60	22.41	21.95	52.60	30.65	L1	PASS
5	6.8076	10.42	33.89	60.00	26.11	24.71	50.00	25.29	L1	PASS
6	20.2929	10.56	38.00	60.00	22.00	33.72	50.00	16.28	L1	PASS

Test Graph



Final Data List										
NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Type	Verdict
1	0.1678	10.26	51.01	65.07	14.06	27.67	55.07	27.40	N	PASS
2	0.1896	10.26	49.87	64.05	14.18	31.69	54.05	22.36	N	PASS
3	0.2045	10.26	46.98	63.43	16.45	28.85	53.43	24.58	N	PASS
4	0.2303	10.26	40.03	62.44	22.41	22.93	52.44	29.51	N	PASS
5	6.7335	10.43	33.82	60.00	26.18	24.67	50.00	25.33	N	PASS
6	19.6403	10.64	37.08	60.00	22.92	32.81	50.00	17.19	N	PASS


3.2 Automatically Deactivate

Test Method

1. Connect EUT test port to spectrum analyzer.
2. Set the EUT to transmit maximum output power at 433.92MHz.
3. RBW=1MHz, VBW $\geq$ 3RBW, Span=0MHz, Sweep = 10s, Detector function = Average, Sweep time = single
4. Remark transmission time and record test plot.

Test Setup:

The component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The press a button of the EUT is to emit the specified signals for the purpose of measurements.




Limits:

According to §15.231 (a) (1) & RSS-210 A1.1, automatically deactivate limit as below:

A manually operated transmitter shall be equipped with a push-to-operate switch and be under manual control at all times during transmission. When released, the transmitter shall cease transmission within no more than 5 seconds of being released.

Test Data:

Time of Transmitting (s)	Limit (sec)	Result
4.24	5	Pass



Test Result: Pass


3.3 20dB bandwidth

Test Method:

1. Connect EUT test port to spectrum analyzer.
2. Set the EUT to transmit maximum output power at 433.92MHz.
3. Then set the EUT to transmit at high, middle and low frequency separately.
4. Set Span = approximately 1.5 to 5 times the 99% bandwidth.
5. Set RBW $\geq 1\%$ to 5% of the 99% bandwidth, VBW : $3 \times \text{RBW}$.
6. Set Sweep = auto.
7. Set Detector function = Peak.
8. Allow the trace to stabilize.
9. Repeat above procedures until all frequencies measured were complete.

Test Setup:

The component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The press a button of the EUT is to emit the specified signals for the purpose of measurements.



Limit:

According to §15.231 (c), automatically deactivate limit as below:

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz.

According to RSS-GEN 6.7, no limit for 99% bandwidth

Test Result

20dB Bandwidth (KHz)	99% Bandwidth (KHz)	Limit (KHz)	Result
82.46	79.682	1084.80	Pass



3.4 Field strength of fundamental , Field strength of spurious emission for transmitter and Restricted bands

Test Method:

- 1: The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- 2: The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
- 3: The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- 4: For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- 5: Use the following spectrum analyzer settings According to C63.10:
For Above 1GHz
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 1MHz, VBW $\geq$ RBW for peak measurement and VBW = 10Hz for average measurement, Sweep = auto, Detector function = peak, Trace = max hold.
For Below 1GHz
Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 KHz, VBW $\geq$ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.
For Below 30MHz
Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 200 Hz, VBW $\geq$ RBW from 9KHz to 0.15MHz, RBW 9KHz VBW $\geq$ RBW from 0.15MHz to 30MHz for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.


Note:

- 1: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for peak detection (PK) at frequency above 1GHz.
- 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average ((duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor (20log(1/duty cycle)).
- 4: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.

Test Setup:


Test Setup 1: Radiated Emission test below 30MHz

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.4. The test distance is 3m. The setup is according to ANSI C63.4.




Test Setup 2: Radiated Emission test below 1GHz

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.4. The test distance is 3m. The setup is according to ANSI C63.4.



Test Setup 3: Radiated Emission test above 1GHz

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.4. The test distance is 3m. The setup is according to ANSI C63.4.



Limit:

Radiated emissions which fall in the restricted bands, as defined in section 15.205, must comply with the radiated emission limits specified in section 15.209.

§ 15.209

Frequency MHz	Field Strength uV/m	Field Strength dBµV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

§15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

RSS-GEN 8.10

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	1660 - 1710	9.0 - 9.2
0.495 - 0.505	16.69475 - 16.69525	1718.8 - 1722.2	9.3 - 9.5
2.1735 - 2.1905	25.5 - 25.67	2200 - 2300	10.6 - 12.7
3.020 - 3.026	37.5 - 38.25	2310 - 2390	13.25 - 13.4
4.125 - 4.128	73 - 74.6	2483.5 - 2500	14.47 - 14.5
4.17725 - 4.17775	74.8 - 75.2	2655 - 2900	15.35 - 16.2
.20725 - 4.20775	108 - 138	3260 - 3267	17.7 - 21.4
5.677 - 5.683	149.9 - 150.05	3332 - 3339	22.01 - 23.12
6.215 - 6.218	156.52475 - 156.52525	3345.8 - 3358	23.6 - 24.0
6.26775 - 6.26825	156.7 - 156.9	3500 - 4400	31.2 - 31.8
6.31175 - 6.31225	162.0125 - 167.17	4500 - 5150	36.43 - 36.5
8.291 - 8.294	167.72 - 173.2	5350 - 5460	Above 38.6
8.362 - 8.366	240 - 285	7250 - 7750	
8.37625 - 8.38675	322 - 335.4	8025 - 8500	
8.41425 - 8.41475	399.9 - 410		
12.29 - 12.293	608 - 614		
12.51975 - 12.52025	960 - 1427		

§15.231 (b) In addition to the provisions of §15.205, the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	¹ 1,250 to 3,750	¹ 125 to 375
174-260	3,750	375
260-470	¹ 3,750 to 12,500	¹ 375 to 1,250
Above 470	12,500	1,250

RSS-210 A1.2 (b) Unwanted emissions shall be 10 times below the fundamental emissions field strength limits in Table A1 or comply with the limits specified in RSS-Gen, whichever is less stringent.

Fundamental Frequency (MHz), Excluding Restricted Frequency Bands Specified in RSS-Gen	Field Strength of the Fundamental Emissions (µV/m at 3m)
70-130	1,250
130-174	1,250 to 3,750*
174-260 ^(Note 1)	3,750
260-470 ^(Note 1)	3,750 to 12,500*
Above 470	12,500

* Linear interpolation with frequency, f, in MHz:

For 130-174 MHz: Field Strength (µV/m) = (56.82 × f) – 6136

For 260-470 MHz: Field Strength (µV/m) = (41.67 × f) – 7083

Note 1: Frequency bands 225-328.6 MHz and 335.4-399.9 MHz are designated for the exclusive use of the Government of Canada. Manufacturers should be aware of possible harmful interference and degradation of their licence-exempt radio equipment in these frequency bands.

Field Strength of the Fundamental Emissions

The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit.

Fundamental Average (dBµV/m) = 80.82dBuV/m (Average)

Fundamental Peak (dBµV/m) = 80.82dBuV/m + 20 = 100.82dBuV/m

Field Strength of the Spurious Emissions

The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit.

Fundamental Average (dBµV/m) = 60.82dBuV/m (Average)

Fundamental Peak (dBµV/m) = 60.82dBuV/m + 20 = 80.82dBuV/m

Remark:

- (1) “*” means the emission(s) appear within the restrict bands shall follow the requirement of section 15.205.
- (2) Data of measurement within this frequency range shown “--” in the table above means the reading of emissions are the noise floor or attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (3) Above 1GHz: Corrector factor = Antenna Factor + Cable Loss - Amplifier Gain.
- (4) Below 1GHz: Corrector factor = Antenna Factor + Cable Loss - Amplifier Gain.

- (5) Note: The low frequency, which started from 9 kHz to 30MHz with X/Y/Z axis, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Field Strength of the Fundamental Emissions
PK


NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	433.92	78.04	-5.61	100.82	22.78	100	24	Horizontal	PASS
2	433.92	78.75	-5.61	100.82	22.07	100	46	Vertical	PASS

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

Result of PK=Reading Level +Antenna Factor + Cable Loss - Amplifier Gain.


Result of AV= Reading Level +Antenna Factor + Cable Loss - Amplifier Gain+Duty factor.

Field strength of spurious emission for transmitter 30MHz – 1GHz



NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	48.4300	21.57	-9.18	40.00	18.43	100	348	Horizontal	PASS
2	61.0400	19.58	-10.17	40.00	20.42	100	198	Horizontal	PASS
3	140.580	21.90	-9.89	43.50	21.60	100	175	Horizontal	PASS
4	288.020	31.57	-9.17	46.00	14.43	100	13	Horizontal	PASS
5	710.940	32.40	-0.10	46.00	13.60	100	289	Horizontal	PASS
6	868.080	49.53	3.05	80.82	31.29	100	24	Horizontal	PASS

Test Graph



NO.	Freq. [MHz]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	43.5800	20.69	-9.08	40.00	19.31	100	360	Vertical	PASS
2	54.2500	20.87	-9.53	40.00	19.13	100	338	Vertical	PASS
3	151.250	23.94	-9.62	43.50	19.56	100	207	Vertical	PASS
4	215.270	25.83	-11.75	43.50	17.67	100	277	Vertical	PASS
5	650.800	34.96	-1.04	46.00	11.04	100	15	Vertical	PASS
6	868.080	51.68	3.05	80.82	29.14	100	40	Vertical	PASS

Field strength of spurious emission for transmitter above 1GHz

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	1149.433	63.53	37.19	-26.34	74.00	36.81	150	186	Horizontal	PASS
2	1600.4003	67.95	42.40	-25.55	74.00	31.60	150	51	Horizontal	PASS
3	2168.7792	63.23	42.07	-21.16	74.00	31.93	150	233	Horizontal	PASS
4	2603.7358	67.52	47.50	-20.02	74.00	26.50	150	244	Horizontal	PASS
5	3470.9807	60.76	41.94	-18.82	74.00	32.06	150	62	Horizontal	PASS
6	4287.525	59.44	43.06	-16.38	74.00	30.94	150	20	Horizontal	PASS

NO.	Freq. [MHz]	Reading [dBμV/m]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Polarity	Verdict
1	1114.7432	62.89	36.61	-26.28	74.00	37.39	150	184	Vertical	PASS
2	1597.7318	63.67	38.10	-25.57	74.00	35.90	150	68	Vertical	PASS
3	2203.469	62.30	41.05	-21.25	74.00	32.95	150	84	Vertical	PASS
4	2603.7358	65.65	45.63	-20.02	74.00	28.37	150	91	Vertical	PASS
5	3036.024	60.77	41.20	-19.57	74.00	32.80	150	152	Vertical	PASS
6	3964.6431	58.81	41.72	-17.09	74.00	32.28	150	198	Vertical	PASS

END