



FCC RF Test Report

APPLICANT : Texas Instruments Incorporated
EQUIPMENT : WiFi and Bluetooth Module
BRAND NAME : Texas Instruments
MODEL NAME : WL18MODGI
FCC ID : Z64-WL18DBMOD
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure

The product was received on Oct. 09, 2014 and testing was completed on Dec. 16, 2014. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

**SPORTON INTERNATIONAL INC.****No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.**

SPORTON INTERNATIONAL INC.

TEL : 886-3-327-3456

FAX : 886-3-328-4978

FCC ID : Z64-WL18DBMOD

Page Number : 1 of 45

Report Issued Date : Dec. 19, 2014

Report Version : Rev. 01

Report Template No.: BU5-FR15EWL Version 1.0



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	6
1.5 Modification of EUT	6
1.6 Testing Location	7
1.7 Applicable Standards	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency and Channel	8
2.2 Pre-Scanned RF Power	9
2.3 Test Mode	11
2.4 Connection Diagram of Test System	12
2.5 Support Unit used in test configuration and system	13
2.6 EUT Operation Test Setup	13
2.7 Measurement Results Explanation Example	13
3 TEST RESULT	14
3.1 6dB Bandwidth Measurement	14
3.2 Maximum Conducted Output Power Measurement	16
3.3 Power Spectral Density Measurement	17
3.4 Unwanted Emissions Measurement	19
3.5 AC Conducted Emission Measurement	37
3.6 Frequency Stability Measurement	41
3.7 Automatically Discontinue Transmission	42
3.8 Antenna Requirements	43
4 LIST OF MEASURING EQUIPMENT	44
5 UNCERTAINTY OF EVALUATION	45
APPENDIX A. TEST RESULT OF CONDUCTED TEST RESULTS	
APPENDIX B. TEST RESULT OF RADIATED TEST RESULTS	
APPENDIX C. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR4O0971E	Rev. 01	Initial issue of report	Dec. 19, 2014



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	$\leq -17, -27$ dBm/MHz & 15.209(a)	Pass	Under limit 2.65 dB at 5724.28 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 15.20 dB at 0.150 MHz
3.6	15.407(g)	Frequency Stability	Within Operation Band	Pass	-
3.7	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.8	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Texas Instruments Incorporated

12500 TI Boulevard, M/S 8751, Dallas, TX 75243, USA

1.2 Manufacturer

Jorjin Technologies Inc

17F, No. 239, Sec. 1, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	WiFi and Bluetooth Module
Brand Name	Texas Instruments
Model Name	WL18MODGI
FCC ID	Z64-WL18DBMOD
EUT supports Radios application	WLAN 11a/b/g/n HT20/HT40 Bluetooth v4.0 EDR/LE
HW Version	WG7837-T0B
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	5725 MHz ~ 5850 MHz
Maximum Output Power	<Ant. 1> 802.11a : 17.87 dBm / 0.0612 W 802.11n HT20 : 17.55 dBm / 0.0569 W 802.11n HT40 : 13.63 dBm / 0.0231 W <Ant. 2> 802.11a : 17.88 dBm / 0.0614 W 802.11n HT20 : 17.56 dBm / 0.0570 W 802.11n HT40 : 13.80 dBm / 0.0240 W
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

Antenna Information			
Antenna Type	Brand	2.4GHz~2.5GHz	4.9GHz~5.8GHz
PCB	Ethertronics	-0.6	4.5
Dipole	LSR	2	2
PCB	Laird	2	4
Chip	Pulse	3.2	4.2
PIFA	LSR	2	3
Chip	TDK	2.4	3.96

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		
	TH02-HY	CO05-HY	03CH07-HY

Note: The test site complies with ANSI C63.4 2009 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v01
- ♦ ANSI C63.10-2009

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151	5755	159	5795
	153	5765	161	5805
	155	5775	165	5825

Note: The above Frequency and Channel in boldface were 802.11n HT40.



2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test in the following tables. Final Output Power equals to Measured Output Power adds the duty factor.

<Ant. 1>

5GHz 802.11a mode			
Data Rate (MHz)	6M bps		
Channel	149	157	165
Frequency (MHz)	5745	5785	5825
Average Power (dBm)	12.27	17.87	13.91

5GHz 802.11n HT20 mode			
Data Rate (MHz)	MCS0		
Channel	149	157	165
Frequency (MHz)	5745	5785	5825
Average Power (dBm)	12.62	17.55	13.63

5GHz 802.11n HT40 mode		
Data Rate (MHz)	MCS0	
Channel	151	159
Frequency (MHz)	5755	5795
Average Power (dBm)	10.35	13.63



<Ant. 2>

5GHz 802.11a mode			
Data Rate (MHz)	6M bps		
Channel	149	157	165
Frequency (MHz)	5745	5785	5825
Average Power (dBm)	12.82	17.88	14.03

5GHz 802.11n HT20 mode			
Data Rate (MHz)	MCS0		
Channel	149	157	165
Frequency (MHz)	5745	5785	5825
Average Power (dBm)	12.72	17.56	13.87

5GHz 802.11n HT40 mode		
Data Rate (MHz)	MCS0	
Channel	151	159
Frequency (MHz)	5755	5795
Average Power (dBm)	10.39	13.80

2.3 Test Mode


Final results of test modes, data rates and test channels are shown as following table.

Test Cases				
Conducted TCs	Test Items	Mode	Data rate	Test Channel
	6dB Bandwidth Power Spectral Density	802.11a	6 Mbps	L/M/H
		802.11n HT20	MCS0	L/M/H
		802.11n HT40	MCS0	L/M/H
	Output Power	802.11a	6 Mbps	L/M/H
		802.11n HT20	MCS0	L/M/H
		802.11n HT40	MCS0	L/M/H
	Frequency Stability	802.11a	6 Mbps	L
Radiated TCs	Test Items	Mode	Data rate	Test Channel
	Radiated Band Edge	802.11a	6 Mbps	L/M/H
		802.11n HT20	MCS0	L/M/H
		802.11n HT40	MCS0	L/H
	Radiated Spurious Emission	802.11a	6 Mbps	L/M/H
		802.11n HT20	MCS0	L/M/H
		802.11n HT40	MCS0	L/H
AC Conducted Emission	Mode 1 : WLAN (5GHz) Link + Bluetooth Link + Adapter			


Ch. #		Band IV : 5725-5850 MHz		
		802.11a	802.11n HT20	802.11n HT40
L	Low	149	149	151
M	Middle	157	157	-
H	High	165	165	159

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
2.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Notebook	Lenovo	M490S	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Speaker	MI	MDZ-03-AC	N/A	N/A	N/A
5.	Fixture	N/A	N/A	N/A	N/A	N/A
6.	Evaluation board	N/A	WG1300BE00	N/A	N/A	N/A

2.6 EUT Operation Test Setup

For WLAN function, programmed RF utility, "RTTT Tool" installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Description of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.
Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.


3.1.4 Test Setup





3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.


Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).


1. The testing follows Method SA-2 of FCC KDB 789033 D01 General UNII Test Procedures v01r03.
 - Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 300 kHz.
 - Set VBW $\geq$ 1 MHz.
 - Number of points in sweep $\geq$ 2 Span / RBW.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(500\text{kHz}/\text{RBW})$ to the test result.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part 15.205.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5725-5850 MHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an EIRP of -17 dBm/MHz (78.3dBμV/m); for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an EIRP of -27 dBm/MHz (68.3dBμV/m).
- (2) Unwanted spurious emissions fallen in restricted bands per FCC Part 15.205 shall comply with the general field strength limits set forth in § 15.209 as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
-17	78.3
- 27	68.3

- (3) KDB789033 v01r03 H)2)c)(i) As specified in 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in 15.407(b)(4)). However, an out-of-band emission that complies with both the average and peak limits of 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz peak emission limit.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01.

Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW $\geq$ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold

(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz

- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
1	802.11a	93.01	3413.46	0.29	300Hz
1	802.11an20	92.92	3157.05	0.32	1kHz
1	802.11an40	86.61	1554.49	0.64	1kHz
2	802.11a	93.42	3413.46	0.29	300Hz
2	802.11an20	93.4	3173.08	0.32	1kHz
2	802.11an40	86.1	1538.46	0.65	1kHz




2. The EUT was placed on a rotatable table top 0.8 meter above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For Conducted Measurement Setup:




For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.



3.4.6 Test Result of Conducted Spurious at Band Edges in the Restricted Band

15E 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Grounding	Peak
Ant.				Limit	Line	Level	Gain	Loss	Factor	Avg
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dBi)	(dB)	(dB)	(P/A)
802.11a CH 149 5745MHz		5713.56	-37.75	-16.55	-21.2	-44.75	4.5	2.5	0	P
		5715	-52.39	-11.19	-41.2	-59.39	4.5	2.5	0	A
		5724.2	-22.79	-5.79	-17	-29.79	4.5	2.5	0	P
	*	5745	12.84	-	-	5.84	4.5	2.5	0	P
	*	5745	4.35	-	-	-2.65	4.5	2.5	0	A
802.11a CH 157 5785MHz		5710.6	-36.17	-14.97	-21.2	-43.17	4.5	2.5	0	P
		5685	-48.13	-6.93	-41.2	-55.13	4.5	2.5	0	A
		5724.6	-36.71	-19.71	-17	-43.71	4.5	2.5	0	P
	*	5788	18.22	-	-	11.22	4.5	2.5	0	P
	*	5788	9.55	-	-	2.55	4.5	2.5	0	A
		5850.96	-34.33	-17.33	-17	-41.33	4.5	2.5	0	P
		5888.16	-38.53	-17.33	-21.2	-45.53	4.5	2.5	0	P
		5890	-48.28	-7.08	-41.2	-55.28	4.5	2.5	0	A
802.11a CH 165 5825MHz	*	5827	14.04	-	-	7.04	4.5	2.5	0	P
	*	5827	5.49	-	-	-1.51	4.5	2.5	0	A
		5850.08	-24.65	-7.65	-17	-31.65	4.5	2.5	0	P
		5860.32	-33.42	-12.22	-21.2	-40.42	4.5	2.5	0	P
		5860.64	-51.64	-10.44	-41.2	-58.64	4.5	2.5	0	A



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Grounding	Peak
Ant.				Limit	Line	Level	Gain	Loss	Factor	Avg
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dBi)	(dB)	(dB)	(P/A)
802.11a CH 149 5745MHz		5714.12	-34.42	-13.22	-21.2	-41.42	4.5	2.5	0	P
		5710.84	-52.58	-11.38	-41.2	-59.58	4.5	2.5	0	A
		5723.4	-24.24	-7.24	-17	-31.24	4.5	2.5	0	P
	*	5747	12.1	-	-	5.1	4.5	2.5	0	P
	*	5747	3.37	-	-	-3.63	4.5	2.5	0	A
802.11a CH 157 5785MHz		5710.04	-36.8	-15.6	-21.2	-43.8	4.5	2.5	0	P
		5685.32	-48.15	-6.95	-41.2	-55.15	4.5	2.5	0	A
		5723.8	-36.14	-19.14	-17	-43.14	4.5	2.5	0	P
	*	5788	18.06	-	-	11.06	4.5	2.5	0	P
	*	5788	9.4	-	-	2.4	4.5	2.5	0	A
		5856.32	-38.63	-21.63	-17	-45.63	4.5	2.5	0	P
		5887.44	-38.09	-16.89	-21.2	-45.09	4.5	2.5	0	P
802.11a CH 165 5825MHz		5890	-48.58	-7.38	-41.2	-55.58	4.5	2.5	0	A
	*	5822	13.99	-	-	6.99	4.5	2.5	0	P
	*	5822	5.62	-	-	-1.38	4.5	2.5	0	A
		5850.48	-25.29	-8.29	-17	-32.29	4.5	2.5	0	P
		5861	-35.02	-13.82	-21.2	-42.02	4.5	2.5	0	P
		5860.96	-50.42	-9.22	-41.2	-57.42	4.5	2.5	0	A



15E 5725~5850MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Grounding	Peak
Ant.				Limit	Line	Level	Gain	Loss	Factor	Avg
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dBi)	(dB)	(dB)	(P/A)
802.11n HT20 CH 149 5745MHz		5713.56	-38.26	-17.06	-21.2	-45.26	4.5	2.5	0	P
		5714.84	-51.96	-10.76	-41.2	-58.96	4.5	2.5	0	A
		5723.16	-22.73	-5.73	-17	-29.73	4.5	2.5	0	P
	*	5744	13.27	-	-	6.27	4.5	2.5	0	P
	*	5744	4.26	-	-	-2.74	4.5	2.5	0	A
802.11n HT20 CH 157 5785MHz		5697.8	-36.66	-15.46	-21.2	-43.66	4.5	2.5	0	P
		5685.08	-48.86	-7.66	-41.2	-55.86	4.5	2.5	0	A
		5721.08	-37.55	-20.55	-17	-44.55	4.5	2.5	0	P
	*	5784	17.71	-	-	10.71	4.5	2.5	0	P
	*	5784	9.03	-	-	2.03	4.5	2.5	0	A
		5858.4	-37.52	-20.52	-17	-44.52	4.5	2.5	0	P
		5888.48	-38.28	-17.08	-21.2	-45.28	4.5	2.5	0	P
		5888	-49.04	-7.84	-41.2	-56.04	4.5	2.5	0	A
802.11n HT20 CH 165 5825MHz	*	5826	13.6	-	-	6.6	4.5	2.5	0	P
	*	5826	5.28	-	-	-1.72	4.5	2.5	0	A
		5851.04	-26.71	-9.71	-17	-33.71	4.5	2.5	0	P
		5867.52	-33.67	-12.47	-21.2	-40.67	4.5	2.5	0	P
		5860.72	-51.93	-10.73	-41.2	-58.93	4.5	2.5	0	A



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Grounding	Peak
Ant.				Limit	Line	Level	Gain	Loss	Factor	Avg
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dBi)	(dB)	(dB)	(P/A)
802.11n HT20 CH 149 5745MHz		5714.44	-37.34	-16.14	-21.2	-44.34	4.5	2.5	0	P
		5714.92	-52.95	-11.75	-41.2	-59.95	4.5	2.5	0	A
		5724.28	-19.65	-2.65	-17	-26.65	4.5	2.5	0	P
	*	5746	13.08	-	-	6.08	4.5	2.5	0	P
	*	5746	4.49	-	-	-2.51	4.5	2.5	0	A
802.11n HT20 CH 157 5785MHz		5686.36	-38.37	-17.17	-21.2	-45.37	4.5	2.5	0	P
		5685.88	-48.97	-7.77	-41.2	-55.97	4.5	2.5	0	A
		5718.92	-35.53	-18.53	-17	-42.53	4.5	2.5	0	P
	*	5783	17.46	-	-	10.46	4.5	2.5	0	P
	*	5783	9.37	-	-	2.37	4.5	2.5	0	A
		5852.88	-38.75	-21.75	-17	-45.75	4.5	2.5	0	P
		5886.88	-38.68	-17.48	-21.2	-45.68	4.5	2.5	0	P
		5886.96	-49.02	-7.82	-41.2	-56.02	4.5	2.5	0	A
802.11n HT20 CH 165 5825MHz	*	5822	14.08	-	-	7.08	4.5	2.5	0	P
	*	5822	5.24	-	-	-1.76	4.5	2.5	0	A
		5852	-24	-7	-17	-31	4.5	2.5	0	P
		5860.06	-33.1	-11.9	-21.2	-40.1	4.5	2.5	0	P
		5860.96	-50.83	-9.63	-41.2	-57.83	4.5	2.5	0	A



15E 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Grounding	Peak
Ant.				Limit	Line	Level	Gain	Loss	Factor	Avg
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dBi)	(dB)	(dB)	(P/A)
802.11n HT40 CH 151 5755MHz		5714.28	-29.49	-8.29	-21.2	-36.49	4.5	2.5	0	P
		5714.6	-47.83	-6.63	-41.2	-54.83	4.5	2.5	0	A
		5723.88	-26.23	-9.23	-17	-33.23	4.5	2.5	0	P
	*	5755	7.57	-	-	0.57	4.5	2.5	0	P
	*	5755	-1.4	-	-	-8.4	4.5	2.5	0	A
		5857.2	-44.61	-27.61	-17	-51.61	4.5	2.5	0	P
		5860.08	-45.97	-24.77	-21.2	-52.97	4.5	2.5	0	P
		5864.88	-56.78	-15.58	-41.2	-63.78	4.5	2.5	0	A
802.11n HT40 CH 159 5795MHz		5711.72	-35.52	-14.32	-21.2	-42.52	4.5	2.5	0	P
		5711.56	-51.13	-9.93	-41.2	-58.13	4.5	2.5	0	A
		5720.04	-32.59	-15.59	-17	-39.59	4.5	2.5	0	P
	*	5791	11.73	-	-	4.73	4.5	2.5	0	P
	*	5791	2.7	-	-	-4.3	4.5	2.5	0	A
		5852.24	-34.76	-17.76	-17	-41.76	4.5	2.5	0	P
		5872.4	-35.82	-14.62	-21.2	-42.82	4.5	2.5	0	P
		5878.32	-52.18	-10.98	-41.2	-59.18	4.5	2.5	0	A



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Grounding	Peak
Ant.				Limit	Line	Level	Gain	Loss	Factor	Avg
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dBi)	(dB)	(dB)	(P/A)
802.11n HT40 CH 151 5755MHz		5714.12	-32.14	-10.94	-21.2	-39.14	4.5	2.5	0	P
		5714.6	-46.85	-5.65	-41.2	-53.85	4.5	2.5	0	A
		5724.04	-24.26	-7.26	-17	-31.26	4.5	2.5	0	P
	*	5755	7.43	-	-	0.43	4.5	2.5	0	P
	*	5755	-1.13	-	-	-8.13	4.5	2.5	0	A
		5853.52	-45.84	-28.84	-17	-52.84	4.5	2.5	0	P
		5861.76	-45.95	-24.75	-21.2	-52.95	4.5	2.5	0	P
		5863.28	-56.59	-15.39	-41.2	-63.59	4.5	2.5	0	A
802.11n HT40 CH 159 5795MHz		5711.48	-36.34	-15.14	-21.2	-43.34	4.5	2.5	0	P
		5711.8	-51.38	-10.18	-41.2	-58.38	4.5	2.5	0	A
		5718.52	-35.58	-18.58	-17	-42.58	4.5	2.5	0	P
	*	5799	12	-	-	5	4.5	2.5	0	P
	*	5799	2.64	-	-	-4.36	4.5	2.5	0	A
		5853.04	-33.47	-16.47	-17	-40.47	4.5	2.5	0	P
		5862.4	-34.01	-12.81	-21.2	-41.01	4.5	2.5	0	P
		5878.24	-52.61	-11.41	-41.2	-59.61	4.5	2.5	0	A



3.4.7 Test Result of Conducted Spurious Emission in the Restricted Band

15E 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Grounding	Peak
Ant.				Limit	Line	Level	Gain	Loss	Factor	Avg
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dBi)	(dB)	(dB)	(P/A)
802.11a CH 149 5745MHz		103.17	-60.49	-8.79	-51.7	-72.19	4.5	2.5	4.7	P
		174.72	-60.61	-8.91	-51.7	-72.31	4.5	2.5	4.7	P
		243.84	-60.33	-11.13	-49.2	-72.03	4.5	2.5	4.7	P
		420.4	-61.11	-11.91	-49.2	-72.81	4.5	2.5	4.7	P
		623.4	-59.3	-10.1	-49.2	-71	4.5	2.5	4.7	P
		823.6	-60.48	-11.28	-49.2	-72.18	4.5	2.5	4.7	P
		11490	-63.32	-42.12	-21.2	-70.32	4.5	2.5	0	P
		17232	-54.61	-33.41	-21.2	-61.61	4.5	2.5	0	P
802.11a CH 157 5785MHz		101.01	-61.16	-9.46	-51.7	-72.86	4.5	2.5	4.7	P
		162.03	-60.08	-8.38	-51.7	-71.78	4.5	2.5	4.7	P
		258.42	-60.28	-11.08	-49.2	-71.98	4.5	2.5	4.7	P
		429.5	-59.97	-10.77	-49.2	-71.67	4.5	2.5	4.7	P
		586.3	-59.72	-10.52	-49.2	-71.42	4.5	2.5	4.7	P
		813.1	-60.76	-11.56	-49.2	-72.46	4.5	2.5	4.7	P
		11570	-60.97	-39.77	-21.2	-67.97	4.5	2.5	0	P
		17352	-54.99	-33.79	-21.2	-61.99	4.5	2.5	0	P
802.11a CH 165 5825MHz		101.82	-61.64	-9.94	-51.7	-73.34	4.5	2.5	4.7	P
		136.11	-60.24	-8.54	-51.7	-71.94	4.5	2.5	4.7	P
		185.79	-59.67	-7.97	-51.7	-71.37	4.5	2.5	4.7	P
		393.1	-62	-12.8	-49.2	-73.7	4.5	2.5	4.7	P
		487.6	-60.7	-11.5	-49.2	-72.4	4.5	2.5	4.7	P
		646.5	-60.24	-11.04	-49.2	-71.94	4.5	2.5	4.7	P
		11650	-66.14	-44.94	-21.2	-73.14	4.5	2.5	0	P
		17472	-55.66	-34.46	-21.2	-62.66	4.5	2.5	0	P



15E 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Grounding	Peak
Ant.				Limit	Line	Level	Gain	Loss	Factor	Avg
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dBi)	(dB)	(dB)	(P/A)
802.11a CH 149 5745MHz		98.58	-60.83	-9.13	-51.7	-72.53	4.5	2.5	4.7	P
		164.19	-60.52	-8.82	-51.7	-72.22	4.5	2.5	4.7	P
		258.15	-61.13	-11.93	-49.2	-72.83	4.5	2.5	4.7	P
		398.7	-59.91	-10.71	-49.2	-71.61	4.5	2.5	4.7	P
		640.9	-59.31	-10.11	-49.2	-71.01	4.5	2.5	4.7	P
		762.7	-60.29	-11.09	-49.2	-71.99	4.5	2.5	4.7	P
		11490	-62.94	-41.74	-21.2	-69.94	4.5	2.5	0	P
		17232	-54.78	-33.58	-21.2	-61.78	4.5	2.5	0	P
802.11a CH 157 5785MHz		103.44	-61.91	-10.21	-51.7	-73.61	4.5	2.5	4.7	P
		145.83	-61.02	-9.32	-51.7	-72.72	4.5	2.5	4.7	P
		250.05	-60.61	-11.41	-49.2	-72.31	4.5	2.5	4.7	P
		381.9	-61.41	-12.21	-49.2	-73.11	4.5	2.5	4.7	P
		513.5	-61.19	-11.99	-49.2	-72.89	4.5	2.5	4.7	P
		746.6	-60.01	-10.81	-49.2	-71.71	4.5	2.5	4.7	P
		11570	-65.87	-44.67	-21.2	-72.87	4.5	2.5	0	P
		17352	-55.44	-34.24	-21.2	-62.44	4.5	2.5	0	P
802.11a CH 165 5825MHz		94.8	-60.66	-8.96	-51.7	-72.36	4.5	2.5	4.7	P
		147.45	-61.6	-9.9	-51.7	-73.3	4.5	2.5	4.7	P
		261.93	-60.64	-11.44	-49.2	-72.34	4.5	2.5	4.7	P
		388.2	-60.43	-11.23	-49.2	-72.13	4.5	2.5	4.7	P
		575.8	-59.75	-10.55	-49.2	-71.45	4.5	2.5	4.7	P
		762.7	-60.72	-11.52	-49.2	-72.42	4.5	2.5	4.7	P
		11650	-58.13	-36.93	-21.2	-65.13	4.5	2.5	0	P
		17472	-54.86	-33.66	-21.2	-61.86	4.5	2.5	0	P



15E 5725~5850MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Grounding	Peak
Ant.				Limit	Line	Level	Gain	Loss	Factor	Avg
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dBi)	(dB)	(dB)	(P/A)
802.11n HT20 CH 149 5745MHz		119.1	-59.67	-7.97	-51.7	-71.37	4.5	2.5	4.7	P
		178.5	-60.95	-9.25	-51.7	-72.65	4.5	2.5	4.7	P
		219	-59.73	-10.53	-49.2	-71.43	4.5	2.5	4.7	P
		419	-59.16	-9.96	-49.2	-70.86	4.5	2.5	4.7	P
		598.9	-61.23	-12.03	-49.2	-72.93	4.5	2.5	4.7	P
		743.1	-59.5	-10.3	-49.2	-71.2	4.5	2.5	4.7	P
		11490	-62.95	-41.75	-21.2	-69.95	4.5	2.5	0	P
		17232	-55.25	-34.05	-21.2	-62.25	4.5	2.5	0	P
802.11n HT20 CH 157 5785MHz		105.33	-60.87	-9.17	-51.7	-72.57	4.5	2.5	4.7	P
		174.18	-59.97	-8.27	-51.7	-71.67	4.5	2.5	4.7	P
		199.56	-60.6	-8.9	-51.7	-72.3	4.5	2.5	4.7	P
		451.9	-60.65	-11.45	-49.2	-72.35	4.5	2.5	4.7	P
		628.3	-61	-11.8	-49.2	-72.7	4.5	2.5	4.7	P
		823.6	-59.69	-10.49	-49.2	-71.39	4.5	2.5	4.7	P
		11570	-65.65	-44.45	-21.2	-72.65	4.5	2.5	0	P
		17352	-55.27	-34.07	-21.2	-62.27	4.5	2.5	0	P
802.11n HT20 CH 165 5825MHz		105.06	-61.79	-10.09	-51.7	-73.49	4.5	2.5	4.7	P
		160.68	-61.15	-9.45	-51.7	-72.85	4.5	2.5	4.7	P
		214.68	-60.14	-8.44	-51.7	-71.84	4.5	2.5	4.7	P
		405	-61.03	-11.83	-49.2	-72.73	4.5	2.5	4.7	P
		589.1	-60.39	-11.19	-49.2	-72.09	4.5	2.5	4.7	P
		749.4	-60.72	-11.52	-49.2	-72.42	4.5	2.5	4.7	P
		11650	-65.73	-44.53	-21.2	-72.73	4.5	2.5	0	P
		17472	-54.22	-33.02	-21.2	-61.22	4.5	2.5	0	P



15E 5725~5850MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Grounding	Peak
Ant.				Limit	Line	Level	Gain	Loss	Factor	Avg
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dBi)	(dB)	(dB)	(P/A)
802.11n HT20 CH 149 5745MHz		92.37	-62.68	-10.98	-51.7	-74.38	4.5	2.5	4.7	P
		183.36	-60.1	-8.4	-51.7	-71.8	4.5	2.5	4.7	P
		265.71	-60.46	-11.26	-49.2	-72.16	4.5	2.5	4.7	P
		363	-61.56	-12.36	-49.2	-73.26	4.5	2.5	4.7	P
		511.4	-60.64	-11.44	-49.2	-72.34	4.5	2.5	4.7	P
		771.8	-61.37	-12.17	-49.2	-73.07	4.5	2.5	4.7	P
		11490	-61.06	-39.86	-21.2	-68.06	4.5	2.5	0	P
		17232	-55.64	-34.44	-21.2	-62.64	4.5	2.5	0	P
802.11n HT20 CH 157 5785MHz		71.31	-61.75	-6.55	-55.2	-73.45	4.5	2.5	4.7	P
		122.34	-60.97	-9.27	-51.7	-72.67	4.5	2.5	4.7	P
		240.06	-61.15	-11.95	-49.2	-72.85	4.5	2.5	4.7	P
		419.7	-61.24	-12.04	-49.2	-72.94	4.5	2.5	4.7	P
		611.5	-59.25	-10.05	-49.2	-70.95	4.5	2.5	4.7	P
		747.3	-61.31	-12.11	-49.2	-73.01	4.5	2.5	4.7	P
		11570	-58.14	-36.94	-21.2	-65.14	4.5	2.5	0	P
		17352	-54.3	-33.1	-21.2	-61.3	4.5	2.5	0	P
802.11n HT20 CH 165 5825MHz		48.63	-60.14	-4.94	-55.2	-71.84	4.5	2.5	4.7	P
		153.12	-60.05	-8.35	-51.7	-71.75	4.5	2.5	4.7	P
		264.9	-60	-10.8	-49.2	-71.7	4.5	2.5	4.7	P
		410.6	-60.19	-10.99	-49.2	-71.89	4.5	2.5	4.7	P
		577.9	-59.65	-10.45	-49.2	-71.35	4.5	2.5	4.7	P
		915.3	-60.11	-10.91	-49.2	-71.81	4.5	2.5	4.7	P
		11650	-60.33	-39.13	-21.2	-67.33	4.5	2.5	0	P
		17472	-54.65	-33.45	-21.2	-61.65	4.5	2.5	0	P



15E 5725~5850MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Grounding	Peak
Ant.				Limit	Line	Level	Gain	Loss	Factor	Avg
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dBi)	(dB)	(dB)	(P/A)
802.11n HT40 CH 151 5755MHz		101.01	-60.87	-9.17	-51.7	-72.57	4.5	2.5	4.7	P
		163.65	-60.75	-9.05	-51.7	-72.45	4.5	2.5	4.7	P
		222.78	-60.75	-11.55	-49.2	-72.45	4.5	2.5	4.7	P
		377	-61.13	-11.93	-49.2	-72.83	4.5	2.5	4.7	P
		580.7	-59.94	-10.74	-49.2	-71.64	4.5	2.5	4.7	P
		803.3	-59.68	-10.48	-49.2	-71.38	4.5	2.5	4.7	P
		11510	-66.47	-45.27	-21.2	-73.47	4.5	2.5	0	P
		17268	-54.71	-33.51	-21.2	-61.71	4.5	2.5	0	P
802.11n HT40 CH 159 5795MHz		101.28	-60.89	-9.19	-51.7	-72.59	4.5	2.5	4.7	P
		155.55	-60.84	-9.14	-51.7	-72.54	4.5	2.5	4.7	P
		231.69	-61.25	-12.05	-49.2	-72.95	4.5	2.5	4.7	P
		421.8	-60.92	-11.72	-49.2	-72.62	4.5	2.5	4.7	P
		573.7	-60.59	-11.39	-49.2	-72.29	4.5	2.5	4.7	P
		757.1	-60.11	-10.91	-49.2	-71.81	4.5	2.5	4.7	P
		11590	-63.58	-42.38	-21.2	-70.58	4.5	2.5	0	P
		17388	-54.38	-33.18	-21.2	-61.38	4.5	2.5	0	P



15E 5725~5850MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Grounding	Peak
Ant.				Limit	Line	Level	Gain	Loss	Factor	Avg
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dBi)	(dB)	(dB)	(P/A)
802.11n HT40 CH 151 5755MHz		45.12	-61.51	-6.31	-55.2	-73.21	4.5	2.5	4.7	P
		177.69	-60.95	-9.25	-51.7	-72.65	4.5	2.5	4.7	P
		280.83	-61.11	-11.91	-49.2	-72.81	4.5	2.5	4.7	P
		337.8	-60.72	-11.52	-49.2	-72.42	4.5	2.5	4.7	P
		568.1	-60.46	-11.26	-49.2	-72.16	4.5	2.5	4.7	P
		807.5	-58.5	-9.3	-49.2	-70.2	4.5	2.5	4.7	P
		11510	-66.5	-45.3	-21.2	-73.5	4.5	2.5	0	P
		17268	-55.86	-34.66	-21.2	-62.86	4.5	2.5	0	P
802.11n HT40 CH 159 5795MHz		46.47	-61.93	-6.73	-55.2	-73.63	4.5	2.5	4.7	P
		115.86	-60.1	-8.4	-51.7	-71.8	4.5	2.5	4.7	P
		246.81	-61.11	-11.91	-49.2	-72.81	4.5	2.5	4.7	P
		345.5	-61.51	-12.31	-49.2	-73.21	4.5	2.5	4.7	P
		630.4	-60.59	-11.39	-49.2	-72.29	4.5	2.5	4.7	P
		797	-60.46	-11.26	-49.2	-72.16	4.5	2.5	4.7	P
		11590	-60.87	-39.67	-21.2	-67.87	4.5	2.5	0	P
		17388	-55.8	-34.6	-21.2	-62.8	4.5	2.5	0	P



3.4.8 Test Result of Cabinet Radiated Spurious at Band Edges

Please refer to Appendix B of this report.

3.4.9 Test Result of Cabinet Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B of this report.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	20~22℃
Test Engineer :	Kai-Chun CHu	Relative Humidity :	46~48%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WLAN (5GHz) Link + Bluetooth Link + Adapter		



Final Result : QuasiPeak


Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	50.3	Off	L1	19.5	15.7	66.0
0.190000	42.7	Off	L1	19.5	21.3	64.0
0.494000	36.0	Off	L1	19.4	20.1	56.1
0.710000	31.1	Off	L1	19.6	24.9	56.0
0.926000	29.5	Off	L1	19.5	26.5	56.0
26.030000	33.3	Off	L1	19.9	26.7	60.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	40.8	Off	L1	19.5	15.2	56.0
0.190000	31.9	Off	L1	19.5	22.1	54.0
0.494000	29.1	Off	L1	19.4	17.0	46.1
0.710000	23.6	Off	L1	19.6	22.4	46.0
0.926000	23.0	Off	L1	19.5	23.0	46.0
26.030000	28.8	Off	L1	19.9	21.2	50.0



Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Kai-Chun CHu	Relative Humidity :	46~48%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WLAN (5GHz) Link + Bluetooth Link + Adapter		



Final Result : QuasiPeak

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	50.6	Off	N	19.5	15.4	66.0
0.190000	43.7	Off	N	19.5	20.3	64.0
0.494000	35.3	Off	N	19.4	20.8	56.1
0.702000	30.4	Off	N	19.6	25.6	56.0
1.254000	29.4	Off	N	19.6	26.6	56.0
26.366000	30.6	Off	N	20.1	29.4	60.0

Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.150000	40.7	Off	N	19.5	15.3	56.0
0.190000	31.2	Off	N	19.5	22.8	54.0
0.494000	27.8	Off	N	19.4	18.3	46.1
0.702000	22.3	Off	N	19.6	23.7	46.0
1.254000	24.0	Off	N	19.6	22.0	46.0
26.366000	26.2	Off	N	20.1	23.8	50.0

3.6 Frequency Stability Measurement

3.6.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
2. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
3. The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

3.6.4 Test Setup



3.6.5 Test Result of Frequency Stability

Please refer to Appendix A.



3.7 Automatically Discontinue Transmission

3.7.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.



3.8 Antenna Requirements

3.8.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2), if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.8.2 Antenna Anti-Replacement Construction

Non-standard antenna connector is used.

3.8.3 Antenna Gain

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

For power spectral density (PSD) measurements on all devices,

Array Gain = $10 \log(N_{ANT}/N_{SS}=1)$ dB.

For power measurements on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

The EUT supports CDD mode.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain "DG" is calculated as following table.

			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant 1	Ant 2	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	4.50	4.50	4.50	7.51	0.00	1.51

Power limit reduction = Composite gain – 6dBi, (min = 0)

PSD limit reduction = Composite gain + PSD Array gain – 6dBi, (min = 0)



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 09, 2014	Dec. 09, 2014 ~ Dec. 13, 2014	Jun. 08, 2015	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	1036004	300MHz~40GHz	Aug. 09, 2014	Dec. 09, 2014 ~ Dec. 13, 2014	Aug. 08, 2015	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	1027253	300MHz~40GHz	Aug. 09, 2014	Dec. 09, 2014 ~ Dec. 13, 2014	Aug. 08, 2015	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV30	101749	10Hz ~ 30GHz	Feb. 10, 2014	Dec. 15, 2014 ~ Dec. 16, 2014	Feb. 09, 2015	Radiation (03CH07-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9 kHz~7 GHz	Aug. 30, 2014	Dec. 15, 2014 ~ Dec. 16, 2014	Aug. 29, 2015	Radiation (03CH07-HY)
Loop Antenna	R&S	HFH2-Z2	100315	9 kHz~30 MHz	Jul. 28, 2014	Dec. 15, 2014 ~ Dec. 16, 2014	Jul. 27, 2015	Radiation (03CH07-HY)
Bilog Antenna	Schaffner	CBL6111C	2726	30MHz ~ 1GHz	Sep. 27, 2014	Dec. 15, 2014 ~ Dec. 16, 2014	Sep. 26, 2015	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	75962	1GHz~18GHz	Aug. 19, 2014	Dec. 15, 2014 ~ Dec. 16, 2014	Aug. 18, 2015	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	18GHz~40GHz	Oct. 02, 2014	Dec. 15, 2014 ~ Dec. 16, 2014	Oct. 01, 2015	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10 MHz ~ 1000MHz	Mar. 17, 2014	Dec. 15, 2014 ~ Dec. 16, 2014	Mar. 16, 2015	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1 GHz~26.5 GHz	Oct. 21, 2014	Dec. 15, 2014 ~ Dec. 16, 2014	Oct. 20, 2015	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590074	DC~18 GHz	Jul. 07, 2014	Dec. 15, 2014 ~ Dec. 16, 2014	Jul. 06, 2015	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590075	DC~18 GHz	Apr. 21, 2014	Dec. 15, 2014 ~ Dec. 16, 2014	Apr. 20, 2015	Radiation (03CH07-HY)
Turn Table	ChainTek	ChainTek 3000	N/A	0 ~ 360 degree	N/A	Dec. 15, 2014 ~ Dec. 16, 2014	N/A	Radiation (03CH07-HY)
Antenna Mast	ChainTek	ChainTek 3000	N/A	N/A	N/A	Dec. 15, 2014 ~ Dec. 16, 2014	N/A	Radiation (03CH07-HY)
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100356	9kHz ~ 2.75GHz	Nov. 12, 2014	Dec. 10, 2014	Nov. 11, 2015	Conduction (CO05-HY)
LISN (for auxiliary equipment)	Rohde & Schwarz	ENV216	100081	9kHz ~ 30MHz	Dec. 08, 2014	Dec. 10, 2014	Dec. 07, 2015	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz ~ 30MHz	Dec. 02, 2014	Dec. 10, 2014	Dec. 01, 2015	Conduction (CO05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Dec. 10, 2014	N/A	Conduction (CO05-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
--	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.50
--	------



Appendix A. Test Result of conducted Test Results

Report Number : FR4O0971E

Test Engineer:	Alex Lee	Temperature:	21~25	°C
Test Date:	2014/12/12	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% OBW

FCC Band IV									
Mod.	Data Rate	NTX	Channel	Freq. (MHz)	6 dB Bandwidth (MHz)		FCC 6 dB Bandwidth Min. Limit (MHz)		Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745		15.08	0.5	0.5	Pass
11a	6Mbps	1	157	5785		15.08	0.5	0.5	Pass
11a	6Mbps	1	165	5825		15.08	0.5	0.5	Pass
HT20	MCS0	1	149	5745		15.12	0.5	0.5	Pass
HT20	MCS0	1	157	5785		15.12	0.5	0.5	Pass
HT20	MCS0	1	165	5825		15.12	0.5	0.5	Pass
HT40	MCS0	1	151	5755		32.64	0.5	0.5	Pass
HT40	MCS0	1	159	5795		31.36	0.5	0.5	Pass

TEST RESULTS DATA
Average Power Table

FCC Band IV														
Mod.	Data Rate	N	Tx Channel	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	4.90	4.90	12.27	12.82	-	30.00	30.00	4.50	4.50	Pass
11a	6Mbps	1	157	5785	4.90	4.90	17.87	17.88		30.00	30.00	4.50	4.50	Pass
11a	6Mbps	1	165	5825	4.90	4.90	13.91	14.03		30.00	30.00	4.50	4.50	Pass
HT20	MCS0	1	149	5745	4.77	4.77	12.62	12.72		30.00	30.00	4.50	4.50	Pass
HT20	MCS0	1	157	5785	4.77	4.77	17.55	17.56		30.00	30.00	4.50	4.50	Pass
HT20	MCS0	1	165	5825	4.77	4.77	13.63	13.87		30.00	30.00	4.50	4.50	Pass
HT40	MCS0	1	151	5755	5.17	5.14	10.35	10.39		30.00	30.00	4.50	4.50	Pass
HT40	MCS0	1	159	5795	5.17	5.14	13.63	13.80		30.00	30.00	4.50	4.50	Pass

TEST RESULTS DATA
Power Spectral Density

FCC Band IV																
Mod.	Data Rate	Nt	Channel	Freq. (MHz)	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745		4.90		2.22		-0.13	-	30.00	30.00	4.50	4.50	Pass
11a	6Mbps	1	157	5785		4.90		2.22		4.86		30.00	30.00	4.50	4.50	Pass
11a	6Mbps	1	165	5825		4.90		2.22		0.91		30.00	30.00	4.50	4.50	Pass
HT20	MCS0	1	149	5745		4.77		2.22		-0.32		30.00	30.00	4.50	4.50	Pass
HT20	MCS0	1	157	5785		4.77		2.22		4.49		30.00	30.00	4.50	4.50	Pass
HT20	MCS0	1	165	5825		4.77		2.22		0.79		30.00	30.00	4.50	4.50	Pass
HT40	MCS0	1	151	5755		5.14		2.22		-5.98		30.00	30.00	4.50	4.50	Pass
HT40	MCS0	1	159	5795		5.14		2.22		-2.30		30.00	30.00	4.50	4.50	Pass

TEST RESULTS DATA
Frequency Stability

Band IV										
Mod.	Data Rate	NTX	Channel	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)	Note
11a	6Mbps	1	149	5745	5745.000	0.000	0.00	20	108	
11a	6Mbps	1	149	5745	5745.000	0.000	0.00	20	132	
11a	6Mbps	1	149	5745	5745.000	0.000	0.00	20	120	
11a	6Mbps	1	149	5745	5745.000	0.000	0.00	-30	120	
11a	6Mbps	1	149	5745	5745.000	0.000	0.00	50	120	



Appendix B. Radiated Spurious Emission

Test Engineer :	Nick Yu, Derreck Chen and Ken Wu	Temperature :	23~25°C
		Relative Humidity :	48~51%

15E Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5698.44	56.23	-17.77	74	42.96	35.21	12.18	34.12	100	0	P	H
		5697	42.24	-11.76	54	28.97	35.21	12.18	34.12	100	0	A	H
	*	5747	60.54	-	-	47.14	35.24	12.33	34.17	100	0	P	H
													H
													H
		5693.16	56.31	-17.69	74	43.04	35.21	12.18	34.12	100	0	P	V
		5693.64	42.29	-11.71	54	29.02	35.21	12.18	34.12	100	0	A	V
	*	5746	60.92	-	-	47.52	35.24	12.33	34.17	100	0	P	V
													V
													V
802.11a CH 157 5785MHz		5698.36	56.02	-17.98	74	42.75	35.21	12.18	34.12	100	0	P	H
		5721.32	42.29	-11.71	54	28.95	35.23	12.26	34.15	100	0	A	H
	*	5784	65.89	-	-	52.45	35.27	12.4	34.23	100	0	P	H
		5861.92	56.73	-17.27	74	43.27	35.32	12.49	34.35	100	0	P	H
		5861.52	42.55	-11.45	54	29.09	35.32	12.49	34.35	100	0	A	H
													H
		5719.56	55.96	-18.04	74	42.62	35.23	12.26	34.15	100	0	P	V
		5703.72	42.32	-11.68	54	28.96	35.22	12.26	34.12	100	0	A	V
	*	5788	62.89	-	-	49.44	35.28	12.4	34.23	100	0	P	V
		5885.52	56.67	-17.33	74	43.24	35.33	12.49	34.39	100	0	P	V
		5866.64	42.57	-11.43	54	29.11	35.32	12.49	34.35	100	0	A	V
													V



WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 165 5825MHz	*	5825	63.05	-	-	49.57	35.3	12.45	34.27	100	0	P	H
		5889.76	56.32	-17.68	74	42.88	35.34	12.49	34.39	100	0	P	H
		5870.16	42.58	-11.42	54	29.12	35.32	12.49	34.35	100	0	A	H
													H
													H
													H
													H
													H
	*	5824	60.59	-	-	47.11	35.3	12.45	34.27	100	0	P	V
		5862.08	56.6	-17.4	74	43.14	35.32	12.49	34.35	100	0	P	V
		5857.44	42.55	-11.45	54	29.09	35.32	12.45	34.31	100	0	A	V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15E Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		11490	43.06	-30.94	74	44.46	38.19	17.38	56.97	100	0	P	H
		17235	49.98	-24.02	74	42.58	42.21	21.38	56.19	100	0	P	H
													H
													H
		11490	42.87	-31.13	74	44.27	38.19	17.38	56.97	100	0	P	V
		17235	48.56	-25.44	74	41.16	42.21	21.38	56.19	100	0	P	V
													V
													V
802.11a CH 157 5785MHz		11571	42.37	-31.63	74	43.39	38.3	17.46	56.78	100	0	P	H
		17355	48.09	-25.91	74	40.74	42.12	21.45	56.22	100	0	P	H
													H
													H
		11571	42.62	-31.38	74	43.64	38.3	17.46	56.78	100	0	P	V
		17355	47.92	-26.08	74	40.57	42.12	21.45	56.22	100	0	P	V
													V
													V
802.11a CH 165 5825MHz		11649	44.26	-29.74	74	44.95	38.39	17.53	56.61	100	0	P	H
		17475	48.87	-25.13	74	41.56	42.03	21.53	56.25	100	0	P	H
													H
													H
		11649	43.63	-30.37	74	44.32	38.39	17.53	56.61	100	0	P	V
		17475	49.03	-24.97	74	41.72	42.03	21.53	56.25	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

15E Emission below 1GHz

5GHz WIFI 802.11a (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
5GHz 802.11a LF		50.25	24.41	-15.59	40	45.44	8.4	1.77	31.2	174	55	P	H	
		141.24	22.67	-20.83	43.5	39.66	11.5	2.61	31.1			P	H	
		294.6	28.92	-17.08	46	43.66	13.15	3.16	31.05			P	H	
		304.2	26.42	-19.58	46	40.89	13.25	3.28	31			P	H	
		468.7	28.67	-17.33	46	38.22	17.48	3.77	30.8			P	H	
		661.2	27.96	-18.04	46	33.77	20.32	4.35	30.48			P	H	
													H	
													H	
													H	
													H	
													H	
													H	
		42.42	26.44	-13.56	40	43.97	11.9	1.77	31.2				P	V
		201.72	29.27	-14.23	43.5	48.56	9.12	2.69	31.1				P	V
		277.05	27.18	-18.82	46	42.12	12.83	3.16	30.93				P	V
		324.5	26.09	-19.91	46	40.21	13.6	3.28	31				P	V
		664.7	32.8	-13.2	46	38.57	20.35	4.35	30.47	116	49		P	V
		900.6	32.2	-13.8	46	34.47	23.23	4.8	30.3				P	V
														V
														V
														V
														V
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix C. Setup Photographs

<Conducted Emission>



<Radiated Emission>

X Plane

LF



HF

