

A Specifications

CPU

- Intel Mobile Banias 1.3GHz, 1.4GHz, 1.5GHz, 1.6GHz
- 1 MB L2 Cache on CPU
- Intel ODEM system controller

System Memory

- Upgradable to 1024MB with two 512MB SO-DIMM modules.

Hard Disk Drive (HDD)

- One 2.5in. (9.5 mm) up to 60GB

Optical Disc Drive (ODD)

- 5.25 in. CD-ROM device, or
- 5.25 in. DVD-RW device, or
- 5.25 in. DVD-ROM & CD-RW combo device, or
- 5.25 in. DVD-ROM device

Display

- Color TFT 15 in. LCD panel supporting 1400 X 1050 SXGA+ Resolution, or
- Color TFT 15 in. LCD panel supporting 1024 X 768 XGA Resolution, or
- Color TFT 14.1 in LCD panel supporting 1024 X 768 XGA Resolution

Keyboard

- 85 US (standard) Key with 101/102 key emulation
- 1 Windows Key, 1 Application Key
- Standard pitch, 2.5 mm travel length
- Palm-rest

External Interfaces

- One 25-pin Parallel port with EPP/ECP capability
- One 15-pin CRT port with DDC 2B support
- One 7-pin TV-out port
- One MIC-in port
- One headphone-out port
- One 2-pin AC Adapter jack
- One type II PCMCIA Card Bus slot
- Three 4-pin USB ports
- One RJ11/RJ45 port
- FIR transmitter-receiver
- Secure Digital disc slot

External Controls

- Power switch
- Lid switch
- Wireless Communication switch
- 2 User-Defined buttons

AC Adapter

- Universal AC adapter module. Lite-on 60W 90-264V AC, 47-63Hz, or
- Universal AC adapter module. ASTEC 60W 90-264V AC, 47-63Hz

Power Management Functions

- Standby mode, Suspend to RAM, or Suspend to Disk mode, by time out or by hot key
- HDD Local Stand-By mode by time out
- LCD Local Stand-By mode by time out
- Low battery alarm by beep
- Auto-backlight off when LCD cover closed
- Full ACPI 1.0B supported
- LCD Auto-DIM mode by time out