



802.11n ht20 Band Edge, Left Side – Chain0




Date: 12.APR.2015 12:56:23

802.11n ht20 Band Edge, Right Side – Chain0




Date: 12.APR.2015 12:57:00

802.11n ht40 Band Edge, Left Side – Chain0




Date: 12.APR.2015 12:55:25

802.11n ht40 Band Edge, Right Side – Chain0




Date: 12.APR.2015 12:54:36

802.11a Band Edge, Left Side – Chain1




Date: 12.APR.2015 13:33:56

802.11a Band Edge, Right Side – Chain1




Date: 12.APR.2015 13:33:30

802.11n ht20 Band Edge, Left Side – Chain1




Date: 12.APR.2015 13:32:39

802.11n ht20 Band Edge, Right Side – Chain1




Date: 12.APR.2015 13:33:08

802.11n ht40 Band Edge, Left Side – Chain1



Date: 12.APR.2015 13:31:57

802.11n ht40 Band Edge, Right Side – Chain1



Date: 12.APR.2015 13:31:07

FCC §15.407(a) –EMISSION BANDWIDTH AND OCCUPIED BANDWIDTH**Applicable Standard**

15.407(a) (e)

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v01

Test Data**Environmental Conditions**

Temperature:	22.9 °C
Relative Humidity:	54 %
ATM Pressure:	101 kPa

The testing was performed by Allen Qiao on 2015-04-12.

Test Result: Pass.

Please refer to the following tables and plots.

Test mode: Transmitting


5150MHz-5250MHz:

Mode	Channel	Frequency MHz	26 dB Bandwidth (MHz)		99% occupied bandwidth (MHz)		Result
			Chain0	Chain1	Chain0	Chain1	
802.11a	Low	5180	24.64	25.44	17.36	17.68	PASS
	Middle	5200	24.24	25.52	17.12	17.68	PASS
	High	5240	24.24	25.2	17.12	17.68	PASS
802.11n20	Low	5180	25.28	26.40	18.24	18.80	PASS
	Middle	5200	25.52	26.80	18.32	18.72	PASS
	High	5240	25.12	26.56	18.24	18.88	PASS
802.11n40	Low	5190	48.00	50.08	36.64	37.12	PASS
	High	5230	48.96	49.76	37.12	37.12	PASS


5725MHz-5850MHz:

Mode	Channel	Frequency MHz	26 dB Bandwidth (MHz)		6dB Bandwidth (MHz)		99% occupied bandwidth (MHz)		Result
			Chain0	Chain1	Chain0	Chain1	Chain0	Chain1	
802.11a	Low	5745	24.40	24.00	16.56	16.48	17.28	17.12	PASS
	Middle	5785	23.76	23.68	16.48	16.48	17.20	17.28	PASS
	High	5825	23.92	24.00	16.48	16.48	17.28	17.12	PASS
802.11n20	Low	5745	24.88	25.68	17.04	17.84	18.32	18.72	PASS
	Middle	5785	24.80	25.36	17.60	17.84	18.48	18.56	PASS
	High	5825	25.36	25.44	17.44	17.84	18.72	18.72	PASS
802.11n40	Low	5755	48.96	49.28	36.48	36.8	36.96	36.96	PASS
	High	5795	48.32	47.68	36.64	36.64	36.96	36.80	PASS

5150MHz-5250MHz:


802.11a Low Channel – Chain0

Date: 12.APR.2015 11:13:22

802.11a Middle Channel – Chain0


Date: 12.APR.2015 11:16:50

802.11a High Channel – Chain0



Date: 12.APR.2015 11:18:10

802.11n ht20 Low Channel – Chain0



Date: 12.APR.2015 11:19:25

Ref Offset 1.5 dBm *Att 30 dB RBW 300 kHz Delta 1 [T1] 0.17 dB
 VEW 1 MHz SWT 20 ms 25.520000000 MHz

Offset 1.5 dB

1.5 dBm


D1 4.31 dBm

D2 21.69 dBm

3dB


Center 5.2 GHz 4 MHz/ Span 40 MHz

802.11n ht20 High Channel – Chain0




Page 100 of 160

802.11n ht40 Low Channel – Chain0




Date: 12.APR.2015 11:22:12

802.11n ht40 High Channel – Chain0




Date: 12.APR.2015 11:23:14

802.11a Low Channel – Chain1




Date: 12.APR.2015 11:48:27

802.11a Middle Channel – Chain1




Date: 12.APR.2015 11:49:08

802.11a High Channel – Chain1



Date: 12.APR.2015 11:49:58

802.11n ht20 Low Channel – Chain1



Date: 12.APR.2015 11:51:07

Ref Offset 1.5 dBm *Att 30 dB RBW 300 kHz Delta 1 [T1] -0.62 dB
 VEW 1 MHz SWT 20 ms 26.800000000 MHz

Offset 1.5 dB

1. PK
 MAXH

D1 3.92 dBm

T1

Temp 1 [T1 OBW] -21.82 dBm

5.186720000 GHz

Temp 2 [T1 OBW] -5.79 dBm


5.190640000 GHz

5.209360000 GHz

22.08 dBm


Center 5.2 GHz 4 MHz/ Span 40 MHz

802.11n ht20 High Channel – Chain1




Page 104 of 160

802.11n ht40 Low Channel – Chain1




Date: 12.APR.2015 11:54:31

802.11n ht40 High Channel – Chain1




Date: 12.APR.2015 11:55:30

5725MHz-5850MHz: 26 dB Bandwidth


802.11a Low Channel – Chain0

Date: 12.APR.2015 12:22:29

802.11a Middle Channel – Chain0


Date: 12.APR.2015 12:23:40

802.11a High Channel – Chain0



Date: 12.APR.2015 12:24:30

802.11n ht20 Low Channel – Chain0




Date: 12.APR.2015 12:25:29

Ref 15.5 dBm *Att 30 dB
 RBW 300 kHz Delta 1 [T1]
 VEW 1 MHz -0.89 dB
 SWT 20 ms 24.800000000 MHz

Offset 1.5 dB
 D1 3.51 dBm
 D2 22.49 dBm
 T1 5.772280000 GHz
 T2 5.775560000 GHz
 Temp 1 [T1 OBW] -8.23 dBm
 Temp 2 [T1 OBW] -6.52 dBm


Center 5.785 GHz 4 MHz/ Span 40 MHz

802.11n ht20 High Channel – Chain0




Page 108 of 160

802.11n ht40 Low Channel – Chain0




Date: 12.APR.2015 12:29:41

802.11n ht40 High Channel – Chain0




Date: 12.APR.2015 12:31:00

802.11a Low Channel – Chain1




Date: 12.APR.2015 13:01:00


802.11a Middle Channel – Chain1



Date: 12.APR.2015 13:02:01


802.11a High Channel – Chain1

Date: 12.APR.2015 13:02:45

802.11n ht20 Low Channel – Chain1


Date: 12.APR.2015 13:03:51

802.11n ht20 Middle Channel – Chain1




Date: 12.APR.2015 13:06:52

802.11n ht20 High Channel – Chain1




Date: 12.APR.2015 13:07:39

802.11n ht40 Low Channel – Chain1




Date: 12.APR.2015 13:08:51

802.11n ht40 High Channel – Chain1




Date: 12.APR.2015 13:09:51

6 dB Bandwidth


802.11a Low Channel – Chain0

Date: 12.APR.2015 12:46:12

802.11a Middle Channel – Chain0


Date: 12.APR.2015 12:46:59

802.11a High Channel – Chain0




Date: 12.APR.2015 12:47:37

802.11n ht20 Low Channel – Chain0




Date: 12.APR.2015 12:43:56

802.11n ht20 Middle Channel – Chain0




Date: 12.APR.2015 12:44:35

802.11n ht20 High Channel – Chain0




Date: 12.APR.2015 12:45:27

802.11n ht40 Low Channel – Chain0




Date: 12.APR.2015 12:41:52

802.11n ht40 High Channel – Chain0




Date: 12.APR.2015 12:42:46

802.11a Low Channel – Chain1




Date: 12.APR.2015 13:26:59

802.11a Middle Channel – Chain1




Date: 12.APR.2015 13:26:12

802.11a High Channel – Chain1




Date: 12.APR.2015 13:25:40

802.11n ht20 Low Channel – Chain1




Date: 12.APR.2015 13:23:53

802.11n ht20 Middle Channel – Chain1




Date: 12.APR.2015 13:24:29

802.11n ht20 High Channel – Chain1




Date: 12.APR.2015 13:25:08

802.11n ht40 Low Channel – Chain1



Date: 12.APR.2015 13:23:07

802.11n ht40 High Channel – Chain1



Date: 12.APR.2015 13:22:25

FCC §15.407(a) (1) (ii) (4) –MAXIMUM CONDUCTED OUTPUT POWER**Applicable Standard**

(a) Power limits:

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 + 10 \log B$ dBm, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(4) The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v01.

Test Data

Environmental Conditions

Temperature:	25.4°C ~26.2 °C
Relative Humidity:	47%~56 %
ATM Pressure:	101.2 kPa ~101.6 kPa

The testing was performed by Allen Qiao from 2014-11-12 & 2014-11-17.

Test Mode: Transmitting

5150-5250 MHz band

Mode	Channel	Frequency	Maximum Conducted Output Power (dBm)				Result
		MHz	Chain 0	Chain 1	Total	Limits	
802.11a	Low	5180	13.94	14.65	17.32	28	PASS
	Middle	5200	13.89	14.11	17.01	28	PASS
	High	5240	13.46	13.74	16.61	28	PASS
802.11n20	Low	5180	12.36	12.79	15.59	28	PASS
	Middle	5200	12.63	12.51	15.58	28	PASS
	High	5240	12.06	12.33	15.21	28	PASS
802.11n40	Low	5190	8.51	9.79	12.21	28	PASS
	High	5230	8.17	9.54	11.92	28	PASS


5725-5850 MHz band

Mode	Channel	Frequency	Maximum Conducted Output Power (dBm)				Result
		MHz	Chain 0	Chain 1	Total	Limits	
802.11a	Low	5745	11.21	11.26	14.25	28	PASS
	Middle	5785	11.47	11.13	14.31	28	PASS
	High	5825	12.00	11.60	14.81	28	PASS
802.11n20	Low	5745	11.02	10.70	13.87	28	PASS
	Middle	5785	10.91	10.73	13.83	28	PASS
	High	5825	11.29	11.04	14.18	28	PASS
802.11n40	Low	5755	7.27	7.42	10.36	28	PASS
	High	5795	7.17	7.20	10.20	28	PASS

- Note: 1. Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dBi
 $= 8 > 6$ dBi, so the limit = $30 - (8 - 6) = 28$ dBm
2. Duty cycle is 100%.
3. The EUT is only for indoor use.


5150MHz-5250MHz:

802.11a Low Channel – Chain0




Date: 12.APR.2015 11:27:44

802.11a Middle Channel – Chain0




Date: 12.APR.2015 11:28:09

802.11a High Channel – Chain0




Date: 12.APR.2015 11:28:43

802.11n ht20 Low Channel – Chain0




Date: 12.APR.2015 11:25:32

802.11n ht20 Middle Channel – Chain0




Date: 12.APR.2015 11:26:00

802.11n ht20 High Channel – Chain0




Date: 12.APR.2015 11:26:34

802.11n ht40 Low Channel – Chain0




Date: 12.APR.2015 11:24:36

802.11n ht40 High Channel – Chain0




Date: 12.APR.2015 11:24:07

802.11a Low Channel – Chain1




Date: 12.APR.2015 12:01:42


802.11a Middle Channel – Chain1



Date: 12.APR.2015 12:02:11


802.11a High Channel – Chain1

Date: 12.APR.2015 12:02:39

802.11n ht20 Low Channel – Chain1


Date: 12.APR.2015 11:59:43

802.11n ht20 Middle Channel – Chain1




Date: 12.APR.2015 12:00:11

802.11n ht20 High Channel – Chain1




Date: 12.APR.2015 12:00:41

802.11n ht40 Low Channel – Chain1



Date: 12.APR.2015 11:58:45


802.11n ht40 High Channel – Chain1



Date: 12.APR.2015 11:58:04


5725MHz-5850MHz:

802.11a Low Channel – Chain0




Date: 12.APR.2015 12:36:15

802.11a Middle Channel – Chain0




Date: 12.APR.2015 12:36:47

802.11a High Channel – Chain0




Date: 12.APR.2015 12:37:16

802.11n ht20 Low Channel – Chain0




Date: 12.APR.2015 12:34:14

802.11n ht20 Middle Channel – Chain0




Date: 12.APR.2015 12:34:43

802.11n ht20 High Channel – Chain0




Date: 12.APR.2015 12:35:20

802.11n ht40 Low Channel – Chain0




Date: 12.APR.2015 12:32:40

802.11n ht40 High Channel – Chain0




Date: 12.APR.2015 12:31:53

802.11a Low Channel – Chain1




Date: 12.APR.2015 13:14:21

802.11a Middle Channel – Chain1




Date: 12.APR.2015 13:14:53

802.11a High Channel – Chain1




Date: 12.APR.2015 13:15:20

802.11n ht20 Low Channel – Chain1




Date: 12.APR.2015 13:12:18

802.11n ht20 Middle Channel – Chain1




Date: 12.APR.2015 13:13:03

802.11n ht20 High Channel – Chain1




Date: 12.APR.2015 13:13:36

802.11n ht40 Low Channel – Chain1



Date: 12.APR.2015 13:11:20

802.11n ht40 High Channel – Chain1



Date: 12.APR.2015 13:10:30

FCC §15.407(a) - POWER SPECTRAL DENSITY

Applicable Standard

(a) Power limits:

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm $10 \log B$, where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(3) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. However, fixed point-to-point U-NII devices operating in this band may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted power. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

Test Procedure

According to KDB 789033 D02 General UNII Test Procedures New Rules v01

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSP 38	100478	2014-05-09	2015-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	22.9 °C
Relative Humidity:	54 %
ATM Pressure:	101 kPa

The testing was performed by Allen Qiao on 2015-04-12.

Test Mode: Transmitting

Test Result: Compliance. Please refer to the following table and plot.

5150MHz-5250MHz:

Mode	Channel	Frequency MHz	PSD (dBm/MHz)			Limit (dBm/MHz)	Result
			Chain0	Chain1	Total		
802.11a	Low	5180	3.86	3.67	6.78	15	PASS
	Middle	5200	3.38	3.28	6.34	15	PASS
	High	5240	2.88	3.30	6.11	15	PASS
802.11n20	Low	5180	1.78	1.78	4.79	15	PASS
	Middle	5200	1.74	1.45	4.61	15	PASS
	High	5240	1.94	0.93	4.47	15	PASS
802.11n40	Low	5190	-5.14	-4.48	-1.79	15	PASS
	High	5230	-5.07	-4.46	-1.74	15	PASS

Note: 1. Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dBi
 $= 8 > 6$ dBi, so the limit shall be reduced to $17 - (8 - 6) = 15$ dBm

2. Duty cycle is 100%.

3. The EUT is only for indoor use.

5725MHz-5850MHz:

Mode	Channel	Frequency	Power Spectral Density (dBm/300kHz)		Power Spectral Density (dBm/500kHz)			Limits (dBm/500kHz)
		MHz	Chain 0	Chain 1	Chain0 Integrated Value	Chain 1 Integrated Value	Total	
802.11a	Low	5745	-3.32	-2.55	-1.10	-0.33	2.31	28
	Middle	5785	-2.75	-1.99	-0.53	0.23	2.88	28
	High	5825	-2.44	-2.09	-0.22	0.13	2.97	28
802.11n20	Low	5745	-3.82	-3.67	-1.60	-1.45	1.48	28
	Middle	5785	-2.77	-3.96	-0.55	-1.74	1.90	28
	High	5825	-2.80	-2.19	-0.58	0.03	2.74	28
802.11n40	Low	5755	-10.34	-9.84	-8.12	-7.62	-4.85	28
	High	5795	-10.58	-10.75	-8.36	-8.53	-5.44	28

Note: If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10 \log(500 \text{ kHz} / \text{RBW})$ to the measured result, whereas RBW ($< 500 \text{ KHz}$) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.


Note: 1. Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dBi
 $= 8 > 6$ dBi, so the limit shall be reduced to $30 - (8 - 6) = 28$ dBm

2. Duty cycle is 100%.

3. The EUT is only for indoor use.


5150MHz-5250MHz:

802.11a Low Channel – Chain0




Date: 12.APR.2015 11:29:33

802.11a Middle Channel – Chain0




Date: 12.APR.2015 11:29:12

802.11a High Channel – Chain0




Date: 12.APR.2015 11:28:55

802.11n ht20 Low Channel – Chain0




Date: 12.APR.2015 11:30:04

802.11n ht20 Middle Channel – Chain0




Date: 12.APR.2015 11:30:22

802.11n ht20 High Channel – Chain0




Date: 12.APR.2015 11:30:46

802.11n ht40 Low Channel – Chain0




Date: 12.APR.2015 11:31:15

802.11n ht40 High Channel – Chain0




Date: 12.APR.2015 11:31:34

802.11a Low Channel – Chain1




Date: 12.APR.2015 12:03:34

802.11a Middle Channel – Chain1




Date: 12.APR.2015 12:03:14

802.11a High Channel – Chain1




Date: 12.APR.2015 12:02:55

802.11n ht20 Low Channel – Chain1




Date: 12.APR.2015 12:04:12

802.11n ht20 Middle Channel – Chain1




Date: 12.APR.2015 12:04:31

802.11n ht20 High Channel – Chain1




Date: 12.APR.2015 12:04:57

802.11n ht40 Low Channel – Chain1



Date: 12.APR.2015 12:05:27


802.11n ht40 High Channel – Chain1



Date: 12.APR.2015 12:05:48


5725MHz-5850MHz:

802.11a Low Channel – Chain0




Date: 12.APR.2015 13:43:13

802.11a Middle Channel – Chain0




Date: 12.APR.2015 13:43:30

802.11a High Channel – Chain0




Date: 12.APR.2015 13:43:47

802.11n ht20 Low Channel – Chain0




Date: 12.APR.2015 13:42:55

802.11n ht20 Middle Channel – Chain0




Date: 12.APR.2015 13:42:39

802.11n ht20 High Channel – Chain0




Date: 12.APR.2015 13:42:19

802.11n ht40 Low Channel – Chain0




Date: 12.APR.2015 13:44:13

802.11n ht40 High Channel – Chain0




Date: 12.APR.2015 13:44:29

802.11a Low Channel – Chain1




Date: 12.APR.2015 13:18:33


802.11a Middle Channel – Chain1



Date: 12.APR.2015 13:18:51


802.11a High Channel – Chain1

Date: 12.APR.2015 13:19:21

802.11n ht20 Low Channel – Chain1


Date: 12.APR.2015 13:20:41

802.11n ht20 Middle Channel – Chain1




Date: 12.APR.2015 13:20:10

802.11n ht20 High Channel – Chain1




Date: 12.APR.2015 13:19:47

802.11n ht40 Low Channel – Chain1



Date: 12.APR.2015 13:21:17

802.11n ht40 High Channel – Chain1



Date: 12.APR.2015 13:21:35

